

Carolina Sandstone is an acrylic based mineral plaster used for decorative coats over stable prepared surfaces.

Product Descriptions & Uses

This system is used as a finish that can be applied on interior surfaces. A typical installation will produce textured or polychromatic stone like effects.

Carolina Sandstone is a cost-effective way to produce very decorative elements on a variety of surfaces. After correct surface preparation apply .1 or 2 thin coats. It has good workability, and this will allow time to create the decorative elements and proper finishing with a sealer.

Application

Application is done with combination of spatulas, rollers and steel finishing trowels. This will allow correct layering and translucency between coats.

To get the best and most efficient results we recommend a coat of primer under **Carolina Sandstone**. Protek manufactures two specific primers for plastering, Drywall Sealer (Texprime) for bear walls and Sharktooth primer on previously painted surfaces.

A careful inspection should be done prior to application for cracks, unsound surfaces and the hygrometry of the substrate. We recommend a test area be applied to test for adhesion where a doubt is present. **Before commencing the application remove all loose dirt, grease and other contaminants that could prevent adhesion.**

If the surface is a level 3, we recommend leveling with drywall compound before attempting plaster, allow 24 hours drying time, and prime with Drywall Sealer.

If the substrate is a level 5 prime with Drywall Sealer followed by a full coat of **Carolina Sandstone**. When this coat has dried you can commence the decorative application. (See details for an example finish on page 2).

We strongly suggest that all installers follow proper procedures. One way to gain experience is through one of our programs given at an approved training facility.

Colouring & Crackle

Carolina Sandstone is supplied in tintable bases ready to use. It is normally tinted with universal colorants according to paint manufacturers colour fan decks. Protek utilizes the Colour Is Fan Deck for this purpose, which is also available online. Alternative methods of introducing colour over Carolina Sandstone are as follows:

Glazes can be used adding colored effects on the finish.

Stonewash Pigments are a natural oxide colorant that is nonfading and soluble in water. When applied as a wash over it will work very similar to a wiping stain on wood. **Carolina Sandstone** allows about 20/25% penetration and after wiping off the excess the result is a stone like texture.

Aquaglass crackle system is very effective creating distressed walls. It also is very effective when relief stencilled.

Protection

Protek has several options to protect the finished effect:

Zero Gloss Varnish used over Stonewash to get a washable stone effect with no visible film or colour change.

Flat Wax is a universal protective coating; it can be applied with spatulas and polished to a sheen

Satin Wax A self-polishing coating used where extra protection is needed also over effects that need sheen but cannot be polished with spatulas.

Packaging

Pails—gallons - US measure
Neutral base 24kg –.6kg

Coverage

The coverage will vary greatly according to the thickness of application. A 24 kg pail will vary from 500sq. ft. to 700sq. ft. as a multi layer plaster effect.

Carolina Sandstone Composition

It is a hybrid plaster using acrylic polymer technology combined with natural mineral fillers and additives to enhance application and shelf life (3 years)

Technical Data

Ingredients:	CAS, NA or UN No.
Acrylic copolymer emulsion	Proprietary
Surfactant	Proprietary
Water	7732 – 18 -5
Coalescing agent	25265 – 77 – 4
Titanium dioxide	13463 – 67 – 7
Kaolin clay	1332 – 58 – 7
Calcium carbonate	471 – 34 – 1

VOC 30g per lb. 66g per kg

Shelf Life

If stored sealed and in a dry atmosphere a 36-month shelf life from the date on the label. Do not store below 0° or above 40° C or in direct sunlight. If freezing occurs leave for 24 hours at room temperature, then stir and use. **Carolina Sandstone** plaster is protected from multiple freeze thaws without glycol.

Example of Carolina Sandstone Finish:

1. Apply a full coat of Carolina as smoothly as possible; a second coat of the same material in a cross-hatch pattern coat, usually 1½ coats. You can colour the surface with a glaze or stonewash pigment in water, seal with wax or Zero Gloss.



Caution

SKIN ABSORPTION: No evidence of harmful effects from available information.
EYE CONTACT: May cause irritation.
INGESTION: May cause irritation of stomach with abdominal discomfort.
FIRST AID: do not rub eyes, immediately flush with clean water. Skin: wash with soap and water. Inhalation: move to fresh air if symptoms persist or develop call medical help. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**