



SAFETY DATA SHEET

Revision Date: 15-Apr-2025

Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR COATING NEUTRAL BASE
Product Code EGG-190F
Alternate Product Code XF0941
Product Class WATERBORNE EPOXY
Color All
Recommended use Paint
Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
www.inslx.ca

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.insl-x.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)
CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage

Suspected of causing cancer
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Aliphatic polyamine	U84660-00-1	10 - 30%	HMIRC # 9649	Granted: April 21, 2016
Talc	14807-96-6	10 - 30%	-	-
Nepheline syenite	37244-96-5	10 - 30%	-	-
2-Propoxyethanol	2807-30-9	5 - 10%	-	-
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5%	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice	Immediately call a POISON CENTER or doctor/physician.
Eye Contact	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before reuse.
Inhalation	Call a physician or poison control center immediately. Move to fresh air. If not breathing, give artificial respiration.
Ingestion	Never give anything by mouth to an unconscious person. Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data	
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Setaflash closed cup
Flammability Limits In Air	
Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable
NFPA	
Health hazards	1
Flammability	0
Stability	0
Special:	Not Applicable

NFPA Legend

0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
----------	--

Storage

Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Talc	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWAEV
Nepheline syenite	-	-	-	10 mg/m ³ - TWA	-
2-Propoxyethanol	-	-	-	25 ppm - TWA 110 mg/m ³ - TWA Danger of cutaneous absorption	-
Dipropylene glycol monomethyl ether	TWA: 50 ppm	100 ppm - TWA 606 mg/m ³ - TWA 150 ppm - STEL 909 mg/m ³ - STEL Substance may be readily absorbed through intact skin	100 ppm - TWA 150 ppm - STEL Skin absorption can contribute to overall exposure.	100 ppm - TWA 150 ppm - STEL Danger of cutaneous absorption	100 ppm - TWAEV 606 mg/m ³ - TWAEV 150 ppm - STEV 909 mg/m ³ - STEV Skin absorption can contribute to overall exposure.

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
Alberta - Alberta Occupational Exposure Limits
British Columbia - British Columbia Occupational Exposure Limits
Ontario - Ontario Occupational Exposure Limits
Quebec - Quebec Occupational Exposure Limits
N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Skin Protection

Respiratory Protection

Safety glasses with side-shields
Protective gloves and impervious clothing.
In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Odor

Odor Threshold

Density (lbs./gal)

liquid
little or no odor
No information available
10.2 - 10.6

Specific Gravity	1.22 - 1.27
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	45 - 55
Vol. % Solids	30 - 40
Wt. % Volatiles	45 - 55
Vol. % Volatiles	60 - 70
VOC Regulatory Limit (g/L)	< 250
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	No information available
Freezing Point (°C)	No information available
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Setaflash closed cup
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure	Eye contact, skin contact and inhalation.
------------------------------	---

Acute Toxicity

Product Information

No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Causes eye irritation Risk of serious damage to eyes May cause burns Severely irritating to eyes

Skin contact

Irritating to skin. Prolonged skin contact may cause skin irritation and/or dermatitis. May cause burns.

Inhalation

Harmful by inhalation. Causes respiratory tract irritation. Vapours may be irritating to eyes, nose, throat, and lungs. May cause additional affects as listed under "Ingestion".

Ingestion

Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Can burn mouth, throat, and stomach.

Sensitization

No information available.

Neurological Effects

No information available.

Mutagenic Effects

No information available.

Reproductive Effects

No information available.

Developmental Effects

No information available.

Target organ effects

Respiratory system, Eyes, Central Vascular System (CVS).

STOT - single exposure

May cause disorder and damage to the. Respiratory system. Digestive System.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if swallowed. kidney.

Other adverse effects

No information available.

Aspiration Hazard

No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

2407 mg/kg

ATEmix (dermal)

11108 mg/kg

ATEmix (inhalation-dust/mist)

7.9 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Propoxyethanol 2807-30-9	= 3089 mg/kg (Rat)	= 870 mg/kg (Rabbit) = 960 µL/kg (Rabbit)	= 1530 ppm (Rat) 7 h
Dipropylene glycol monomethyl ether 34590-94-8	= 5.35 g/kg (Rat)	= 9500 mg/kg (Rabbit)	-

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

None

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION

HMIS

Health hazards	1*
Flammability	0
Reactivity:	0
Personal protection	-

HMIS Legend

0 - Minimal Hazard
1 - Slight Hazard
2 - Moderate Hazard
3 - Serious Hazard
4 - Severe Hazard
* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 15-Apr-2025
Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet