

General Description

An interior acrylic primer that quickly sands to a powder in just one hour. Ideal for wood surfaces, drywall and plaster. Provides an ultrasmooth base for a uniform topcoat.

- Ready to sand in 1 hour
- Excellent flow & leveling
- Excellent sealing properties & holdout

Usage

Ideal for priming new interior wood surfaces such as walls, doors & trim, as well as drywall & plaster. Can be used on previously painted surfaces that have been properly prepared. Excellent for new construction, OEM and similar high-production environments.

Colours	White (00)
Bases	N/A
Colorant System	Gennex® (up to 60 mL per 3.79 L)

Technical Data

Vehicle	Acrylic
Pigment	Titanium Dioxide
Volume Solids	34 ± 2%
Spread Rate Per 3.79 L	32.5 – 41.8 sq. m. (350 – 450 sq. ft.)
Recommended	Wet: 3.6 – 4.6 mils
Film Thickness	Dry: 1.2 – 1.6 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.

Dry Time @ 25 °C (77 °F) @ 50% RH	To Touch:	30 minutes
	To Sand:	1 hour
	To Recoat:	1 – 2 hours

High humidity and cool temperatures will result in longer dry, recoat and service times

Surface Temperature	Min:	10 °C (50 °F)
During Application	Max:	32.2 °C (90 °F)
Viscosity		97 ± 4 KU
Flash Point		None
Sheen / Gloss		3 – 7 @ 60°
Clean Up		Water
Thinner		Water
Weight Per 3.79 L		5.2 kg (11.4 lbs.)
Storage Temperature	Min:	4.4 °C (40 °F)
	Max:	32.2 °C (90 °F)
VOC		< 100 g/L

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have as light sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Remove any powder or loose particles before priming.

Difficult Substrates: If the surfaces to be painted exhibit severe tannin or smoke staining, an alkyl-based Benjamin Moore primer may be your best choice for conquering these severe conditions. Consult your Benjamin Moore retailer for further guidance.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat.

Special Note: Certain custom colours require Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

Wood, and engineered wood products:

Fast Sanding Primer (K507)

Drywall:

Fast Sanding Primer (K507)

Plaster / Masonry (Cured):

Fast Sanding Primer (K507)

Severe stains / bleeding woods:

Fresh Start® Undercoater and Primer/Sealer (K032)

Repaint, All Substrates:

Prime bare areas with the primer recommended above for the substrate.

Compliance & Certifications

Eligible for LEED® v4	✓
CDPH Emissions Certified	✓
Eligible for CHPS low emitting credit (Collaborative for High Performance Schools)	✓
MPI	50

Limitations

- Do not paint when air or surface temperature is below 10 °C (50 °F).
- For interior use only.
- Not intended for blocking severe stains.

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180
visit www.benjaminmoore.ca

Application

Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

Spray, Airless:

Pressure / 1,500 – 2,500 PSI

Tip / 0.013 – 0.017

Thinning/Cleaning

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added; up to 8 fl. oz. per gallon. Never add other paints or solvents.

Clean Up: Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information.**