



# Benjamin Moore®

## SAFETY DATA SHEET

Revision Date: 11-Sep-2025

Revision Number: 6

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** REGAL SELECT EXTERIOR HIGH BUILD PAINT SOFT GLOSS  
**Product Code** FINISH BASE 1  
**Alternate Product Code** F4031X  
**Product Class** F4031X  
**Color** Water thinned paint  
**Recommended use** All  
**Restrictions on use** Paint  
No information available

**Manufactured For**

Benjamin Moore & Co., Limited  
1651 Stellar Drive, Unit 1  
Whitby, Ontario L1N 0R1  
Phone: 1-800-361-5898  
[www.benjaminmoore.com/en-ca](http://www.benjaminmoore.com/en-ca)

**Manufacturer**

Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
[www.benjaminmoore.com](http://www.benjaminmoore.com)

**Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)  
CANUTEC: 613-996-6666 (Transport Emergency Only)

### 2. HAZARDS IDENTIFICATION

**Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

|                                   |             |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Skin sensitization                | Category 1  |
| Germ cell mutagenicity            | Category 1B |
| Reproductive toxicity             | Category 1B |

**Label elements**

**Danger**

**Hazard statements**

Causes serious eye irritation

May cause an allergic skin reaction  
May cause genetic defects  
May damage fertility or the unborn child



**Appearance** liquid

**Odor** little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing should not be allowed out of the workplace  
Wear protective gloves/clothing and eye/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

##### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing

If eye irritation persists: Get medical advice/attention

##### **Skin**

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Other information**

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

### **3. COMPOSITION INFORMATION ON COMPONENTS**

| Chemical name                                                             | CAS No.    | Weight-%    | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|---------------------------------------------------------------------------|------------|-------------|------------------------------------------------------------------------------|-------------------------------------------------------------|
| Titanium dioxide                                                          | 13463-67-7 | 10 - 30%    | -                                                                            | -                                                           |
| Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 25265-77-4 | 1 - 5%      | -                                                                            | -                                                           |
| Sodium C14-C16 olefin sulfonate                                           | 68439-57-6 | 0.25 - 0.5% | -                                                                            | -                                                           |
| Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester                        | 10605-21-7 | 0.1 - 0.25% | -                                                                            | -                                                           |
| Trimethylolpropane                                                        | 77-99-6    | 0.1 - 0.25% | -                                                                            | -                                                           |

\*The exact percentage (concentration) of composition has been withheld as a trade secret

#### 4. FIRST AID MEASURES

##### General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

##### Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

##### Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

##### Inhalation

Remove to fresh air immediately. Get medical attention immediately.

##### Ingestion

Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

##### Most Important Symptoms/Effects

May cause allergic skin reaction.

##### Notes To Physician

Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

|                                            |                                                                   |
|--------------------------------------------|-------------------------------------------------------------------|
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity to mechanical impact           | No                                                                |
| Sensitivity to static discharge            | No                                                                |
| Flash Point Data                           |                                                                   |
| Flash point (°F)                           | Not Applicable                                                    |
| Flash Point (°C)                           | Not applicable                                                    |
| Method                                     | Not applicable                                                    |
| Flammability Limits In Air                 |                                                                   |
| Lower flammability limit:                  | Not applicable                                                    |
| Upper flammability limit:                  | Not applicable                                                    |
| NFPA                                       |                                                                   |
| Health hazards                             | 2                                                                 |
| Flammability                               | 0                                                                 |
| Stability                                  | 0                                                                 |
| Special:                                   | Not Applicable                                                    |

#### NFPA Legend

0 - Not Hazardous  
1 - Slightly  
2 - Moderate  
3 - High  
4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Personal Precautions      | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.                          |
| Other Information         | Prevent further leakage or spillage if safe to do so.                                             |
| Environmental precautions | See Section 12 for additional Ecological Information.                                             |
| Methods for Cleaning Up   | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

## 7. HANDLING AND STORAGE

|          |                                                                                                                                                                            |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Storage**

Keep container tightly closed. Keep out of the reach of children.

**Incompatible Materials**

No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits**

| Chemical name      | ACGIH TLV                                                                                                                                      | Alberta                     | British Columbia                                                                         | Ontario                     | Quebec                                   |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------|-----------------------------|------------------------------------------|
| Titanium dioxide   | TWA: 0.2 mg/m <sup>3</sup><br>nanoscale respirable particulate matter<br>TWA: 2.5 mg/m <sup>3</sup><br>finescale respirable particulate matter | TWA: 10 mg/m <sup>3</sup> ; | TWA: 10 mg/m <sup>3</sup> ; total dust<br>TWA: 3 mg/m <sup>3</sup> ; respirable fraction | TWA: 10 mg/m <sup>3</sup> ; | TWAEV: 10 mg/m <sup>3</sup> ; total dust |
| Trimethylolpropane | TWA: 0.5 ppm<br>inhalable fraction and vapor                                                                                                   | -                           | Adverse reproductive effect                                                              | -                           | -                                        |

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

**Skin Protection**

**Respiratory Protection**

Safety glasses with side-shields

Protective gloves and impervious clothing.

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance**

liquid

**Odor**

little or no odor

**Odor Threshold**

No information available

**Density (lbs./gal)**

10.8 - 11.2

**Specific Gravity**

1.29 - 1.35

**pH**

No information available

|                                |                          |
|--------------------------------|--------------------------|
| Viscosity (cps)                | No information available |
| Solubility(ies)                | No information available |
| Water solubility               | No information available |
| Evaporation Rate               | No information available |
| Vapor pressure @20 °C (kPa)    | No information available |
| Relative vapor density         | No information available |
| Wt. % Solids                   | 50 - 60                  |
| Vol. % Solids                  | 35 - 45                  |
| Wt. % Volatiles                | 40 - 50                  |
| Vol. % Volatiles               | 55 - 65                  |
| VOC Regulatory Limit (g/L)     | < 50                     |
| Boiling Point (°F)             | 212                      |
| Boiling Point (°C)             | 100                      |
| Freezing point (°F)            | 32                       |
| Freezing Point (°C)            | 0                        |
| Flash point (°F)               | Not Applicable           |
| Flash Point (°C)               | Not applicable           |
| Method                         | Not applicable           |
| Flammability (solid, gas)      | Not applicable           |
| Upper flammability limit:      | Not applicable           |
| Lower flammability limit:      | Not applicable           |
| Autoignition Temperature (°F)  | No information available |
| Autoignition Temperature (°C)  | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient          | No information available |

## 10. STABILITY AND REACTIVITY

|                                    |                                          |
|------------------------------------|------------------------------------------|
| Reactivity                         | Not Applicable                           |
| Chemical Stability                 | Stable under normal conditions.          |
| Conditions to avoid                | Prevent from freezing.                   |
| Incompatible Materials             | No materials to be especially mentioned. |
| Hazardous Decomposition Products   | None under normal use.                   |
| Possibility of hazardous reactions | None under normal conditions of use.     |

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

|                              |                                           |
|------------------------------|-------------------------------------------|
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. |
|------------------------------|-------------------------------------------|

#### Acute Toxicity

**Product Information**

No information available

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms**

No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Eye contact**

May cause slight irritation

**Skin contact**

Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.

**Inhalation**

May cause irritation of respiratory tract.

**Ingestion**

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Sensitization**

May cause an allergic skin reaction.

**Neurological Effects**

No information available.

**Mutagenic Effects**

Suspected of causing genetic defects.

**Reproductive Effects**

May damage fertility or the unborn child.

**Developmental Effects**

No information available.

**Target organ effects**

Respiratory system, Lungs, Eyes.

**STOT - single exposure**

No information available.

**STOT - repeated exposure**

No information available.

**Other adverse effects**

No information available.

**Aspiration Hazard**

No information available.

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

35051 mg/kg

**ATEmix (dermal)**

141584 mg/kg

**Component Information**

Caution - This mixture contains a substance not yet fully tested

| Chemical name                                                                                 | Oral LD50             | Dermal LD50              | Inhalation LC50         |
|-----------------------------------------------------------------------------------------------|-----------------------|--------------------------|-------------------------|
| Titanium dioxide<br>13463-67-7                                                                | > 2000 mg/kg ( Rat )  | -                        | > 5.09 mg/L ( Rat ) 4 h |
| Propanoic acid, 2-methyl-,<br>monoester with<br>2,2,4-trimethyl-1,3-pentanediol<br>25265-77-4 | = 6500 mg/kg ( Rat )  | > 15200 mg/kg ( Rat )    | > 3.55 mg/L ( Rat ) 6 h |
| Sodium C14-C16 olefin sulfonate<br>68439-57-6                                                 | = 2220 mg/kg ( Rat )  | > 740 mg/kg ( Rabbit )   | > 52 mg/L ( Rat ) 4 h   |
| Carbamic acid,<br>1H-benzimidazol-2-yl-, methyl ester<br>10605-21-7                           | > 5050 mg/kg ( Rat )  | > 10000 mg/kg ( Rabbit ) | -                       |
| Trimethylolpropane<br>77-99-6                                                                 | = 14100 mg/kg ( Rat ) | > 10000 mg/kg ( Rabbit ) | > 0.85 mg/L ( Rat ) 4 h |

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                           | NTP |
|------------------|--------------------------------|-----|
| Titanium dioxide | 2B - Possible Human Carcinogen |     |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

### Product Information

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### Bioaccumulation

There is no data for this product.

#### Mobility in Environmental Media

No information available.

#### Ozone

Not applicable

### Component Information

#### Acute Toxicity to Fish

##### Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

##### Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

### **Acute Toxicity to Aquatic Invertebrates**

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester  
LC50: 0.22 mg/L (water flea - 48 hr.)

### **Acute Toxicity to Aquatic Plants**

No information available

## **13. DISPOSAL CONSIDERATIONS**

### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## **14. TRANSPORT INFORMATION**

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## **15. REGULATORY INFORMATION**

### **International Inventories**

TSCA: United States Yes - All components are listed or exempt.  
DSL: Canada Yes - All components are listed or exempt.

### **National Pollutant Release Inventory (NPRI)**

#### **NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

*None*

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

*None*

### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

## 16. OTHER INFORMATION

### HMIS

|                     |    |
|---------------------|----|
| Health hazards      | 2* |
| Flammability        | 0  |
| Reactivity:         | 0  |
| Personal protection | -  |

### HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 11-Sep-2025  
**Reason for revision** Not available

### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and

completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**