



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

Stain Shield

“Natural Look” Penetrating Sealer
Interior/Exterior

Stain Shield is a “State-of-the-Art” premium, oil and water repellent sealer. It maintains a “Natural Look” appearance without changing color, texture, or adding any sheen while forming a barrier that resists moisture, stains and mildew. Suitable for interior and exterior applications. This product is breathable and does not leave a surface coating.

Recommended as a top coat for Meoded plaster finishes in both interior and exterior applications, and for sealing Lime Wash in exterior applications.

FEATURES

- Unsurpassed water & oil resistance •
Excellent as a plaster seal for
interior/exterior applications
- Easy to apply
- Long Lasting
- Resists Mildew
- Resists Efflorescence

COVERAGE

One quart will seal between 80-120 square feet per two-layer application.

Coverage will vary depending on porosity and absorbency rate of surface. Temperature and application method will also affect coverage.

PREPARATION

Always read product label carefully before using. **TEST FIRST!** Due to differences in materials, always test product in several small inconspicuous areas to determine suitability of product for your use. Surface must be clean, dry, and free of all surface coatings and waxes. To remove permanent sealers, use a high

quality stripper. Let plaster finishes dry for 48 hours before applying Stain Shield.

APPLICATION

Apply generously using a solvent resistant natural bristle brush, sponge, paint roller, sprayer or paint pad. Make sure the product is spread out evenly on the surface. Allow sealant to soak into the surface. If applied too heavily, pooling and dripping may occur. Wipe off any excess material to avoid drip marks. Two coats recommended. Second coat can be applied after 1-2 hours of dry time.

Cure Time: Stain Shield cures in 24 hours.

Allow surface to dry for 24 hours, before allowing traffic. Keep surface free from staining materials for 72 hours.

NOTE: Apply when temperature is between 50°F – 90°F. Avoid puddling and rundown. If sealant comes in contact with surrounding surface, wipe off. If residue appears, reapply some Stain Shield and buff surface with a clean towel. In most instances, expense of labor exceeds material cost of sealing project. Do not under apply the product as the labor cost of doing the job twice exceeds the material costs.

Stain Resistance Tests

Independent test for staining (CTI- T-72) has shown Stain Shield to be extremely effective against a variety of contaminants on a wide range of surfaces, including limestone, concrete, marble, and quarry tile.

VOC

Stain Shield Sealer is VOC compliant.



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

CLEAN & MAINTENANCE

For any cleaning of minor stains, scrub using a rag and warm soapy water. For any rigid stains, lightly sand and re-apply sealer. Re-apply sealant every 2-5 years depending on usage.

DELIVERY, STORAGE AND HANDLING

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.

AVAILABILITY

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our website www.meodedPaint.com for referrals to local sources.

WARRANTY

Meoded Paints & Decoration™ warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also

excludes any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

WARNING!

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

TECHNICAL SERVICES & SUPPORT

Meoded provides customers with any level of assistance that may need to gain full value from our products. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need. Every Meoded product comes with instructions that are more than adequate to guide any finish contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skill and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans.