



Fire Retardant Paint

Latex Intumescent Coating
Flat FR-210

General Description

Insl-X® Fire Retardant Paint is a high-quality latex decorative, intumescent, fire retardant coating for interior ceilings, walls and trim. This product provides a high-hiding flat finish that retards flame spread by reacting to heat and forming a thick cellular char blanket (intumescence). By reducing excessive heat penetration, this product retards flame spread and minimizes smoke generation. It is suitable for primed or previously painted wood, drywall, cellulose tile, cured plaster, masonry and metal. It applies like conventional latex paint, low in VOCs, and washes without spotting. This product may also be topcoated with conventional acrylic paint without affecting the flame spread rating.

- Class "A" when tested in accordance with ASTM E84 / UL 723 & ASTM E2768
- Applies like regular paint
- Soap and water cleanup
- Low VOC

Usage

For interior use on primed or previously painted wood, drywall, cellulose tile, cured plaster, masonry and metal.

Colors	White
Bases	N/A
Colorant System	Do not tint

Technical Data

Vehicle	100% Acrylic
Pigment	Titanium Dioxide
Volume Solids	49 ± 2%
Spread Rate Per Gallon	150 Sq. Ft.
Recommended	Wet: 10.7 mils
Film Thickness	Dry: 5.2 mils
10 minute burn class A rating: ASTM E84 / UL 723 with one coat applied at a spread rate of 150 square feet/gallon (10.7 mils WFT/5.2 mils DFT)	
30 minute burn class A rating: ASTM E2768 with two coats applied at a spread rate of 150 square feet/gallon (10.7 mils WFT/5.2 mils DFT)	
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Dry Time @ 77 °F	To Touch: 30 Minutes
(25 °C) @ 50% RH	To Recoat: 2 hours
High humidity and cool temperatures will result in longer dry, recoat and service times.	
Surface Temperature	Min: 50 °F
During Application	Max: 95 °F
Viscosity	96 ± 4 KU
Flash Point	N/A
Sheen / Gloss	< 10 @ 85°
Clean Up	Warm, soapy water
Thinner	refer to page 2
Weight Per Gallon	11.5 lbs.
Storage Temperature	Min: 40 °F
	Max: 90 °F
VOC	< 50 g/L

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime plaster before and after applying patching compound. Remove any powder or loose particles.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Priming

Drywall / Plaster:

Prime All® Multi-Surface Latex Primer/Sealer (AP-1000), Aqua Lock® Plus 100% Acrylic Primer/Sealer (AQ-0XXX) or equivalent

Wood:

Aqua Lock® Plus 100% Acrylic Primer/Sealer (AQ-0XXX), Prime Lock Plus Alkyd Primer/Sealer (PS-8100) or equivalent

Bleeding Type Wood:

Prime Lock Plus Alkyd Primer/Sealer (PS-8100), Max Block™ Water-Based Stain Blocking Primer (SB-5000) or equivalent

Ferrous Metal:

Alkyd or Acrylic Metal Primer

Galvanized Metal / Aluminum:

Acrylic Metal Primer

Masonry (smooth):

Prime All® Multi-Surface Latex Primer/Sealer (AP-1000), Aqua Lock® Plus 100% Acrylic Primer/Sealer (AQ-0XXX) or equivalent

Masonry (porous):

Acrylic Block Filler

Compliance & Certifications

FEDERAL	✓
OTC	✓
OTC II	✓
CARB	✓
CARB07	✓
CARB19	✓
UTAH	✓
AZMC	✓
SCAQMD	✓



UL® Flame Spread Rating	Flame Spread Index	0
	Smoke Development Index	35

Class "A", tested over Douglas fir.
Standard 10 minute test results per ASTM E84 / UL 723

NGC® Flame Spread Rating	Flame Spread Index	Pass
	Smoke Development Index	Pass

Class "A", tested over Douglas fir.
30 minute extended test results per ASTM E2768

MPI	64
-----	----

Limitations

- Do not paint when air or surface temperature is below 50 °F (10 °C).

Technical Assistance

Available through your local authorized independent retailer.

call 1-866-708-9180
visit www.insl-x.com

Application

Stir product with a circular, lifting motion before you begin to paint. Fire Retardant Paint may be applied by brush, roller, or spray, at a rate of application not to exceed 150 square feet per gallon. Surface texture and porosity will affect actual yield. Apply when surface temperature is between 50 °F and 95 °F.

Brush: Nylon / polyester

Roller: Professional/High-Capacity Quality

Spray, Airless:

Pressure / 1,500 – 2,500 PSI

Tip / 0.013 – 0.017

Thinning/Clean Up

Thinning with clean water may be necessary under certain conditions to adjust open time or spray characteristics.

Add water – Max of 8 fl. oz. to a gallon of paint

Never add other paints or solvents.

Clean Up: Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm— www.P65Warnings.ca.gov

Refer to the product label & Safety Data Sheet for product specific information.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If swallowed, do not induce vomiting. Get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

KEEP OUT OF REACH OF CHILDREN

PROTECT FROM FREEZING

**Refer to Safety Data Sheet for additional health
and safety information.**