THE SCRAPINGHUB BLOG

Turn Web Content Into Useful Data





Scrapy & AutoExtract API integration

SCRAPY & AUTOEXTRACT API INTEGRATION

🗂 October 15, 2019 📤 Attila Tóth Q 0 Comments

We've just released a new open-source Scrapy middleware which makes it easy to integrate AutoExtract into your existing Scrapy spider. If you haven't heard about AutoExtract yet, it's an Albased web scraping tool which automatically extracts data from web pages without the need to write any code. Learn more about AutoExtract here.

Installation

This project uses Python 3.6+ and pip. A virtual environment is strongly encouraged.

```
$ pip install git+https://github.com/scrapinghub/scrapy-autoextract
```

Configuration

Enable middleware

```
DOWNLOADER_MIDDLEWARES = {
    'scrapy_autoextract.AutoExtractMiddleware': 543,
}
```

This middleware should be the last one to be executed so make sure to give it the highest value.

AutoExtract settings

Mandatory

These settings must be defined in order for AutoExtract to work.

- AUTOEXTRACT_USER: your AutoExtract API key
- AUTOEXTRACT_PAGE_TYPE: the kind of data to be extracted (current options: "product" or "article")

Optional

- AUTOEXTRACT_URL: AutoExtract service url (default: autoextract.scrapinghub.com)
- AUTOEXTRACT_TIMEOUT: response timeout from AutoExtract (default: 660 seconds)

Spider

AutoExtract requests are opt-in and they must be enabled for each request, by adding:

```
meta['autoextract'] = {'enabled': True}
```

If the request was sent to AutoExtract, inside your Scrapy spider you can access the AutoExtract result through the meta attribute:

```
def parse(self, response):
    yield response.meta['autoextract']
```

Example

```
In the Scrapy settings file:
DOWNLOADER MIDDLEWARES = {
'scrapy autoextract.AutoExtractMiddleware': 543,
}
# Disable AutoThrottle middleware
AUTHTHROTTLE ENABLED = False
AUTOEXTRACT_USER = 'my_autoextract_apikey'
AUTOEXTRACT PAGE TYPE = 'article'
In the spider:
class ExampleSpider(Spider):
    name = 'example'
    start urls = ['example.com']
    def start_requests(self):
        yield scrapy.Request(url, meta={'autoextract': {'enabled': True}}, self.r
    def parse(self, response):
        yield response.meta['autoextract']
Example output:
[{
      "query":{
         "domain": "example.com",
         "userQuery":{
            "url": "https://www.example.com/news/2019/oct/15/lorem-dolor-sit",
            "pageType": "article"
         },
         "id": "1570771884892-800e44fc7cf49259"
      },
      "article":{
         "articleBody": "Lorem ipsum dolor sit amet, consectetur adipiscing elit,
         "description": "Duis aute irure dolor in reprehenderit in voluptate velit
         "probability": 0.9717171744215637,
         "inLanguage": "en",
         "headline": "'Lorem Ipsum Dolor Sit Amet",
         "author": "Attila Toth",
         "articleBodyHtml":"<article>\n\nLorem ipsum...",
         "images":["https://i.example.com/img/media/12a71d2200e99f9fff125972b88ft
```

"mainImage":"https://i.example.com/img/media/12a71d2200e99f9fff125972b8{

}]

Limitations

- The incoming spider request is rendered by AutoExtract, not just downloaded by Scrapy, which can change the result the IP is different, headers are different, etc.
- Only GET requests are supported
- Custom headers and cookies are not supported (i.e. Scrapy features to set them don't work)
- Proxies are not supported (they would work incorrectly, sitting between Scrapy and AutoExtract, instead of AutoExtract and website)
- AutoThrottle extension can work incorrectly for AutoExtract requests, because AutoExtract timing
 can be much larger than the time required to download a page, so it's best to use
 AUTOTHROTTLE_ENABLED=False in the settings.
- Redirects are handled by AutoExtract, not by Scrapy, so these kinds of middlewares might have no effect
- Retries should be disabled, because AutoExtract handles them internally (use RETRY_ENABLED=False in the settings) There is an exception, if there are too many requests sent in a short amount of time and AutoExtract returns HTTP code 429. For that case it's best to use RETRY_HTTP_CODES=[429].

Check out the middleware on Github or learn more about AutoExtract!

Share this:

Tweet Share Like 28 Share

Related

Extracting clean article HTML with News API

March 12, 2020

In "Autoscraping", "data extraction", "AutoExtract", "News Data Extraction"

Job Postings Beta API: Extract Job Postings at Scale

March 05, 2020

In "Web Scraping", "Autoscraping", "data extraction", "Developer API", "AutoExtract", "Jobs Data"

Building spiders made easy: GUI For Your Scrapy Shell

March 03, 2020

In "Open source", "Scrapy", "spider"



NEXT Web Scraping Questions & Answers Part II

PREVIOUS > Web Scraping Questions & Answers Part I

Leave a Reply			
First Name*			
Last Name			
Email*			
Website			
Comment*			

20	Scrapy & AutoExtract API Integration
☐ I would like to receive ema	il updates from Scrapinghub on blog posts, products, news,
events and offers. You may	unsubscribe at any time.
☐ I have read and agree to So	crapinghub's Privacy Policy and Cookie Policy . *
protected by reCAPTCHA	
Privacy - Terms	
SUBMIT COMMENT	



Story of the Month

HOW TO SCRAPE THE WEB WITHOUT GETTING BLOCKED

Getting data from publicly available websites should not be a problem. In reality though, it's not that easy.

Search	n Q
AWL W	/EB DATA AT SCALE WITHOUT BOTTLENECKS OR SLOWDOWNS.
St	art your Free Trial
FOLLC	WUS
POPUI	_AR POSTS
Lear	n how to configure and utilize proxies with Python Requests module
An Ir	troduction to XPath: How to Get Started
Hand	lling JavaScript in Scrapy with Splash
How	to Build your own Price Monitoring Tool
How	to Crawl the Web Politely with Scrapy

Select Month

RECENT POSTS
Transitioning to Remote Working as a Company
A Practical Guide to Web Data QA Part I: Validation Techniques
COVID-19: Handling the Situation as a Fully Remote Company
Extracting clean article HTML with News API
Job Postings Beta API: Extract Job Postings at Scale
CATEGORIES
Select Category ▼
ARCHIVES

© 2019