

How to Complete an Interactive Configuration Process?


Mikoláš Janota Goetz Botterweck
Radu Grigore Joao Marques-Silva

Lero
University College Dublin
Ireland


lero

SFI grant no. 03/CE2/I303.1


Feature Diagrams



Feature Diagrams



Configuration



Legend


Selection

Deselection

Autoselect

Autodeselect

Configuration



Legend


Selection

Deselection

Autoselect

Autodeselect

Configuration



Legend


Selection

Deselection

Autoselect

Autodeselect

Configuration



Legend


Selection

Deselection

Autoselect

Autodeselect

"I'm Done"



Legend


Selection

Deselection

Autoselect

Autodeselect

"I'm Done"



Legend


Selection

Deselection

Autoselect

Autodeselect

"I'm Done" sometimes doesn't work



Legend


Selection

Deselection

Autoselect

Autodeselect

"I'm Done" sometimes doesn't work



Legend

Selection

Deselection

Autoselect

Autodeselect

How is a configuration process completed?

Conditions

- All features must have a value.
- Values must conform to the constraints.

How is a configuration process completed?

Conditions

- All features must have a value.
- Values must conform to the constraints.

Scenarios

- **manual** — user fills in everything

How is a configuration process completed?

Conditions

- All features must have a value.
- Values must conform to the constraints.

Scenarios

- **manual** — user fills in everything
- **blind completion** — automated tool fills in everything

How is a configuration process completed?


Conditions

- All features must have a value.
- Values must conform to the constraints.

Scenarios

- **manual** — user fills in everything
- **blind completion** — automated tool fills in everything
- **smart completion** — automated tool fills as much as possible *without making decisions* for the user

Smart Completion



Legend

Selection

Deselection

Autoselect

Autodeselect

Decisions and Dispensable Variables

- A set of variables is **deselectable** *iff* they can be all deselected all at once.

$$\mathcal{D}(\phi, X) \stackrel{\text{def}}{=} \text{SAT} \left(\phi \wedge \bigwedge_{v \in X} \neg v \right)$$

Decisions and Dispensable Variables

- A set of variables is **deselectable** *iff* they can be all deselected all at once.

$$\mathcal{D}(\phi, X) \stackrel{\text{def}}{=} \text{SAT} \left(\phi \wedge \bigwedge_{v \in X} \neg v \right)$$

- A set of variables X **must be decided** *iff*
 - 1 X it is not deselectable.
 - 2 All of the proper subsets of X are deselectable.

$$\neg \mathcal{D}(\phi, X) \wedge (\forall Y \subsetneq X) (\mathcal{D}(\phi, Y))$$

Decisions and Dispensable Variables

- A set of variables is **deselectable** *iff* they can be all deselected all at once.

$$\mathcal{D}(\phi, X) \stackrel{\text{def}}{=} \text{SAT} \left(\phi \wedge \bigwedge_{v \in X} \neg v \right)$$

- A set of variables X **must be decided** *iff*
 - 1 X it is not deselectable.
 - 2 All of the proper subsets of X are deselectable.

$$\neg \mathcal{D}(\phi, X) \wedge (\forall Y \subsetneq X) (\mathcal{D}(\phi, Y))$$

- A variable is **dispensable** *iff* it does not belong to any set that must be decided.

Examples

$$x \vee y \vee z$$

- Deselectable: $\{x, y\}$, $\{x, z\}$, $\{y, z\}$, $\{x\}$, $\{y\}$, $\{z\}$, and \emptyset
- Not deselectable: $\{x, y, z\}$
- $\{x, y, z\}$ must be decided and none of the variables are dispensable.

Examples

$$x \vee y \vee z$$

- Deselectable: $\{x, y\}$, $\{x, z\}$, $\{y, z\}$, $\{x\}$, $\{y\}$, $\{z\}$, and \emptyset
- Not deselectable: $\{x, y, z\}$
- $\{x, y, z\}$ must be decided and none of the variables are dispensable.

$$x \Rightarrow (y \vee z)$$

- $\{x, y, z\}$ is deselectable therefore does not have to be decided and all variables are dispensable.

Examples

$$x \vee y \vee z$$

- Deselectable: $\{x, y\}$, $\{x, z\}$, $\{y, z\}$, $\{x\}$, $\{y\}$, $\{z\}$, and \emptyset
- Not deselectable: $\{x, y, z\}$
- $\{x, y, z\}$ must be decided and none of the variables are dispensable.

$$x \Rightarrow (y \vee z)$$

- $\{x, y, z\}$ is deselectable therefore does not have to be decided and all variables are dispensable.

$$(x \Rightarrow (y \vee z)) \wedge x$$

- $\{y, z\}$ must be decided.


Relation to Minimal Models

- A model of a formula is (point-wise) minimal *iff* flipping some **T**ue values to **F**alse, yields a non-model.

Relation to Minimal Models

- A model of a formula is **(point-wise) minimal** iff flipping some **T** values to **F**, yields a non-model.


$$x \vee (y \wedge z)$$



Relation to Minimal Models

- A model of a formula is **(point-wise) minimal** iff flipping some **T** values to **F**, yields a non-model.


$$x \vee (y \wedge z)$$



Relation to Minimal Models

- A model of a formula is **(point-wise) minimal** iff flipping some **T** values to **F**, yields a non-model.

$$x \vee (y \wedge z)$$



Dispensable Variables and Minimal Models

- A variable is dispensable *iff* it is False in all minimal models.

Dispensable Variables and Minimal Models

- A variable is dispensable *iff* it is False in all minimal models.

$$x \vee y \vee z$$

x	y	z
T	F	F
F	T	F
F	F	T

Dispensable Variables and Minimal Models

- A variable is dispensable *iff* it is False in all minimal models.

$$x \vee y \vee z$$

x	y	z
T	F	F
F	T	F
F	F	T

$$x \Rightarrow (y \vee z)$$

x	y	z
F	F	F

Non-monotonic Reasoning

- Propositional Circumscription

$$\phi \models_{\min} \psi$$


- Generalized Closed World Assumption (GCWA)

What about non-boolean configuration?

- For a general set of possibilities, it is hard to help the user.




Allowed Possibilities




What about non-boolean configuration?

- For a general set of possibilities, it is hard to help the user.
- But it is possible, if there is a preference on the possibilities.




What about non-boolean configuration?

- For a general set of possibilities, it is hard to help the user.
- But it is possible, if there is a preference on the possibilities.
- We can focus on the **most preferred** possibilities.



What about non-boolean configuration?

- For a general set of possibilities, it is hard to help the user.
- But it is possible, if there is a preference on the possibilities.
- We can focus on the **most preferred** possibilities.



General Case Meets the Boolean Case

- A value c is **settled** for a variable v *iff* v has the value c in all most preferred possibilities.

General Case Meets the Boolean Case

- A value c is **settled** for a variable v *iff* v has the value c in all most preferred possibilities.

Settled Values and Dispensable Variables


- A variable is dispensable *iff* False is settled for it under the point-wise preference for False.

General Case Meets the Boolean Case

- A value c is **settled** for a variable v iff v has the value c in all most preferred possibilities.

Settled Values and Dispensable Variables

- A variable is dispensable iff False is settled for it under the point-wise preference for False.



Summary

- Motivation was to provide **smart completion**.

Summary

- Motivation was to provide **smart completion**.
- In configuration of Boolean constraints it led to defining **dispensable variables**.

Summary

- Motivation was to provide **smart completion**.
- In configuration of Boolean constraints it led to defining **dispensable variables**.
- Dispensable variables are closely related to **CWA**.

Summary

- Motivation was to provide **smart completion**.
- In configuration of Boolean constraints it led to defining **dispensable variables**.
- Dispensable variables are closely related to **CWA**.
- In non-Boolean case, smart completion can be provided in the presence of **preference**.

Summary

- Motivation was to provide **smart completion**.
- In configuration of Boolean constraints it led to defining **dispensable variables**.
- Dispensable variables are closely related to **CWA**.
- In non-Boolean case, smart completion can be provided in the presence of **preference**.
- Dispensable variables can be seen as a *preference for deselecting*.
- Analogously CWA as a preference for False.

Experimental Results

Name	Features	Clauses	Length	Done	Minimal models
tightvnc	21	22	5.5	5.5	1.0 ± 0.0
apl	27	41	12.2	11.9	1.0 ± 0.0
gg4	58	139	10.0	3.8	15.3 ± 22.6
berkeley	94	183	26.6	17.9	1.7 ± 1.1
violet	170	341	56.1	47.1	1.6 ± 0.9
E-shop	287	420	143	N/A	N/A