Using Java for VLSI Development

and/or

Advanced Open Source Java Software Engineering

Joseph R. Kiniry

KindSoftware, LLC and Fulcrum Microsystems, Inc.

Java for AVLSI?

- What is AVLSI?
  - Delay insensitive circuits
  - Power invariant
  - Design scalability
  - Process invariant
- How is VLSI design typically done?
  - High level specification (e.g., VHDL)
  - Low-level specification (e.g., Verilog)
  - Automated layout
- How are we doing it?
- How is Java used?

Challenges

- Performance
  - You try simulating a CPU in Java!
- Scalability
  - Massive memory and thread use
- Robustness
  - If simulation takes five days and it crashes on day four...
- **Correctness!**
  - Fabricating a chip = no patches

Design Process

- Multiple specification levels.
  - Multiple Java realizations
  - CSP (Concurrent Sequential Processes)
  - Production rules
  - Layout
- Unit testing
  - Cell, Unit, CPU
  - With and without OS
  - At multiple refinement levels
- Cosimulation for behavioral equivalence
  - Formal refinement checking

Observations

- (Mis)use of concurrency
  - Thread per anything
- Data structure (ab)use
  - Generic Java data structures
- Aimless optimization
  - (Aimless) optimization is the root of all evil.
- Untracked requirement changes
  - Complexity has a requires clause
- Documentation process
  - Least favorite part coupled with rapid corporate development and hard delivery dates.

Response

- Commercial tools where necessary
  - Analysis: JProbe and JProfiler
  - Revision control: P4 (was CVS)
  - Simulation: Cadence

- Open Source tools where possible
  - Custom code coverage: Gretel
  - Metrics: Java NCSS, SlocCount
  - Documentation: SGML and LaTeX@
  - Specification: JML
  - Build system: Ant

- Process, process, process
  - Documentation
  - **Specification**

Results

- Performance
  - Typical: 10 minute change = 10 percent
  - Atypical: one man month = 1000 percent
  - ...and nothing in between.
- Memory use
  - Garbage collection (ab)use
    - Iterators, Events, and StringBuffers
  - OS VM abuse
  - Overall memory size
- System montoring
  - Subsystem tailored to design space
  - Optional compilation
  - Framework licensing (IDebug)

Key Aspects

- Lightweight specification
  - Semantic properties via Javadoc
  - Standard system overviews
    - Abstract
    - Overview
    - Requirements
    - Dictionary
  - System tracking
    - Development state
    - Deliverabes
    - Tasks
    - Risk analysis
- High-level specification
  - Extended BON

Key Aspects, cont.

- Detailed specification
- Several alternatives, OS and commerical
  - iContract, Jass, JML, MetaMata, jContract
- Design by Contract as a start
- Model-based specification for completeness
- JML = Java Modeling Language

Semantic Properties

- Domain-specific specification constructs that augment an existing language with richer semantics.

- Used in system analysis, design, implementation, testing, and maintenance via documentation and source-code analysis and transformation tools.

- Three forms: *informal*, *semi-formal*, and *formal*.

- Advance over existing work because:

  - Specified as annotations, which is popular with programmers.

  - More natural model because little-to-no math.

  - Higher-level contructs, thus more expressive.

Example of Annotated Java

```
/**
 * Returns a boolean indicating whether any debugging facilities
 * are turned off for a particular thread.
 *
 * @concurrency GUARDED
 * @require (thread != null) Parameters must be valid.
 * @modify QUERY
 * @param thread the thread to check.
 * @return a boolean indicating whether any debugging facilities
 * are turned off for the specified thread.
 * @review kiniry Are the isOff() methods necessary at all?
 **/

public synchronized boolean isOff(Thread thread)
{
  return (!isOn(thread));
}
```

Extended BON, cont.

- Extensions - semantically well-understood best practice programming constructs in specifi c domains.

  - *concurrency* - sequential, concurrent, guarded.

  - *temporal logic contracts* - for run-time testing.

  - *modifies* - predicates about state change.

  - *generates* - concurrency dynamism.

- Bijective refi nement.

  - specifi cation changes $\leftrightarrow$ program changes.

- "Weak" language plus quality tools $\Rightarrow$ stronger system than most of industry's best practices.

Extended BON

- A lightweight specifi cation language for software.

- A design model checker for multiple languages.

- Extended BON = BON + semantic properties.

- BON - the Business Object Notation.

  - Textual and graphical syntax.

  - Well-understood semantics.

  - Seamless, reversible specifi cation language.

- BON specifi cations capture important system aspects...

  - static and dynamic structure, contracts, test cases.

- ...but are not complete and are relatively weak.

JML

- Syntax is extension of Java

- Contracts a la Eiffel
  - requires, ensures and interplay with inheritance

- Side-effects (or lack thereof)
  - pure, assignable

- Refinement (spec to impl, spec to spec)
  - also, refines

- Specification scoping (contract visibility)

- Model variables
  - Software cosimulation

- Documentation generation, static analysis, and dynamic run-time checks

JML Tools

- JMLDoc
  - JML plus Javadoc
- Typechecking
  - jml
- Compilation
  - jmlc
- Static analysis
  - ESCJava, LOOP, Daikon, etc.

For More Information

- JML
  - `http://www.jmlspecs.org/`
- Extended BON
  - `http://ebon.sf.net/`
- Fulcrum Microsystems
  - `http://www.fulcrummicro.com/`
- KindSoftware
  - `http://www.kindsoftware.com/`
    - IDebug, semantic properties, code standards, formal methods and advanced software engineering consulting, etc.