```sql
CREATE PROCEDURE DeleteStudent
    @ID INT
AS
BEGIN
    DELETE FROM Student
    WHERE Student_ID = @ID;
END;
GO

EXEC GetStudents;
EXEC InsertStudent 105, 'Karan', 80, 1;
EXEC UpdateStudent 105, 90;
EXEC DeleteStudent 105;
GO

CREATE TRIGGER CheckMarks
ON Student
AFTER INSERT, UPDATE
AS
BEGIN
    IF EXISTS (
        SELECT 1 FROM inserted
        WHERE Marks < 0 OR Marks > 100
    )
    BEGIN
        RAISERROR('Marks must be between 0 and 100', 16, 1);
        ROLLBACK TRANSACTION;
    END
END;
GO

CREATE TRIGGER StudentDelete
ON Student
AFTER DELETE
AS
BEGIN
    PRINT 'Student deleted successfully';
```

Output:

Student_ID	Name	Marks	Dept_ID	Dept_ID	Dept_Name
101	Rahul	85	1	1	CSE
102	Priya	92	2	2	IT
103	Amit	70	1	1	CSE
104	Neha	88	3	3	ECE

Student_ID	Name	Marks	Dept_ID	Dept_ID	Dept_Name
101	Rahul	85	1	1	CSE
102	Priya	92	2	2	IT
103	Amit	70	1	1	CSE
104	Neha	88	3	3	ECE

Student_ID	Name	Marks	Dept_ID	Dept_ID	Dept_Name
101	Rahul	85	1	1	CSE
103	Amit	70	1	1	CSE
102	Priya	92	2	2	IT
104	Neha	88	3	3	ECE

Student_ID	Name	Marks	Dept_ID	Dept_ID	Dept_Name
101	Rahul	85	1	1	CSE
102	Priya	92	2	2	IT
103	Amit	70	1	1	CSE
104	Neha	88	3	3	ECE