```sql
SELECT Dept_ID, COUNT(*) AS Total_Students
FROM Student
GROUP BY Dept_ID;

SELECT Dept_ID, AVG(CAST(Marks AS FLOAT)) AS Average_Marks
FROM Student
GROUP BY Dept_ID
HAVING AVG(CAST(Marks AS FLOAT)) > 75;

SELECT * FROM Student
ORDER BY Marks DESC;
GO

CREATE PROCEDURE GetStudents
AS
BEGIN
    SELECT * FROM Student;
END;
GO

CREATE PROCEDURE InsertStudent
    @ID INT, @Name VARCHAR(30), @Marks INT, @Dept INT
AS
BEGIN
    INSERT INTO Student VALUES (@ID, @Name, @Marks, @Dept);
END;
GO

CREATE PROCEDURE UpdateStudent
    @ID INT, @Marks INT
AS
BEGIN
    UPDATE Student SET Marks = @Marks
    WHERE Student_ID = @ID;
END;
GO
```

```
Dept_ID     Total_Students
----------- --------------
          1              2
          2              1
          3              1
Dept_ID     Average_Marks
----------- ------------------------
          1                   77.5
          2                   92.0
          3                   88.0
Student_ID  Name                           Marks       Dept_ID
----------- ------------------------------ ----------- -----------
        102 Priya                                   92           2
        104 Neha                                    88           3
        101 Rahul                                   85           1
        103 Amit                                    70           1
Student_ID  Name                           Marks       Dept_ID
----------- ------------------------------ ----------- -----------
        101 Rahul                                   85           1
        102 Priya                                   92           2
        103 Amit                                    70           1
        104 Neha                                    88           3
Student deleted successfully
```