PENETRATION TESTING REPORT

FOOTPRINTING, RECONNAISSANCE & NETWORK SCANNING PHASES

W2-PM-FINAL | CYBERSECURITY & ETHICAL HACKING | NETWORKWALKS

Pentester Name	**Kinza Abbasi**
Program	Networkwalks Cybersecurity & Ethical Hacking Internship (Week 2)
Report Date	10 November 2026
Modules Completed	W2-PM1: Footprinting with multiple Kali tools W2-PM2: GHDB-based footprinting W2-PM5: Zenmap network scanning W2-PM-FINAL: This report
Client / Target	1. **networkwalks.com** (public website and DNS records) 2. **My own local network** (VirtualBox host-only subnet `192.168.56.0/24` on my Windows PC)
Permission Secured?	Yes. Testing was limited to the scope defined in the Networkwalks Letter of Authorization.
Phases Covered	**Phase 1:** Reconnaissance & Footprinting **Phase 2:** Scanning & Network Discovery **Phases 3-5:** Not in scope for Week 2

1. Liability Disclaimer

I performed these activities only on systems and devices where I had written permission, or on devices and networks that I own. All material in this report is for education and research purposes only. Nothing here should be used to break the law. The instructor, the authors and Networkwalks are not responsible for how this knowledge is used. Unauthorised access is a crime in most countries, even when nothing is damaged.

2. Executive Summary

This report documents my Week 2 practical work covering the first two phases of a penetration test: **Phase 1 (Reconnaissance & Footprinting)** and **Phase 2 (Scanning & Network Discovery)**. I completed three project modules and combined them in this final report. Only passive and light information-gathering techniques and a host-discovery ping scan were used. No exploitation, brute-forcing or access to third-party systems took place.

Kali tools used	GHDB dorks documented	Math e-books verified	Live hosts found (own LAN)	Exploits attempted
6	**10**	**10**	**1**	**0**

Key outcomes

- **Technology exposure:** The site discloses **WordPress 7.1.4** and **WP Download Manager 3.3.76** through its generator metadata, and advertises its REST API (`/wp-json/`) in HTTP headers.

- **Infrastructure map:** The domain resolves to `192.232.216.135`. The same IP serves web and mail, and the name servers belong to HostGator.
- **Defences observed:** ModSecurity (SpiderLabs) WAF, HTTPS with HTTP/2, registrar lock and WHOIS privacy, and a cookie set with `Secure` and `HttpOnly` flags.
- **Gaps observed:** Several common security headers were not present in the captured response, the SPF policy ends in a soft fail (`~all`), and DNSSEC is unsigned.
- **Local scan:** The ping sweep of `192.168.56.0/24` found one live host, which is my own VirtualBox host-only adapter.
- **Ethics:** I did not open any exposed third-party camera feeds, because such devices are outside my authorised scope. Only the dorks were documented (Section 5.2).

3. Scope and Methodology

3.1 Scope

In scope	Details
networkwalks.com	Public website and associated DNS records (passive and light reconnaissance only).
My local network	The VirtualBox host-only subnet `192.168.56.0/24` on my own Windows PC.
Public search engines / GHDB	Used for research. No third-party system was contacted or accessed.

Out of scope: exploitation, privilege escalation, denial-of-service, brute-force or password attacks, access to any third-party data, social engineering, and any system not listed above.

3.2 Approach

I followed the first two phases of a standard penetration-testing workflow. For each activity I recorded the exact command, the output, and a screenshot as evidence. I then interpreted the output from an attacker's point of view and from a defender's point of view.

1. **Reconnaissance (Phase 1):** collect public information about the target using six Kali Linux tools, and study how Google dorks (GHDB) surface exposed information.
2. **Scanning (Phase 2):** identify my own IP configuration, sweep the local subnet for live hosts, and record their IP and MAC addresses and the resulting topology.
3. **Analysis:** assess the observations, rate the risk, and recommend improvements.

3.3 Test Environment

- **Kali Linux** (virtual machine) for footprinting tools.
- **Windows PC** with Nmap/Zenmap and VirtualBox for network scanning.
- **Web browser** for exploit-db.com (GHDB), Google search and OpenStax.
- **Date of testing:** 10 November 2026.

4. Tools Used

Tool	Purpose
Kali Linux / Windows	Operating systems used for reconnaissance and scanning.

Tool	Purpose
whois	Find domain registration details (registrar, dates, status, name servers).
whatweb	Fingerprint web technologies (server, CMS, plugins, IP address).
nslookup	Resolve the domain name to its IP address using DNS.
curl -I	Read the HTTP response headers of the website.
wafw00f	Detect whether a Web Application Firewall (WAF) protects the site.
dnsrecon	Enumerate DNS records (SOA, NS, MX, A, TXT, SRV).
GHDB (exploit-db.com) + Google	Google Hacking Database dorks and search operators for passive footprinting.
Zenmap (Nmap GUI)	Scan the local subnet to find live hosts, IP addresses, MAC addresses and topology.
Windows CMD (`ipconfig`)	Identify the local IP address, subnet mask and MAC address.

5. Activities Performed and Results

5.1 W2-PM1: Footprinting with Multiple Kali Tools

I ran six Kali Linux tools against `networkwalks.com`. Each tool answers a different reconnaissance question, and together they build a profile of the target without any intrusive action. Evidence is in Figure 1 to Figure 9.

Tool 1: WHOIS (domain registration)

Command: `whois networkwalks.com` | Evidence: Figure 1 to Figure 4

Item	Observation
Registrar	GoDaddy.com, LLC (IANA ID 146)
Created / Updated / Expires	6 Nov 2019 / 12 Nov 2025 / 6 Nov 2027
Domain status	clientDeleteProhibited, clientRenewProhibited, clientTransferProhibited, clientUpdateProhibited (registrar lock)
Name servers	NS6135.HOSTGATOR.COM, NS6136.HOSTGATOR.COM, NS29.DOMAINCONTROL.COM, NS30.DOMAINCONTROL.COM
DNSSEC	Unsigned
Registrant	Hidden behind a privacy service (Domains By Proxy, LLC)

> **Why it matters:** *WHOIS reveals who hosts and manages the domain. The registrar lock and privacy service are good protections, while the mixed name servers show the hosting setup an attacker would map next.*

Tool 2: WhatWeb (web technology fingerprinting)

Command: `whatweb networkwalks.com` | Evidence: Figure 5

Item	Observation
HTTP status	`https://networkwalks.com` returned **200 OK** (plain HTTP showed "Connection reset by peer")

Item	Observation
Web server	Apache
CMS	**WordPress 7.1.4**
Plugin	**WP Download Manager 3.3.76** (from generator meta tag)
Libraries	jQuery 3.7.1, Bootstrap, HTML5, Google Tag Manager
IP address / country	`192.232.216.135` / United States
Other	Contact email `info@networkwalks.com`, HttpOnly cookie `__wpdm_client`, page title "Networkwalks Academy"
Uncommon headers	permissions-policy, link, upgrade, referrer-policy, x-endurance-cache-level, x-nginx-cache

> **Why it matters:** *Exact CMS and plugin versions let an attacker look up known vulnerabilities for that software. A version number alone does not prove a weakness, but it narrows down where to look.*

Tool 3: Nslookup (DNS resolution)

Command: `nslookup networkwalks.com` | Evidence: Figure 6

The domain resolved to **192.232.216.135** (non-authoritative answer). This is the public IP address of the web server.

> **Why it matters:** *The IP address is the starting point for host-level reconnaissance such as reverse DNS, hosting identification and, with authorisation, port scanning.*

Tool 4: Curl (HTTP response headers)

Command: `curl -I https://networkwalks.com` | Evidence: Figure 7

Header	Observation
Status	HTTP/2 200
server	Apache
link	Advertises the WordPress REST API: `/wp-json/` and `/wp-json/wp/v2/pages/53`
set-cookie	`__wpdm_client` set with `secure` and `HttpOnly` flags
referrer-policy	`no-referrer-when-downgrade`
x-nginx-cache / x-endurance-cache-level	Caching layer used by the hosting provider
permissions-policy	Present
Not seen in this response	Strict-Transport-Security, Content-Security-Policy, X-Frame-Options, X-Content-Type-Options

> **Why it matters:** *Headers expose the technology stack and show which browser-side protections are enabled. The missing headers are hardening opportunities, not confirmed vulnerabilities.*

Tool 5: Wafw00f (WAF detection)

Command: `wafw00f networkwalks.com` | Evidence: Figure 8

Wafw00f v2.4.2 reported that the site is behind a **ModSecurity (SpiderLabs)** Web Application Firewall, using only two requests.

> **Why it matters:** *A WAF filters many common web attacks, so its presence is a positive control. Knowing the WAF product also tells an attacker which filtering behaviour to expect.*

Tool 6: DNSRecon (DNS enumeration)

Command: `dnsrecon -d networkwalks.com` | Evidence: Figure 9

Record	Observation
SOA	`ns6135.hostgator.com` (50.87.144.87)
NS	`ns6136.hostgator.com` (192.232.216.131) and `ns6135.hostgator.com` (50.87.144.87)
A	`networkwalks.com` to 192.232.216.135
MX	`mail.networkwalks.com` to 192.232.216.135 (same IP as the website)
TXT	Google site-verification record and an SPF record: `v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all`
SRV	8 `_autodiscover._tcp` records pointing to `cpanelemaildiscovery.cpanel.net` on port 443
DNSSEC	No answer to the DNSSEC query
Total	8 records found

> **Why it matters:** *DNS records reveal the mail setup, hosting provider and email-authentication policy. The soft-fail SPF (`~all`) is weaker than a strict policy against email spoofing, and web and mail sharing one IP suggests shared hosting.*

5.2 W2-PM2: Footprinting with the Google Hacking Database (GHDB)

GHDB is a collection of ready-made Google search queries ("dorks") hosted on exploit-db.com. Dorks use search operators such as `intitle:`, `inurl:`, `intext:`, `site:` and `filetype:` to find information that websites have left publicly indexed. Because the results come from Google, the target is never contacted directly, which makes this one of the quietest forms of footprinting. Defenders use the same dorks to check what their own domains leak.

Method: (1) open exploit-db.com and select GHDB, (2) search the keyword "cam", (3) copy a dork, (4) run it in Google, (5) review the results and record the findings. Evidence: Figure 10 and Figure 11.

Task 1: Camera-related dorks

The task asked for ten exposed camera links. The ten dorks below were selected from GHDB and run in Google. **I did not open, log in to or view any exposed camera feed.** Those devices belong to unknown third parties, and the Letter of Authorization limits testing to networkwalks.com and my own network. Accessing them would be unauthorised access, so only the dorks are documented here. One dork targets a website built for public webcams, which is not a vulnerability.

No.	Relevant Dork	What the dork targets	Link / Credentials
01	`intitle:"Index of /webcam/"`	Open directory listings named /webcam/	Link not opened (out of scope). Credentials: N/A
02	`intitle:"Toshiba Network Camera"`	Web interfaces of Toshiba network cameras	Link not opened (out of scope). Credentials: N/A
03	`intitle:"Device(IP CAMERA)" "language" -com|net`	IP camera login pages, excluding .com and .net domains	Link not opened (out of scope). Credentials: N/A
04	`intitle:"NoVus IP camera" -com`	NoVus IP camera interfaces	Link not opened (out of scope). Credentials: N/A

No.	Relevant Dork	What the dork targets	Link / Credentials
05	`inurl:webcam site:skylinewebcams.com inurl:roma`	Intentionally public tourist webcams (Rome)	Public site by design. Credentials: N/A
06	`intitle:"Login" intext:"cam"`	Login portals that mention "cam"	Link not opened (out of scope). Credentials: N/A
07	`intitle:"Login" intext:"camera"`	Login portals that mention "camera"	Link not opened (out of scope). Credentials: N/A
08	`intitle:"webcamXP" inurl:8080`	webcamXP servers on port 8080	Link not opened (out of scope). Credentials: N/A
09	`intitle:ip camera login page`	Generic IP camera login pages	Link not opened (out of scope). Credentials: N/A
10	`intitle:"Microseven M7CAM IP Camera"`	Microseven M7CAM camera interfaces	Link not opened (out of scope). Credentials: N/A

Figure 11 shows a public vendor support page for an IP camera that states the default login is "admin". This shows how default credentials are openly documented, which is why unchanged defaults on internet-facing cameras are a serious exposure.

> **Why it matters:** *Cameras and login portals that appear in search results are discoverable by anyone. Exposed devices with default or no credentials are a common cause of privacy breaches and botnet infections.*

Task 2: Downloadable mathematics e-books (PDF)

I used the dork pattern `site:openstax.org filetype:pdf "<book title>"` to locate ten free mathematics textbooks. OpenStax publishes open-licensed textbooks that are meant to be downloaded. I opened each PDF to confirm it loaded and recorded its page count (Figure 12 to Figure 21).

No.	Book	Link	Relevant Dork	PDF pages
01	Elementary Algebra 2e	openstax.org/details/books/elementary-algebra-2e	`site:openstax.org filetype:pdf "Elementary Algebra"`	1,290
02	Intermediate Algebra 2e	openstax.org/details/books/intermediate-algebra-2e	`site:openstax.org filetype:pdf "Intermediate Algebra"`	1,335
03	College Algebra 2e	openstax.org/details/books/college-algebra-2e	`site:openstax.org filetype:pdf "College Algebra"`	1,073
04	Algebra and Trigonometry	openstax.org/details/books/algebra-and-trigonometry	`site:openstax.org filetype:pdf "Algebra and Trigonometry"`	1,467
05	Precalculus 2e	openstax.org/details/books/precalculus-2e	`site:openstax.org filetype:pdf "Precalculus"`	1,411

No.	Book	Link	Relevant Dork	PDF pages
06	Calculus Volume 1	openstax.org/details/books/calculus-volume-1	`site:openstax.org filetype:pdf "Calculus Volume 1"`	769
07	Calculus Volume 2	openstax.org/details/books/calculus-volume-2	`site:openstax.org filetype:pdf "Calculus Volume 2"`	737
08	Calculus Volume 3	openstax.org/details/books/calculus-volume-3	`site:openstax.org filetype:pdf "Calculus Volume 3"`	913
09	Introductory Statistics 2e	openstax.org/details/books/introductory-statistics-2e	`site:openstax.org filetype:pdf "Introductory Statistics"`	847
10	Prealgebra 2e	openstax.org/details/books/prealgebra-2e	`site:openstax.org filetype:pdf "Prealgebra"`	1,074

No username or password was required for any of the ten downloads.

> **Why it matters:** *Public search can surface both intended files (like these textbooks) and unintended ones. The same `filetype:` and `site:` operators are used by defenders to find documents their own organisation has accidentally exposed.*

5.3 W2-PM5: Network Scanning with Zenmap

Zenmap is the official graphical interface for Nmap. I used it to discover live hosts on my own local subnet. Evidence: Figure 22 to Figure 26.

Task	Requirement	Result
1	Download and install Zenmap	Installed the official Nmap installer from nmap.org, including the Npcap driver and the Zenmap GUI. The "Nmap - Zenmap GUI" shortcut is present on the desktop.
2	Find local IP address and LAN subnet	Command `ipconfig /all`. Adapter: Ethernet 3 (VirtualBox Host-Only). IPv4 address `192.168.56.1`, subnet mask `255.255.255.0` (/24). Active subnet: **192.168.56.0/24**.
3	Find live hosts in the subnet	Zenmap target `192.168.56.0/24` with the **Ping scan** profile. Generated command: `nmap -sn 192.168.56.0/24`. Scanned 256 IP addresses in 13.71 seconds.
4	How many hosts are live?	**1 host up**
5	IP addresses of live hosts	`192.168.56.1`
6	MAC addresses of live hosts	`0A-00-27-00-00-08` (VirtualBox Host-Only adapter, from `ipconfig /all`). The physical Ethernet adapter (`80-E8-2C-58-4E-82`) was disconnected and was not part of this scan.
7	Display and save topology as PDF	Opened the **Topology** tab, enabled the **Legend**, and used **Save Graphic** to export the map as a PDF to the desktop. The map shows `localhost` linked to `192.168.56.1`.

Interpretation: The only live host is my own machine's host-only adapter, and no other virtual machines answered the ping sweep. Nmap shows hosts by pinging them, so a host that blocks ping would not appear. This is a host-discovery scan only. No ports were scanned and no service probing was done.

> **Why it matters:** *Host discovery shows which devices are reachable on a network. Defenders run it regularly to find unknown devices, and attackers run it to choose targets.*

6. Risk Analysis and Impact

The table below summarises the risks suggested by my observations. These are **observations from information gathering, not confirmed vulnerabilities**. No exploitation or vulnerability validation was performed, so further authorised testing would be needed to confirm any real weakness.

#	Finding	Evidence / Observation	Potential Impact	Risk Level
1	Web technology and version disclosure	WhatWeb showed WordPress 7.1.4 and WP Download Manager 3.3.76	Attackers can look up known issues for these exact versions if they are not kept up to date	**Medium**
2	Missing browser security headers	curl -I did not show HSTS, CSP, X-Frame-Options or X-Content-Type-Options; referrer-policy is `no-referrer-when-downgrade`	Weaker protection against clickjacking, content sniffing and downgrade attacks	**Medium**
3	Email authentication gaps	SPF ends in `~all` (soft fail); DNSSEC unsigned; DMARC not checked	Easier email spoofing and weaker DNS integrity	**Medium**
4	Server IP and shared hosting visible	Nslookup and DNSRecon show web and mail on 192.232.216.135	Gives attackers a clear infrastructure target	**Low**
5	REST API advertised	Link header exposes `/wp-json/`	Aids enumeration if the API is not restricted	**Low**
6	WAF product identifiable	Wafw00f detected ModSecurity (SpiderLabs)	Reveals part of the security architecture	**Low**
7	Public exposure through search engines	GHDB dorks locate camera interfaces and login portals; default credentials are publicly documented	Exposed devices can be found and abused by anyone	**Medium**
8	Local host visibility	Zenmap found one live host (own host-only adapter)	Unknown devices could go unnoticed without regular discovery	**Low**

Risk level key: Medium = worth fixing soon; Low = hardening or awareness item.

Positive Security Observations

- A **ModSecurity (SpiderLabs)** WAF protects the website.
- The site uses **HTTPS with HTTP/2**, and the session cookie has the **Secure** and **HttpOnly** flags.
- The domain has a **registrar lock** (four client prohibited statuses) and **WHOIS privacy**.

- A **Permissions-Policy** header is present.

7. Recommendations

Website and hosting

1. **Reduce version disclosure.** Remove or hide the generator meta tags and unnecessary version strings for WordPress and plugins.
2. **Keep software updated.** Apply WordPress core, theme and plugin updates promptly and review them against current security advisories.
3. **Add security headers.** Enable `Strict-Transport-Security`, `X-Content-Type-Options: nosniff`, a `Content-Security-Policy` (including `frame-ancestors` or `X-Frame-Options`), and consider a stricter `Referrer-Policy` such as `strict-origin-when-cross-origin`.
4. **Restrict the REST API where possible.** Limit unauthenticated access to `/wp-json/` endpoints that the site does not need.
5. **Keep the WAF tuned and monitored.** ModSecurity rules should be kept current and logs reviewed.

DNS and email

6. **Tighten email authentication.** After confirming all legitimate senders, move SPF from `~all` to `-all`, and verify that DKIM and DMARC are configured.
7. **Consider enabling DNSSEC** with the registrar and DNS provider, and review DNS records on a regular schedule.
8. **Monitor domain expiry.** Keep auto-renew enabled and registrar lock in place.

Exposure through search engines and devices

9. **Search your own domain with dorks.** Use `site:yourdomain` with `filetype:`, `intitle:"index of"` and login-related operators to find accidental exposure.
10. **Never expose cameras or admin panels directly to the internet.** Change default credentials, place devices behind a VPN or firewall, and keep firmware updated.

Network and process

11. **Run internal discovery scans regularly** and investigate any unknown device. Keep an up-to-date network diagram and device inventory.
12. **Test only with written authorisation.** Define the scope in a signed Letter of Authorization before any reconnaissance or scanning.

8. Limitations

- Findings reflect a single point in time (10 November 2026) and one response from each tool.
- The scan covered only the VirtualBox host-only subnet because the physical Ethernet adapter was disconnected.
- No port scanning, vulnerability scanning or exploitation was performed, so no risk in this report is confirmed.
- Third-party cameras discovered through dorks were deliberately not accessed.

9. Conclusion

In Week 2 I completed practical work on footprinting, reconnaissance and network scanning. With six Kali Linux tools I built a profile of `networkwalks.com`: its registrar and name servers, technology stack, IP address, HTTP headers, WAF and DNS records. With GHDB I saw how Google can act as a quiet reconnaissance tool, and how the same technique helps defenders find their own leaks. With Zenmap I identified my local network configuration, ran a host-discovery scan and exported the topology.

The main lesson is that a lot can be learned about a target before any exploitation, using only public information and light scanning. A good security report explains what was done, what was found, what it means, how risky it is and how to fix it. Most importantly, reconnaissance and scanning must stay inside an authorised scope. This is why I chose not to access exposed third-party cameras, even though the exercise could technically be done.

10. Evidence Collected

W2-PM1: Footprinting with Kali tools




Figure 1: *WHOIS: registrar, dates, status (part 1)*




Figure 2: *WHOIS: Verisign registry record (part 2)*




Figure 3: *WHOIS: registrant privacy and name servers (part 3)*




Figure 4: *WHOIS: DNSSEC and terms of use (part 4)*




Figure 5: *whatweb networkwalks.com output*



Figure 6: *nslookup resolves networkwalks.com to 192.232.216.135*




Figure 7: *curl -I https://networkwalks.com HTTP response headers*




Figure 8: *wafw00f detects ModSecurity (SpiderLabs) WAF*




Figure 9: *dnsrecon -d networkwalks.com DNS enumeration*

W2-PM2: GHDB footprinting




Figure 10: *GHDB on exploit-db.com filtered with the keyword "cam"*



Figure 11: *Public vendor IP-camera guide stating the default login is "admin"*




Figure 12: *Elementary Algebra 2e (1,290 pp.)*




Figure 13: *Intermediate Algebra 2e (1,335 pp.)*




Figure 14: *College Algebra 2e (1,073 pp.)*




Figure 15: *Algebra and Trigonometry 2e (1,467 pp.)*




Figure 16: *Precalculus 2e (1,411 pp.)*




Figure 17: *Calculus Volume 1 (769 pp.)*




Figure 18: *Calculus Volume 2 (737 pp.)*




Figure 19: *Calculus Volume 3 (913 pp.)*




Figure 20: *Introductory Statistics 2e (847 pp.)*




Figure 21: *Prealgebra 2e (1,074 pp.)*

W2-PM5: Zenmap network scanning




Figure 22: *Nmap - Zenmap GUI installed (desktop shortcut)*




Figure 23: *ipconfig shows the VirtualBox Host-Only adapter 192.168.56.1 / 255.255.255.0*

```
C:\Users\HP>ipconfig /all

Windows IP Configuration

   Host Name . . . . . . . . . . . . : kinza-abbasi
   Primary Dns Suffix  . . . . . . . :
   Node Type . . . . . . . . . . . . : Mixed
   IP Routing Enabled. . . . . . . . : No
   WINS Proxy Enabled. . . . . . . . : No

Ethernet adapter Ethernet:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . : iiudc.local
   Description . . . . . . . . . . . : Realtek PCIe GbE Family Controller
   Physical Address. . . . . . . . . : 80-E8-2C-58-4E-82
   DHCP Enabled. . . . . . . . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes

Ethernet adapter Ethernet 3:

   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : VirtualBox Host-Only Ethernet Adapter
   Physical Address. . . . . . . . . : 0A-00-27-00-00-08
   DHCP Enabled. . . . . . . . . . . : No
   Autoconfiguration Enabled . . . . : Yes
   Link-local IPv6 Address . . . . . : fe80::2bb8:d80e:d7d6:1748%8(Preferred)
   IPv4 Address. . . . . . . . . . . : 192.168.56.1(Preferred)
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . :
   DHCPv6 IAID . . . . . . . . . . . : 906625063
   DHCPv6 Client DUID. . . . . . . . : 00-01-00-01-30-D5-BC-30-80-E8-2C-58-4E-82
   NetBIOS over Tcpip. . . . . . . . : Enabled

Wireless LAN adapter Local Area Connection* 1:

   Media State . . . . . . . . . . . : Media disconnected
   Connection-specific DNS Suffix  . :
   Description . . . . . . . . . . . : Microsoft Wi-Fi Direct Virtual Adapter
```

Figure 24: *ipconfig /all shows adapter descriptions and MAC addresses*




Figure 25: *Zenmap ping scan: nmap -sn 192.168.56.0/24 (1 host up, 256 IPs scanned in 13.71 s)*




Figure 26: *Zenmap topology with legend: localhost connected to 192.168.56.1*

- End of Report -

Author

Kinza Abbasi

BSIT Student, International Islamic University Islamabad (IIUI)

Networkwalks Cybersecurity & Ethical Hacking Internship

Project Information

Program: Cybersecurity program at Networkwalks | **Week:** 02 | **Repository:** GitHub