

Quantum Error Correction and Stabilizer Codes

River McCubbin

December 12, 2024

Overview

1. Quantum Computing

Overview

1. Quantum Computing
2. Quantum Errors

Overview

1. Quantum Computing
2. Quantum Errors
3. Quantum Error Correction

Quantum Computing

	Data	Operations
Classical	Bits	Gates
Quantum	Vectors	(Unitary) Operators

Quantum States

Qubits:

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle$$

where

$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \qquad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

unit vectors in \mathbb{C}^2 , i.e. $\alpha^2 + \beta^2 = 1$.

Quantum Operations

Quantum Gates (Unitary Operators):

$$U(|\psi\rangle) = \alpha U|0\rangle + \beta U|1\rangle$$

such that

$$U^*U = UU^* = I$$

in $M_2(\mathbb{C})$.

(Complex) Tensors

$$|\psi\rangle, |\phi\rangle, |\gamma\rangle \in \mathbb{C}^2:$$

(Complex) Tensors

$|\psi\rangle, |\phi\rangle, |\gamma\rangle \in \mathbb{C}^2$:

bilinear:

$$(a|\phi\rangle) \otimes |\psi\rangle = a(|\phi\rangle \otimes |\psi\rangle) = |\phi\rangle \otimes (a|\psi\rangle)$$

$$(|\phi\rangle + |\psi\rangle) \otimes |\gamma\rangle = |\phi\rangle \otimes |\gamma\rangle + |\psi\rangle \otimes |\gamma\rangle$$

(Complex) Tensors

$|\psi\rangle, |\phi\rangle, |\gamma\rangle \in \mathbb{C}^2$:

bilinear:

$$(a|\phi\rangle) \otimes |\psi\rangle = a(|\phi\rangle \otimes |\psi\rangle) = |\phi\rangle \otimes (a|\psi\rangle)$$

$$(|\phi\rangle + |\psi\rangle) \otimes |\gamma\rangle = |\phi\rangle \otimes |\gamma\rangle + |\psi\rangle \otimes |\gamma\rangle$$

symmetric: $|\phi\rangle \otimes |\psi\rangle = |\psi\rangle \otimes |\phi\rangle$

Tensor Example

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle,$$

$$|\phi\rangle = \boldsymbol{a} |0\rangle + \boldsymbol{b} |1\rangle,$$

Tensor Example

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle,$$

$$|\phi\rangle = a |0\rangle + b |1\rangle,$$

$$\begin{aligned} |\psi\rangle \otimes |\phi\rangle &= (\alpha |0\rangle + \beta |1\rangle) \otimes (a |0\rangle + b |1\rangle) \\ &= \alpha |0\rangle \otimes a |0\rangle + \alpha |0\rangle \otimes b |1\rangle + \beta |1\rangle \otimes a |0\rangle + \beta |1\rangle \otimes b |1\rangle \\ &= a\alpha |00\rangle + b\alpha |01\rangle + a\beta |10\rangle + b\beta |11\rangle \end{aligned}$$

Multi-Qubit Gates

- ▶ Tensors of single-qubit gates $X \otimes X, I \otimes X$

Multi-Qubit Gates

- ▶ Tensors of single-qubit gates $X \otimes X, I \otimes X$
- ▶ Other: CNOT, SWAP

Common Gates

$$X|0\rangle = |1\rangle$$

$$Z|0\rangle = |0\rangle$$

$$H|0\rangle = |+\rangle$$

$$\text{CNOT}|00\rangle = |00\rangle$$

$$\text{CNOT}|10\rangle = |11\rangle$$

$$X|1\rangle = |0\rangle$$

$$Z|1\rangle = -|1\rangle$$

$$H|1\rangle = |-\rangle$$

$$\text{CNOT}|01\rangle = |01\rangle$$

$$\text{CNOT}|11\rangle = |10\rangle$$

where

$$|+\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$$

$$|-\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$$

Quantum Errors

- ▶ X errors: $X|0\rangle = |1\rangle, X|1\rangle = |0\rangle$

Quantum Errors

- ▶ X errors: $X|0\rangle = |1\rangle, X|1\rangle = |0\rangle$
- ▶ Z errors: $Z|0\rangle = |0\rangle, Z|1\rangle = -|1\rangle$

No-Cloning

There does not exist an operator U such that

$$U|\psi\rangle = |\psi\rangle \otimes |\psi\rangle$$

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via
$$\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$$

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.

Detect the syndrome by applying a controlled ZZ gate on the first two qubits controlled by the third.

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.

Detect the syndrome by applying a controlled ZZ gate on the first two qubits controlled by the third. Map the third qubit back to the standard basis by applying another H gate.

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.

Detect the syndrome by applying a controlled ZZ gate on the first two qubits controlled by the third. Map the third qubit back to the standard basis by applying another H gate.

The syndrome is 0 if no errors are detected, 1 if errors are detected.

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.

Detect the syndrome by applying a controlled ZZ gate on the first two qubits controlled by the third. Map the third qubit back to the standard basis by applying another H gate.

The syndrome is 0 if no errors are detected, 1 if errors are detected.

Correction: This code is not capable of correcting errors.

Bit Flip Code

Encoding: With input state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, encode via $\text{CNOT}(|\psi\rangle \otimes |0\rangle) \otimes |0\rangle = (\alpha|00\rangle + \beta|11\rangle) \otimes |0\rangle$

Channel: Applies an X gate to one of the first two qubits with probability p .

Syndrome: First, map the third qubit to $|+\rangle$ by applying an H gate.


Detect the syndrome by applying a controlled ZZ gate on the first two qubits controlled by the third. Map the third qubit back to the standard basis by applying another H gate.

The syndrome is 0 if no errors are detected, 1 if errors are detected.

Correction: This code is not capable of correcting errors.

Notice that this code has (in classical terms) distance 1!

Bit Flip Circuit



Example

X-Error detection example.

Example

X-Error detection example.

X-Error correction example.

Conclusion

A similar method can be used to correct Z -errors (attached file).

Conclusion

A similar method can be used to correct Z -errors (attached file).
We can extend both of these to correct arbitrary numbers of errors,
at the cost of much larger codes.

Thank You!

- [1] Jason Crann. *MATH 5821 Lecture Notes*. 2024.
- [2] Craig Gidney. *Quirk*.
<https://github.com/Strilanc/Quirk>.
- [3] Daniel Gottesman. *Stabilizer Codes and Quantum Error Correction*. 1997. arXiv: [quant-ph/9705052](https://arxiv.org/abs/quant-ph/9705052) [quant-ph].
URL: <https://arxiv.org/abs/quant-ph/9705052>.
- [4] Michael A. Nielsen and Isaac L. Chuang. *Quantum Computation and Quantum Information: 10th Anniversary Edition*. Cambridge University Press, 2010.
- [5] Joschka Roffe. “Quantum error correction: an introductory guide”. In: *Contemporary Physics* 60.3 (July 2019), pp. 226–245. ISSN: 1366-5812. DOI: [10.1080/00107514.2019.1667078](https://doi.org/10.1080/00107514.2019.1667078). URL: <http://dx.doi.org/10.1080/00107514.2019.1667078>.