

Composition of Movement Primitives

May 15, 2025

Contents

1	ProMPs	1
1.1	Recap	1
1.2	Coupling between joints	1
1.3	Hierarchical Bayesian Model	2
1.4	Via-Points Modulation	2
2	Composition of MPs	3

1 ProMPs

1.1 Recap

From (Paraschos et al., 2013, 2018):

- q_t : joint angle over time
- \dot{q}_t : joint velocity over time
- $\tau = \{q_t\}_{t=0\dots T}$: trajectory
- \mathbf{w} : weight vector of a single trajectory
- ϕ_t : basis function
- $\Phi_t = [\phi_t, \dot{\phi}_t]$: $n \times 2$ dimensional time-dependent basis matrix
- $z(t)$: monotonically increasing phase variable
- $\epsilon_y \sim \mathcal{N}(\mathbf{0}, \Sigma_y)$: zero-mean i.i.d. Gaussian noise

$$\mathbf{y}_t = \begin{bmatrix} q_t \\ \dot{q}_t \end{bmatrix} = \Phi_t^\top \mathbf{w} + \epsilon_y \quad (1)$$

$$p(\tau|\mathbf{w}) = \prod_t \mathcal{N}(\mathbf{y}_t | \Phi_t^\top \mathbf{w}, \Sigma_y) \quad (2)$$

$$p(\tau; \theta) = \int p(\tau|\mathbf{w}) \cdot p(\mathbf{w}; \theta) d\mathbf{w} \quad (3)$$

1.2 Coupling between joints

$$p(\mathbf{y}_t|\mathbf{w}) = \mathcal{N}\left(\begin{bmatrix} \mathbf{y}_{1,t} \\ \vdots \\ \mathbf{y}_{d,t} \end{bmatrix} \middle| \begin{bmatrix} \Phi_t^\top & \cdots & \mathbf{0} \\ \vdots & \ddots & \vdots \\ \mathbf{0} & \cdots & \Phi_t^\top \end{bmatrix} \mathbf{w}, \Sigma_y\right) = \mathcal{N}(\mathbf{y}_t | \Psi_t \mathbf{w}, \Sigma_y) \quad (4)$$

with:

- $\mathbf{w} = [\mathbf{w}_1^\top, \dots, \mathbf{w}_n^\top]^\top$: combined weight vector
- Φ_t : block-diagonal basis matrix containing the basis functions and their derivatives for each dimension
- $\mathbf{y}_{i,t} = [q_{i,t}, \dot{q}_{i,t}]^\top$: joint angle and velocity for the i^{th} joint

1.3 Hierarchical Bayesian Model

The Hierarchical Bayesian Model used in ProMPs is illustrated in Fig. 1.




Figure 1: Hierarchical Bayesian Model used in ProMPs.

- $\theta = \{\mu_w, \Sigma_w\}$
- $p(\mathbf{w}; \theta) = \mathcal{N}(\mathbf{w} | \mu_w, \Sigma_w)$: prior over the weight vector \mathbf{w} , with parameters θ , assumed to be Gaussian

$$p(\mathbf{y}_t; \theta) = \int \mathcal{N}(\mathbf{y}_t | \Psi_t^\top \mathbf{w}, \Sigma_y) \cdot p(\mathbf{w}; \theta) d\mathbf{w} \quad (5)$$

$$= \int \mathcal{N}(\mathbf{y}_t | \Psi_t^\top \mathbf{w}, \Sigma_y) \cdot \mathcal{N}(\mathbf{w} | \mu_w, \Sigma_w) d\mathbf{w} \quad (6)$$

$$= \int \mathcal{N}(\mathbf{w} | \Psi_t^\top \mathbf{w}, \Sigma_w + \Sigma_y) d\mathbf{w} \quad (\text{product of Gaussian densities}) \quad (7)$$

$$\dots \text{Missing development} \dots \quad (8)$$

$$= \mathcal{N}(\mathbf{y}_t | \Psi_t^\top \mu_w, \Psi_t^\top \Sigma_w \Psi_t + \Sigma_y) \quad (9)$$

1.4 Via-Points Modulation

- $\mathbf{x}_t^* = [\mathbf{y}_t^*, \Sigma_t^*]$: desired observation
- \mathbf{y}_t^* : desired position and velocity vector at time t
- Σ_t^* : accuracy of the desired observation

Using Bayes rule:

$$p(\mathbf{w} | \mathbf{x}_t^*) = \frac{p(\mathbf{x}_t^* | \mathbf{w}) \cdot p(\mathbf{w})}{p(\mathbf{x}_t^*)} \quad (10)$$

$$p(\mathbf{w} | \mathbf{x}_t^*) \propto \mathcal{N}(\mathbf{y}_t^* | \Psi_t^\top \mathbf{w}, \Sigma_t^*) \cdot p(\mathbf{w}) \quad (11)$$

From (Deisenroth et al., 2020; Soch et al., 2025; Bishop and Bishop, 2023), the parameters of a conditional multivariate Gaussian $p(\mathbf{x} | \mathbf{y}) = \mathcal{N}(\mu_{x|y}, \Sigma_{x|y})$ are the following:

$$\mu_{x|y} = \mu_x + \Sigma_{xy} \Sigma_{yy}^{-1} (\mathbf{y} - \mu_y) \quad (12)$$

$$\Sigma_{x|y} = \Sigma_{xx} - \Sigma_{xy} \Sigma_{yy}^{-1} \Sigma_{yx} \quad (13)$$

...ToDo expand... (14)

$$\mu_w^{[new]} = \mu_w + \Sigma_w \Psi_t \left(\Sigma_y^* \Psi_t^\top \Sigma_w \Psi_t \right)^{-1} (y_t^* - \Psi_t^\top \mu_w) \quad (15)$$

$$\Sigma_w^{[new]} = \Sigma_w - \Sigma_w \Psi_t \left(\Sigma_y^* \Psi_t^\top \Sigma_w \Psi_t \right)^{-1} \Psi_t^\top \Sigma_w \quad (16)$$

2 Composition of MPs

ToDo

References

- A. Paraschos, C. Daniel, J. R. Peters, and G. Neumann, “Probabilistic Movement Primitives,” in *Advances in Neural Information Processing Systems*, vol. 26. Curran Associates, Inc., 2013. [Online]. Available: <https://proceedings.neurips.cc/paper/2013/hash/e53a0a2978c28872a4505bdb51db06dc-Abstract.html>
- A. Paraschos, C. Daniel, J. Peters, and G. Neumann, “Using probabilistic movement primitives in robotics,” *Autonomous Robots*, vol. 42, no. 3, pp. 529–551, Mar. 2018. [Online]. Available: <https://doi.org/10.1007/s10514-017-9648-7>
- M. P. Deisenroth, A. A. Faisal, and C. S. Ong, *Mathematics for machine learning*. Cambridge University Press, 2020.
- J. Soch, T. B. of Statistical Proofs, K. Saritaş, Maja, P. Monticone, T. J. Faulkenberry, O. A. Martin, A. Kipnis, S. Balkus, lfkdlfdlk, C. Allefeld, H. Atze, A. Knapp, C. D. McInerney, Lo4ding00, V. Ohan, amvosk, and maxgrozo, “Statproofbook/statproofbook.github.io: Statproofbook 2024,” Jan. 2025. [Online]. Available: <https://doi.org/10.5281/zenodo.14646799>
- C. Bishop and H. Bishop, *Deep Learning: Foundations and Concepts*. Springer International Publishing, 2023. [Online]. Available: <https://books.google.com/books?id=0uTgEAAQBAJ>