I set the bar at 0.20.

My own test needed 0.72.

I built a benchmark that compares seven ways to build a portfolio across 18 US ETFs over 168 months, after trading costs, under a rule fixed before the run. The best one still failed the rule.

What this is

An open-source evaluation benchmark for regularized portfolio models — models that shrink noisy historical estimates before choosing weights. I built it as a third-year Machine Learning student to work on the part of empirical research that is easy to skip: whether a model's edge is real, and whether the evaluation can see it. It is not a trading strategy or investment advice.

The short version: the portfolio was not clearly better, and the test was too weak to detect the improvement I said would matter.



The test's 80% detection threshold, in net excess Sharpe. A real 0.20 improvement would usually be missed.

The result is a correction of the test, not a win for the portfolio.

THE PROBLEM

Portfolio construction is an estimation problem.

The standard method estimates average returns and correlations from history, then picks the portfolio with the best trade-off between return and risk. The estimates are noisy. The optimizer can load on assets that looked good by chance. With 18 assets and 60 months of history, there are more parameters than independent observations; regularization — shrinking noisy estimates — is the standard response.

The project asks a narrow question: do "robust" methods — a shrinkage covariance (which pulls noisy correlations toward a simpler estimate), a Black–Litterman mean (which blends the historical average with a prior) — beat a plain baseline out of sample, after costs, once you account for having tried more than one method?

Why it matters

A better estimator is only useful if it survives the noise, the costs, and the decision. That is what the benchmark tests.

This is a question about evidence, not a pitch for a strategy.

WHAT I BUILT

A benchmark, not a backtest.

The engine	A walk-forward test: re-estimate each month on the previous 60 months, then test the next month. 168 out-of-sample months in 14 non-overlapping folds.
The universe	18 US ETFs across equity, bonds, commodities and real estate; eligibility rules applied at each date.
The methods	Five standard baselines plus two variants that change one assumption in the standard mean-variance model.
The apparatus	A pre-registered decision rule, a leakage test suite, a numerical check that the optimizer solved the problem, and a reproduction check.

1176 optimizer solves; every one checked numerically. The code and the frozen data snapshot are public.

The benchmark is the deliverable, not just the headline number.

HOW I JUDGED IT

One metric, one rule, fixed before the run.

Net excess Sharpe: return above cash, after 10 bps (0.10%) one-way trading costs, divided by volatility. A summary of the path, not a forecast.

The rule: a method had to beat the best baseline by at least 0.20 net Sharpe, clear the significance tests (the edge is unlikely to be luck), and pass five more checks on turnover, drawdown, cost levels, folds and concentration.

Why both tests

Significance alone admits tiny effects. Size alone admits noise. Requiring both, plus robustness, is what makes a null informative.

The rule was written before the run. The run is exploratory because the planned blind test was compromised.


THE RESULT

It finished first. It still failed.

0.8538

net excess Sharpe — the highest of the seven

Gap over the best baseline	+0.064
Materiality bar	0.20
Original test (probability edge is real)	0.587 of 0.95
Checks failed	3 of 8



A ranking and a verdict are different objects.

The number is a summary of one path, not a return you could spend.

The bar was 0.20. The test needed 0.72.

A test has a detection threshold: the smallest true effect it can reliably notice. This one needed about 0.72 to have an 80% chance of noticing it. The bar was 0.20. A real 0.20 improvement would have been missed most of the time.



What went wrong

The original test compared the candidate's Sharpe with the baseline's observed Sharpe. The design was built for a paired comparison. The test was measuring a different question.

A test can be rigorous and still answer the wrong question.

THE CORRECTION

The same data, the right test.

0.917

probability M2 beats B3 on a paired resampling test

Sharpe gap	+0.064
90% range	−0.011 to 0.147
p-value	0.083
Original test	0.587

The two strategies hold almost the same portfolio ($\rho = 0.986$), so comparing them month by month is far more sensitive than comparing each to zero.

The original test was not wrong. It was answering a different question.

THE READING

The data exclude a 0.20 advantage.

0.147 < 0.20

the 90% upper bound is below the materiality bar

NOT MATERIAL

M2 is plausibly a little better. It is not materially better — not enough to justify the extra complexity. The data exclude the 0.20 improvement the study was designed to detect.

This is a bounded result: material, not material, or undecided. Here it is not material.

The result is a bound, not a shrug.

The cap did not rescue shrinkage.

I thought the 30% position cap was doing the job of keeping the portfolio simple, which would explain why the shrinkage method added nothing. I tested it.

Position limit	Shrinkage	Black–Litterman
0.20	−0.015 (−0.107, 0.073)	+0.049 (−0.031, 0.140)
0.30	−0.004 (−0.096, 0.080)	+0.064 (−0.011, 0.147)
0.40	+0.010 (−0.084, 0.097)	+0.119 (0.037, 0.206)
1.00	−0.003 (−0.095, 0.083)	+0.138 (0.044, 0.237)

Shrinkage: not supported. The gap stays at or below zero; every interval includes zero.

Black–Litterman: depends on the cap. The gap grows as the cap loosens, but remains below 0.20. The looser cap also means larger positions: the largest holding rises from 0.30 to 0.80.

The mechanism test did not support the shrinkage explanation. It did show the cap binding the mean treatment.

The benchmark itself is the result.

The headline number was not enough. The test, the benchmark and the decision rule decide what a number means.

The correction is a better test on the same data, not a new strategy.

A real test needs a new sample, registered before I look at it.

As an ML student, the lesson I would carry: a model can be well implemented and still be judged by a test that cannot see its effect.

What I would check in my own work

Before trusting a metric, ask what decision it is supposed to support. A test can be rigorous and still answer the wrong question.

Code, paper and the reproduction check: github.com/kira-ml/robustfolio