


Pattern Matching



Strings

- A string is a sequence of characters
- Examples of strings:
 - Python program
 - HTML document
 - DNA sequence
 - Digitized image
- An alphabet Σ is the set of possible characters for a family of strings
- Example of alphabets:
 - ASCII
 - Unicode
 - $\{0, 1\}$
 - $\{A, C, G, T\}$
- Let P be a string of size m
 - A substring $P[i..j]$ of P is the subsequence of P consisting of the characters with ranks between i and j
 - A prefix of P is a substring of the type $P[0..i]$
 - A suffix of P is a substring of the type $P[i..m-1]$
- Given strings T (text) and P (pattern), the pattern matching problem consists of finding a substring of T equal to P
- Applications:
 - Text editors
 - Search engines
 - Biological research

Brute-Force Pattern Matching

- The brute-force pattern matching algorithm compares the pattern P with the text T for each possible shift of P relative to T , until either
 - a match is found, or
 - all placements of the pattern have been tried
- Brute-force pattern matching runs in time $O(nm)$
- Example of worst case:
 - $T = aaa \dots ah$
 - $P = aaah$
 - may occur in images and DNA sequences
 - unlikely in English text

Algorithm *BruteForceMatch*(T, P)

Input text T of size n and pattern P of size m

Output starting index of a substring of T equal to P or -1 if no such substring exists

for $i \leftarrow 0$ **to** $n - m$

 { test shift i of the pattern }

$j \leftarrow 0$

while $j < m \wedge T[i + j] = P[j]$

$j \leftarrow j + 1$

if $j = m$

return i {match at i }

else

break while loop {mismatch}

return -1 {no match anywhere}

Right to Left Matching

- ❑ Matching the pattern from right to left
- ❑ For a pattern **abc**:

T: **bbacdcbaabcddcdaddaaabcbcb**

P: **abc**

- ❑ Worst case is still $O(n \cdot m)$

Bad Character Rule (BCR) (1)

- On a mismatch between the pattern and the text, we can shift the pattern by more than one place.

ddbb**a**cdcbaabcddcdaddaaabcbcb
acab**c**

Bad Character Rule (BCR) (2)

□ Preprocessing –

- A table, for each position in the pattern and a character, last occurrence of the mismatched character in P preceding the mismatch . $O(n |\Sigma|)$ space. $O(1)$ access time.

a c a b c
1 2 3 4 5

	1	2	3	4	5
a	1	1	3	3	3
b				4	4
c		2	2	2	5