

set9.py

```
1  # # Function to compute the LCS (Longest Common Subsequence) length table
2  def lcs_length(X, Y):
3      n, m = len(X), len(Y)
4
5      # Initialize a (n+1) x (m+1) DP table with zeros
6      L = []
7      for i in range(n + 1):
8          L.append([0] * (m + 1))
9
10     # Fill the DP table using the standard LCS recurrence relation
11     for i in range(1, n + 1):
12         for j in range(1, m + 1):
13             # If characters match, extend the LCS by 1
14             if X[i - 1] == Y[j - 1]:
15                 L[i][j] = L[i - 1][j - 1] + 1
16             # Otherwise, take the maximum from top or left cell
17             else:
18                 L[i][j] = max(L[i - 1][j], L[i][j - 1])
19     return L
20
21
22 # Function to reconstruct one possible LCS from the computed DP table
23 def reconstruct_lcs(X, Y, L):
24     i, j = len(X), len(Y)
25     lcs = [] # To store LCS characters
26     indices_X = [] # To store corresponding indices in X
27     indices_Y = [] # To store corresponding indices in Y
28
29     # Start from the bottom-right of the DP table and trace back
30     while i > 0 and j > 0:
31         # If current characters match, they are part of the LCS
32         if X[i - 1] == Y[j - 1]:
33             lcs.append(X[i - 1])
34             indices_X.append(i - 1)
35             indices_Y.append(j - 1)
36             i -= 1
37             j -= 1
38         # Move in the direction of the larger value (up or left)
39         elif L[i - 1][j] >= L[i][j - 1]:
40             i -= 1
41         else:
42             j -= 1
43
44     # Since we built the LCS in reverse order, reverse it at the end
45     lcs.reverse()
46     indices_X.reverse()
47     indices_Y.reverse()
48
```

```

49     # Return the LCS string and the corresponding indices
50     return ''.join(lcs), indices_X, indices_Y
51
52
53 # Function to neatly print the DP table with row/column labels
54 def print_LCS_table(X, Y, L):
55     n, m = len(X), len(Y)
56
57     print("LCS DP Table:")
58     # Print the header row (Y string)
59     print(" ", end="")
60     print(" ".join([''] + list(Y)))
61
62     # Print each row with corresponding X character
63     for i in range(n + 1):
64         if i == 0:
65             print('', end=" ")
66         else:
67             print(X[i - 1], end=" ")
68         print(*L[i]) # Print the DP row
69
70 X = "ABCB DAB"
71 Y = "BDCAB"
72 L = lcs_length(X, Y)
73 lcs_str, indices_X, indices_Y = reconstruct_lcs(X, Y, L)
74 print_LCS_table(X, Y, L)
75 print("\nLCS length:", L[len(X)][len(Y)])
76 print("One possible LCS:", f"\n{lcs_str}\n")
77 print("Indices in X:", indices_X)
78 print("Indices in Y:", indices_Y)
79 print("Time complexity: O(nm), Space: O(nm)")
80
81
82
83
84 # Function to compute the optimal order of matrix multiplication
85 # using Dynamic Programming (Matrix Chain Multiplication problem)
86 def matrix_chain_order(dims):
87     """
88     Parameters:
89         dims: list of matrix dimensions where the i-th matrix Ai has dimensions
90             dims[i] x dims[i+1]
91             (e.g., for matrices A1:A2:A3 with sizes 10x20, 20x30, 30x40 -> dims = [10, 20,
92 30, 40])
93
94     Returns:
95         N: 2D table storing minimum multiplication costs for each subchain
96         P: 2D table storing the index (k) where the optimal split occurs
97     """
98     n = len(dims) - 1 # Number of matrices (A0, A1, ..., A{n-1})

```

```

98
99 # Initialize DP tables:
100 # N[i][j] → minimum cost (scalar multiplications) for matrices Ai...Aj
101 # P[i][j] → split point that achieved this minimum cost
102 N = [[0] * n for _ in range(n)]
103 P = [[0] * n for _ in range(n)]
104
105 print("DP Table for chain lengths:")
106
107 # Base case: A single matrix has zero cost (no multiplication needed)
108 print(" Length 1:")
109 for i in range(n):
110     N[i][i] = 0
111     print(f" N[{i}][{i}] = 0")
112
113 # chain_len represents the number of matrices in the current subchain
114 for chain_len in range(2, n + 1):
115     print(f" Length {chain_len}:")
116     for i in range(n - chain_len + 1):
117         j = i + chain_len - 1
118         N[i][j] = float("inf") # Initialize with infinity (will take min over all k)
119
120         parts = [] # To store all possible cost expressions for clarity
121
122         # Try every possible split point k between i and j
123         for k in range(i, j):
124             # Cost of multiplying the subchains (Ai..Ak) and (A{k+1}..Aj),
125             # plus cost of multiplying the resulting two matrices
126             cost = N[i][k] + N[k + 1][j] + dims[i] * dims[k + 1] * dims[j + 1]
127
128             # Store formatted expression
129             if chain_len == 2:
130                 # For chain length 2, show only the multiplication cost
131                 parts.append(f"{dims[i]}*{dims[k+1]}*{dims[j+1]} = {cost}")
132             else:
133                 # For longer chains, include subproblem cost additions
134                 parts.append(f"{N[i][k]} + {dims[i]}*{dims[k+1]}*{dims[j+1]} = {cost}")
135
136             # If this cost is smaller than the current best, update it
137             if cost < N[i][j]:
138                 N[i][j] = cost
139                 P[i][j] = k # store split point
140
141         if chain_len == 2:
142             print(f" N[{i}][{j}] = {parts[0]}")
143         else:
144             parts_str = ", ".join(parts)
145             print(f" N[{i}][{j}] = min({parts_str}) = {N[i][j]}")
146
147 return N, P

```

```

148
149
150 def print_optimal_parenthesization(P, i, j):
151     """
152     Recursively prints the optimal parenthesization order
153     based on the split table P.
154     Example: ((A0 * A1) * (A2 * A3))
155     """
156     if i == j:
157         # Single matrix (base case)
158         print(f"A{i}", end="")
159     else:
160         # Recursively print parenthesis around subchains
161         print("(", end="")
162         print_optimal_parenthesization(P, i, P[i][j])
163         print(" * ", end="")
164         print_optimal_parenthesization(P, P[i][j] + 1, j)
165         print(")", end="")
166
167
168 dims = [3, 100, 5, 5] # Matrix dimensions: A0 = 3x100, A1 = 100x5, A2 = 5x5
169
170 N, P = matrix_chain_order(dims)
171
172 print(" Minimum cost:", N[0][len(dims) - 2])
173 print(" Optimal parenthesization: ", end="")
174 print_optimal_parenthesization(P, 0, len(dims) - 2)
175 print()
176 print(" Time complexity: O(n^3), Space complexity: O(n^2)")
177

```