Status	Finished
Started	Monday, 5 October 2026, 11:19 AM
Completed	Monday, 5 October 2026, 11:28 AM
Duration	8 mins 27 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [1, 4, 8] ✓

b. (1, 4, 8)

c. [2, 3, 9]

d. [1, 2, 4, 3, 8, 9]

Question **2**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,0,9}

b. {9}

c. {0,9} ✓

d. It will throw an error as there are two 0 while creating the set.

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40)

b. (10, 20, 30, 40) (40, 50, 60, 70, 80)

c. (30, 40, 50)(40, 50, 60, 70, 80)

d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

b. TypeError: update() doesn't allow list as a argument.

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. Name Error

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. (Computer)

b. () ✓

c. Error

d. Computer

Question **6**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove “ECE” from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. sampleSet.delete("ECE")

b. remove.sampleSet("ECE")

c. del.sampleSet("ECE")

d. sampleSet.discard("ECE") ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True
False

c. True ✓
True

d. False
True

Question **8**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t = (11, 3)
x = 3 * t
print(x)
```

- a. (11, 3, 11, 3, 11, 3) ✓
- b. (11,3)(11,3)(11,3)
- c. [11,11,11,3,3,3]
- d. (11,3,11,11,3,11,11,11,3)

Question **9**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")

print type(a)
```

- a. <class 'tuple'>
- b. <class 'int'>
- c. str
- d. <class 'str'> ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

- a. tupl1=tupl+tupl ✓
- b. tupl.append(2)
- c. tupl.sort()
- d. tupl[1]=2

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

- a. i,ii ✓
- b. ii
- c. iii
- d. All of the above

Question **12**

Incorrect

Mark 0.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

- a. ['2', '3', '8', '30']
- b. ['30', '8', '3', '2'] ✗
- c. ['8', '30', '3', '2']
- d. ['2', '3', '30', '8']

Question **13**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. (55,78,64,25)
- b. 12
- c. (12)
- d. Error ✓

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, '10', 50, 20, 60, 30} ✓

b. {40, '10', 50, 20, 60, 30}

c. {40, 10, 50, 20, 60, 30}

d. SynatxError: Different types cannot be used with sets

Question **15**

Incorrect

Mark 0.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. A new set will be created with the unique elements of set1 and set2. ✗

b. A new set will be created with the elements of both set1 and set2

c. Elements of set1 will get appended to set2

d. Elements of set2 will get appended to set1