

INCOMING QUALITY INSPECTION REPORT

#	INSPECTION PARAMETER	SPECIFICATION	NOMINAL	TOLERANCE	MIN	MAX	MEASURED	RESULT	INSTRUMENT
1	Rim Diameter	As per DWG TR-16-001	406.4 mm (16.00 in)	± 0.05 mm	406.35	406.45		PASS FAIL	CMM
2	Rim Width	As per DWG TR-16-001	203.2 mm (8.00 in)	± 0.05 mm	203.15	203.25		PASS FAIL	CMM
3	PCD (Bolt Circle)	As per DWG TR-16-001	120.00 mm	± 0.03 mm	119.97	120.03		PASS FAIL	CMM
4	Center Bore Dia	As per DWG TR-16-001	67.10 mm	+0.00/-0.02	67.08	67.10		PASS FAIL	BORE GAUGE
5	Bolt Hole Dia (x5)	As per DWG TR-16-001	14.00 mm	± 0.02 mm	13.98	14.02		PASS FAIL	PIN GAUGE
6	Offset (ET)	As per DWG TR-16-001	45.0 mm	± 0.5 mm	44.5	45.5		PASS FAIL	CMM
7	Radial Runout	ISO 1101	0.00 mm	MAX 0.3 mm	0.00	0.30		PASS FAIL	DIAL GAUGE
8	Lateral Runout	ISO 1101	0.00 mm	MAX 0.25 mm	0.00	0.25		PASS FAIL	DIAL GAUGE
9	Weight	As per BOM	9.50 kg	± 0.3 kg	9.20	9.80		PASS FAIL	SCALE
10	Surface Finish	MIL-A-8625	Ra 1.6 µm	MAX Ra 2.0	-	2.0		PASS FAIL	PROFILOMETER
11	Visual Inspection	No cracks, porosity, or casting defects	ZERO DEFECTS	-	-	-		PASS FAIL	VISUAL
12	Hardness Test	ASTM E18	95 HRB	± 5 HRB	90	100		PASS FAIL	HARDNESS TESTER

TR-16-001 | SUPPLIER: ALCOA INDIA

REVISION HISTORY

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL QC SHEET FOR 16" RIM	2025-03-01	QM
B	ADDED HARDNESS TEST FOR 16" RIM	2025-07-15	QM
C	UPDATED TOLERANCES PER ECO-2025-089	2026-01-10	QM

INSPECTION SIGN-OFF

Inspector Name: _____ Signature: _____ Date: ____/____/____
QC Manager: _____ Signature: _____ Date: ____/____/____
Lot Size: _____ Sample Size: _____ AQL: 1.0 Sampling Plan: ISO 2859-1 Level II

NOTES:

1. THIS INSPECTION SHEET IS FOR 16 INCH RIM (PART NO: TR-16-001) ONLY
2. ALL DIMENSIONS REFERENCE DRAWING TR-16-001 REV E
3. REJECT ENTIRE LOT IF ANY CRITICAL DIMENSION (ITEMS 1-6) FAILS

ACME AUTOMOTIVE COMPONENTS PVT. LTD.

PART NAME QC INSP - RIM 16 INCH	DRAWN BY K. DEEKONDA
PART NUMBER QC-TR-16-001	DATE 2026-03-05
MATERIAL N/A (INSPECTION DOC)	SCALE 1:2
REV C	SHEET 1 OF 1