

HALF ELEVATION & HALF SECTIONAL A-A
(ALONG C/L OF PROPOSED ALIGNMENT)

—C. G. or, teaching@monocero.net

NOTES: 1. ALL DIMENSIONS ARE SHOWN IN MM. LEVELS ARE IN METER & CHAINAGE ARE IN KILOMETERS UNLESS OTHERWISE MENTIONED.		29. STATE APPROVAL HAS BEEN OBTAINED FOR THE ROB. 30. FOUNDATION & STRUCTURAL DETAILS ARE TENTATIVE AND SHALL BE PROVIDED AS
--	--	--

**TYPICAL SECTION OF ROB AT APPROACH
PORTION WITH BOTH SIDE SLIP ROAD**

Diagram showing a 500mm grid and a 400mm dimension.

BH FOR P1 (BH1) DEPTH (M) NG/L
 BELOW G.L. 0.00 71 888

LONGITUDINAL SECTION
(SCALE HORIZ. 1:2000 & VERT. 1:4000)

BASALT
SLIGHTLY
WEATHERED
GREYISH STRONG
BASALT

	CONSULTANT: RITES/U/CEDS/RSP-RMUMBA/ROB-34/GAD. CONSTRUCTION: GWCE-RSP-1013-ROB HEAD, QUANTITY
--	--