# Assignment 1

February 11th, 2023

# Programming Assignment<sup>1</sup>

#### Pseudo-random Generator

[10]

Implement a provably-secure *pseudo-random generator*. Your goal is to create a pseudo-random generator which outputs a pseudo-random bit-string value of length  $\ell(n)$  when the in-class function **generate**() is invoked.

### **Pseudo-random Function**

[10]

Implement a provably-secure *pseudo-random function*. Create a keyed pseudo-random function that outputs a pseudo-random integer value when the in-class function **evaluate()** is invoked.

# Encryption Scheme against Eavesdropping Adversary [5]

Implement a secure encryption-decryption scheme for an eavesdropping attack. You must implement both the encryption and the decryption functionalities as **two different** functions.

## **CPA-Secure Encryption Scheme**

[15+10]

Implement a variable-length **CPA-secure** encryption-decryption scheme using block ciphers in **randomized counter mode** using the previously implemented PRF. Your goal is to output the *ciphertext* when the in-class function  $\mathbf{enc}()$  is invoked and return the *plaintext* when the in-class function  $\mathbf{dec}()$  is invoked. You can additionally attempt to implement other modes of operation, which will be considered as a part of **bonus**.

<sup>&</sup>lt;sup>1</sup>Only the constructions taught in class would be considered valid for the coding assignment.

### Message Authentication Codes

[20]

Implement a variable-length message authentication code scheme. You are supposed to return the tag when the in-class function mac() is invoked and return a boolean value when the function vrfy() is invoked.

CBC-MAC [20]

Implement a variable-length **CBC-MAC** using the previously implemented PRF.<sup>2</sup>

### **CCA-Secure Encryption Scheme**

[20]

Implement a **CCA-secure** scheme using the **CPA** and **CBC-MAC** implementations. You are supposed to return the *cipher-text* when the in-class function **enc()** is invoked and return the *plain-text* (or not) when the in-class function **dec()** is invoked. Can we use the variable-length MAC construction as defined in Section 5? Justify.

## Theory Assignment

Prove that the above constructions are secure in the respective adversarial settings.

### Guidelines and Submission Format

#### **Boilerplate**

The programming assignment would be automatically graded, so it's crucial that you adhere to the **boilerplate conventions**.

#### Testing

The **input** and **output** files for your testing are provided here.

<sup>&</sup>lt;sup>2</sup>Refer to pg. 121 in the textbook. It is required that you follow the third implementation.

#### **Submission Format**

Submit a zip file containing all the **codes** in respective directories with **PDFs** containing theoretical proofs to all the constructions. It must be named as *Rollno-A1.*zip. The deadline for the final submission is 11:59 PM, 21st February.

```
__init__.py
CBC_MAC
  CBC_MAC.py
  CBC_MAC.pdf
CCA
  {\tt CCA.py}
  CCA.pdf
{\tt CPA}
  CPA.py
  CPA.pdf
EAV
  EAV.py
  EAV.pdf
MAC
  MAC.py
  MAC.pdf
PRF
  PRF.py
  PRF.pdf
{\tt PRG}
   PRG.py
   PRG.pdf
```