

A palindrome is a string that reads the same from left to right as it does from right to left.

Given a string, S , of N lowercase English letters, we define a k -length rotation as cutting the first k characters from the beginning of S and appending them to the end of S . For each S , there are N possible k -length rotations (where $0 \leq k < N$). See the Explanation section for examples.

Given N and S , find all N k -length rotations of S ; for each rotated string, S_k , print the maximum possible length of any palindromic substring of S_k on a new line.

Input Format

The first line contains an integer, N (the length of S).

The second line contains a single string, S .

Constraints

- $1 \leq N \leq 5 \times 10^5$
- $0 \leq k < N$
- S is comprised of lowercase English letters.

Output Format

There should be N lines of output, where each line k contains an integer denoting the maximum length of any palindromic substring of rotation S_k .

Sample Input 0

13

```
133
134     return ans
135
136 if __name__ == '__main__':
137     fptr = open(os.environ['OUTPUT_PATH'], 'w')
138
139     n = int(input().strip())
140
141     s = input()
```

Line: 148 Col: 17

Upload Code as File

☐ Test against custom input

Run Code

Submit Code



You have earned 120.00 points!

You are now 40 points away from the 3rd star for your problem solving badge. 60%

160/200

Congratulations

You solved this challenge. Would you like to challenge your friends? [Twitter](#) [LinkedIn](#)

Next Challenge

Description Accepted × Editorial Solutions Submissions

- Constraints:**
- `1 <= haystack.length, needle.length <= 104`
 - `haystack` and `needle` consist of only lowercase English characters.



Seen this question in a real interview before? 1/6

Yes No

Accepted 43,30,027 / 9.2M Acceptance Rate 47.3 %

🏷 Topics

🔒 Companies

🔖 Similar Questions

💬 Discussion (581)

Copyright © 2026 LeetCode. All rights reserved.

👍 7.8K 🔄 581 ☆ 📄 ?

117 Online

</> Code

Python Auto

```
5
6     n = len(haystack)
7     m = len(needle)
8
9     for i in range(n - m + 1):
10         if haystack[i:i + m] == needle:
11             return i
12
13     return -1
14
15
```

Saved

Ln 14, Col 9

☑ Testcase >_ Test Result

Accepted Runtime: 0 ms

☑ Case 1 ☑ Case 2

Input

haystack =
"sadbutsad"

needle =
"sad"

Output

Given a string of lowercase letters in the range `ascii[a-z]`, determine the index of a character that can be removed to make the string a **palindrome**. There may be more than one solution, but any will do. If the word is already a palindrome or there is no solution, return `-1`. Otherwise, return the index of a character to remove.

Example

`s = "bcbc"`

Either remove 'b' at index `0` or 'c' at index `3`.

Function Description

Complete the `palindromeIndex` function in the editor below.

`palindromeIndex` has the following parameter(s):

- string `s`: a string to analyze

Returns

- int: the index of the character to remove or `-1`

Input Format

The first line contains an integer `q`, the number of queries.

Each of the next `q` lines contains a query string `s`.

Constraints

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^5 + 5$
- All characters are in the range `ascii[a-z]`.

Sample Input

```
25         return right
26     else:
27         return -1
28     left += 1
29     right -= 1
30
31     return -1
32
```

Line: 31 Col: 14

📁 Upload Code as File

☐ Test against custom input

Run Code

Submit Code



You have earned 25.00 points!

You are now 60 points away from the 2nd star for your problem solving badge.

14%

40/100

Congratulations

You solved this challenge. Would you like to challenge your friends? [Twitter](#) [LinkedIn](#)

Next Challenge

✅ Test case 0

https://leetcode.com/problems/find-all-anagrams-in-a-string/description/

Problem List

Submit

00:54:34

Premium

Description

Accepted

Editorial

Solutions

Submissions

The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- $1 \leq s.length, p.length \leq 3 \times 10^4$
- s and p consist of lowercase English letters.

Discover moreMaster Coding Skills

Seen this question in a real interview before? 1/6

YesNo

Accepted 12,89,919 / 2.4M | Acceptance Rate 54.4%

Topics

Companies

Similar Questions

Discussion (187)

13.4K18761 Online

Code

PythonAuto

```
1 class Solution(object):
2     def findAnagrams(self, s, p):
3         result = []
4
5         if len(s) < len(p):
6             return result
7
8         p_count = [0] * 26
9         s_count = [0] * 26
10
11         for i in range(len(p)):
```

SavedLn 27, Col 22

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

s =
"cbaebabacd"

p =
"abc"

Output

Search

ENG IN

09:26 02-09-2026

A space explorer's ship crashed on Mars! They send a series of SOS messages to Earth for help.



Letters in some of the SOS messages are altered by cosmic radiation during transmission. Given the signal received by Earth as a string, *s*, determine how many letters of the SOS message have been changed by radiation.

Example

```
34 s = input()
35
36 result = marsExploration(s)
37
38 fptr.write(str(result) + '\n')
39
40 fptr.close()
41
```

Line: 29 Col: 27

Upload Code as File

☐ Test against custom input

Run Code

Submit Code



You have earned 15.00 points!

You are now 15 points away from the 1st star for your problem solving badge.

50%

15/30

Congratulations

You solved this challenge. Would you like to challenge your friends? [Twitter](#) [LinkedIn](#)

Next Challenge

✓ Test case 0

Compiler Message

https://leetcode.com/problems/rotate-string/description/

Problem List

Submit

00:54:34

Premium

DescriptionAccepted × EditorialSolutionsSubmissions

Constraints:

- `1 <= s.length, goal.length <= 100`
- `s` and `goal` consist of lowercase English letters.

Discover moreOnline assessment tools

Seen this question in a real interview before? 1/6

YesNo

Accepted 10,13,017 / 1.5M | Acceptance Rate 66.6%

TopicsCompaniesDiscussion (303)

Copyright © 2026 LeetCode. All rights reserved.

5.1K30324 Online

Code

PythonAuto

```
1 class Solution(object):
2     def rotateString(self, s, goal):
3         if len(s) != len(goal):
4             return False
5
6         return goal in (s + s)
7
```

SavedLn 6, Col 31

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

s =
"m"

goal =
"f"

Output

Search

ENG IN

09:27 02-09-2026

Calculate the sum of similarities of a string S with each of it's suffixes.

Each of the next t lines contains a string to process, s .

- $1 \leq t \leq 10$
- $1 \leq |s| \leq 100000$
- s is composed of characters in the range `ascii[a-z]`

Output t lines, each containing the answer for the corresponding test case.

2
ababaa
aa

11
3

For the second case, the answer is $2 + 1 = 3$.

```
30
31     t = int(input().strip())
32
33     for t_itr in range(t):
34         s = input()
35
36         result = stringSimilarity(s)
37
38         fptr.write(str(result) + '\n')
```

Line: 42 Col: 1

 Upload Code as File☐ Test against custom input

Run Code

Submit Code



You have earned 100.00 points!

You are now 180 points away from the 4th star for your problem solving badge.

35%

295/475

You solved this challenge. Would you like to challenge your friends?

Next Challenge

✔ Test case 0

Compiler Message

Success

✓ Test case 1

✔ Test case 2

Input (stdin)

✔ Test case 3


2	ababaa
3	aa

Download

Description Accepted Editorial Solutions Submissions

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of lowercase English letters.



Seen this question in a real interview before? 1/6

Yes No

Accepted 647,236/1.3M Acceptance Rate 48.7%

Topics

Companies

Similar Questions

Discussion (159)

Copyright © 2026 LeetCode. All rights reserved.

6.9K 159

16 Online

Code

Python3 Auto

```
1 class Solution(object):
2     def repeatedSubstringPattern(self, s):
3         return s in (s + s)[1:-1]
```

Saved

Ln 3, Col 34

Test Result Testcase

Accepted Runtime: 0 ms

Case 1 Case 2 Case 3

Input

s =
"abab"

Output

true

Given two strings, determine if they share a common substring. A substring may be as small as one character.

Example

$s1 = \text{'and'}$

$s2 = \text{'art'}$

These share the common substring a .

$s1 = \text{'be'}$

$s2 = \text{'cat'}$

These do not share a substring.

Function Description

Complete the function `twoStrings` in the editor below.

`twoStrings` has the following parameter(s):

- string $s1$: a string
- string $s2$: another string

Returns

- string: either YES or NO

Input Format

The first line contains a single integer p , the number of test cases.

The following p pairs of lines are as follows:

- The first line contains string $s1$.
- The second line contains string $s2$.

Constraints

- $s1$ and $s2$ consist of characters in the range `ascii[a-z]`.
- $1 \leq p \leq 10$
- $1 \leq |s1|, |s2| \leq 10^5$

Output Format

For each pair of strings, return YES or NO.

Sample Input

```
21     return "NO"
22
23     if __name__ == '__main__':
24         fptr = open(os.environ['OUTPUT_PATH'], 'w')
25
26         q = int(input().strip())
27
28         for q_itr in range(q):
29             s1 = input()
30
31             s2 = input()
32
33             result = twoStrings(s1, s2)
34
35             fptr.write(result + '\n')
36
37         fptr.close()
38
```

Line: 21 Col: 16

Upload Code as File

Test against custom input

Run Code

Submit Code



You have earned 25.00 points!

You are now 155 points away from the 4th star for your problem solving badge.

44%

320/475

Congratulations

You solved this challenge. Would you like to challenge your friends? [Twitter](#) [LinkedIn](#)

Next Challenge

Test case 0

Compiler Message

Success

1600. Throne Inheritance

Solved

Medium Topics Companies Hint

A kingdom consists of a king, his children, his grandchildren, and so on. Every once in a while, someone in the family dies or a child is born.

The kingdom has a well-defined order of inheritance that consists of the king as the first member. Let's define the recursive function `Successor(x, curOrder)`, which given a person `x` and the inheritance order so far, returns who should be the next person after `x` in the order of inheritance.

```
Successor(x, curOrder):
    if x has no children or all of x's children are in curOrder:
        if x is the king return null
        else return Successor(x's parent, curOrder)
    else return x's oldest child who's not in curOrder
```

For example, assume we have a kingdom that consists of the king, his children Alice and Bob (Alice is older than Bob), and finally Alice's son Jack.

1. In the beginning, `curOrder` will be `["king"]`.
2. Calling `Successor(king, curOrder)` will return Alice, so we append to `curOrder` to get `["king", "Alice"]`.
3. Calling `Successor(Alice, curOrder)` will return Jack, so we append to `curOrder` to get `["king", "Alice", "Jack"]`.
4. Calling `Successor(Jack, curOrder)` will return Bob, so we append to `curOrder` to get `["king", "Alice", "Jack", "Bob"]`.

322 19

23 Online

Code

Python Auto

```
1 from collections import defaultdict
2
3 class ThroneInheritance(object):
4
5     def __init__(self, kingName):
6         self.king = kingName
7         self.family_tree = defaultdict(list)
8         self.dead = set()
9
10    def birth(self, parentName, childName):
11        self.family_tree[parentName].append(childName)
```

Saved

Ln 27, Col 21

Testcase Test Result

Accepted Runtime: 0 ms

Case 1

Input

```
["ThroneInheritance","birth","birth","birth","birth","birth","birth","getInheritanceOrder","death","getInheritanceOrder"]
```

```
[["king"],["king","andy"],["king","bob"],["king","catherine"],["andy","matthew"],["bob","alex"],["bob","asha"],[null],["bob"],[null]]
```

Output

