

SET file One-Page Protocol

Parsing - SET files are initially parsed on NewLine (LF or CRLF)

Preamble (optional) - comments containing information about the file and its content

`myconfig.set` (filename of the document - strongly recommended as the first line)

Settings for the SET-File parsing tool

Using the simplified gset protocol

Group(s) – Sections of the file containing related information, beginning with the Group name

[GROUPS]

- Each Group MUST have a unique name within the file - enclosed in square brackets []
- May only contain Letters, Numbers, hyphens (-), and underscores (_)
- A Group may contain diverse types of information: Key|Value, Table, Delimited String
- A Text-Group may be used to store extensive text information (even multi-line)
- Groups end with an empty line, the next group, [EOG] End-of-Group, or [EOF] End-of-File

[THIS-FILE] - an optional special Group containing information and settings for the file / file-parser

[THIS-FILE]

If used, this should be the first Group in the file

Version|4.2

Created | 2025-11-27

```
Delimiter|:[]:~:|:\:~:!
```

Text-Group(s) - a special type of Group

[{TEXT-GROUPS}]

- All contents of a Text-Group are a single entity allowing multiple lines and unusual characters
- No escaping is needed inside a Text-Group, all content is "as-is"
- Unlike other Groups Text-Groups do not end on empty lines.
- Text Group names may be use in a Line, as a Linked Reference -
License | [{LICENSE}]

Line(s) - within a group hold information in delimited arrays:

```
Protocol | RS232 | 9600 | 8 | N | 1 | none
```

- A Line could be just a single entry (a one-item array)
The parser might look for the contents of "line 3 of [CONFIG]" – reading the whole line, no delimiter
- A Line may be a Key|Value pair - one delimiter
- A Line may be a delimited array of data like a csv - but by default "|" pipe delimited
- A field in a line, may reference a [{TEXT-GROUP}] in the same SET File
- Spaces before/after delimiters may provide readability -
but the parser must account for its use or not, as needed
- A field within a line may itself be an array of data (nested array),
by simply using the secondary delimiter (default = !)
- {FieldNames} the first line of a Group may use field names, making the Group a table

Comments - Any text outside of a Group is considered a comment

- Any comment immediately preceding a Group is assumed to be related to that group