

LPI 101-400



Number: 101-400
Passing Score: 800
Time Limit: 120 min
File Version: 4.0



LPI Level 1 Exam 101, Junior Level Linux Certification, Part 1 of 2

Version 4.0

Sections

1. System Architecture
2. Linux Installation and Package Management
3. GNU and Unix Commands
4. Devices, Linux Filesystems, Filesystem Hierachy Standard

Exam A**QUESTION 1**

Which of the following information is stored within the BIOS? (Choose TWO correct answers.)

- A. Boot device order
- B. Linux kernel version
- C. Timezone
- D. Hardware configuration
- E. The system's hostname

Correct Answer: AD

Section: System Architecture

Explanation

Explanation/Reference:

QUESTION 2

Which of the following commands reboots the system when using SysV init? (Choose TWO correct answers.)

- A. shutdown -r now
- B. shutdown -r "rebooting"
- C. telinit 6
- D. telinit 0
- E. shutdown -k now "rebooting"

Correct Answer: AC

Section: System Architecture

Explanation

Explanation/Reference:

QUESTION 3

Which of the following are init systems used within Linux systems? (Choose THREE correct answers.)

- A. startd
- B. systemd
- C. Upstart

- D. SysInit
- E. SysV init

Correct Answer: BCE
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 4

SIMULATION

Which file in the /proc filesystem lists parameters passed from the bootloader to the kernel? (Specify the file name only without any path.)

Correct Answer: cmdline, /proc/cmdline
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 5

What information can the lspci command display about the system hardware? (Choose THREE correct answers.)

- A. Device IRQ settings
- B. PCI bus speed
- C. System battery type
- D. Device vendor identification
- E. Ethernet MAC address

Correct Answer: ABD
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 6

Which of the following commands brings a system running SysV init into a state in which it is safe to perform maintenance tasks? (Choose TWO correct answers.)

- A. shutdown -R 1 now
- B. shutdown -single now
- C. init 1
- D. telinit 1
- E. runlevel 1

Correct Answer: CD
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 7

What is the first program that is usually started, at boot time, by the Linux kernel when using SysV init?

- A. /lib/init.so
- B. /sbin/init
- C. /etc/rc.d/rcinit
- D. /proc/sys/kernel/init
- E. /boot/init

Correct Answer: B
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 8

SIMULATION

Which command will display messages from the kernel that were output during the normal boot sequence?

Correct Answer: dmesg, /bin/dmesg
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 9

Which of the following commands will write a message to the terminals of all logged in users?

- A. bcast
- B. mesg
- C. print
- D. wall
- E. yell

Correct Answer: D

Section: System Architecture

Explanation

Explanation/Reference:

QUESTION 10

Which of the following kernel parameters instructs the kernel to suppress most boot messages?

- A. silent
- B. verbose=0
- C. nomsg
- D. quiet

Correct Answer: D

Section: System Architecture

Explanation

Explanation/Reference:

QUESTION 11

Which of the following options for the kernel's command line changes the systemd boot target to rescue.target instead of the default target?

- A. systemd.target=rescue.target
- B. systemd.runlevel=rescue.target
- C. systemd.service=rescue.target
- D. systemd.default=rescue.target
- E. systemd.unit=rescue.target

Correct Answer: E
Section: System Architecture
Explanation

Explanation/Reference:

QUESTION 12

After modifying GNU GRUB's configuration file, which command must be run for the changes to take effect?

- A. kill -HUP \$(pidof grub)
- B. grub-install
- C. grub
- D. No action is required

Correct Answer: D
Section: Linux Installation and Package Management
Explanation

Explanation/Reference:

QUESTION 13

Which of the following commands is used to update the list of available packages when using dpkg based package management?

- A. apt-get update
- B. apt-get upgrade
- C. apt-cache update
- D. apt-get refresh
- E. apt-cache upgrade

Correct Answer: A
Section: Linux Installation and Package Management
Explanation

Explanation/Reference:

QUESTION 14

Which of the following commands lists the dependencies of a given dpkg package?

- A. apt-cache depends-on package
- B. apt-cache dependencies package
- C. apt-cache depends package
- D. apt-cache requires package

Correct Answer: C

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 15

Which of the following options is used in a GRUB Legacy configuration file to define the amount of time that the GRUB menu will be shown to the user?

- A. hidemenu
- B. splash
- C. timeout
- D. showmenu

Correct Answer: C

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 16

What can the Logical Volume Manager (LVM) be used for? (Choose THREE correct answers.)

- A. To create RAID 9 arrays.
- B. To dynamically change the size of logical volumes.
- C. To encrypt logical volumes.
- D. To create snapshots.
- E. To dynamically create or delete logical volumes.

Correct Answer: BDE

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 17

Which of the following commands updates the linker cache of shared libraries?

- A. mkcache
- B. soconfig
- C. mkldconfig
- D. lddconfig
- E. ldconfig

Correct Answer: E

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 18

Which of the following commands lists all currently installed packages when using RPM package management?

- A. yum --query --all
- B. yum --list --installed
- C. rpm --query --all
- D. rpm --list installed

Correct Answer: C

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 19

Which of the following commands can be used to download the RPM package kernel without installing it?

- A. yum download --no-install kernel
- B. yumdownloader kernel
- C. rpm --download --package kernel

D. rpmdownload kernel

Correct Answer: B

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 20

When using rpm --verify to check files created during the installation of RPM packages, which of the following information is taken into consideration?
(Choose THREE correct answers.)

- A. Timestamps
- B. MD5 checksums
- C. Inodes
- D. File sizes
- E. GnuPG signatures

Correct Answer: ABD

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 21

Which RPM command will output the name of the package which supplied the file /etc/exports?

- A. rpm -F /etc/exports
- B. rpm -qf /etc/exports
- C. rpm -KI /etc/exports
- D. rpm -qp /etc/exports
- E. rpm -qi /etc/exports

Correct Answer: B

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 22**SIMULATION**

In which directory must definition files be placed to add additional repositories to yum?

Correct Answer: /etc/yum.repos.d, /etc/yum.repos.d/, yum.repos.d, yum.repos.d/

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 23**SIMULATION**

What is the name of the main configuration file for GNU GRUB? (Specify the file name only without any path.)

Correct Answer: menu.lst, grub.conf, grub.cfg

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 24

When removing a package, which of the following dpkg options will completely remove the files including configuration files?

- A. --clean
- B. --delete
- C. --purge
- D. remove

Correct Answer: C

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 25

Which file should be edited to select the network locations from which Debian installation package files are loaded?

- A. /etc/dpkg/dpkg.cfg
- B. /etc/apt/apt.conf
- C. /etc/apt/apt.conf.d
- D. /etc/apt/sources.list
- E. /etc/dpkg/dselect.cfg

Correct Answer: D

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 26

SIMULATION

Which option to the yum command will update the entire system? (Specify ONLY the option name without any additional parameters.)

Correct Answer: update, upgrade

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 27

SIMULATION

Which command will disable swapping on a device? (Specify ONLY the command without any path or parameters.)

Correct Answer: swapoff, /sbin/swapoff

Section: Linux Installation and Package Management

Explanation

Explanation/Reference:

QUESTION 28

SIMULATION

Which Debian package management tool asks the configuration questions for a specific already installed package just as if the package were being installed for the first time? (Specify ONLY the command without any path or parameters.)

Correct Answer: dpkg-reconfigure

Section: Linux Installation and Package Management

Explanation**Explanation/Reference:****QUESTION 29**

Which of the following commands overwrites the bootloader located on /dev/sda without overwriting the partition table or any data following it?

- A. dd if=/dev/zero of=/dev/sda bs=512
- B. dd if=/dev/zero of=/dev/sda bs=512 count=1
- C. dd if=/dev/zero of=/dev/sda bs=440 count=1
- D. dd if=/dev/zero of=/dev/sda bs=440

Correct Answer: C

Section: Linux Installation and Package Management

Explanation**Explanation/Reference:****QUESTION 30**

Which of the following commands can be used to create a USB storage media from a disk image?

- A. gdisk
- B. dd
- C. cc
- D. fdisk
- E. mount

Correct Answer: B

Section: GNU and Unix Commands

Explanation**Explanation/Reference:****QUESTION 31**

In Bash, inserting 1>&2 after a command redirects

- A. standard error to standard input.

- B. standard input to standard error.
- C. standard output to standard error.
- D. standard error to standard output.
- E. standard output to standard input.

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 32

What command will generate a list of user names from /etc/passwd along with their login shell?

- A. column -s : 1,7 /etc/passwd
- B. chop -c 1,7 /etc/passwd
- C. colrm 1,7 /etc/passwd
- D. cut -d: -f1,7 /etc/passwd

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 33

In a nested directory structure, which find command line option would be used to restrict the command to searching down a particular number of subdirectories?

- A. -dirmax
- B. -maxdepth
- C. -maxlevels
- D. -n
- E. -s

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 34

Which of the following statements is correct regarding the command `foo 1> bar`?

- A. The stdout from the command `foo` is appended to the file `bar`.
- B. The stdout from the command `foo` overwrites the file `bar`.
- C. The command `foo` receives its stdin from the file `bar`.
- D. The command `foo` receives its stdin from the stdout of the command `bar`.
- E. The stderr from the command `foo` is saved to the file `bar`.

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 35

Which of the following commands kills the process with the PID 123 but allows the process to "clean up" before exiting?

- A. `kill -PIPE 123`
- B. `kill -KILL 123`
- C. `kill -STOP 123`
- D. `kill -TERM 123`

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 36

SIMULATION

Which signal is missing from the following command that is commonly used to instruct a daemon to reinitialize itself, including reading configuration files?

`killall -s _____ daemon`

Correct Answer: HUP, SIGHUP, 1
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 37

What is the maximum niceness value that a regular user can assign to a process with the nice command when executing a new process?

- A. 9
- B. 19
- C. 49
- D. 99

Correct Answer: B
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 38

Immediately after deleting 3 lines of text in vi and moving the cursor to a different line, which single character command will insert the deleted content below the current line?

- A. i (lowercase)
- B. P (uppercase)
- C. p (lowercase)
- D. U (uppercase)
- E. u (lowercase)

Correct Answer: C
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 39

A user accidentally created the subdirectory `\dir` in his home directory. Which of the following commands will remove that directory?

- A. `rmdir '~/\dir'`
- B. `rmdir "~/\dir"`
- C. `rmdir ~/'dir'`
- D. `rmdir ~/\dir`
- E. `rmdir ~/\dir`

Correct Answer: E

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 40

In compliance with the FHS, in which of the directories are man pages found?

- A. `/usr/share/man`
- B. `/opt/man`
- C. `/usr/doc/`
- D. `/var/pkg/man`
- E. `/var/man`

Correct Answer: A

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 41

Which of the following commands will send output from the program `myapp` to both standard output (`stdout`) and the file `file1.log`?

- A. `cat < myapp | cat > file1.log`
- B. `myapp 0>&1 | cat > file1.log`
- C. `myapp | cat > file1.log`
- D. `myapp | tee file1.log`
- E. `tee myapp file1.log`

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 42

What is the purpose of the Bash built-in export command?

- A. It allows disks to be mounted remotely.
- B. It runs a command as a process in a subshell.
- C. It makes the command history available to subshells.
- D. It sets up environment variables for applications.
- E. It shares NFS partitions for use by other systems on the network.

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 43

What is the output of the following command?

```
echo "Hello World" | tr -d aieou
```

- A. Hello World
- B. eoo
- C. Hll Wrld
- D. eoo Hll Wrld

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 44

Which of the following characters can be combined with a separator string in order to read from the current input source until the separator string, which is on a separate line and without any trailing spaces, is reached?

- A. <<
- B. <|
- C. !<
- D. &<

Correct Answer: A

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 45

In the vi editor, how can commands such as moving the cursor or copying lines into the buffer be issued multiple times or applied to multiple rows?

- A. By using the command :repeat followed by the number and the command.
- B. By specifying the number right in front of a command such as 4l or 2yj.
- C. By selecting all affected lines using the shift and cursor keys before applying the command.
- D. By issuing a command such as :set repetition=4 which repeats every subsequent command 4 times.

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 46

Which of the following files, located in the user home directory, is used to store the Bash history?

- A. .bash_history
- B. .bash_histfile
- C. .history
- D. .bashrc_history
- E. .history_bash

Correct Answer: A
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 47

SIMULATION

Which Bash environment variable defines in which file the user history is stored when exiting a Bash process? (Specify ONLY the variable name.)

Correct Answer: HISTFILE
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 48

Which of the following commands displays the contents of a gzip compressed tar archive?

- A. gzip archive.tgz | tar xvf -
- B. tar ztf archive.tgz
- C. gzip -d archive.tgz | tar tvf -
- D. tar cf archive.tgz

Correct Answer: B
Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 49

Which grep command will print only the lines that do not end with a / in the file foo?

- A. grep '\$' foo
- B. grep '/' foo
- C. grep -v '\$' foo
- D. grep -v '/' foo

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 50

Which of the following commands is used to change options and positional parameters for a running Bash?

- A. history
- B. set
- C. bashconf
- D. setsh
- E. envsetup

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 51

Which of the following commands replaces each occurrence of 'bob' in the file letter with 'Bob' and writes the result to the file newsletter?

- A. sed '/bob/Bob' letter > newsletter
- B. sed s/bob/Bob/ letter < newsletter
- C. sed 's/bob/Bob' letter > newsletter
- D. sed 's/bob/Bob/g' letter > newsletter
- E. sed 's/bob, Bob/' letter > newsletter

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 52

From a Bash shell, which of the following commands directly executes the instruction from the file /usr/local/bin/runme.sh without starting a subshell?
(Please select TWO answers.)

- A. source /usr/local/bin/runme.sh
- B. . /usr/local/bin/runme.sh
- C. /bin/bash /usr/local/bin/runme.sh
- D. /usr/local/bin/runme.sh
- E. run /usr/local/bin/runme.sh

Correct Answer: AB

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 53

Regarding the command:
nice -5 /usr/bin/prog

Which of the following statements is correct?

- A. /usr/bin/prog is executed with a nice level of -5.
- B. /usr/bin/prog is executed with a nice level of 5.
- C. /usr/bin/prog is executed with a priority of -5.
- D. /usr/bin/prog is executed with a priority of 5.

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 54

Which shell command is used to continue background execution of a suspended command?

- A. &
- B. bg
- C. cont

- D. `exec`
- E. `:&`

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 55

Which of the following shell redirections will write standard output and standard error output to a file named filename?

- A. `2>&1 >filename`
- B. `>filename 2>&1`
- C. `1>&2>filename`
- D. `>>filename`
- E. `1&2>filename`

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 56

In the vi editor, which of the following commands will copy the current line into the vi buffer?

- A. `c`
- B. `cc`
- C. `1c`
- D. `yy`
- E. `1y`

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 57

Which of the following sequences in the vi editor saves the opened document and exits the editor? (Choose TWO correct answers.)

- A. esc ZZ
- B. ctrl :w!
- C. esc zz
- D. esc :wq!
- E. ctrl XX

Correct Answer: AD

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 58

When starting a program with the nice command without any additional parameters, which nice level is set for the resulting process?

- A. -10
- B. 0
- C. 10
- D. 20

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 59

Which of the following commands will reduce all consecutive spaces down to a single space?

- A. tr '\s' ' ' < a.txt > b.txt
- B. tr -c ' ' < a.txt > b.txt
- C. tr -d ' ' < a.txt > b.txt
- D. tr -r ' ' '\n' < a.txt > b.txt

E. `tr -s ' ' < a.txt > b.txt`

Correct Answer: E

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 60

Which character, added to the end of a command, runs that command in the background as a child process of the current shell?

- A. !
- B. +
- C. &
- D. %
- E. #

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 61

Which of the following commands will print the last 10 lines of a text file to the standard output?

- A. `cat -n 10 filename`
- B. `dump -n 10 filename`
- C. `head -n 10 filename`
- D. `tail -n 10 filename`

Correct Answer: D

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 62

Which of the following commands prints a list of usernames (first column) and their primary group (fourth column) from the /etc/passwd file?

- A. `fmt -f 1,4 /etc/passwd`
- B. `split -c 1,4 /etc/passwd`
- C. `cut -d : -f 1,4 /etc/passwd`
- D. `paste -f 1,4 /etc/passwd`

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 63

Which of the following signals is sent to a process when the key combination CTRL+C is pressed on the keyboard?

- A. SIGTERM
- B. SIGINT
- C. SIGSTOP
- D. SIGKILL

Correct Answer: B

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 64

What happens after issuing the command `vi` without any additional parameters?

- A. `vi` starts and loads the last file used and moves the cursor to the position where `vi` was when it last exited.
- B. `vi` starts and requires the user to explicitly either create a new or load an existing file.
- C. `vi` exits with an error message as it cannot be invoked without a file name to operate on.
- D. `vi` starts in command mode and opens a new empty file.
- E. `vi` starts and opens a new file which is filled with the content of the `vi` buffer if the buffer contains text.

Correct Answer: D

Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 65

Which of the following command sets the Bash variable named TEST with the content FOO?

- A. set TEST="FOO"
- B. TEST = "FOO"
- C. var TEST="FOO"
- D. TEST="FOO"

Correct Answer: D

Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 66

Which variable defines the directories in which a Bash shell searches for executable commands?

- A. BASHEXEC
- B. BASHRC
- C. PATH
- D. EXECPATH
- E. PATHRC

Correct Answer: C

Section: GNU and Unix Commands
Explanation

Explanation/Reference:

QUESTION 67

Which of the following commands determines the type of a file by using a definition database file which contains information about all common file types?

- A. magic
- B. type
- C. file
- D. pmagic
- E. hash

Correct Answer: C

Section: GNU and Unix Commands

Explanation

Explanation/Reference:

QUESTION 68

Which of the following commands can be used to search for the executable file foo when it has been placed in a directory not included in \$PATH?

- A. apropos
- B. which
- C. find
- D. query
- E. whereis

Correct Answer: C

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 69

What does the command mount -a do?

- A. It ensures that all file systems listed with the option noauto in /etc/fstab are mounted.
- B. It shows all mounted file systems that have been automatically mounted.
- C. It opens an editor with root privileges and loads /etc/fstab for editing.
- D. It ensures that all file systems listed with the option auto in /etc/fstab are mounted.
- E. It ensures that all file systems listed in /etc/fstab are mounted regardless of their options.

Correct Answer: D

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard
Explanation

Explanation/Reference:

QUESTION 70

Which of the following settings for umask ensures that new files have the default permissions -rw-r----- ?

- A. 0017
- B. 0640
- C. 0038
- D. 0027

Correct Answer: D

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard
Explanation

Explanation/Reference:

QUESTION 71

Which of the following is the device file name for the second partition on the only SCSI drive?

- A. /dev/hda1
- B. /dev/sda2
- C. /dev/sd0a2
- D. /dev/sd1p2

Correct Answer: B

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard
Explanation

Explanation/Reference:

QUESTION 72

In order to display all currently mounted filesystems, which of the following commands could be used? (Choose TWO correct answers.)

- A. cat /proc/self/mounts

- B. free
- C. mount
- D. lsmounts
- E. cat /proc/filesystems

Correct Answer: AC

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 73

Which of the following commands can be used to locate programs and their corresponding man pages and configuration files?

- A. dirname
- B. which
- C. basename
- D. query
- E. whereis

Correct Answer: E

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 74

Which of the following commands changes the number of days before the ext3 filesystem on /dev/sda1 has to run through a full filesystem check while booting?

- A. tune2fs -d 200 /dev/sda1
- B. tune2fs -c 200 /dev/sda1
- C. tune2fs -i 200 /dev/sda1
- D. tune2fs -n 200 /dev/sda1
- E. tune2fs --days 200 /dev/sda1

Correct Answer: C

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 75**

Which type of filesystem is created by mkfs when it is executed with the block device name only and without any additional parameters?

- A. ext2
- B. ext3
- C. ext4
- D. XFS
- E. VFAT

Correct Answer: A

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 76**

How many fields are in a syntactically correct line of /etc/fstab?

- A. 3
- B. 4
- C. 5
- D. 6
- E. 7

Correct Answer: D

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 77****SIMULATION**

Which command is used to create and initialize the files used to store quota information? (Specify ONLY the command without any path or parameters.)

Correct Answer: quotacheck

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 78

Which of the following file permissions belong to a symbolic link?

- A. -rwxrwxrwx
- B. +rwxrwxrwx
- C. lrwxrwxrwx
- D. srwxrwxrwx

Correct Answer: C

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 79

Creating a hard link to an ordinary file returns an error. What could be the reason for this?

- A. The source file is hidden.
- B. The source file is read-only.
- C. The source file is a shell script.
- D. The source file is already a hard link.
- E. The source and the target are on different filesystems.

Correct Answer: E

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 80

Which of the following commands creates an ext3 filesystem on /dev/sdb1? (Choose TWO correct answers.)

- A. /sbin/mke2fs -j /dev/sdb1
- B. /sbin/mkfs -t ext3 /dev/sdb1
- C. /sbin/mkfs -c ext3 /dev/sdb1
- D. /sbin/mke3fs -j /dev/sdb1

Correct Answer: AB

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 81

Which of the following commands will change the quota for a specific user?

- A. edquota
- B. repquota
- C. quota -e
- D. quota

Correct Answer: A

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference:

QUESTION 82

Which utility would be used to change how often a filesystem check is performed on an ext2 filesystem without losing any data stored on that filesystem?

- A. mod2fs
- B. fsck
- C. tune2fs
- D. mke2fs
- E. fixe2fs

Correct Answer: C

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 83**

Which of the following Linux filesystems preallocates a fixed number of inodes at the filesystem's make/creation time and does NOT generate them as needed? (Choose TWO correct answers.)

- A. ext3
- B. JFS
- C. ext2
- D. XFS
- E. procfs

Correct Answer: AC

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 84**

What is the purpose of the Filesystem Hierarchy Standard?

- A. It is a security model used to ensure files are organized according to their permissions and accessibility.
- B. It provides unified tools to create, maintain and manage multiple filesystems in a common way.
- C. It defines a common internal structure of inodes for all compliant filesystems.
- D. It is a distribution neutral description of locations of files and directories.

Correct Answer: D

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation**Explanation/Reference:****QUESTION 85****SIMULATION**

Which umask value will result in the default access permissions of 600 (rw-----) for files and 700 (rwx-----) for directories? (Specify only the numerical umask value.)

Correct Answer: 0077, 077

Section: Devices, Linux Filesystems, Filesystem Hierachy Standard

Explanation

Explanation/Reference: