

Hands-on Lab: Monitoring and Optimizing Your Databases in MySQL

Estimated time needed: 45 minutes

In this lab, you'll learn how to monitor and optimize your database in MySQL with the help of phpMyAdmin.

Objectives

After completing this lab, you will be able to:

1. Maintain the health and performance of your database with phpMyAdmin
2. Identify the difference between an unoptimized and optimized database
3. Optimize your database with phpMyAdmin by applying best practices

Software Used in this Lab

In this lab, you will use [MySQL](#). MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.




To complete this lab, you will utilize the MySQL relational database service available as part of the IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

The World database used in this lab comes from the following source: <https://dev.mysql.com/doc/world-setup/en/> under [CC BY 4.0 License](#) with [Copyright 2021 - Statistics Finland](#).

You will use a modified version of the database for the lab, so to follow the lab instructions successfully please use the database provided with the lab, rather than the database from the original source.

The following ERD diagram shows the schema of the World database:




The first row is the table name, the second is the primary key, and the remaining items are any additional attributes.

Exercise 1: Create Your Database

To begin, we'll create the **World** database and load the necessary data.

1. First, we'll launch MySQL. We can do that by navigating to the **Skills Network Toolbox**, selecting **Databases** and then **MySQL**.

Press **Start**. This will start a session of MySQL in SN Labs.



The **Inactive** label will change to **Starting**. This may take a few moments.

When it changes to **Active**, it means your session has started.

The screenshot shows the Skills Network Toolbox interface. On the left, there's a sidebar with icons for various tools like File, Edit, Selection, View, Go, Run, Terminal, Help, Databases, MySQL (ACTIVE), PostgreSQL (INACTIVE), Cassandra (INACTIVE), MongoDB (INACTIVE), BIG DATA, CLOUD, OTHER, and Settings. The MySQL section is highlighted. On the right, the MySQL tab is active, showing the MySQL logo with an 'ACTIVE' status. It displays version information: v8.0.22, v5.0.4, and v14.14. A message says, "Connect to MySQL and phpMyAdmin directly in your Skills Network Labs environment." Below this are three tabs: Summary (selected), Connection Information, and Details. The Summary tab contains a note: "Your database and phpMyAdmin server are now ready to use and available with the following login credentials. For more information on how to use MySQL, please check out the Details section." It includes fields for Username and Password, both of which are redacted. Below these fields is a link to "phpMyAdmin". At the bottom, it says "You can manage MySQL via:" followed by "MySQL CLI" and "New Terminal" buttons.

2. In the menu bar, select **Terminal > New Terminal**. This will open the Terminal.

To download the zip file containing the **.sql** file for the **World** database, copy and paste the following into the Terminal:

```
1. 1
1. wget https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DB0231EN-SkillsNetwork/datasets/World/world_mysql_script.sql
```

Copied!

3. Next, initiate a MySQL command-line session by clicking **MySQL CLI** from the MySQL tab. Doing this will allow us to create a table in MySQL via the command-line.

MySQL x

MySQL

ACTIVE

v8.0.22 | v5.0.4 | v14.14

Connect to MySQL and phpMyAdmin directly in your Skills Network Labs environment.

Stop

Summary **Connection Information** **Details**

Your database and phpMyAdmin server are now ready to use and available with the following login credentials. For more details on how to navigate MySQL, please check out the Details section.

Username: [REDACTED] 


Password: [REDACTED] 

You can manage MySQL via:

phpMyAdmin 

Or to interact with the database in the terminal, select one of these options:

MySQL CLI  **New Terminal**



4. In the Terminal, create a new database called **world**.

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

5. Now, we'll want to use the newly created database, **world**. How can we go about doing that?

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

6. In order to complete the database creation process, we'll want to execute the MySQL script containing the data that we downloaded. This file will create tables and insert data into those tables.

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

This may take about thirty seconds or so.

7. With our database created, we'll want to take a look at the tables inside it to get a general idea of the data we have. What tables do we have?

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

Exercise 2: Monitor Your Database

Database monitoring refers to the tasks related to reviewing the operational status of your database. Monitoring is critical in maintaining the health and performance of your database because it'll help you identify issues in a timely manner. In doing so, you'll be able to avoid problems such as database outages that affect your users.

With phpMyAdmin, we can take a look at how our database is doing and how we can improve it.

1. In the MySQL tab, select button next to **phpMyAdmin** to access the tool in a new tab.

The screenshot shows a dark-themed MySQL monitoring interface. At the top, it displays "MySQL X" and "ACTIVE". Below that, it lists three connection details: "v8.0.22", "v5.0.4", and "v14.14". A large blue button labeled "Stop" is visible. Below these, there are three tabs: "Summary" (underlined), "Connection Information", and "Details". A message states: "Your database and phpMyAdmin server are now ready to use and available with the following details. For more information about your MySQL, please check out the Details section." It includes fields for "Username" and "Password" with copy/cut icons. A section titled "You can manage MySQL via:" contains a "phpMyAdmin" button with a red box around its icon, and another button with a square icon containing a double arrow. Below this, a message says "Or to interact with the database in the terminal, select one of these options:" followed by "MySQL CLI" and "New Terminal" buttons.

2. On the phpMyAdmin homepage, you'll notice a left sidebar and right panel.

On the left sidebar, you'll see all your databases, including the one we just created, **world**.

For now, we'll want to focus on the right panel to see more information about our servers and databases.

Select **Status**.

phpMyAdmin

Server: mysql:3306

Databases SQL Status

New

information_schema

mysql

performance_schema

sys

world

General settings

Server connection collation: utf8mb4

More settings

Appearance settings

Language English

Theme: pmahomme

3. There are several subpages on the **Status** page: **Server**, **Processes**, **Query Statistics**, **All Status Variables**, **Monitor** and **Advisor**. These subpages will give you an inside look at the current processes on your server.

The screenshot shows the MySQL Status page with the following sections:

- Network traffic since startup: 10.3 MiB**
- Traffic** (Received: 1.7 MiB, Sent: 8.7 MiB, Total: 10.3 MiB) and **Connections** (Max. concurrent connections: 4, Failed attempts: 203, Aborted: 0, Total: 1,325) tables.
- A callout box stating: "This MySQL server works as master in replication process."

Replication status

Master status


Variable	Value
File	binlog.000002
Position	1690985
Binlog_Do_DB	
Binlog_Ignore_DB	

Feel free to explore the rest of the subpages to gain a better understanding of the current status of your server.

If you'd like a refresher on the information provided by each subpage, you can revisit the previous reading, [Monitoring and Optimizing Your Databases in MySQL](#).

In this lab, we'll be taking a look at the **Monitor** subpage.

4. From the available sections, click **Monitor**.

[Server](#)[Processes](#)[Query statistics](#)[All status variables](#)[Monitor](#)[II Pause monitor](#) [Settings](#) [Instructions/Setup](#)

When you first arrive at this page, you may only have three charts: **Questions**, **Connections / Processes** and **Traffic**. We can add a few more graphs to help track important metrics.

5. Select **Settings** then **Add chart**.

[Server](#)[Processes](#)[Query statistics](#)[All status variables](#)[Monitor](#)[II Pause monitor](#) [Settings](#) [Instructions/Setup](#)[Add chart](#)[Enable charts dragging](#)Refresh rate **2**

Chart columns

5 seconds

3

Chart arrangement [?](#)[Import - Export -](#)

16

12

8

4

0

18:14:26

18:14:48

18:15:10

18:15:32

18:15:44

18:14:26



Questions




Comments



6. In the dialog box, you can choose a chart based on a status variable or select **Preset chart**. In this case, we'll be adding two preset charts.

First, let's select **System CPU Usage**.

Press **Add chart to grid**.



Now, you should see the **System CPU Usage** following chart.



Console

18:19:05

18:19:27

18:19:49

18:20:


Notice how there was a spike in your charts. Recall that **Questions** includes any queries run in the background by phpMyAdmin. In this case, the interaction was MySQL bringing up the **System CPU Usage** chart.

7. Repeat this process to add the **System memory** chart.


- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

What happens when we run a query? Let's take a look!

8. On the left sidebar, press the + sign next to the database **world**. Then, right-click **city** and select **Open link in new tab**.



Doing this will run a `SELECT * FROM city` query. Notice the spike in the charts. Hovering over the number will provide you more insight into the number of questions, or queries, that are run.



To confirm that we ran the query, we can navigate to the new tab we opened and take a look at the success message:

s.ai/tools/theia X  localhost:8080 / mysql | phpMyA X  localhost:8080 / mysql / world / >

Server: mysql:3306 » Database: world » Table: city

Browse Structure SQL Search Insert Export

Showing rows 0 - 24 (4006 total, Query took 0.0007 seconds.)

```
SELECT * FROM `city`
```

1 < > >> Number of rows: 25 Filter rows: Search this

+ Options

	ID	Name	CountryCode	District
<input type="checkbox"/>	1	Kabul	AFG	Kabol
<input type="checkbox"/>	2	Qandahar	AFG	Qandahar
<input type="checkbox"/>	3	Herat	AFG	Herat
<input type="checkbox"/>	4	Mazar-e-Sharif	AFG	Balkh
<input type="checkbox"/>	5	Amsterdam	NLD	Noord-Hol
<input type="checkbox"/>	6	Rotterdam	NLD	Zuid-Holla
<input type="checkbox"/>	7	Haag	NLD	Zuid-Holla
<input type="checkbox"/>	8	Utrecht	NLD	Utrecht
<input type="checkbox"/>	9	Eindhoven	NLD	Noord-Bra
<input type="checkbox"/>	10	Tilburg	NLD	Noord-Bra
<input type="checkbox"/>	11	Groningen	NLD	Groningen
<input type="checkbox"/>	12	Breda	NLD	Noord-Bra
<input type="checkbox"/>	13	Apoeldoorn	NLD	Goldorpen

<input type="checkbox"/>		Edit		Copy		Delete	13	Aperloo	NLD	Gelderland
<input type="checkbox"/>		Edit		Copy		Delete	14	Nijmegen	NLD	Gelderland
<input type="checkbox"/>		Edit		Copy		Delete	15	Enschede	NLD	Overijssel

Since phpMyAdmin limits queries to displaying the first 25 rows (similar to the `LIMIT` clause), the query did not take long to load.

The **Status** page is helpful in monitoring the health and performance of your server and database. Particularly with the **Monitor** page's charts, you'll be able to see real-time information on how your databases are doing. If there are unexpected irregularities, such as a sudden spike in queries or a high volume of incoming traffic, then that may point to a problem that needs to be attended to.

Exercise 3: Optimize Your Database

Database optimization refers to maximizing the speed and efficiency of retrieving data from your database. When you optimize your database, you are improving its performance, which can also improve the performance of slow queries. By optimizing your database, you'll improve the experience for both yourself and your users.

We can see this in practice with the following scenario:

Imagine that you are the organizer of a sports tournament with a total of 120 participating teams. There's three pieces of information that you've collected from each team: their (unique) team number, their three-letter team code for the system, and the date of the team's creation.

How can we go about optimizing a database containing that information? Let's take a look!

Task A: Create Your Table

1. To start, we'll create a database in phpMyAdmin.

On the left sidebar, select the **New** button to create a new database.

The screenshot shows the phpMyAdmin interface. On the left, there is a sidebar with a tree view of databases: information_schema, mysql, performance_schema, sys, and world. A red box highlights the 'New' button under the 'Databases' section. The main area has two tabs: 'General settings' and 'Appearance settings'. Under 'General settings', there is a dropdown for 'Server connection collation' set to 'utf8mb4_unicode_ci'. Under 'Appearance settings', there is a dropdown for 'Language' set to 'English' and another for 'Theme' set to 'pmahomme'.

2. On the **Databases** page, you can enter a Database name and leave it as the **UTF-8** encoding. UTF-8 is the most commonly used character encoding for content or data.

Let's call our database `tournament_teams`.

Press **Create**.

The screenshot shows the MySQL Workbench interface with the 'Databases' tab selected. At the top, there's a toolbar with icons for Databases, SQL, Status, User accounts, Export, Import, Settings, and Binary. Below the toolbar, a 'Create database' button is highlighted with a red box and labeled '1'. A dropdown menu is open, showing 'tournament_teams' selected, with another red box around it. To the right of the dropdown is a 'Create' button highlighted with a red box and labeled '2'. Below these controls is a table listing existing databases:

Database	Collation	Master replication	Action
information_schema	utf8_general_ci	Replicated	Check privileges
mysql	utf8mb4_0900_ai_ci	Replicated	Check privileges
performance_schema	utf8mb4_0900_ai_ci	Replicated	Check privileges
sys	utf8mb4_0900_ai_ci	Replicated	Check privileges
world	utf8mb4_0900_ai_ci	Replicated	Check privileges

Total: 5

At the bottom of the interface, there are buttons for 'Check all' and 'With selected: Drop'.

3. Now, we can make a table. Let's call it **teams**.

Recall the information we want to store in this database: team number, team code and team creation date. We can make three columns for that.

The screenshot shows the MySQL Workbench interface with the 'Structure' tab selected. The title bar indicates 'Server: mysql:3306 » Database: tournament_teams'. The main area displays a message: 'No tables found in database.' with a warning icon. Below this, there's a 'Create table' button highlighted with a red box and labeled '1'. The 'Name:' field contains 'teams' and is also highlighted with a red box and labeled '2'. To the right of the name field is a 'Number of columns:' input field containing '3' with an up/down arrow, also highlighted with a red box.

Press **Go**.

4. We can now add in the column names and data types.

We'll enter the following information into the table. Below are only the values that you'll need to fill out. Anything else can be left as is:

Name	Type	Length/Values
team_no	INT	
team_code	CHAR	100
creation_date	CHAR	100

Since the team number is unique, with each of the 120 teams having their own number ranging from 1 to 120, that will be our primary key. We will set that later. It is a numeric data type, so we use **INT** for now.

The team code and creation date are both set as the **CHAR** data type. Notice that for the **CHAR** type, we must include the length of the value. To be safe, we've set that to 100.

You might be thinking that these data types aren't the best choices for this database. You'd be correct! Given what we know, there are better choices for each of the entries, but let's first take a look at an unoptimized database and how we can optimize it.

When all the values are entered, press Save.

Browse **Structure** **SQL** **Search** **Insert** **Export**

Table name: teams Add 1 column(s) G

Name	Type	Length/Values	Default
team_no	INT		None
team_code	CHAR	100	None
creation_date	CHAR	100	None

Structure

Table comments:

Collation:

PARTITION definition:

Partition by: (Expression or column)

Partitions: ▲

- On the **Structure** page, select the checkbox next to **team_no** and click **Primary**.



1	#	Name	Type	Collation	Attributes	Null	Default	Com
<input checked="" type="checkbox"/>	1	team_no	int			No	None	
<input type="checkbox"/>	2	team_code	char(100)	utf8mb4_0900_ai_ci		No	None	
<input type="checkbox"/>	3	creation_date	char(100)	utf8mb4_0900_ai_ci		No	None	

 Check all

With selected:



This will set **team_no** as the primary key of the table. If you were successful in doing so, you'll receive a success message, like the following:



✓ Your SQL query has been executed successfully.

```
ALTER TABLE `teams` ADD PRIMARY KEY(`team_no`);
```

Table structure

Relation view

#	Name	Type	Collation	Attributes	Null	Default	Com
<input type="checkbox"/>	1 team_no	int			No	<i>None</i>	
<input type="checkbox"/>	2 team_code	char(100)	utf8mb4_0900_ai_ci		No	<i>None</i>	
<input type="checkbox"/>	3 creation_date	char(100)	utf8mb4_0900_ai_ci		No	<i>None</i>	



Check all

With selected:

Browse

Change

Drop



Move columns

Normalize



1

column(s)

after creation_date

Go

Indexes

Action	Keyname	Type	Unique	Packed	Column	Cardinality	Collation
Edit Drop	PRIMARY	BTREE	Yes	No	team_no	0	A

Create an index on

1

columns

Go

Notice that **team_no** was automatically added as a PRIMARY index as well.

6. Let's import the data! This sample teams data has been prepared specifically for this lab and is composed of team numbers, team code names, and the creation date of these teams.

You can download the file by clicking the following link: [tournament_teams_data.sql](#).

To import it, navigate to **Import**, then select **Browse** and find the file you just downloaded.

← Server: mysql:3306 » Database: tournament_teams » Table: teams

Browse **Structure** **SQL** **Search** **Insert** **Export**

File to import:

File may be compressed (gzip, bzip2, zip) or uncompressed.

A compressed file's name must end in **.[format].[compression]**. Example: **.sql.zip**

2

Browse your computer: **Browse...** tournament_teams_data.sql (Max: 2,048KiB)

You may also drag and drop a file on any page.

Character set of the file: **utf-8** ▾

Partial import:

Allow the interruption of an import in case the script detects it is close to the PHP tim

Skip this number of queries (for SQL) starting from the first one: **0** ▾

Other options:

Enable foreign key checks

Format:

SQL ▾

Format-specific options:

SQL compatibility mode:

NON

Do not use AUTO_INCREMENT for zero values

Press **Go**.

When your import is successful, you'll see the following message:

 ***Import has been successfully finished, 120 queries executed. (tournament_teams_da***

7. Now, we can take a look at the imported data by navigating back to **Browse**. This automatically loads a `SELECT * FROM teams` statement, which will load the first 25 rows from the **teams** table.

← Server: mysql:3306 » Database: tournament_teams » Table: teams

Browse **Structure** **SQL** **Search** **Insert** **Export**

Showing rows 0 - 24 (120 total, Query took 0.0006 seconds.)

```
SELECT * FROM `teams`
```

1 < > >> | Show all | Number of rows: 25 Filter rows

+ Options

	team_no	team_code	creation_date
<input type="checkbox"/>  Edit  Copy  Delete	1	ACE	2021-01-01
<input type="checkbox"/>  Edit  Copy  Delete	2	FAX	2021-01-03
<input type="checkbox"/>  Edit  Copy  Delete	3	RED	2021-01-04
<input type="checkbox"/>  Edit  Copy  Delete	4	MAZ	2021-01-05
<input type="checkbox"/>  Edit  Copy  Delete	5	AMS	2021-01-06
<input type="checkbox"/>  Edit  Copy  Delete	6	ROT	2022-02-10
<input type="checkbox"/>  Edit  Copy  Delete	7	HAS	2021-01-08
<input type="checkbox"/>  Edit  Copy  Delete	8	BLU	2021-01-09
<input type="checkbox"/>  Edit  Copy  Delete	9	EIN	2021-01-10
<input type="checkbox"/>  Edit  Copy  Delete	10	TIL	2021-01-11
<input type="checkbox"/>  Edit  Copy  Delete	11	GRO	2021-01-12
<input type="checkbox"/>  Edit  Copy  Delete	12	BRE	2021-01-13
<input type="checkbox"/>  Edit  Copy  Delete	13	APE	2021-01-14
<input type="checkbox"/>  Edit  Copy  Delete	14	NIJ	2021-01-15
<input type="checkbox"/>  Edit  Copy  Delete	15	ENS	2021-01-16
<input type="checkbox"/> Edit Copy Delete	16	UAD	2021-01-17



The limit is implemented by phpMyAdmin, but you can easily show all rows by checking the **Show all** checkbox.

You will receive a warning asking if you'd like to see all rows. Since there's only 120 rows in this example, you can click **OK**. In larger datasets, loading all the rows will likely crash your browser.

← Server: mysql:3306 » Database: tournament_teams » Table: teams

Browse **Structure** **SQL** **Search** **Insert** **Export**

Showing rows 0 - 119 (120 total, Query took 0.0008 seconds.)

```
SELECT * FROM `teams`
```

Show all | Number of rows: All Filter rows: Search this table

+ Options

	team_no	team_code	creation_date
<input type="checkbox"/> Edit Copy Delete	1	ACE	2021-01-01
<input type="checkbox"/> Edit Copy Delete	2	FAX	2021-01-03
<input type="checkbox"/> Edit Copy Delete	3	RED	2021-01-04
<input type="checkbox"/> Edit Copy Delete	4	MAZ	2021-01-05
<input type="checkbox"/> Edit Copy Delete	5	AMS	2021-01-06
<input type="checkbox"/> Edit Copy Delete	6	ROT	2022-02-10
<input type="checkbox"/> Edit Copy Delete	7	HAS	2021-01-08
<input type="checkbox"/> Edit Copy Delete	8	BLU	2021-01-09
<input type="checkbox"/> Edit Copy Delete	9	EIN	2021-01-10
<input type="checkbox"/> Edit Copy Delete	10	TIL	2021-01-11
<input type="checkbox"/> Edit Copy Delete	11	GRO	2021-01-12
<input type="checkbox"/> Edit Copy Delete	12	BRE	2021-01-13
<input type="checkbox"/> Edit Copy Delete	13	APE	2021-01-14
<input type="checkbox"/> Edit Copy Delete	14	NIJ	2021-01-15
<input type="checkbox"/> Edit Copy Delete	15	ENS	2021-01-16
<input type="checkbox"/> Edit Copy Delete	16	HAR	2021-01-17

	Edit		Copy		Delete	
<input type="checkbox"/>		Edit		Copy		Delete

TO FROM

2021-01-17

17 LAM

2021-01-18

We can now confirm that all 120 rows have been loaded.

- On the left sidebar, select the **tournament_teams** database.

phpMyAdmin

Recent Favorites

New information_schema mysql performance_schema sys tournament_teams world

Structure SQL Search

Filters

Containing the word:

Table	Action
teams	<input type="button" value="Browse"/> <input type="button" value="Structure"/> <input type="button" value="Sum"/>

1 table

Check all With selected:

Print Data dictionary

Create table

Name: Number

about:blank

26/33



With this view, you can see all the tables in the database, including the **teams** table that we just created. As you can see, the size of the database is currently 64 KiB, that is, 64 kilobytes. While this is a small size, do remember that this would not be the case with larger datasets as this sample table only has 120 entries.

Keep this number in mind as we start optimizing this table.

Task B: Optimize Your Data Types

- Under **Action** for the **teams** table, select **Structure**. This will bring you back to the **Structure** page.

Next to **team_no**, click **Change**. This function is helpful when you need to make adjustments to a column, for any reason.

#	Name	Type	Collation	Attributes	Null	Default	Comments
1	team_no	int			No	<i>None</i>	
2	team_code	char(100)	utf8mb4_0900_ai_ci		No	<i>None</i>	
3	creation_date	char(100)	utf8mb4_0900_ai_ci		No	<i>None</i>	

With selected: **Browse** **Change** **Drop**

- In this editor, let's change the **Type** to one that would be better suited for this column.

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

- Change the data type for **team_code**!

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

- Finally, let's change the **creation_date**.

- ▶ Hint (Click Here)
- ▶ Solution (Click Here)

- After updating your data types, your **Structure** page should look like the following:

← Server: mysql:3306 » Database: tournament_teams » Table: teams

Browse **Structure** **SQL** **Search** **Insert** **Export**

✓ Table teams has been altered successfully.

```
ALTER TABLE `teams` CHANGE `creation_date` `creation_date` DATE NO
```

Table structure **Relation view**

#	Name	Type	Collation	Attributes	Null	Default	Comment
<input type="checkbox"/>	1 team_no 	tinyint			No	<i>None</i>	
<input type="checkbox"/>	2 team_code	char(3)	utf8mb4_0900_ai_ci		No	<i>None</i>	
<input type="checkbox"/>	3 creation_date	date			No	<i>None</i>	

 Check all With selected:    

6. We can look at our rows by clicking **Browse**.

As you can see, we still have all 120 entries. Great! So, let's take a look at the size of this table.

7. Return to the **tournament_teams** database in the left sidebar.

← Server: mysql:3306 » Database: tournament_teams

Structure **SQL** **Search** **Query** **Export** **Import**

Filters

Containing the word:

Table	Action
<input type="checkbox"/> teams 	     
1 table	Sum

 Check all With selected:

Upon first glance, we can see that the size of the database has reduced to 16 KiB, four times smaller than the original unoptimized database!

8. We can take optimization a step further by selecting the **teams** table and, in the dropdown, selecting **optimize table**. This is equivalent to performing the **OPTIMIZE TABLE** function in the command-line interface. This command reorganizes the table data and indexes to reduce storage and make accessing the table more efficient. The exact changes made to the table depend on the storage engine in use.

phpMyAdmin

Recent Favorites

New information_schema mysql performance_schema sys tournament_teams

New teams world

Server: mysql:3306 » Database: tournament

Structure SQL Search

Filters

Containing the word:

Table	Action
<input checked="" type="checkbox"/> teams	Browse Structure SQL

1 table Sum

Check all

[Print](#) [Data dictionary](#)

[Create table](#)

Name:

✓ With selected:
Copy table
Show create
Export

Delete data or table
Empty
Drop

Table maintenance
Analyze table
Check table
Checksum table
Optimize table Repair table

Prefix
Add prefix to ta
Replace table p
Copy table with



With the InnoDB engine, which is what we are currently using, the table is actually rebuilt, with the index statistics updated to free unused space.

phpMyAdmin

Recent Favorites

- New
- information_schema
- mysql
- performance_schema
- sys
- tournament_teams
 - New
 - teams
- world

Server: mysql:3306 » Database: tournament_teams

Structure SQL Search

Your SQL query has been executed successfully.

```
OPTIMIZE TABLE `teams`
```

+ Options

Table	Op	Msg_type	Ms
tournament_teams.teams	optimize	note	Tak
tournament_teams.teams	optimize	status	OK

Query results operations

Print Copy to clipboard Create view

Filters

Containing the word:

Table	Action
<input type="checkbox"/> teams	

1 table Sum

Check all With selected:

Print Data dictionary

Create table

Name: Number

That is what the returned table tells us: InnoDB “optimizes” tables by recreating and analyzing them, and that the optimization had been completed.

Conclusion

Congratulations! You now know how to monitor and optimize your database with the help of the handy tool, phpMyAdmin. Now, you can apply what you have learned to any database that you create or modify in the future.

Author(s)

Kathy An

Other Contributor(s)

Rav Ahuja

Changelog

Date	Version	Changed by	Change Description
2021-10-12	1.0	Kathy An	Created initial version
2021-10-13	1.1	Steve Hord	Copy edits
2023-05-04	1.2	Rahul Jaideep	Updated Markdown file

© IBM Corporation 2023. All rights reserved.