

# 04 CSI online spoken: Spoken - Plotting and analysis - final data

Kirsten Stark

26 September, 2024

## Load packages

```
#library(dplyr)  
library(tidyr)  
library(lme4)
```

```
## Loading required package: Matrix
```

```
##
```

```
## Attaching package: 'Matrix'
```

```
## The following objects are masked from 'package:tidyr':
```

```
##
```

```
##      expand, pack, unpack
```

```
library(lmerTest)
```

```
##
```

```
## Attaching package: 'lmerTest'
```

```
## The following object is masked from 'package:lme4':
```

```
##
```

```
##      lmer
```

```
## The following object is masked from 'package:stats':
```

```
##
```

```
##      step
```

```
library(Rmisc)
```

```
## Loading required package: lattice
```

```
## Warning: package 'lattice' was built under R version 4.3.2
```

```
## Loading required package: plyr
```

```

library(Cairo)
#library(strengejacke)
library(ggplot2)
# devtools::install_github("strengejacke/sjPlot")
library(sjPlot)

## Install package "strengejacke" from GitHub ('devtools::install_github("strengejacke/strengejacke")')

library(dplyr)

##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:plyr':
##
##      arrange, count, desc, failwith, id, mutate, rename, summarise,
##      summarize

## The following objects are masked from 'package:stats':
##
##      filter, lag

## The following objects are masked from 'package:base':
##
##      intersect, setdiff, setequal, union

options(scipen=999)

rm(list = ls())
options( "encoding" = "UTF-8" )
set.seed(99)

```

## Load preprocessed data

```

# input
input = "aphasia_final.csv"

# load data
df <- read.csv2(here::here("data","transient_data_files", input), sep=",") #>% select(-"X")

```

Check amount of participants and trials

```

# no. of participants:
length(unique(df$subject))

```

```
## [1] 40
```

```
# no. of trials is 160 per participant?
nrow(df) == 3*160 * length(unique(df$subject))
```

```
## [1] TRUE
```

```
#table(df$subject, df$session)
```

```
# how many non-responses
df %>% filter(VOT==0) %>% dplyr::group_by(type, subject, session) %>%
  dplyr::summarise(length(VOT))
```

```
## 'summarise()' has grouped output by 'type', 'subject'. You can override using
## the '.groups' argument.
```

```
## # A tibble: 86 x 4
## # Groups:   type, subject [37]
##   type subject session 'length(VOT)'
##   <chr>   <int>   <int>         <int>
## 1 PWA      101       1           8
## 2 PWA      101       2           4
## 3 PWA      103       1          40
## 4 PWA      103       2          21
## 5 PWA      103       3          27
## 6 PWA      104       1          75
## 7 PWA      104       2          52
## 8 PWA      104       3          37
## 9 PWA      105       1          10
## 10 PWA     105       2           7
## # i 76 more rows
```

```
# table(df$VOT==0, df$subject, df$session)
```

## Drop filler trials

```
all_data <- df
df <- df %>% filter(category!="Filler") %>% droplevels()
```

## Add ordinal position

```
# add position number
df <- df %>% group_by(subject, session, category) %>%
  add_count() %>%
  dplyr::mutate(PosOr = seq(1:n)) %>% dplyr::select(-n)
table(df$PosOr)
```

```
##
##   1    2    3    4    5
## 2880 2880 2880 2880 2880
```

```
#table(df$PosOr, df$session, df$subject)
```

## Factorize columns

```
# factorize columns
df$VOT <- as.numeric(as.character(df$VOT))
is.numeric(df$VOT)
```

```
## [1] TRUE
```

```
df$PosOr <- as.factor(df$PosOr)
df$group <- as.factor(df$type)
df$subject <- as.factor(df$subject)
df$session <- as.factor(df$session)
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df$session)<-my.simple
levels(df$session)
```

```
## [1] "1" "2" "3"
```

```
## Define contrast of group
contrasts(df$group) <- MASS::contr.sdif(2)
levels(df$group)
```

```
## [1] "control" "PWA"
```

```
## Define Ordinal position as continuous predictor variable
df$PosOr_cont <- as.numeric(scale(as.numeric(as.character(df$PosOr)),
                                   center = T, scale = F))
```

## Errors and correct responses

Correct responses start with 1.

1 - correct.

1.1 - correct with alternative response.

1.2 - correct with phonematic paraphasia ( $\leq 25\%$  of the word).

1.3 - correct with correct article [\*].

1.4 - correct, but VOT invalid.

0 - wrong. 0.1 - wrong with phonematic paraphasia ( $> 25\%$  of the word). 0.2 - wrong: semantic paraphasia (word in the experiment). 0.3 - wrong: semantic paraphasia (word not in the experiment). 0.4 - wrong: null reaction. 0.5 - wrong: replacement without connection to the word (word in the experiment)

0.6 - wrong: replacement without connection to the word (word not in the experiment).

0.7 - superordinate word.

0.8 - neologism. 0.9 - etc.

0.99 - TECHNICAL ERROR.

We will consider all responses in 1.1-1.3 for analyses of response times and responses 1.1-1.4 and 0.1-0.9 (not 1.4 and 0.99) for analyses of error rates.

```
## Add technical errors in the missing trials
sum(is.na(df$VOT)) # NA VOT so far are technical errors
```

```
## [1] 4
```

```
df$error[is.na(df$VOT)] <- "99"
df$correct[is.na(df$VOT)] <- "0"

## Two trials were forgotten to be classified, but AR == 99 --> technical error?
#sum(is.na(df$correct))
#df %>% filter(is.na(correct))
df$error[is.na(df$correct) & df$AR == "99"] <- "99"
df$correct[is.na(df$correct) & df$AR == "99"] <- "0"
sum(is.na(df$correct))
```

```
## [1] 0
```

```
## NR and 0.4 are the same -> replace this
df$error[df$error=="NR"] <- "4"

## Rename broken names
# unique(df$error)
df$error <- stringr::str_replace(df$error, ";;;;;", "")
df$error <- stringr::str_replace(df$error, "ok", "") # subject 113, session 2, trial 121 (Couch)
df$error <- gsub("?", NA, df$error, fixed = TRUE)
# unique(df$error)

# unique(df$correct)
df$correct <- stringr::str_replace(df$correct, ";;;;;", "")
# unique(df$correct)
```

```
## Overall amount of correct answers
sum(df$correct != 0)
```

```
## [1] 12589
```

```
sum(is.na(df$correct)) # these are the technical errors where no audio file was recorded
```

```
## [1] 0
```

```
## Overview of correct responses
```

```
table(df$correct)
```

```
##
```

```
##      0      1    1.1    1.2    1.3    1.4
```

```
## 1811 10901 1207   124   223   134
```

```
#df$VOT[df$correct==1.4]
```

```
# Overview of incorrect responses
```

```
sum(df$correct==0, na.rm=T)
```

```
## [1] 1811
```

```
sum(df$correct == 0 & !is.na(df$error)) # here the error classification was missing
```

```
## [1] 1810
```

```
df[df$correct == 0 & is.na(df$error),]
```

```
## # A tibble: 1 x 41
```

```
## # Groups:   subject, session, category [1]
```

```
##   type subject session trial item category supercategory VOT correct AR
```

```
##   <chr> <fct>   <fct>   <int> <chr> <chr>   <chr>           <dbl> <chr> <chr>
```

```
## 1 PWA  113     2       121 couch Sitzen Möbel         1846 0     Cous
```

```
## # i 31 more variables: error <chr>, gender <int>, age <int>, language <int>,
```

```
## # handedness <int>, CH01 <int>, CH01_01 <int>, CH01_02 <int>, CH01_03 <int>,
```

```
## # CH01_04 <int>, CH02 <int>, CH02_01 <int>, CH02_02 <int>, CH02_03 <int>,
```

```
## # CH02_04 <int>, CH03 <int>, array <int>, comments <lgl>, timetotal <chr>,
```

```
## # time_correct <chr>, SD22_OS <int>, SD22_BID <chr>, SD22_BNM <int>,
```

```
## # SD22_FmF <int>, SD22_ScW <int>, SD22_ScH <int>, SD22_QnW <int>,
```

```
## # OR02_01 <chr>, PosOr <fct>, group <fct>, PosOr_cont <dbl>
```

```
df$error[df$correct == 0 & is.na(df$error)] <- 1 # phonet. paraphrasia > 25 %
```

Overview of correctness classifications by group

```
df %>% group_by(type) %>% dplyr::count(correct)
```

```
## # A tibble: 12 x 3
```

```
## # Groups:   type [2]
```

```
##   type correct      n
```

```
##   <chr>   <chr>   <int>
```

```
## 1 PWA     0     1563
```

```
## 2 PWA     1     4756
```

```
## 3 PWA      1.1      502
## 4 PWA      1.2      107
## 5 PWA      1.3      153
## 6 PWA      1.4      119
## 7 control  0        248
## 8 control  1       6145
## 9 control  1.1     705
## 10 control 1.2      17
## 11 control 1.3      70
## 12 control 1.4      15
```

Errors

```
table(df$error)
```

```
##
##  1  2  3  4  5  6  7  8  9 99
## 57 188 94 851 33 46 137 32 270 103
```

Show amount of incorrect trials per ordinal position (excluding fillers):

```
## How many incorrect (correct) non-filler trials per ordinal position?
table(df$PosOr[df$category != "Filler" & df$correct == 0],
      df$correct[df$category != "Filler" & df$correct == 0])
```

```
##
##      0
## 1 320
## 2 349
## 3 375
## 4 347
## 5 420
```

```
table(df$PosOr[df$category != "Filler" & startsWith("1", df$correct)],
      df$correct[df$category != "Filler" & startsWith("1", df$correct)])
```

```
##
##      1
## 1 2254
## 2 2200
## 3 2158
## 4 2202
## 5 2087
```

```
## How many incorrect trials (no technical errors) per ordinal position?
table(df$PosOr[df$category != "Filler" & df$correct == 0 &
            df$error != 99])
```

```
##
##  1  2  3  4  5
## 303 333 347 331 394
```

Show amount of incorrect trials per subject

```
df %>% filter(category != "Filler") %>%  
  group_by(subject, session) %>%  
  dplyr::count(correct) %>%  
  mutate(prop=round(n/160*100,2)) %>% #round(prop.table(n), 4)) %>%  
  filter(correct == "0") %>%  
  dplyr::select(-c(correct, n))
```

```
## # A tibble: 115 x 3  
## # Groups:   subject, session [115]  
##   subject session prop  
##   <fct>   <fct>   <dbl>  
## 1 101     1       5.62  
## 2 101     2       2.5  
## 3 101     3       0.62  
## 4 102     1       1.25  
## 5 102     2       1.88  
## 6 102     3       2.5  
## 7 103     1      26.2  
## 8 103     2      20.6  
## 9 103     3      23.1  
## 10 104    1      43.8  
## # i 105 more rows
```

Total percentage of errors

```
sum(df$correct[df$category != "Filler"]=="0", na.rm=T)/nrow(df%>%filter(category != "Filler"))
```

```
## [1] 0.1257639
```

## Summarise erroneous and correct responses

```
classification_summary <- df %>% group_by(group, session) %>% count(correct) %>%  
  mutate(correct = case_when(correct == "0" ~ "wrong sum",  
                             correct == "1" ~ "correct",  
                             correct == "1.1" ~  
                               "correct with alternative response",  
                             correct == "1.2" ~  
                               "correct with phonematic paraphasia (<=25% of the word)",  
                             correct == "1.3" ~ "correct with correct article",  
                             correct == "1.4" ~ "correct, but VOT invalid")) %>%  
  rename(classification=correct)  
  
x <- df %>% group_by(group, session) %>% count(error) %>%  
  mutate(error=as.character(error)) %>%  
  mutate(error=case_when(  
    error == "1" ~  
      "wrong with phonematic paraphasia (> 25 % of the word)",  
    error == "2" ~
```



```

    "wrong: semantic paraphrasia (word in the experiment)",
    error == "3" ~
    "wrong: semantic paraphrasia (word not in the experiment)",
    error == "4" ~
    "wrong: null reaction",
    error == "5" ~
    "wrong: replacement without connection to the word (word in the experiment) ",
    error == "6" ~
    "wrong: replacement without connection to the word (word not in the experiment)",
    error == "7" ~ "wrong: superordinate word",
    error == "8" ~ "wrong: neologism",
    error == "9" ~ "wrong: etc.",
    error == "99" ~ "TECHNICAL ERROR",
    is.na(error) ~ "sum correct")) %>%
  rename(classification = error)
(classification_summary <- rbind(classification_summary, x) %>%
  arrange(group, session))

```

```

## # A tibble: 96 x 4
## # Groups:   group, session [6]
##   group session classification      n
##   <fct>   <fct>   <chr>          <int>
## 1 control 1      wrong sum          116
## 2 control 1      correct          1917
## 3 control 1      correct with alternative response      291
## 4 control 1      correct with phonematic paraphasia (<=25% of the word)      2
## 5 control 1      correct with correct article          66
## 6 control 1      correct, but VOT invalid              8
## 7 control 1      wrong: semantic paraphrasia (word in the experiment)      15
## 8 control 1      wrong: semantic paraphrasia (word not in the experimen~      13
## 9 control 1      wrong: null reaction              14
## 10 control 1      wrong: replacement without connection to the word (wor~      2
## # i 86 more rows

```

```

# Export as word file
library(flextable)
huxt_word <- huxtable::huxtable(classification_summary)
huxt_word <- huxtable::set_number_format(huxt_word, round(2))
huxtable::quick_docx(
  huxt_word, file = here::here(
    "results", "tables",
    "CSI_online_aphasia_classification_summary.docx"),
  open = FALSE)

# by ordinal position
x <- df %>% group_by(group, session, PosOr) %>% count(error) %>%
  mutate(error=as.character(error)) %>%
  mutate(error=case_when(
    error == "1" ~
      "wrong with phonematic paraphrasia (> 25 % of the word)",
    error == "2" ~
      "wrong: semantic paraphrasia (word in the experiment)",
    error == "3" ~

```

```

    "wrong: semantic paraphrasia (word not in the experiment)",
    error == "4" ~
    "wrong: null reaction",
    error == "5" ~
    "wrong: replacement without connection to the word (word in the experiment) ",
    error == "6" ~
    "wrong: replacement without connection to the word (word not in the experiment)",
    error == "7" ~ "wrong: superordinate word",
    error == "8" ~ "wrong: neologism",
    error == "9" ~ "wrong: etc.",
    error == "99" ~ "TECHNICAL ERROR",
    is.na(error) ~ "sum correct")) %>%
rename(classification = error)
(x %>% filter(group=="PWA") %>%
  arrange(group, session, PosOr))

```

```

## # A tibble: 153 x 5
## # Groups:   group, session, PosOr [15]
##   group session PosOr classification      n
##   <fct> <fct>   <fct> <chr>          <int>
## 1 PWA     1       1     "wrong: semantic paraphrasia (word in the experime~    5
## 2 PWA     1       1     "wrong: semantic paraphrasia (word not in the expe~    6
## 3 PWA     1       1     "wrong: null reaction"                    53
## 4 PWA     1       1     "wrong: replacement without connection to the word~    2
## 5 PWA     1       1     "wrong: replacement without connection to the word~    4
## 6 PWA     1       1     "wrong: superordinate word"                6
## 7 PWA     1       1     "wrong: neologism"                        3
## 8 PWA     1       1     "wrong: etc."                            22
## 9 PWA     1       1     "TECHNICAL ERROR"                        2
## 10 PWA    1       1     "sum correct"                            377
## # i 143 more rows

```

```

## correct responses, but VOT invalid
# 1.4 - correct, but VOT invalid.
(df %>% filter(group=="PWA" & correct=="1.4") %>%
  group_by(group, session, PosOr) %>%
  count(correct) %>%
  arrange(group, session, PosOr))

```

```

## # A tibble: 15 x 5
## # Groups:   group, session, PosOr [15]
##   group session PosOr correct      n
##   <fct> <fct>   <fct> <chr>    <int>
## 1 PWA     1       1     1.4      15
## 2 PWA     1       2     1.4       9
## 3 PWA     1       3     1.4      12
## 4 PWA     1       4     1.4       7
## 5 PWA     1       5     1.4      11
## 6 PWA     2       1     1.4       5
## 7 PWA     2       2     1.4       7
## 8 PWA     2       3     1.4       5
## 9 PWA     2       4     1.4       4

```

```
## 10 PWA 2 5 1.4 7
## 11 PWA 3 1 1.4 9
## 12 PWA 3 2 1.4 7
## 13 PWA 3 3 1.4 4
## 14 PWA 3 4 1.4 6
## 15 PWA 3 5 1.4 11
```

## Subset data for reaction time and error analyses and delete fillers

As correct reaction times will be considered:

- 1 - correct.
- 1.1 - correct with alternative response.
- 1.2 - correct with phonematic paraphasia ( $\leq 25\%$  of the word).
- 1.3 - correct with correct article [\*].

```
df %>% mutate(correct_class = case_when(
  correct == 1 ~ 1,
  correct == 1.1 ~ 1,
  correct == 1.2 ~ 1,
  correct == 1.3 ~ 1,
  correct == 1.4 ~ 0,
  correct == 0 ~ 0)) -> df

# Fillers included
# df %>% group_by(group, session) %>% dplyr::count(correct_class)
table(df$correct_class)
```

```
##
##      0      1
## 1945 12455
```

```
# Fillers excluded
# df %>% filter(category != "Filler") %>%
#   group_by(group, session) %>% dplyr::count(correct_class)
table(df$correct_class[df$category != "Filler"])
```

```
##
##      0      1
## 1945 12455
```

```
### Save data frame for RT analyses: Only correct responses and no fillers
df_RTs <- df %>% filter(correct_class == 1 & category != "Filler")
# table(df_RTs$correct_class, df_RTs$correct)
# sum(df_RTs$VOT == 0); sum(is.na(df_RTs$VOT))

df_RTs %>% group_by(group, session) %>% count()
```

```
## # A tibble: 6 x 3
## # Groups:   group, session [6]
##   group session     n
##   <fct>   <fct> <int>
```

```
## 1 control 1      2276
## 2 control 2      2312
## 3 control 3      2349
## 4 PWA      1      1723
## 5 PWA      2      1864
## 6 PWA      3      1931
```

```
(df_RTs %>% group_by(group, session) %>% count(correct) -> x)
```

```
## # A tibble: 24 x 4
## # Groups:   group, session [6]
##   group session correct     n
##   <fct>   <fct>   <chr>  <int>
## 1 control 1      1      1917
## 2 control 1      1.1    291
## 3 control 1      1.2      2
## 4 control 1      1.3     66
## 5 control 2      1     2095
## 6 control 2      1.1    209
## 7 control 2      1.2      6
## 8 control 2      1.3      2
## 9 control 3      1     2133
## 10 control 3     1.1    205
## # i 14 more rows
```

```
# sum(x$n)
```

```
print(paste0("Amount of trials that went into RT analyses: ",
             nrow(df_RTs)))
```

```
## [1] "Amount of trials that went into RT analyses: 12455"
```

```
table(df_RTs$group)
```

```
##
## control      PWA
##    6937    5518
```

```
# by ordinal position
```

```
(df_RTs %>% filter(group=="PWA") %>% group_by(group, session, PosOr) %>%
  mutate(correct=case_when(correct=="1" ~ "correct",
                           correct=="1.1" ~ "correct with alternative response",
                           correct=="1.2" ~ "correct with phonematic paraphasia (<=25% of the word)",
                           correct=="1.3" ~ "correct with correct article")) %>%
  count(correct) -> x)
```

```
## # A tibble: 60 x 5
## # Groups:   group, session, PosOr [15]
##   group session PosOr correct     n
##   <fct> <fct>   <fct> <chr>  <int>
## 1 PWA    1      1      correct 310
```

```
## 2 PWA 1 1 correct with alternative response 34
## 3 PWA 1 1 correct with correct article 14
## 4 PWA 1 1 correct with phonematic paraphasia (<=25% of the w~ 4
## 5 PWA 1 2 correct 285
## 6 PWA 1 2 correct with alternative response 35
## 7 PWA 1 2 correct with correct article 15
## 8 PWA 1 2 correct with phonematic paraphasia (<=25% of the w~ 10
## 9 PWA 1 3 correct 270
## 10 PWA 1 3 correct with alternative response 42
## # i 50 more rows
```

As errors on the participant side will be considered:

- 1 - wrong with phonematic paraphasia (> 25 % of the word).
- 2 - wrong: semantic paraphasia (word in the experiment).
- 3 - wrong: semantic paraphasia (word not in the experiment).
- 4 - wrong: null reaction.
- 5 - wrong: replacement without connection to the word (word in the experiment).
- 6 - wrong: replacement without connection to the word (word not in the experiment).
- 7 - superordinate word.
- 8 - neologism.
- 9 - etc.

```
df %>% mutate(error_class = case_when(
  error == 1 | error == 2 | error == 3 |
    error == 4 | error == 5 | error == 6 | error == 7 |
    error == 8 | error == 9 ~ 1,
  error == 99 | is.na(error) ~ 0)) -> df
# Overview including Fillers
# df %>% group_by(group, session) %>% count(error_class)
table(df$error_class)
```

```
##
##      0      1
## 12692 1708
```

```
# Overview excluding Fillers
# df %>% filter(category != "Filler") %>%
#   group_by(group, session) %>% count(error_class)
table(df$error_class[df$category != "Filler"])
```

```
##
##      0      1
## 12692 1708
```

```
#### Subset data for error analyses: All trials excluding technical errors, invalid RTs and fillers
df_errors <- df %>% filter(category != "Filler" &
                           (error != "99" | is.na(error)))

print(paste0("Amount of trials that went into RT analyses: ",
             nrow(df_errors)))
```

```
## [1] "Amount of trials that went into RT analyses: 14297"
```

```
table(df_errors$group)
```

```
##  
## control      PWA  
##      7119     7178
```

---

## RESPONSE TIMES

```
sum(!is.na(df_RTs$error))
```

```
## [1] 0
```

### Descriptives

```
(means_final<- df_RTs %>%  
  filter(category != "Filler") %>%  
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",  
    withinvars = c("session", "PosOr"),  
    betweenvars = "group", na.rm = T))
```

##	group	session	PosOr	N	VOT	sd	se	ci
## 1	control	1	1	461	1297.252	386.6087	18.00616	35.38453
## 2	control	1	2	456	1278.075	368.6706	17.26458	33.92821
## 3	control	1	3	446	1352.942	419.3224	19.85549	39.02218
## 4	control	1	4	457	1329.444	375.5740	17.56861	34.52548
## 5	control	1	5	456	1347.666	395.4900	18.52052	36.39636
## 6	control	2	1	466	1204.941	327.2233	15.15832	29.78730
## 7	control	2	2	462	1244.987	364.0399	16.93667	33.28264
## 8	control	2	3	464	1213.458	289.9285	13.45959	26.44945
## 9	control	2	4	466	1244.242	296.8703	13.75225	27.02425
## 10	control	2	5	454	1266.531	329.4120	15.46007	30.38236
## 11	control	3	1	469	1199.645	323.1567	14.92199	29.32239
## 12	control	3	2	471	1173.122	282.9187	13.03621	25.61646
## 13	control	3	3	467	1208.308	305.2131	14.12358	27.75378
## 14	control	3	4	470	1232.751	306.1228	14.12039	27.74706
## 15	control	3	5	472	1263.283	349.0940	16.06835	31.57453
## 16	PWA	1	1	362	1280.805	463.4011	24.35582	47.89711
## 17	PWA	1	2	345	1352.300	518.0623	27.89154	54.85942
## 18	PWA	1	3	337	1374.660	515.0242	28.05516	55.18588
## 19	PWA	1	4	357	1334.771	468.7956	24.81129	48.79513
## 20	PWA	1	5	322	1390.007	538.3805	30.00277	59.02691
## 21	PWA	2	1	375	1168.998	438.9850	22.66909	44.57485
## 22	PWA	2	2	386	1188.463	443.3652	22.56670	44.36939
## 23	PWA	2	3	370	1212.971	435.7079	22.65138	44.54198
## 24	PWA	2	4	378	1245.738	457.2034	23.51600	46.23896

```
## 25    PWA      2    5 355 1308.230 496.4997 26.35147 51.82511
## 26    PWA      3    1 395 1144.157 373.7086 18.80332 36.96739
## 27    PWA      3    2 386 1183.630 457.0922 23.26538 45.74310
## 28    PWA      3    3 396 1224.247 442.1547 22.21911 43.68250
## 29    PWA      3    4 384 1223.097 437.4259 22.32230 43.88959
## 30    PWA      3    5 370 1273.044 469.5947 24.41307 48.00619
```

```
(means_final_cat<- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "category",
    withinvars = c("session", "PosOr"),
    betweenvars = "group", na.rm = T))
```

```
##      group session PosOr   N      VOT      sd      se      ci
## 1 control      1      1 461 1297.378 386.0154 17.97853 35.33023
## 2 control      1      2 456 1276.834 377.8956 17.69658 34.77718
## 3 control      1      3 446 1352.899 418.0216 19.79390 38.90113
## 4 control      1      4 457 1327.830 368.6545 17.24493 33.88939
## 5 control      1      5 456 1347.895 380.1481 17.80207 34.98447
## 6 control      2      1 466 1205.679 326.2835 15.11479 29.70175
## 7 control      2      2 462 1246.112 368.7969 17.15799 33.71756
## 8 control      2      3 464 1212.429 286.3328 13.29267 26.12143
## 9 control      2      4 466 1244.625 303.0652 14.03923 27.58818
## 10 control     2      5 454 1268.504 339.2988 15.92408 31.29423
## 11 control     3      1 469 1199.602 319.6380 14.75951 29.00311
## 12 control     3      2 471 1172.419 275.1627 12.67883 24.91421
## 13 control     3      3 467 1208.130 297.3314 13.75886 27.03708
## 14 control     3      4 470 1233.023 302.7635 13.96544 27.44258
## 15 control     3      5 472 1263.295 350.2301 16.12065 31.67729
## 16    PWA      1      1 362 1284.565 539.6713 28.36449 55.78039
## 17    PWA      1      2 345 1361.937 594.3400 31.99819 62.93673
## 18    PWA      1      3 337 1367.845 597.1421 32.52840 63.98497
## 19    PWA      1      4 357 1336.280 555.5199 29.40123 57.82193
## 20    PWA      1      5 322 1365.528 590.1073 32.88540 64.69813
## 21    PWA      2      1 375 1173.590 498.9082 25.76351 50.65949
## 22    PWA      2      2 386 1185.887 507.5593 25.83409 50.79356
## 23    PWA      2      3 370 1204.526 509.7624 26.50128 52.11249
## 24    PWA      2      4 378 1242.418 522.0492 26.85131 52.79711
## 25    PWA      2      5 355 1303.733 563.8296 29.92497 58.85308
## 26    PWA      3      1 395 1159.867 431.3062 21.70137 42.66497
## 27    PWA      3      2 386 1187.291 497.2603 25.30988 49.76289
## 28    PWA      3      3 396 1225.908 509.9080 25.62384 50.37616
## 29    PWA      3      4 384 1222.496 520.3697 26.55500 52.21185
## 30    PWA      3      5 370 1278.875 536.4006 27.88614 54.83569
```

```
(means_final_wo_session <- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("PosOr"),
    betweenvars = "group", na.rm = T))
```

```
##      group PosOr   N      VOT      sd      se      ci
## 1 control      1 1396 1233.645 377.5129 10.103901 19.82048
```

```
## 2 control 2 1389 1231.481 370.6296 9.944638 19.50814
## 3 control 3 1377 1256.889 376.4044 10.143497 19.89839
## 4 control 4 1393 1268.317 356.9347 9.563421 18.76027
## 5 control 5 1382 1292.193 389.9203 10.488703 20.57551
## 6 PWA 1 1132 1196.084 464.1391 13.795102 27.06687
## 7 PWA 2 1117 1237.396 516.8288 15.463937 30.34167
## 8 PWA 3 1103 1266.420 506.7019 15.256848 29.93575
## 9 PWA 4 1119 1266.373 493.1586 14.742514 28.92611
## 10 PWA 5 1047 1320.946 542.9417 16.779533 32.92538
```

```
# Export as word file
library(flextable)
huxt_word <- huxtable::huxtable(means_final)
huxt_word <- huxtable::set_number_format(huxt_word, round(2))
huxtable::quick_docx(huxt_word,
  file = here::here("results", "tables",
    "CSI_online_aphasia_subject_RT_by_session.docx"),
  open = FALSE)
```

Calculate the main effects

```
## Ordinal position effect
x <- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = "PosOr", #c("session", "PosOr"),
    # betweenvars = "group",
    na.rm = T)
((x$VOT[2]-x$VOT[1])+(x$VOT[3]-x$VOT[2])+(x$VOT[4]-x$VOT[3])+
  (x$VOT[5]-x$VOT[4]))/4
```

```
## [1] 21.94008
```

```
((x$VOT[5]-x$VOT[1]))/4
```

```
## [1] 21.94008
```

```
## session effect
x <- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = "session", #c("session", "PosOr"),
    # betweenvars = "group",
    na.rm = T)
(x$VOT[2]-x$VOT[1])
```

```
## [1] -101.4722
```

```
(x$VOT[3]-x$VOT[1])
```

```
## [1] -118.8204
```



```
## group effect
x <- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySE(., "VOT", #idvar = "subject",
                    #withinvars = "session", #c("session", "PosOr"),
                    groupvars = "group",
                    na.rm = T)

(x$VOT[2]-x$VOT[1])
```

```
## [1] 173.2174
```

Calculate mean and SD of ordinal position effects

```
# First calculate the OrdPos effect for each subject and each category separately
df_RTs$OrdPos_manual <- NA_real_
isEmptyNumeric <- function(x) {
  return(identical(x, numeric(0)))
}

for (i in unique(df_RTs$subject)) {
  for(j in unique(df_RTs$category)) {
    for(l in unique(df_RTs$session)) {
      for (k in 2:5) {
        x <- df_RTs$VOT[df_RTs$subject==i &
                        df_RTs$category==j &
                        df_RTs$session==l &
                        df_RTs$PosOr==k]

        xM1 <- df_RTs$VOT[df_RTs$subject==i &
                          df_RTs$category==j &
                          df_RTs$session==l &
                          df_RTs$PosOr==k-1]

        if(!isEmptyNumeric(x) & !isEmptyNumeric(xM1)){
          if(!is.na(x) & !is.na(xM1)){
            df_RTs$OrdPos_manual[df_RTs$subject==i &
                                df_RTs$category==j &
                                df_RTs$session==l &
                                df_RTs$PosOr==k] <- x - xM1
          }
        }
      }
    }
  }
}

# return summarySEwithin
df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "OrdPos_manual",
                        idvar = "subject",
                        withinvars = c("session"),
                        betweenvars = "group",
                        na.rm = T)
```

##	group	session	N	OrdPos_manual	sd	se	ci
## 1	control	1	1726	20.18442	587.7520	14.14731	27.74768
## 2	control	2	1790	20.34033	501.1588	11.84538	23.23223
## 3	control	3	1842	22.63550	468.9750	10.92710	21.43081
## 4	PWA	1	1106	16.76849	788.1171	23.69808	46.49832
## 5	PWA	2	1292	23.61023	685.6362	19.07491	37.42122
## 6	PWA	3	1353	22.18591	673.0508	18.29780	35.89517

```
# without session
df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySE(.,measurevar="OrdPos_manual",
                    groupvars = "group",
                    na.rm = T)
```

##	group	N	OrdPos_manual	sd	se	ci
## 1	control	5358	14.21911	425.1656	5.808403	11.38683
## 2	PWA	3751	30.87817	582.7884	9.515626	18.65631

```
df_RTs %>%
  filter(category != "Filler") %>%
  filter(session=="1") %>%
  Rmisc::summarySE(.,measurevar="OrdPos_manual",
                    groupvars = "group",
                    na.rm = T)
```

##	group	N	OrdPos_manual	sd	se	ci
## 1	control	1726	13.44786	480.4111	11.56359	22.68013
## 2	PWA	1106	26.30561	644.0762	19.36688	38.00001

```
# Rmisc::summarySEwithin(., "OrdPos_manual",
#                           idvar = "subject",
#                           withinvars = c("session"),
#                           betweenvars = "group",
#                           na.rm = T)
# without group
df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "OrdPos_manual",
                          idvar = "subject",
                          withinvars = c("session"),
                          #betweenvars = "group",
                          na.rm = T)
```

##	session	N	OrdPos_manual	sd	se	ci
## 1	1	2832	18.85037	673.0059	12.646555	24.79739
## 2	2	3082	21.71110	585.5095	10.546725	20.67933
## 3	3	3195	22.44511	564.3771	9.984676	19.57702

Trial types within correct responses

```
df %>% group_by(group) %>% count(correct)
```

```
## # A tibble: 12 x 3
## # Groups:   group [2]
##   group correct     n
##   <fct>   <chr> <int>
## 1 control 0       248
## 2 control 1      6145
## 3 control 1.1     705
## 4 control 1.2      17
## 5 control 1.3      70
## 6 control 1.4      15
## 7 PWA     0      1563
## 8 PWA     1      4756
## 9 PWA     1.1     502
## 10 PWA    1.2     107
## 11 PWA    1.3     153
## 12 PWA    1.4     119
```

```
df %>% group_by(group,session) %>% count(correct)
```

```
## # A tibble: 36 x 4
## # Groups:   group, session [6]
##   group session correct     n
##   <fct>   <fct>   <chr> <int>
## 1 control 1       0       116
## 2 control 1       1      1917
## 3 control 1     1.1       291
## 4 control 1     1.2        2
## 5 control 1     1.3       66
## 6 control 1     1.4        8
## 7 control 2       0       84
## 8 control 2       1      2095
## 9 control 2     1.1       209
## 10 control 2    1.2         6
## # i 26 more rows
```

## Plotting

Make plots suitable for APA format, font sizes can be adjusted


```
apatheme <- theme_bw()+
  theme(plot.title=element_text(size=22,hjust = .5),# (family="Arial",size=22,hjust = .5),
        panel.grid.major=element_blank(), panel.grid.minor=element_blank(),
        panel.border=element_blank(),axis.line=element_line(),
        text=element_text(size=16))# text=element_text(family="Arial",size=16))

control_color <- "dark green" # #DDAA33"
PWA_color <- "purple" ##004488"
```

**RTs across session, by ordinal position and group** Line graph (only correct trials, without fillers):  
RTs, split by group but summarised across sessions

```
(plot_vot <- means_final_wo_session %>%
  ggplot(., aes(x=PosOr, y=VOT,color=group, group=group)) +
  geom_point(aes(shape=group), size=3)+
  scale_shape_manual(values=c(16,17))+
  stat_summary(aes(linetype=group),fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dotted", "longdash"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, color=group), width =.1) +
  scale_color_manual(values=c(control_color, PWA_color))+
  apatheme+
  scale_y_continuous(limits = c(1120, 1450),
                     breaks =seq(1150,1450, by = 50)) +
  labs(x="Ordinal position",y ="VOT in ms", colour="Group",
       linetype="Group",
       shape="Group") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"))
```

```
## Warning: Using 'size' aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use 'linewidth' instead.
## This warning is displayed once every 8 hours.
## Call 'lifecycle::last_lifecycle_warnings()' to see where this warning was
## generated.
```



```
filename <- "CSI_online_aphasia_spoken_plot_rt_across_sessions.pdf"
ggsave(plot_vot, filename =
  here::here("results", "figures", filename),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
```

```
means_final<- df_RTs %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("PosOr", "session"),
    betweenvars = "group", na.rm = T)
override.linetype<-c("longdash", "dashed", "dotted")
(plot_rt_repetition_PWA <- means_final %>% filter(group=="PWA") %>%
  mutate(session=case_when(session == "1" ~ "day 1",
    session == "2" ~ "day 2",
    session == "3" ~ "day 8"))) %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
    geom="line", size = 0.5) +
  scale_linetype_manual(values=c("longdash", "dashed", "dotted"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
```

```

width = .1) +
  apatheme+
  scale_y_continuous(limits = c(1120, 1450),
                     breaks = seq(1150, 1450, by = 50)) +
  labs(x = "Ordinal Position", y = "VOT (ms)", colour = "Session",
       linetype = "Session",
       title = "People with Aphasia") +
  theme(
    axis.title.y = element_text(margin = margin(0, 10, 0, 0)),
    axis.title.x = element_text(margin = margin(10, 0, 0, 0)),
    legend.key.width = unit(1, "cm"),
    legend.position = "none") +
  guides(color = guide_legend(
    override.aes = list(linetype = override.linetype))) +
  scale_linetype(guide = "none")


```

RTs by Group, session, and ordinal position

```

## Scale for linetype is already present.
## Adding another scale for linetype, which will replace the existing scale.

```



```

(plot_rt_repetition_control <- means_final %>%
  filter(group == "control") %>%
  mutate(session = case_when(session == "1" ~ "day 1",
                             session == "2" ~ "day 2",

```

```


    session == "3" ~ "day 8")) %>%
ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
geom_point(size = 2)+
stat_summary(aes(linetype=session),fun=mean,
              geom="line", size = 0.5) +
scale_linetype_manual(values=c("longdash", "dashed", "dotted"))+
scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
              width =.1) +

apatheme+
scale_y_continuous(limits = c(1120, 1450),
                   breaks =seq(1150,1450, by = 50)) +
labs(x="Ordinal Position ",y ="VOT (ms)", colour="Session", linetype="Session",
      title = "Control Group") +
theme(
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"))+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```
plots <- cowplot::plot_grid(
  plot_rt_repetition_PWA, plot_rt_repetition_control,
  nrow = 1, ncol=2, rel_widths = c(0.81,1), #rel_height = c(1,1),
  margin(1,1,1,1),
  labels = c("A", "B"), label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_rt_by_repetition.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 25, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

```
# means_subject <- df_RTs %>%
#   filter(category != "Filler") %>%
#   summarySEwithin(., "VOT", withinvars = c("subject", "session", "PosOr"),
#     betweenvars="group")
# (means_subject <- means_subject %>%
#   group_by(subject) %>%
#   dplyr::mutate(VOT_norm = VOT - first(VOT)))
#
# (boxplot <-
#   ggplot() +
#   ## boxplot
#   geom_boxplot(data=means_subject, aes(x = PosOr, y = VOT_norm,
#     color=group),
#     #colour = "grey",
#     width = 0.3, fatten = 1)+
#   # ### individual means
#   geom_jitter(data=means_subject, aes(x = PosOr, y = VOT_norm, color=group),
#     position = position_dodge(0.6),
#     shape=19,
#     #color = "dark grey",
#     size=2)+
#   ### group means
#   stat_summary(data=means_subject, aes(x = PosOr, y = VOT_norm,
#     color=group),
#     fun=mean, geom="point",
#     #colour = "black",
#     shape=18, size=5)+
#   ### line
#   stat_summary(data=means_subject, aes(x = PosOr, y = VOT_norm,
#     color=group, group=group),
#     fun=mean, geom="line",
#     #colour = "black",
```



```
#           linetype = "longdash")+
#
# ## other stuff
# #scale_y_continuous(breaks = seq(600, 1300, by = 50))+
# labs(x="Ordinal Position",y="Normalized RTs (ms)")+
# apatheme +
# theme(
#   axis.title.y = element_text(margin = margin(0,10,0,0)),
#   axis.title.x = element_text(margin = margin(10,0,0,0)) +
#   coord_equal(ratio = 1/100))
#
# filename <- "CSI_online_aphasia_spoken_boxplot.pdf"
# ggsave(boxplot, filename =
#   here::here("results", "figures", filename),
#   width = 18, height = 18, units = "cm",
#   dpi = 300, device = cairo_pdf)
# embedFonts(file = here::here("results", "figures", filename))
```

## Normalized boxplot Export plot grid


```
# cowplot::plot_grid(plot_rt, boxplot,
#   nrow = 1, labels = c("A", "B"), label_fontfamily = "Arial") %>%
# ggsave(filename = here::here("results", "figures",
#   "CSI_online_aphasia_typing_RT_and_normalized_RT"),
#   width = 18, height = 13, units = "cm", dpi = 300,
#   device = cairo_pdf)
# embedFonts(file = here::here("results", "figures", "CSI_online_typing_RT_and_normalized_RT"))
```

```
# (plot_rt_fillers <- df %>%
#   mutate(kind = case_when(category == "Filler" ~"Filler",
#     category != "Filler" ~"Experimental")) %>%
#   ggplot(., aes(x=PosOr, y=timing.01, group=kind, color=kind)) +
#   stat_summary(fun=mean, geom="point", size = 2)+
#   stat_summary(fun=mean, geom="line", size = 1) +
#   apatheme+
#   labs(x="Ordinal Position ",y="RT (ms)", color = "Trial type")+
#   annotate(geom="text", x=1.5, y=1350, label="n = 30",
#     color="black", size = 8))
#
# filename <- "CSI_online_typing_plot_rt_with_fillers.pdf"
# ggsave(plot_rt_fillers, filename =
#   here::here("results", "figures", filename),
#   width = 18, height = 13, units = "cm",
#   dpi = 300, device = cairo_pdf)
# embedFonts(file = here::here("results", "figures", filename))
```

... with fillers for control

**Control: Plot RTs across the experiment** All correct trials (Excluding filler)

```
(plot_RT_s_all <- ggplot(data=df_RT_s, aes(x=trial, y=VOT,
                                           linetype=session, shape=session,
                                           color=group)) +
  stat_summary(aes(color=group, shape=session), fun=mean,
              geom="point", size = 2) +
  stat_summary(aes(color=group, linetype=session), fun=mean,
              geom="line", size = 1) +
  apatheme +
  labs(x="Trial ", y="VOT (ms)") +
  scale_color_manual(values=c(control_color, PWA_color)))
```



```
filename <- "CSI_online_aphasia_spoken_plot_rts_across_experiment.pdf"
ggsave(plot_RT_s_all, filename =
  here::here("results", "figures", filename),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

## Inferential statistics

**Contrast coding** *Center predictor variable*  
 Across both groups.

```
write.csv2(df_RTs,
  here::here("data", "transient_data_files",
    "RT_data_final"),
  sep=",")
```

```
## Warning in write.csv2(df_RTs, here::here("data", "transient_data_files", :
## attempt to set 'sep' ignored
```

```
df_RTs$PosOr.cont <- scale(as.numeric(as.character(df_RTs$PosOr)),
  center = T, scale = F)
table(df_RTs$PosOr.cont)
```

```
##
## -1.98458450421517 -0.984584504215175 0.0154154957848252 1.01541549578483
## 2528 2506 2480 2512
## 2.01541549578483
## 2429
```

```
mean(df_RTs$PosOr.cont); sd(df_RTs$PosOr.cont)
```

```
## [1] -0.000000000000000002197888
```

```
## [1] 1.412368
```

For PWA only

```
df_RTs_PWA <- df_RTs %>% filter(group=="PWA") %>% droplevels()
df_RTs_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RTs_PWA$PosOr)),
  center = T, scale = F)
table(df_RTs_PWA$PosOr.cont)
```

```
##
## -1.96955418629938 -0.969554186299384 0.0304458137006161 1.03044581370062
## 1132 1117 1103 1119
## 2.03044581370062
## 1047
```

```
mean(df_RTs_PWA$PosOr.cont); sd(df_RTs_PWA$PosOr.cont)
```

```
## [1] -0.000000000000000001123241
```

```
## [1] 1.40862
```

*Compute further contrasts*

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTs$session)<-my.simple
levels(df_RTs$session)
```

```
## [1] "1" "2" "3"
```

```
contrasts(df_RTs_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Define contrast of group
contrasts(df_RTs$group) <- MASS::contr.sdif(2)
levels(df_RTs$group)
```

```
## [1] "control" "PWA"
```

```
levels(df_RTs_PWA$group)
```

```
## [1] "PWA"
```

*didLMERconverge function*

```
## This function provides a better convergence check for lme4 v>1.0 models, which have a nasty habit of
didLmerConverge = function(lmerModel){
  relativeMaxGradient=signif(max(abs(with(
    lmerModel@optinfo$derivs,solve(Hessian,gradient)))),3)
  if (relativeMaxGradient < 0.001) {
    cat(sprintf("\tThe relative maximum gradient of %s is less than our 0.001 criterion.\n\tYou can safely
  })
  else {
    cat(sprintf("The relative maximum gradient of %s exceeds our 0.001 criterion.\nThis looks like a real
  })
}


#didLmerConverge(m1)
```

**Check distribution of data** Are the data normally distributed or do they need to be converted? Does a Gamma function fit the data better?

*Histogram of the reaction time data*


```
hist(df_RTs$VOT)
```

**Histogram of df\_RTs\$VOT**



```
hist(df_RTs_PWA$VOT)
```

## Histogram of df\_RTs\_PWA\$VOT



*Exclude unrealistically short reaction times < 200 ms*

```
sum(df_RTs$VOT < 200)
```

```
## [1] 0
```

```
df_RTs <- df_RTs %>% filter(VOT >=200)
```

```
sum(df_RTs_PWA$VOT < 200)
```

```
## [1] 0
```


```
df_RTs_PWA <- df_RTs_PWA %>% filter(VOT >=200)
```

**LMMs: Transformed RTs** In our pre-registration, we planned to conduct a GLMM with a Gamma distribution to account for the non-normality of the data. However, the standard errors seem suspiciously small and additional analyses showed that the GLMM doesn't converge with other types of analyses (see Appendix). Therefore, we decided to conduct an LMM with transformed RTs instead.

**Analysis with factors Ordinal position x Session x Group** *Box-cox test*

(common transformations: -2 ->  $1/(Y^2)$ , -1 ->  $1/y$ , -0.5 ->  $1/(\sqrt{y})$ ), 0 ->  $\log(y)$ , 0.5 ->  $\sqrt{y}$ , 1 ->  $y$ , 2 ->  $y^2$ , 3 ->  $y^3$ )

```
MASS::boxcox(df_RTs$VOT ~ df_RTs$PosOr*df_RTs$session*df_RTs$group)
```



```
## Box-Cox suggests log transformation
df_RTs$lVOT <- log(df_RTs$VOT)
```

*Compute full model, then compute step-wise reduction*

```
library(lmerTest)
# m2_lmm <- lmer(lVOT ~ PosOr.cont*session*group +
#               (PosOr.cont*session/subject) +
#               (PosOr.cont*session*group/category),
#               data = df_RTs,
#               control=lmerControl(optimizer = "bobyqa"))
# didLmerConverge(m2_lmm)
```

Model fails to converge -> Reduce

```
# 1) Increase optimizer iterations
# m2_lmm <- lmer(lVOT ~ PosOr.cont*session*group +
#               (PosOr.cont*session/subject) +
#               (PosOr.cont*session*group/category),
#               data = df_RTs,
#               control=lmerControl(optimizer = "bobyqa",
#                                   optCtrl = list(maxfun = 2e5)))
```

```

# didLmerConverge(m2_lmm)

# 2) Omit correlation parameters as model still fails to converge
# m2_lmm <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                           (PosOr.cont*session||subject) +
#                           (PosOr.cont*session*group||category),
#                           data = df_RTs,
#                           control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))

# 3) Model fit is still singular -> Further reduce the model
# m2_lmm <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                           (PosOr.cont+session||subject) +
#                           (PosOr.cont+group||category),
#                           data = df_RTs,
#                           control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))

# 4) Does the model also converge when correlation parameters are included - yes!
m2_lmm <- lmer(lVOT ~ PosOr.cont*session*group +
               (PosOr.cont+session|subject) +
               (PosOr.cont+group|category),
               data = df_RTs,
               control=lmerControl(optimizer = "bobyqa",
                                   optCtrl = list(maxfun = 2e5)))

# rePCA(m2_lmm)
didLmerConverge(m2_lmm)

```

```

## The relative maximum gradient of 0.00000257 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.

```

```

## Warnings can be ignored

```

```

summary(m2_lmm)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ PosOr.cont * session * group + (PosOr.cont + session |
##           subject) + (PosOr.cont + group | category)
## Data: df_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1158.2
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -4.8980 -0.6647 -0.1747  0.4804  5.6443
##
## Random effects:
##  Groups   Name                Variance  Std.Dev. Corr
##  subject  (Intercept)  0.03572310  0.189006
##           PosOr.cont    0.00010406  0.010201  0.18
##           session2      0.00339920  0.058303 -0.13  0.24
##           session3      0.00406330  0.063744 -0.49  0.26  0.64

```



```

## category (Intercept) 0.00884981 0.094073
##           Pos0r.cont 0.00002358 0.004856 0.07
##           group2-1   0.00090450 0.030075 0.08 0.16
## Residual           0.06154884 0.248090
## Number of obs: 12455, groups: subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate      Std. Error      df t value
## (Intercept)      7.116562      0.035604    58.495400 199.883
## Pos0r.cont        0.016922      0.002489    30.170032   6.800
## session2         -0.076082      0.010856    38.392327  -7.008
## session3         -0.089211      0.011561    36.616785  -7.717
## group2-1          0.157635      0.060276    38.561991   2.615
## Pos0r.cont:session2 0.004635      0.003924  12260.584027   1.181
## Pos0r.cont:session3 0.003648      0.003895  12262.086513   0.937
## Pos0r.cont:group2-1 0.006992      0.004565    37.104902   1.532
## session2:group2-1  -0.025605      0.021711    38.391896  -1.179
## session3:group2-1  -0.020079      0.023122    36.616755  -0.868
## Pos0r.cont:session2:group2-1 0.013305      0.007848  12258.935598   1.695
## Pos0r.cont:session3:group2-1 0.003095      0.007790  12261.681674   0.397
##
##              Pr(>|t|)
## (Intercept)      < 0.0000000000000002 ***
## Pos0r.cont        0.00000014849 ***
## session2          0.00000002268 ***
## session3          0.00000000345 ***
## group2-1          0.0127 *
## Pos0r.cont:session2 0.2376
## Pos0r.cont:session3 0.3489
## Pos0r.cont:group2-1 0.1341
## session2:group2-1  0.2455
## session3:group2-1  0.3908
## Pos0r.cont:session2:group2-1 0.0901 .
## Pos0r.cont:session3:group2-1 0.6912
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Ps0r.c sessn2 sessn3 grp2-1 Ps0.:2 Ps0.:3 P0.:2- s2:2-1
## Pos0r.cont    0.114
## session2     -0.096 0.134
## session3     -0.361 0.151 0.612
## group2-1      0.006 0.008 -0.001 -0.002
## Ps0r.cnt:s2   0.000 -0.011 0.005 0.003 0.000
## Ps0r.cnt:s3   0.000 -0.020 0.003 0.003 0.000 0.515
## Ps0r.cn:2-1   0.001 0.069 0.001 0.002 0.126 -0.011 -0.016
## sssn2:gr2-1  -0.001 0.001 0.051 0.027 -0.114 0.007 0.005 0.146
## sssn3:gr2-1  -0.001 0.002 0.027 0.040 -0.426 0.005 0.007 0.164 0.612
## Ps0r.:2:2-1   0.000 -0.010 0.007 0.005 0.000 0.129 0.075 -0.012 0.005
## Ps0r.:3:2-1   0.000 -0.014 0.005 0.007 0.000 0.075 0.126 -0.022 0.003
##
##              s3:2-1 P0.:2:
## Pos0r.cont
## session2
## session3
## group2-1

```

```
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## Ps0r.cn:2-1
## sssn2:gr2-1
## sssn3:gr2-1
## Ps0r.:2:2-1 0.003
## Ps0r.:3:2-1 0.003 0.515
```

```
anova(m2_lmm)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##
##          Sum Sq Mean Sq NumDF    DenDF F value    Pr(>F)
## Pos0r.cont      2.8457  2.84571     1      30.2 46.2349 0.00000014849 ***
## session          4.1782  2.08908     2      37.5 33.9418 0.00000000389 ***
## group            0.4210  0.42096     1      38.6  6.8394    0.01266 *
## Pos0r.cont:session 0.0949  0.04746     2 12260.9  0.7711    0.46251
## Pos0r.cont:group   0.1444  0.14438     1      37.1  2.3457    0.13411
## session:group      0.0877  0.04386     2      37.5  0.7125    0.49693
## Pos0r.cont:session:group 0.1958  0.09790     2 12259.7  1.5906    0.20385
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
saveRDS(m2_lmm, file = here::here("results", "tables", "CSI_online_aphasia_SessionxGroup_control_lmm_VOT.html"),
tab_model(m2_lmm, transform = NULL,
  show.re.var = F, #T,
  show.stat = T, show.r2 = T, show.icc = T,
  title = "LMM of VOTs Predicted by Ordinal Position and Session",
  dv.labels = "Vocal Onset Time (log-transformed)",
  #string.pred = "",
  df.method = "satterthwaite",
  string.stat = "t-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_spoken_SessionxGroup_lmm_VOT.html"))
```

LMM of VOTs Predicted by Ordinal Position and Session

Vocal Onset Time (log-transformed)

Predictors

Estimates

CI

t-Value

p

(Intercept)

7.12

7.05 – 7.19

199.88

<0.001  
 PosOr cont  
 0.02  
 0.01 – 0.02  
 6.80  
 <0.001  
 session [2]  
 -0.08  
 -0.10 – -0.05  
 -7.01  
 <0.001  
 session [3]  
 -0.09  
 -0.11 – -0.07  
 -7.72  
 <0.001  
 group2-1  
 0.16  
 0.04 – 0.28  
 2.62  
 0.013  
 PosOr cont  $\times$  session [2]  
 0.00  
 -0.00 – 0.01  
 1.18  
 0.238  
 PosOr cont  $\times$  session [3]  
 0.00  
 -0.00 – 0.01  
 0.94  
 0.349  
 PosOr.cont:group2-1  
 0.01  
 -0.00 – 0.02  
 1.53  
 0.134

```

session2:group2-1
-0.03
-0.07 – 0.02
-1.18
0.246
session3:group2-1
-0.02
-0.07 – 0.03
-0.87
0.391
PosOr.cont:session2:group2-1
0.01
-0.00 – 0.03
1.70
0.090
PosOr.cont:session3:group2-1
0.00
-0.01 – 0.02
0.40
0.691
ICC
0.43
N subject
40
N category
24
Observations
12455
Marginal R2 / Conditional R2
0.070 / 0.468

```

```


## Check model
#performance::check_model(m2_lmm)
# ggResidpanel::resid_panel(m2_lmm, smoother = TRUE,
#                             qqbands = TRUE, type = "pearson")
performance::model_performance(m2_lmm)

```


```
## # Indices of model performance
##
## AIC      |      AICc |      BIC | R2 (cond.) | R2 (marg.) | ICC | RMSE | Sigma
## -----
## 1216.212 | 1216.352 | 1431.678 | 0.468 | 0.070 | 0.428 | 0.246 | 0.248
```

PWA only


```
MASS::boxcox(df_RTs$VOT ~ df_RTs$group*df_RTs$PosOr*df_RTs$session)
```



```
MASS::boxcox(df_RTs_PWA$VOT ~ df_RTs_PWA$PosOr*df_RTs_PWA$session)
```



```
## Box-Cox suggests log transformation --> compute with log-transformed RTs as s control analysis  
MASS::boxcox(log(df_RT_PWA$VOT) ~ df_RT_PWA$PosOr*df_RT_PWA$session)
```



```
df_RTs_PWA$VOTlog <- log(df_RTs_PWA$VOT)
```

*Compute full model, then compute step-wise reduction until model convergence*

```
library(lmerTest)
# m1_lmm_PWA <- lmer(VOTlog ~ PosOr.cont*session +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session/category),
#                   data = df_RTs_PWA,
#                   control=lmerControl(optimizer = "bobyqa"))
# didLmerConverge(m1_lmm_PWA)
```

Model fails to converge -> Reduce

```
# 1) Increase optimizer iterations
# m1_lmm_PWA <- lmer(VOTlog ~ PosOr.cont*session +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session/category),
#                   data = df_RTs_PWA,
#                   control=lmerControl(optimizer = "bobyqa",
#                                       optCtrl = list(maxfun = 2e5)))
# didLmerConverge(m1_lmm_PWA)

# 2) Omit correlation parameters as model still fails to converge
# m1_lmm_PWA <- afex::lmer_alt(VOTlog ~ PosOr.cont*session +
```

```

#           (PosOr.cont*session||subject) +
#           (PosOr.cont*session||category),
#           data = df_RTs_PWA,
#           control=lmerControl(optimizer = "bobyqa",
#                               optCtrl = list(maxfun = 2e5)))
# rePCA(m1_lmm_PWA)

# 3) The model still has a singular fit -> reduce
# m1_lmm_PWA <- afex::lmer_alt(VOTlog ~ PosOr.cont*session +
#                             (PosOr.cont*session||subject) +
#                             (PosOr.cont*session-PosOr.cont||category),
#                             data = df_RTs_PWA,
#                             control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))
# m1_lmm_PWA <- afex::lmer_alt(VOTlog ~ PosOr.cont*session +
#                             (PosOr.cont*session||subject) +
#                             (PosOr.cont*session-PosOr.cont-session||category),
#                             data = df_RTs_PWA,
#                             control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))
# m1_lmm_PWA <- afex::lmer_alt(VOTlog ~ PosOr.cont*session +
#                             (PosOr.cont*session||subject) +
#                             (1|category),
#                             data = df_RTs_PWA,
#                             control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))
# m1_lmm_PWA <- afex::lmer_alt(VOTlog ~ PosOr.cont*session +
#                             (PosOr.cont+session||subject) +
#                             (1|category),
#                             data = df_RTs_PWA,
#                             control=lmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))

# 4) Test whether the model also converges including correlation parameters -> yes
m1_lmm_PWA <- lmer(VOTlog ~ PosOr.cont*session +
                  (PosOr.cont+session|subject) +
                  (1|category),
                  data = df_RTs_PWA,
                  control=lmerControl(optimizer = "bobyqa",
                                      optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA)

```

```

## The relative maximum gradient of 0.00000429 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.

```

```

## Warnings can be ignored

```

```

summary(m1_lmm_PWA)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) +
##         (1 | category)

```



```

## Data: df_RT_S_PWA
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1705.5
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.4857 -0.6809 -0.1843  0.5084  5.0807
##
## Random effects:
##   Groups   Name                Variance Std.Dev. Corr
##   category (Intercept) 0.0092445 0.09615
##   subject  (Intercept) 0.0616484 0.24829
##             PosOr.cont 0.0001271 0.01128  0.35
##             session2   0.0009406 0.03067 -0.26  0.07
##             session3   0.0035352 0.05946 -0.68 -0.14  0.21
## Residual                0.0760739 0.27581
## Number of obs: 5518, groups: category, 24; subject, 20
##
## Fixed effects:
##              Estimate Std. Error      df t value
## (Intercept)      7.195573    0.059036   23.613808 121.884
## PosOr.cont        0.020682    0.003710   17.682005  5.575
## session2         -0.088051    0.011650   16.035853 -7.558
## session3         -0.099095    0.016309   17.569075 -6.076
## PosOr.cont:session2  0.011439    0.006552  5438.077615  1.746
## PosOr.cont:session3  0.005320    0.006495  5440.067017  0.819
##
##              Pr(>|t|)
## (Intercept)    < 0.0000000000000002 ***
## PosOr.cont      0.00002905 ***
## session2        0.00000113 ***
## session3        0.00001071 ***
## PosOr.cont:session2  0.0809 .
## PosOr.cont:session3  0.4128
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) PsOr.c sessn2 sessn3 Ps0.:2
## PosOr.cont    0.224
## session2     -0.145  0.031
## session3     -0.523 -0.079  0.341
## PsOr.cnt:s2   0.000 -0.021  0.004  0.003
## PsOr.cnt:s3  -0.001 -0.035  0.003  0.003  0.522

```

```
anova(m1_lmm_PWA)
```

```

## Type III Analysis of Variance Table with Satterthwaite's method
##              Sum Sq Mean Sq NumDF DenDF F value      Pr(>F)
## PosOr.cont    2.3644 2.36438      1   17.7 31.0800 0.0000290471 ***
## session       5.4010 2.70050      2   17.5 35.4984 0.0000006973 ***
## PosOr.cont:session 0.2328 0.11641      2 5437.7  1.5303      0.2166
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

saveRDS(m1_lmm_PWA, file = here::here(
  "results", "tables", "CSI_online_aphasia_PWA_control_lmm_VOT.RDS"))
tab_model(m1_lmm_PWA, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title = "LMM of VOTs Predicted by Ordinal Position and Session",
  df.method = "satterthwaite",
  dv.labels = "Vocal Onset Time (log-transformed)",
  #string.pred = "",
  string.stat = "t-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_PWA_control_lmm_VOT.html"))

```

## LMM of VOTs Predicted by Ordinal Position and Session

Vocal Onset Time (log-transformed)

Predictors

Estimates

CI

t-Value

p

(Intercept)

7.20

7.07 – 7.32

121.88

<0.001

PosOr cont

0.02

0.01 – 0.03

5.57

<0.001

session [2]

-0.09

-0.11 – -0.06

-7.56

<0.001

session [3]

-0.10

-0.13 – -0.06

-6.08

<0.001  
 PosOr cont  $\times$  session [2]  
 0.01  
 -0.00 – 0.02  
 1.75  
 0.081  
 PosOr cont  $\times$  session [3]  
 0.01  
 -0.01 – 0.02  
 0.82  
 0.413  
 N subject  
 20  
 N category  
 24  
 Observations  
 5518

```
## check model fit
#performance::check_model(m1_lmm_PWA)
# ggResidpanel::resid_panel(m1_lmm_PWA, smoother = TRUE,
#                             qqbands = TRUE, type = "pearson")
performance::model_performance(m1_lmm_PWA)
```

```
## # Indices of model performance
##
## AIC      |      AICc |      BIC | R2 (cond.) | R2 (marg.) |  ICC |  RMSE | Sigma
## -----|-----|-----|-----|-----|-----|-----|-----|-----
## 1741.484 | 1741.609 | 1860.568 |      0.495 |      0.019 | 0.485 | 0.274 | 0.276
```

## ERROR RATES

### Descriptives

```
df_errors %>% group_by(group) %>% count(error_class) %>%
  mutate(percentage=n/(nrow(df[df$category!="Filler" &
                                df$group=="PWA",])))
```

### Error types

```
## # A tibble: 4 x 4
## # Groups:   group [2]
##   group error_class      n percentage
##   <fct>      <dbl> <int>      <dbl>
## 1 control      0  6952      0.966
## 2 control      1   167      0.0232
## 3 PWA           0  5637      0.783
## 4 PWA           1  1541      0.214
```

```
df_errors %>% group_by(group, session) %>% count(error_class) %>%
  mutate(percentage=n/(nrow(df[df$category!="Filler" & df$group=="PWA" &
    df$session=="1",])))
```

```
## # A tibble: 12 x 5
## # Groups:   group, session [6]
##   group session error_class      n percentage
##   <fct> <fct>      <dbl> <int>      <dbl>
## 1 control 1          0  2284      0.952
## 2 control 1          1    77      0.0321
## 3 control 2          0  2316      0.965
## 4 control 2          1    57      0.0238
## 5 control 3          0  2352      0.98
## 6 control 3          1    33      0.0138
## 7 PWA     1          0  1777      0.740
## 8 PWA     1          1   609      0.254
## 9 PWA     2          0  1892      0.788
## 10 PWA    2          1   506      0.211
## 11 PWA    3          0  1968      0.82
## 12 PWA    3          1   426      0.178
```

```
df_errors %>% group_by(group) %>% count(error) %>%
  mutate(percentage=n/(nrow(df[df$category!="Filler" &
    df$group=="PWA",])))
```

```
## # A tibble: 20 x 4
## # Groups:   group [2]
##   group error      n percentage
##   <fct> <chr> <int>      <dbl>
## 1 control 1          1  0.000139
## 2 control 2         40  0.00556
## 3 control 3         32  0.00444
## 4 control 4         31  0.00431
## 5 control 5          1  0.000139
## 6 control 6          6  0.000833
## 7 control 7         35  0.00486
## 8 control 8          3  0.000417
## 9 control 9         18  0.0025
## 10 control <NA>  6952  0.966
## 11 PWA     1         56  0.00778
## 12 PWA     2        148  0.0206
## 13 PWA     3         62  0.00861
## 14 PWA     4        820  0.114
## 15 PWA     5         32  0.00444
```

```
## 16 PWA      6      40  0.00556
## 17 PWA      7     102  0.0142
## 18 PWA      8      29  0.00403
## 19 PWA      9     252  0.035
## 20 PWA     <NA>  5637  0.783
```

```
df_errors %>% group_by(group, session) %>% count(error) %>%
  mutate(percentage=n/(nrow(df[df$category!="Filler" & df$group=="PWA" &
    df$session=="1",])))
```

```
## # A tibble: 54 x 5
## # Groups:   group, session [6]
##   group session error    n percentage
##   <fct>   <fct>   <chr> <int>      <dbl>
## 1 control 1      2      15  0.00625
## 2 control 1      3      13  0.00542
## 3 control 1      4      14  0.00583
## 4 control 1      6       2  0.000833
## 5 control 1      7      23  0.00958
## 6 control 1      9      10  0.00417
## 7 control 1     <NA>  2284  0.952
## 8 control 2      1       1  0.000417
## 9 control 2      2      17  0.00708
## 10 control 2     3      11  0.00458
## # i 44 more rows
```

```
table(df_errors$error_class, df_errors$error) # technical errors are not counted as errors
```

```
##
##      1  2  3  4  5  6  7  8  9
## 0  0  0  0  0  0  0  0  0  0
## 1  1  57 188 94 851 33 46 137 32 270
```

```
table(df_errors$error_class[is.na(df_errors$error)]) # correct responses
```

```
##
##      0
## 12589
```

```
error_overview <- data.frame(subject=factor(rep(unique(df$subject),
  each=5*3)),
  group=factor(rep(c("PWA", "control"),
    each=20*5*3)),
  session=factor(rep(c("1", "2", "3"),
    each=5,
    times=
      length(unique(df$subject)))),
  PosOr=factor(rep(c("1", "2", "3", "4", "5"),
    times=length(unique(df$subject))*3)),
```

```

                                error_class=0)
x <- df_errors %>% group_by(subject, session, PosOr) %>%
  count(error_class) %>%
  filter(error_class==1)
for(i in 1:nrow(x)){
  error_overview$error_class[error_overview$subject==x$subject[i] &
    error_overview$session==x$session[i] &
    error_overview$PosOr==x$PosOr[i] ] <-
    x$n[i]
}
error_overview$percentage <- (error_overview$error_class/24)*100

(means_final_errors <- error_overview %>%
  group_by(group,session,PosOr) %>%
  summarise(count=sum(error_class), mean=mean(error_class),
    sd=sd(error_class), se=sd(error_class)/20,
    mean_p = mean(percentage),
    sd_p=sd(percentage), se_p=sd(percentage)/20))

```

## Amount of errors

## 'summarise()' has grouped output by 'group', 'session'. You can override using  
## the '.groups' argument.

```

## # A tibble: 30 x 10
## # Groups:   group, session [6]
##   group session PosOr count mean sd se mean_p sd_p se_p
##   <fct> <fct> <fct> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 control 1 1 13 0.65 0.745 0.0373 2.71 3.10 0.155
## 2 control 1 2 14 0.7 0.733 0.0366 2.92 3.05 0.153
## 3 control 1 3 19 0.95 0.759 0.0380 3.96 3.16 0.158
## 4 control 1 4 14 0.7 0.801 0.0401 2.92 3.34 0.167
## 5 control 1 5 17 0.85 0.745 0.0373 3.54 3.10 0.155
## 6 control 2 1 9 0.45 0.686 0.0343 1.87 2.86 0.143
## 7 control 2 2 15 0.75 1.02 0.0510 3.12 4.25 0.212
## 8 control 2 3 8 0.4 0.503 0.0251 1.67 2.09 0.105
## 9 control 2 4 9 0.45 0.759 0.0380 1.87 3.16 0.158
## 10 control 2 5 16 0.8 0.834 0.0417 3.33 3.47 0.174
## # i 20 more rows

```

```

# Export as word file
library(flextable)
huxt_word <- huxtable::huxtable(means_final_errors)
huxt_word <- huxtable::set_number_format(huxt_word, round(2))
huxtable::quick_docx(huxt_word,
  file =
    here::here(
      "results", "tables",
      "CSI_online_PWA_errors_by_session.docx"),
  open = FALSE)

```

Calculate increase mean by ordinal position, separately for each session (not controlled for random variances, weighted only per session):

```

means_final_errors$increase_count <- NA
means_final_errors$increase_mean <- NA
for(k in 1:length(unique(means_final_errors$group))){
for(i in 1:length(unique(means_final_errors$session))){
  for(j in 2:length(unique(means_final_errors$PosOr))){
    means_final_errors$increase_count[
      means_final_errors$session==unique(means_final_errors$session)[i] &
      means_final_errors$PosOr==unique(means_final_errors$PosOr)[j] &
      means_final_errors$group==unique(means_final_errors$group)[k]] <-
      means_final_errors$count[means_final_errors$session==
        unique(means_final_errors$session)[i] &
        means_final_errors$PosOr==
        unique(means_final_errors$PosOr)[j] &
        means_final_errors$group==unique(means_final_errors$group)[k]] -
      means_final_errors$count[
        means_final_errors$session==
        unique(means_final_errors$session)[i] &
        means_final_errors$PosOr==
        unique(means_final_errors$PosOr)[j-1] &
        means_final_errors$group==unique(means_final_errors$group)[k]]
    means_final_errors$increase_mean[
      means_final_errors$session==unique(means_final_errors$session)[i] &
      means_final_errors$PosOr==
      unique(means_final_errors$PosOr)[j] &
      means_final_errors$group==unique(means_final_errors$group)[k]] <-
      means_final_errors$mean[means_final_errors$session==
        unique(means_final_errors$session)[i] &
        means_final_errors$PosOr==
        unique(means_final_errors$PosOr)[j-1] &
        means_final_errors$group==
        unique(means_final_errors$group)[k]]
  }}}
#means_final_errors

## Calculate overall mean increase per session (weighted: all PosOrs had the same amount of trials)
mean(means_final_errors$increase_mean[
  means_final_errors$session==1], na.rm=T)

```

```
## [1] 0.28125
```

```

means_final_errors$PosOr_effect <- NA
means_final_errors$PosOr_effect[means_final_errors$PosOr==1] <- 1
for(k in 1:length(unique(means_final_errors$group))){
for(i in 1:length(unique(means_final_errors$session))){
  means_final_errors$PosOr_effect[
    means_final_errors$session==unique(means_final_errors$session)[i] &
    means_final_errors$group==unique(means_final_errors$group)[k] &
    means_final_errors$PosOr=="1"] <-
    (means_final_errors$increase_mean[

```

```

means_final_errors$session==unique(means_final_errors$session)[i] &
  means_final_errors$group==unique(means_final_errors$group)[k] &
  means_final_errors$PosOr=="2")+
means_final_errors$increase_mean[
  means_final_errors$session==
    unique(means_final_errors$session)[i] &
  means_final_errors$group==unique(means_final_errors$group)[k] &
  means_final_errors$PosOr=="3")+
means_final_errors$increase_mean[
  means_final_errors$session==
    unique(means_final_errors$session)[i] &
  means_final_errors$group==unique(means_final_errors$group)[k] &
  means_final_errors$PosOr=="4")+
means_final_errors$increase_mean[
  means_final_errors$session==
    unique(means_final_errors$session)[i] &
  means_final_errors$group==unique(means_final_errors$group)[k] &
  means_final_errors$PosOr=="5"])/4
}}
means_final_errors

```

```

## # A tibble: 30 x 13
## # Groups:   group, session [6]
##   group session PosOr count mean sd se mean_p sd_p se_p
##   <fct> <fct> <fct> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 control 1 1 13 0.65 0.745 0.0373 2.71 3.10 0.155
## 2 control 1 2 14 0.7 0.733 0.0366 2.92 3.05 0.153
## 3 control 1 3 19 0.95 0.759 0.0380 3.96 3.16 0.158
## 4 control 1 4 14 0.7 0.801 0.0401 2.92 3.34 0.167
## 5 control 1 5 17 0.85 0.745 0.0373 3.54 3.10 0.155
## 6 control 2 1 9 0.45 0.686 0.0343 1.87 2.86 0.143
## 7 control 2 2 15 0.75 1.02 0.0510 3.12 4.25 0.212
## 8 control 2 3 8 0.4 0.503 0.0251 1.67 2.09 0.105
## 9 control 2 4 9 0.45 0.759 0.0380 1.87 3.16 0.158
## 10 control 2 5 16 0.8 0.834 0.0417 3.33 3.47 0.174
## # i 20 more rows
## # i 3 more variables: increase_count <dbl>, increase_mean <dbl>,
## # PosOr_effect <dbl>

```

Different kinds of errors per ordinal position

```
table(df_errors$error)
```

```

##
## 1 2 3 4 5 6 7 8 9
## 57 188 94 851 33 46 137 32 270

```

```

(df_errors %>% group_by(group, session, error, PosOr) %>%
  count() -> z)

```

```

## # A tibble: 232 x 5
## # Groups:   group, session, error, PosOr [232]

```



```
##      group  session error PosOr      n
##      <fct>   <fct>   <chr> <fct> <int>
##  1 control 1         2      1        1
##  2 control 1         2      2        4
##  3 control 1         2      3        6
##  4 control 1         2      4        2
##  5 control 1         2      5        2
##  6 control 1         3      1        1
##  7 control 1         3      2        2
##  8 control 1         3      3        3
##  9 control 1         3      4        5
## 10 control 1         3      5        2
## # i 222 more rows
```

```
w <- data.frame(group=rep(c("control", "PWA"), each=3*10*5),
                session=rep(c("1","2","3"), each=10, times=2*5),
                error=rep(seq(1:10), each=5, times=2*3),
                PosOr=rep(seq(1:5), timed=10*3*2),
                n=NA)
for(i in 1:nrow(w)){
  l <- z %>% filter(group==w$group[i]&session==w$session[i]&
                    error==w$error[i]&PosOr==w$PosOr[i])
  if(nrow(l)!=0) {
    w$n[i] <- l$n
  }
}
# mean increase per error type and ordinal position
y <- data.frame(group=rep(c("control", "PWA"), each=3*10),
                session=rep(c("1","2","3"), each=10, times=2),
                error=rep(seq(1:10), times=2*3),
                m_increase=NA)
w$error[is.na(w$error)] <- 10
for(i in 1:nrow(y)){
  a1 <- w$n[w$group==y$group[i]& w$error==y$error[i] &
            w$session==y$session[i] & w$PosOr==1]
  a2 <- w$n[w$group==y$group[i]& w$error==y$error[i] &
            w$session==y$session[i] & w$PosOr==2]
  a3 <- w$n[w$group==y$group[i]& w$error==y$error[i] &
            w$session==y$session[i] & w$PosOr==3]
  a4 <- w$n[w$group==y$group[i]& w$error==y$error[i] &
            w$session==y$session[i] & w$PosOr==4]
  a5 <- w$n[w$group==y$group[i]& w$error==y$error[i] &
            w$session==y$session[i] & w$PosOr==5]
  if(!is.na(a2)&!is.na(a1)){ y$m_increase[i] <- a2-a1 }
  if(!is.na(a3)&!is.na(a2)){ y$m_increase[i] <-
    y$m_increase[i]+a3-a2 }
  if(!is.na(a4)&!is.na(a3)){ y$m_increase[i] <-
    y$m_increase[i]+a4-a3}
  if(!is.na(a5)&!is.na(a4)){ y$m_increase[i] <-
    y$m_increase[i]+a5-a4 }
  n <- sum(!is.na(c(a1,a2,a3,a4,a5)))-1
  y$m_increase[i] <- y$m_increase[i]/n
}
y
```

##	group	session	error	m_increase
## 1	control	1	1	NA
## 2	control	1	2	0.2500000
## 3	control	1	3	0.2500000
## 4	control	1	4	0.2500000
## 5	control	1	5	NA
## 6	control	1	6	NA
## 7	control	1	7	0.5000000
## 8	control	1	8	NA
## 9	control	1	9	0.2500000
## 10	control	1	10	NA
## 11	control	2	1	NA
## 12	control	2	2	NA
## 13	control	2	3	1.0000000
## 14	control	2	4	0.0000000
## 15	control	2	5	NA
## 16	control	2	6	NA
## 17	control	2	7	NA
## 18	control	2	8	0.0000000
## 19	control	2	9	NA
## 20	control	2	10	NA
## 21	control	3	1	NA
## 22	control	3	2	NA
## 23	control	3	3	-0.2500000
## 24	control	3	4	-0.5000000
## 25	control	3	5	NA
## 26	control	3	6	NA
## 27	control	3	7	NA
## 28	control	3	8	NA
## 29	control	3	9	NA
## 30	control	3	10	NA
## 31	PWA	1	1	NA
## 32	PWA	1	2	2.5000000
## 33	PWA	1	3	0.2500000
## 34	PWA	1	4	8.0000000
## 35	PWA	1	5	0.0000000
## 36	PWA	1	6	-0.5000000
## 37	PWA	1	7	-0.5000000
## 38	PWA	1	8	0.2500000
## 39	PWA	1	9	-0.7500000
## 40	PWA	1	10	NA
## 41	PWA	2	1	-0.7500000
## 42	PWA	2	2	0.5000000
## 43	PWA	2	3	-0.2500000
## 44	PWA	2	4	6.0000000
## 45	PWA	2	5	0.5000000
## 46	PWA	2	6	-0.2500000
## 47	PWA	2	7	-0.5000000
## 48	PWA	2	8	0.3333333
## 49	PWA	2	9	-0.5000000
## 50	PWA	2	10	NA
## 51	PWA	3	1	-0.2500000
## 52	PWA	3	2	1.0000000
## 53	PWA	3	3	0.0000000

```
## 54      PWA      3      4 2.0000000
## 55      PWA      3      5 -0.7500000
## 56      PWA      3      6      NA
## 57      PWA      3      7 0.2500000
## 58      PWA      3      8      NA
## 59      PWA      3      9 2.5000000
## 60      PWA      3     10      NA
```

```
# mean across sessions
(y %>% group_by(group, error) %>%
  summarise(n=sum(m_increase), isnotna=sum(!is.na(m_increase)),
            mean_increase=mean(m_increase, na.rm=T)) ->
  increase_errors)
```

## 'summarise()' has grouped output by 'group'. You can override using the  
## '.groups' argument.

```
## # A tibble: 20 x 5
## # Groups:   group [2]
##   group error    n isnotna mean_increase
##   <chr> <int> <dbl>   <int>      <dbl>
## 1 PWA      1 NA      2      -0.5
## 2 PWA      2  4      3      1.33
## 3 PWA      3  0      3      0
## 4 PWA      4 16      3      5.33
## 5 PWA      5 -0.25    3     -0.0833
## 6 PWA      6 NA      2     -0.375
## 7 PWA      7 -0.75    3     -0.25
## 8 PWA      8 NA      2      0.292
## 9 PWA      9 1.25    3      0.417
## 10 PWA     10 NA      0      NaN
## 11 control  1 NA      0      NaN
## 12 control  2 NA      1      0.25
## 13 control  3  1      3      0.333
## 14 control  4 -0.25    3     -0.0833
## 15 control  5 NA      0      NaN
## 16 control  6 NA      0      NaN
## 17 control  7 NA      1      0.5
## 18 control  8 NA      1      0
## 19 control  9 NA      1      0.25
## 20 control 10 NA      0      NaN
```

```
increase_errors %>% filter(group=="PWA") %>% count()
```

```
## # A tibble: 1 x 2
## # Groups:   group [1]
##   group    n
##   <chr> <int>
## 1 PWA     10
```

```
y %>% filter(group=="PWA") %>%
  filter(!(error %in% c(4,9,10))) %>%
  group_by(session) %>%
  summarise(mean=mean(m_increase, na.rm=T))
```

```
## # A tibble: 3 x 2
##   session    mean
##   <chr>     <dbl>
## 1 1         0.333
## 2 2        -0.0595
## 3 3         0.05
```

Calculate mean and SD of ordinal position effects in PWA group

```
# First calculate the OrdPos effect for each subject and each category separately
df_errors_PWA <- df_errors %>% filter(category!="Filler" &
                                     group=="PWA")

df_errors_PWA$OrdPos_manual <- NA_real_
isEmptyNumeric <- function(x) {
  return(identical(x, numeric(0)))
}

for (i in unique(df_errors_PWA$subject)) {
  for(j in unique(df_errors_PWA$category)) {
    for(l in unique(df_errors_PWA$session)) {
      for (k in 2:5) {
        x <- df_errors_PWA$error_class[df_errors_PWA$subject==i &
                                       df_errors_PWA$category==j &
                                       df_errors_PWA$session==l &
                                       df_errors_PWA$PosOr==k]
        xM1 <- df_errors_PWA$error_class[df_errors_PWA$subject==i &
                                       df_errors_PWA$category==j &
                                       df_errors_PWA$session==l &
                                       df_errors_PWA$PosOr==k-1]
        if(!isEmptyNumeric(x) & !isEmptyNumeric(xM1)){
          if(!is.na(x) & !is.na(xM1)){
            df_errors_PWA$OrdPos_manual[df_errors_PWA$subject==i &
                                       df_errors_PWA$category==j &
                                       df_errors_PWA$session==l &
                                       df_errors_PWA$PosOr==k] <- x - xM1
          }
        }
      }
    }
  }
}

# return summarySEwithin
df_errors_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "OrdPos_manual",
                        idvar = "subject",
                        withinvars = c("session"),
```

```

betweenvars = c("subject", "group"),
na.rm = T)

```

##	subject	group	session	N	OrdPos_manual	sd	se	ci
## 1	101	PWA	1	90	0.00615124635	0.3661726	0.03859798	0.07669337
## 2	101	PWA	2	95	0.01784715278	0.2184133	0.02240873	0.04449306
## 3	101	PWA	3	96	0.01795680190	0.1250000	0.01275776	0.02532735
## 4	102	PWA	1	96	0.01413859312	0.2172647	0.02217449	0.04402192
## 5	102	PWA	2	96	0.01413859312	0.2806829	0.02864708	0.05687164
## 6	102	PWA	3	96	0.01413859312	0.2172647	0.02217449	0.04402192
## 7	103	PWA	1	96	0.05580525979	0.8190776	0.08359676	0.16596055
## 8	103	PWA	2	96	-0.01711140688	0.7539370	0.07694838	0.15276184
## 9	103	PWA	3	96	0.00372192646	0.8518556	0.08694214	0.17260198
## 10	104	PWA	1	96	0.04538859312	0.7909854	0.08072961	0.16026854
## 11	104	PWA	2	96	0.01413859312	0.7633677	0.07791089	0.15467267
## 12	104	PWA	3	96	-0.01711140688	0.7947194	0.08111071	0.16102512
## 13	105	PWA	1	96	0.04886081534	0.5566583	0.05681370	0.11278945
## 14	105	PWA	2	96	-0.00322251799	0.4165570	0.04251467	0.08440229
## 15	105	PWA	3	96	-0.00322251799	0.4165570	0.04251467	0.08440229
## 16	106	PWA	1	96	0.01066637090	0.8139410	0.08307251	0.16491978
## 17	106	PWA	2	96	0.00024970423	0.7642291	0.07799880	0.15484720
## 18	106	PWA	3	96	0.03149970423	0.6629281	0.06765982	0.13432172
## 19	107	PWA	1	96	0.02108303757	0.5166631	0.05273171	0.10468568
## 20	107	PWA	2	96	0.00024970423	0.3322075	0.03390579	0.06731150
## 21	107	PWA	3	96	0.02108303757	0.3302212	0.03370306	0.06690904
## 22	108	PWA	1	96	0.02793069533	0.5306401	0.05415823	0.10751768
## 23	108	PWA	2	95	-0.00320965555	0.3787467	0.03885859	0.07715464
## 24	108	PWA	3	96	0.01751402866	0.4149746	0.04235317	0.08408168
## 25	109	PWA	1	93	0.05348885622	0.6372055	0.06607513	0.13123092
## 26	109	PWA	2	96	0.00039745837	0.6402097	0.06534113	0.12971854
## 27	109	PWA	3	93	-0.01102727281	0.7098288	0.07360582	0.14618751
## 28	110	PWA	1	96	0.01761081534	0.6877691	0.07019514	0.13935497
## 29	110	PWA	2	96	0.00719414868	0.3767503	0.03845192	0.07633671
## 30	110	PWA	3	96	0.01761081534	0.3067229	0.03130478	0.06214784
## 31	111	PWA	1	96	0.03844414868	0.6402097	0.06534113	0.12971854
## 32	111	PWA	2	96	0.00719414868	0.5179349	0.05286151	0.10494337
## 33	111	PWA	3	96	-0.00322251799	0.6150524	0.06277352	0.12462120
## 34	112	PWA	1	86	-0.00493452048	0.6072409	0.06548046	0.13019271
## 35	112	PWA	2	96	0.02268175859	0.6604424	0.06740612	0.13381807
## 36	112	PWA	3	96	0.02268175859	0.7500000	0.07654655	0.15196412
## 37	113	PWA	1	96	0.00719414868	0.5619515	0.05735393	0.11386195
## 38	113	PWA	2	96	0.01761081534	0.5756861	0.05875572	0.11664484
## 39	113	PWA	3	96	0.01761081534	0.5179349	0.05286151	0.10494337
## 40	114	PWA	1	96	0.02093683874	0.7943054	0.08106845	0.16094123
## 41	114	PWA	2	96	0.02093683874	0.7535006	0.07690383	0.15267341
## 42	114	PWA	3	93	0.00010350540	0.5417363	0.05617544	0.11156928
## 43	115	PWA	1	96	0.02802748201	0.3965310	0.04047078	0.08034465
## 44	115	PWA	2	96	0.00719414868	0.3973597	0.04055536	0.08051256
## 45	115	PWA	3	96	0.00719414868	0.3077935	0.03141404	0.06236476
## 46	116	PWA	1	96	0.00719414868	0.4528782	0.04622169	0.09176166
## 47	116	PWA	2	96	0.01761081534	0.1777047	0.01813691	0.03600631
## 48	116	PWA	3	96	0.01761081534	0.2513123	0.02564946	0.05092061
## 49	117	PWA	1	96	0.00024970423	0.6402097	0.06534113	0.12971854

```
## 50      117    PWA      2 96  0.03149970423 0.4528782 0.04622169 0.09176166
## 51      117    PWA      3 96  0.01066637090 0.3767503 0.03845192 0.07633671
## 52      118    PWA      1 96  0.03149970423 0.6271017 0.06400330 0.12706262
## 53      118    PWA      2 96 -0.02058362910 0.4345294 0.04434897 0.08804384
## 54      118    PWA      3 96  0.03149970423 0.3750000 0.03827328 0.07598206
## 55      119    PWA      1 94  0.01093966439 0.6951148 0.07169562 0.14237329
## 56      119    PWA      2 96  0.05216306865 0.6107588 0.06233531 0.12375124
## 57      119    PWA      3 96 -0.02075359802 0.5179349 0.05286151 0.10494337
## 58      120    PWA      1 96 -0.01033693135 0.7947194 0.08111071 0.16102512
## 59      120    PWA      2 96  0.00007973531 0.8428297 0.08602094 0.17077316
## 60      120    PWA      3 94  0.05349285588 0.7363491 0.07594861 0.15081889
```

```
df_errors_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "error_class",
    idvar = "subject",
    withinvars = c("session"),
    betweenvars = "group",
    na.rm = T)
```


```
##   group session      N error_class      sd      se      ci
## 1   PWA        1 2386  0.2562733 0.4567964 0.009351633 0.01833817
## 2   PWA        2 2398  0.2101726 0.4065913 0.008302971 0.01628175
## 3   PWA        3 2394  0.1777519 0.3926172 0.008024301 0.01573530
```

## Plotting

```
means_final_errors$session_group <- paste0(means_final_errors$group,
                                             means_final_errors$session)
means_final_errors %>% rename(Session = session, Group = group) %>%
  mutate(Group = factor(Group, levels=c("PWA", "control")))->
  means_final_errors

override.linetype<-c("dotted", "dashed")
(plot_error <- means_final_errors %>%
  mutate(Session=case_when(Session == "1" ~ "day 1",
                           Session == "2" ~ "day 2",
                           Session == "3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr, y=mean_p,
               color = Session)) +
  geom_point(size = 2)+
  stat_summary(aes(x=PosOr, y=mean_p, group=session_group,
                  color = Session, linetype=Group),
              fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dotted", "dashed"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(
    aes(ymin=mean_p-se_p, ymax=mean_p+se_p, group = Session), width =.1) +
  apatheme+
  scale_y_continuous(breaks = seq(0, 40, by = 5), limits=c(0,35))+
  theme(
```

```
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm")+
labs(x="Ordinal Position ",y ="Percentage of errors")
```




Errors by ordinal position and repetition

```
override.linetype<-c("solid", "dashed", "dotted")
(plot_error_PWA <- means_final_errors %>% filter(Group=="PWA") %>%
  mutate(Session=case_when(Session == "1" ~ "day 1",
                           Session == "2" ~ "day 2",
                           Session == "3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr, y=mean_p, group=Session, color = Session)) +
  geom_point( size = 2)+
  stat_summary(aes(linetype=Session),fun=mean, geom="line",
              size = 0.5) +
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=mean_p-se_p, ymax=mean_p+se_p, group = Session),
              width =.1) +
  apatheme+
  scale_y_continuous(breaks = seq(10,30, by = 5), limits=c(10,33))+
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  guides(color=guide_legend(
```

```

override.aes=list(linetype=override.linetype)))+
labs(x="Ordinal Position ",y ="Percentage of errors",
      title="Patients with Aphasia")

```




```

(plot_error_control <- means_final_errors %>% filter(Group=="control") %>%
  mutate(Session=case_when(Session == "1" ~ "day 1",
                           Session == "2" ~ "day 2",
                           Session == "3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr, y=mean_p, group=Session, color = Session)) +
  geom_point( size = 2)+
  stat_summary(aes(linetype=Session),fun=mean, geom="line",
              size = 0.5) +
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=mean_p-se_p, ymax=mean_p+se_p, group = Session), width =.1) +
  apatheme+
  scale_y_continuous(breaks = seq(0, 5, by =1), limits=c(0,5.5))+
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"))+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  labs(x="Ordinal Position ",y ="Percentage of errors",
        title="Control group")

```



## Control group



```
filename <- "CSI_online_spoken_plot_error.pdf"
ggsave(plot_error, filename =
  here::here("results", "figures", filename),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("data", "verbal_CSI", "Plots", filename))


ggsave(plot_error_PWA, filename =
  here::here("results", "figures",
    "CSI_online_spoken_plot_error_PWA.pdf"),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
ggsave(plot_error_control, filename =
  here::here("results", "figures",
    "CSI_online_spoken_plot_error_control.pdf"),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
```

```
(plot_errors_all <- ggplot(data=df_errors,
  aes(x=trial, y=error_class, linetype=session,
    shape=session, color=group)) +
  stat_summary(aes(color=group, shape=session), fun=mean,
    geom="point", size = 2)+
```

```

apatheme+
labs(x="Trial ",y ="Errors")+
scale_color_manual(values=c(control_color, PWA_color))

```



Control: Plot Errors accross the experiment

```

filename <- "CSI_online_aphasia_errors_across_experiment.pdf"
ggsave(plot_errors_all, filename =
  here::here("results", "figures", filename),
  width = 18, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))

```

GLMM with binomial distribution

Contrast coding *Center predictor variable*

```

df_errors_PWA <- df_errors %>% filter(group=="PWA") %>% droplevels()
df_errors_PWA$PosOr.cont <-
  c(scale(as.numeric(as.character(df_errors_PWA$PosOr))),
    center = T, scale = F))

df_errors$PosOr.cont <-
  c(scale(as.numeric(as.character(df_errors$PosOr))),
    center = T, scale = F))

```

### Contrast coding

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors$session)<-my.simple
levels(df_errors$session)
```

```
## [1] "1" "2" "3"
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Define contrast of group
contrasts(df_errors$group) <- MASS::contr.sdif(2)
levels(df_errors$group)
```

```
## [1] "control" "PWA"
```

```
levels(df_errors_PWA$group)
```

```
## [1] "PWA"
```

### Error analyses with factors Ordinal position x Session x Group GLMM

Compute the full model with the maximal random structure. If model fails to converge, increase optimizer iterations, exclude correlation parameters, and step-wise reduce the random structure by excluding variables explaining close to zero variance. If the model converges, test whether it also converges with correlation parameters.

```
# m2_error <- glmer(error_class ~ PosOr.cont*session*group +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session*group/category) ,
#                   data=df_errors, family = "binomial",
#                   control=glmerControl(optimizer = "bobyqa"))

# 2) The model fit is singular -> increase optimizer iterations
# m2_error <- glmer(error_class ~ PosOr.cont*session +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session*group/category) ,
```

```

#           data =df_errors, family = "binomial",
#           control=glmerControl(optimizer = "bobyqa",
#                                optCtrl = list(maxfun = 2e5)))

# 3) Further reduce by excluding correlation parameters
# m2_error <- afex::lmer_alt(error_class ~ PosOr.cont*session*group +
# (PosOr.cont*session||subject) +
# (PosOr.cont*session*group||category) ,
# data =df_errors, family = "binomial",
# control=glmerControl(optimizer = "bobyqa",
#                       optCtrl = list(maxfun = 2e5)))

# 4) Model fit is still singular -> further reduce
# m2_error <- afex::lmer_alt(error_class ~ PosOr.cont*session*group +
# (PosOr.cont+session||subject) +
# (PosOr.cont*session*group-session-PosOr.cont:session-
# PosOr.cont:group-session:group||category) ,
# data =df_errors, family = "binomial",
# control=glmerControl(optimizer = "bobyqa",
#                       optCtrl = list(maxfun = 2e5)))
# m2_error <- afex::lmer_alt(error_class ~ PosOr.cont*session*group +
# (PosOr.cont||subject) +
# (PosOr.cont*session*group-
# session-PosOr.cont:session-
# PosOr.cont:group-
# session:group-PosOr.cont||category) ,
# data =df_errors, family = "binomial",
# control=glmerControl(optimizer = "bobyqa",
#                       optCtrl = list(maxfun = 2e5)))
# m2_error <- afex::lmer_alt(error_class ~ PosOr.cont*session*group +
# (PosOr.cont||subject) +
# (group||category) ,
# data =df_errors, family = "binomial",
# control=glmerControl(optimizer = "bobyqa",
#                       optCtrl = list(maxfun = 2e5)))

# does the model also converge when correlation parameters are included? -> yes!
m2_error <- glmer(error_class ~ PosOr.cont*session*group +
  (PosOr.cont|subject) +
  (group|category) ,
  data =df_errors, family = "binomial",
  control=glmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))

# rePCA(m2_error)
didLmerConverge(m2_error)

```

```

## The relative maximum gradient of 0.0000163 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.

```

```
summary(m2_error)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
```

```

## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: error_class ~ Pos0r.cont * session * group + (Pos0r.cont | subject) +
## (group | category)
## Data: df_errors
## Control: glmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
##      AIC      BIC    logLik deviance df.resid
## 6751.3   6887.5  -3357.6   6715.3    14279
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.6525 -0.2781 -0.1491 -0.0628 19.9112
##
## Random effects:
##  Groups   Name                Variance Std.Dev. Corr
##  subject  (Intercept)  1.35055   1.1621
##           Pos0r.cont    0.01236   0.1112   0.28
##  category (Intercept)  0.86949   0.9325
##           group2-1     0.91566   0.9569  -0.85
## Number of obs: 14297, groups:  subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate Std. Error z value      Pr(>|z|)
## (Intercept)      -3.29230    0.27666 -11.900 < 0.0000000000000002
## Pos0r.cont         0.06105    0.03806   1.604      0.108654
## session2          -0.35994    0.09769  -3.685      0.000229
## session3          -0.80417    0.11210  -7.174    0.0000000000000731
## group2-1          2.88334    0.44599   6.465    0.0000000000101315
## Pos0r.cont:session2 -0.01056    0.06886  -0.153      0.878112
## Pos0r.cont:session3 -0.05147    0.07895  -0.652      0.514418
## Pos0r.cont:group2-1  0.05079    0.07378   0.688      0.491170
## session2:group2-1   -0.05772    0.19539  -0.295      0.767674
## session3:group2-1    0.20457    0.22419   0.912      0.361512
## Pos0r.cont:session2:group2-1 -0.07065    0.13771  -0.513      0.607939
## Pos0r.cont:session3:group2-1  0.02124    0.15787   0.135      0.892979
##
## (Intercept)          ***
## Pos0r.cont
## session2              ***
## session3              ***
## group2-1              ***
## Pos0r.cont:session2
## Pos0r.cont:session3
## Pos0r.cont:group2-1
## session2:group2-1
## session3:group2-1
## Pos0r.cont:session2:group2-1
## Pos0r.cont:session3:group2-1
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Ps0r.c sessn2 sessn3 grp2-1 Ps0.:2 Ps0.:3 P0.:2- s2:2-1

```

```
## Pos0r.cont    0.082
## session2      0.019 -0.011
## session3      0.052  0.012  0.384
## group2-1     -0.345  0.003 -0.017 -0.053
## Ps0r.cnt:s2  -0.002  0.082 -0.071 -0.023  0.004
## Ps0r.cnt:s3   0.003  0.242 -0.023 -0.023 -0.004  0.383
## Ps0r.cn:2-1   0.003 -0.471  0.013 -0.013  0.105 -0.060 -0.207
## sssn2:gr2-1  -0.013  0.013 -0.630 -0.229  0.023  0.060  0.018 -0.012
## sssn3:gr2-1  -0.043 -0.012 -0.230 -0.696  0.063  0.018  0.014  0.012  0.384
## Ps0r.:2:2-1   0.003 -0.054  0.060  0.018 -0.003 -0.627 -0.228  0.080 -0.071
## Ps0r.:3:2-1  -0.003 -0.195  0.018  0.014  0.004 -0.228 -0.694  0.242 -0.023
##              s3:2-1 P0.:2:
## Pos0r.cont
## session2
## session3
## group2-1
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## Ps0r.cn:2-1
## sssn2:gr2-1
## sssn3:gr2-1
## Ps0r.:2:2-1 -0.023
## Ps0r.:3:2-1 -0.023  0.383
```

```
# save model output
saveRDS(m2_error, file = here::here("results", "tables", "CSI_online_aphasia_SessionxGroup_glmml_errors.
tab_model(m2_error, transform = NULL,
          show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
          title = "GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session,
          PWA only",
          dv.labels = "Error Rate",
          #string.pred = "",
          string.stat = "z-Value",
          file =
            here::here(
              "results", "tables",
              "CSI_online_aphasia_SessionxGroup_glmml_errors.html"))
```

GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session, PWA only

Error Rate

Predictors

Log-Odds

CI

z-Value

p

(Intercept)

-3.29

-3.83 - -2.75

-11.90  
 <0.001  
 PosOr cont  
 0.06  
 -0.01 – 0.14  
 1.60  
 0.109  
 session [2]  
 -0.36  
 -0.55 – -0.17  
 -3.68  
 <0.001  
 session [3]  
 -0.80  
 -1.02 – -0.58  
 -7.17  
 <0.001  
 group2-1  
 2.88  
 2.01 – 3.76  
 6.46  
 <0.001  
 PosOr cont  $\times$  session [2]  
 -0.01  
 -0.15 – 0.12  
 -0.15  
 0.878  
 PosOr cont  $\times$  session [3]  
 -0.05  
 -0.21 – 0.10  
 -0.65  
 0.514  
 PosOr.cont:group2-1  
 0.05  
 -0.09 – 0.20  
 0.69

```

0.491
session2:group2-1
-0.06
-0.44 – 0.33
-0.30
0.768
session3:group2-1
0.20
-0.23 – 0.64
0.91
0.362
PosOr.cont:session2:group2-1
-0.07
-0.34 – 0.20
-0.51
0.608
PosOr.cont:session3:group2-1
0.02
-0.29 – 0.33
0.13
0.893
N subject
40
N category
24
Observations
14297

```

```

#performance::check_model(m2_error)
# ggResidpanel::resid_panel(m2_error, smoother = TRUE,
#                             qqbands = TRUE, type = "pearson")
performance::model_performance(m2_error)

```

```

## # Indices of model performance
##
## AIC      |      AICc |      BIC | R2 (cond.) | R2 (marg.) |  ICC |  RMSE | Sigma | Log_loss | Score_
## -----
## 6751.266 | 6751.314 | 6887.487 |      0.587 |      0.277 | 0.429 | 0.257 | 1.000 |      0.224 |      -

```

Make the estimates interpretable



```
# Odds Ratio:
x <- data.frame(summary(m2_error)$coefficients)
x$Odds_Ratio <- plogis(x$Estimate)
x %>% dplyr::select(Estimate, Odds_Ratio) %>%
  mutate(Estimate=round(Estimate,2),
         Odds_Ratio=round(Odds_Ratio,2))
```

##	Estimate	Odds_Ratio
## (Intercept)	-3.29	0.04
## PosOr.cont	0.06	0.52
## session2	-0.36	0.41
## session3	-0.80	0.31
## group2-1	2.88	0.95
## PosOr.cont:session2	-0.01	0.50
## PosOr.cont:session3	-0.05	0.49
## PosOr.cont:group2-1	0.05	0.51
## session2:group2-1	-0.06	0.49
## session3:group2-1	0.20	0.55
## PosOr.cont:session2:group2-1	-0.07	0.48
## PosOr.cont:session3:group2-1	0.02	0.51

#### PWA only GLMM

```
# m1_error <- glmer(error_class ~ PosOr.cont*session +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session/category) ,
#                   data =df_errors_PWA, family = "binomial",
#                   control=glmerControl(optimizer = "bobyqa"))

# 2) The model fit is singular -> reduce optimizer iterations
# m1_error <- glmer(error_class ~ PosOr.cont*session +
#                   (PosOr.cont*session/subject) +
#                   (PosOr.cont*session/category) ,
#                   data =df_errors_PWA, family = "binomial",
#                   control=glmerControl(optimizer = "bobyqa",
#                                         optCtrl = list(maxfun = 2e5)))

# 3) Further reduce by excluding correlation parameters
# m1_error <- afex::lmer_alt(error_class ~ PosOr.cont*session +
#                           (PosOr.cont*session//subject) +
#                           (PosOr.cont*session//category) ,
#                           data =df_errors_PWA, family = "binomial",
#                           control=glmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))

# 4) Model fit is still singular -> further reduce
# m1_error <- afex::lmer_alt(error_class ~ PosOr.cont*session +
#                           (PosOr.cont*session//subject) +
#                           (1/category) ,
#                           data =df_errors_PWA, family = "binomial",
#                           control=glmerControl(optimizer = "bobyqa",
#                                                 optCtrl = list(maxfun = 2e5)))
```

```

# m1_error <- afex::lmer_alt(error_class ~ PosOr.cont*session +
#                           (PosOr.cont+session||subject) +
#                           (1|category) ,
#                           data=df_errors_PWA, family = "binomial",
#                           control=glmerControl(optimizer = "bobyqa",
#                                                  optCtrl = list(maxfun = 2e5)))
m1_error <- glmer(error_class ~ PosOr.cont*session +
                 (PosOr.cont |subject) +
                 (1|category) ,
                 data=df_errors_PWA, family = "binomial",
                 control=glmerControl(optimizer = "bobyqa",
                                       optCtrl = list(maxfun = 2e5)))
rePCA(m1_error)

```

```

## $category
## Standard deviations (1, ..., p=1):
## [1] 0.5889541
##
## Rotation (n x k) = (1 x 1):
##      [,1]
## [1,]    1
##
## $subject
## Standard deviations (1, ..., p=2):
## [1] 1.5014522 0.1293152
##
## Rotation (n x k) = (2 x 2):
##      [,1]      [,2]
## [1,] -0.99950726 -0.03138835
## [2,] -0.03138835  0.99950726
##
## attr("class")
## [1] "prcomplst"

```

```

didLmerConverge(m1_error)

```

```

## The relative maximum gradient of 0.00000289 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.

```

```

summary(m1_error)

```

```

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: error_class ~ PosOr.cont * session + (PosOr.cont | subject) +
##          (1 | category)
## Data: df_errors_PWA
## Control: glmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
##      AIC      BIC    logLik deviance df.resid
##  5336.7   5405.5  -2658.3   5316.7     7168
##

```

```
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.7692 -0.3964 -0.2423 -0.1216 10.6603
##
## Random effects:
##   Groups   Name                Variance Std.Dev. Corr
##   category (Intercept) 0.34687   0.5890
##   subject  (Intercept) 2.25215   1.5007
##           Pos0r.cont  0.01893   0.1376   0.34
## Number of obs: 7178, groups:  category, 24; subject, 20
##
## Fixed effects:
##              Estimate Std. Error z value      Pr(>|z|)
## (Intercept)    -1.86442    0.35937   -5.188 0.000000212474493786 ***
## Pos0r.cont       0.08469    0.04309    1.965    0.0494 *
## session2        -0.39126    0.08430   -4.642 0.000003457979079708 ***
## session3        -0.70618    0.08763   -8.059 0.0000000000000000771 ***
## Pos0r.cont:session2 -0.04642    0.05957   -0.779    0.4358
## Pos0r.cont:session3 -0.04163    0.06188   -0.673    0.5011
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Ps0r.c sessn2 sessn3 Ps0.:2
## Pos0r.cont    0.224
## session2      0.009  0.004
## session3      0.017  0.000  0.460
## Ps0r.cnt:s2   0.001  0.050 -0.028 -0.014
## Ps0r.cnt:s3   0.000  0.094 -0.014 -0.029  0.459
```

```
# save model output
saveRDS(m1_error, file =
  here::here("results", "tables",
    "CSI_online_aphasia_PWA_glmm_errors.RDS"))
tab_model(m1_error, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title = "GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session,
  PWA only",
  dv.labels = "Error Rate",
  string.stat = "z-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_PWA_glmm_errors.html"))
```

GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session, PWA only

Error Rate

Predictors

Log-Odds


CI

z-Value

p  
 (Intercept)  
 -1.86  
 -2.57 – -1.16  
 -5.19  
 <0.001  
 PosOr cont  
 0.08  
 0.00 – 0.17  
 1.97  
 0.049  
 session [2]  
 -0.39  
 -0.56 – -0.23  
 -4.64  
 <0.001  
 session [3]  
 -0.71  
 -0.88 – -0.53  
 -8.06  
 <0.001  
 PosOr cont  $\times$  session [2]  
 -0.05  
 -0.16 – 0.07  
 -0.78  
 0.436  
 PosOr cont  $\times$  session [3]  
 -0.04  
 -0.16 – 0.08  
 -0.67  
 0.501  
 N subject  
 20  
 N category  
 24  
 Observations  
 7178

```
#performance::check_model(m1_error)
ggResidpanel::resid_panel(m1_error, smoother = TRUE,
                          qqbands = TRUE, type = "pearson")
```

```
## 'geom_smooth()' using formula = 'y ~ x'
## 'geom_smooth()' using formula = 'y ~ x'
```



```
performance::model_performance(m1_error)
```

```
## # Indices of model performance
##
## AIC      | AICc | BIC | R2 (cond.) | R2 (marg.) | ICC | RMSE | Sigma | Log_loss | Score_
## -----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----
## 5336.693 | 5336.724 | 5405.481 | 0.454 | 0.016 | 0.445 | 0.332 | 1.000 | 0.356 | -
```

Make the estimates interpretable

```
# Odds Ratio:
x <- data.frame(summary(m1_error)$coefficients)
x$Odds_Ratio <- plogis(x$Estimate)
x %>% dplyr::select(Estimate, Odds_Ratio) %>%
  mutate(Estimate=round(Estimate,2),
         Odds_Ratio=round(Odds_Ratio,2))
```

	Estimate	Odds_Ratio
## (Intercept)	-1.86	0.13
## PosOr.cont	0.08	0.52
## session2	-0.39	0.40
## session3	-0.71	0.33
## PosOr.cont:session2	-0.05	0.49
## PosOr.cont:session3	-0.04	0.49

```
# m2_error_control <- glmer(error_class ~ PosOr.cont*session +
#                               (PosOr.cont*session/subject) +
#                               (PosOr.cont*session/category) ,
#                               data=df_errors[df_errors$group=="control",],
#                               family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa"))
# m2_error_control <- afex::lmer_alt(error_class ~ PosOr.cont*session +
#                               (PosOr.cont*session//subject) +
#                               (PosOr.cont*session//category) ,
#                               data=df_errors[df_errors$group=="control",],
#                               family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa"))
# m2_error_control <- afex::lmer_alt(error_class ~ PosOr.cont*session +
#                               (1/subject) +
#                               (PosOr.cont*session-PosOr.cont-session//category) ,
#                               data=df_errors[df_errors$group=="control",],
#                               family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa"))
m2_error_control <- glmer(error_class ~ PosOr.cont*session +
                          (1|subject) +
                          (1|category) ,
                          data =df_errors[df_errors$group=="control",],
                          family = "binomial",
                          control=glmerControl(optimizer = "bobyqa"))

# rePCA(m2_error_control)
didLmerConverge(m2_error_control)
```

Exploratory follow-up: Make sure there is enough power in the control group

```
## The relative maximum gradient of 0.0000012 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
summary(m2_error_control)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: error_class ~ PosOr.cont * session + (1 | subject) + (1 | category)
## Data: df_errors[df_errors$group == "control", ]
## Control: glmerControl(optimizer = "bobyqa")
##
```

```
##      AIC      BIC   logLik deviance df.resid
##   1414.1   1469.1   -699.1   1398.1     7111
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -0.6002 -0.1607 -0.0987 -0.0622  22.0736
##
## Random effects:
##   Groups   Name      Variance Std.Dev.
##   category (Intercept) 1.7351   1.3172
##   subject  (Intercept) 0.2353   0.4851
## Number of obs: 7119, groups:  category, 24; subject, 20
##
## Fixed effects:
##              Estimate Std. Error z value      Pr(>|z|)
## (Intercept)    -4.61206    0.32706  -14.102 < 0.0000000000000002 ***
## PosOr.cont         0.04362    0.05789    0.753      0.4512
## session2        -0.33004    0.17645   -1.870      0.0614 .
## session3        -0.89977    0.20691   -4.349    0.0000137 ***
## PosOr.cont:session2  0.02371    0.12453    0.190      0.8490
## PosOr.cont:session3 -0.06058    0.14603   -0.415      0.6783
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) PsOr.c sessn2 sessn3 Ps0.:2
## PosOr.cont   -0.012
## session2      0.029 -0.017
## session3      0.086  0.017  0.367
## PsOr.cnt:s2  -0.005  0.101 -0.082 -0.025
## PsOr.cnt:s3   0.006  0.315 -0.025 -0.021  0.367
```

```
# save model output
saveRDS(m2_error_control, file = here::here("results", "tables", "CSI_online_aphasia_Session_control_gr
tab_model(m2_error_control, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title = "GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session,
Control group only",
  dv.labels = "Error Rate",
  #string.pred = "",
  string.stat = "z-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_Session_control_group_errors.html"))
```

GLMM (Binomial distribution) of Errors Predicted by Ordinal Position and Session, Control group only

Error Rate

Predictors

Log-Odds

CI

z-Value	
p	
(Intercept)	
	-4.61
	-5.25 – -3.97
	-14.10
	<0.001
PosOr cont	
	0.04
	-0.07 – 0.16
	0.75
	0.451
session [2]	
	-0.33
	-0.68 – 0.02
	-1.87
	0.061
session [3]	
	-0.90
	-1.31 – -0.49
	-4.35
	<0.001
PosOr cont × session [2]	
	0.02
	-0.22 – 0.27
	0.19
	0.849
PosOr cont × session [3]	
	-0.06
	-0.35 – 0.23
	-0.41
	0.678
N subject	
	20
N category	
	24
Observations	
	7119



---

## Control analyses: Covariate tests (AAT, LEMO test, MPO, lesion size)

Add covariates individually into the converging models, and use LRT to assess which covariates explain additional variance when added to the main model. Then conduct one model with all covariates that explain additional variance.

### Add covariates

```
read.csv2(here::here("data", "additional_data",
                    "questionnaire-test_data.csv")) -> tests
```

```
read.csv2(here::here("data", "additional_data",
                    "MRT_ROIs.csv")) -> mrt
mrt$Proband_in <- mrt$Proband_in+100
mrt$SoSci_ID <- toupper(mrt$SoSci_ID)
all(mrt$SoSci_ID %in% df_RTs_PWA$OR02_01) &
  all(df_RTs_PWA$OR02_01 %in% mrt$SoSci_ID)
```

```
## [1] TRUE
```

```
# table(df_RTs_PWA$subject)
```

Combine with PWA data

```
df_RTs_PWA$TokenTest <- NA
df_RTs_PWA$AAT <- NA
df_RTs_PWA$AAT_spontansprache <- NA
df_RTs_PWA$LEMO <- NA
df_RTs_PWA$mont_post_onset <- NA
df_RTs_PWA$LHoverall <- NA
df_RTs_PWA$ATL <- NA
df_RTs_PWA$IFG <- NA
df_RTs_PWA$MTG_ITG <- NA
df_RTs_PWA$SMG_AG <- NA
df_RTs_PWA$Precentral <- NA
df_RTs_PWA$ID <- NA
df_RTs_PWA$SoSci_ID <- NA
df_RTs_PWA$Proband_in <- NA
for(i in 1:nrow(mrt)){
  df_RTs_PWA$TokenTest[
    toupper(df_RTs_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(tests$Token.Test..Prozentrang.[i]))
  df_RTs_PWA$AAT[
    toupper(df_RTs_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(tests$AAT.Ben.gesamt..Prozentrang.[i]))
}
```

```

df_RTs_PWA$AAT_spontansprache[
  toupper(df_RTs_PWA$OR02_01) == toupper(tests$Code[i])] <-
  as.numeric(as.character(tests$AAT.Untertest.Spontansprache.Semantik..Punktwert.Anzahl.korrekt.[i]))
df_RTs_PWA$LEMO[
  toupper(df_RTs_PWA$OR02_01) == toupper(tests$Code[i])] <-
  as.numeric(as.character(tests$LEMO.V15.Syn.aud..Mit.Abl..n.40...Anz.korr[i]))
df_RTs_PWA$months_post_onset[
  toupper(df_RTs_PWA$OR02_01) == toupper(tests$Code[i])] <-
  as.numeric(as.character(tests$MPO..months.post.onset.[i]))
df_RTs_PWA$LHoverall[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$LH.Gesamt[i]))
df_RTs_PWA$ATL[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$ATL[i]))
df_RTs_PWA$IFG[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$IFGorb.op.tri[i]))
df_RTs_PWA$MTG_ITG[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$MTG...ITG[i]))
df_RTs_PWA$SMG_AG[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$SMG...AG[i]))
df_RTs_PWA$Precentral[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$Precentral[i]))
df_RTs_PWA$ID[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  mrt$ID[i]
df_RTs_PWA$SoSci_ID[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  mrt$SoSci_ID[i]
df_RTs_PWA$Proband_in[
  df_RTs_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$Proband_in[i]))
}

```

## Warning: Unknown or uninitialised column: 'months\_post\_onset'.

```
sum(!(df_RTs_PWA$OR02_01==df_RTs_PWA$SoSci_ID), na.rm=T)
```

```
## [1] 0
```

```

write.csv(df_RTs_PWA, here::here(
  "data", "additional_data",
  "CSI_online_aphasia_raw_data_for_RT_analyses_incl_MRT.csv"))

```

```

df_errors_PWA$TokenTest <- NA
df_errors_PWA$AAT <- NA
df_errors_PWA$AAT_spontansprache <- NA

```

```

df_errors_PWA$LEMO <- NA
df_errors_PWA$mont_post_onset <- NA
df_errors_PWA$LHoverall <- NA
df_errors_PWA$ATL <- NA
df_errors_PWA$IFG <- NA
df_errors_PWA$MTG_ITG <- NA
df_errors_PWA$SMG_AG <- NA
df_errors_PWA$Precentral <- NA
df_errors_PWA$ID <- NA
df_errors_PWA$SoSci_ID <- NA
df_errors_PWA$Proband_in <- NA
for(i in 1:nrow(mrt)){
  df_errors_PWA$TokenTest[
    toupper(df_errors_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(tests$Token.Test..Prozentrang.[i]))
  df_errors_PWA$AAT[
    toupper(df_errors_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(tests$AAT.Ben.gesamt..Prozentrang.[i]))
  df_errors_PWA$AAT_spontansprache[
    toupper(df_errors_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(
      tests$AAT.Untertest.Spontansprache.Semantik..Punktwert.Anzahl.korrekt.[i]))
  df_errors_PWA$LEMO[
    toupper(df_errors_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(
      tests$LEMO.V15.Syn.aud..Mit.Abl..n.40...Anz.korr[i]))
  df_errors_PWA$months_post_onset[
    toupper(df_errors_PWA$OR02_01) == toupper(tests$Code[i])] <-
    as.numeric(as.character(tests$MPO..months.post.onset.[i]))
  df_errors_PWA$LHoverall[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$LH.Gesamt[i]))
  df_errors_PWA$ATL[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$ATL[i]))
  df_errors_PWA$IFG[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$IFGorb.op.tri[i]))
  df_errors_PWA$MTG_ITG[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$MTG...ITG[i]))
  df_errors_PWA$SMG_AG[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$SMG...AG[i]))
  df_errors_PWA$Precentral[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    as.numeric(as.character(mrt$Precentral[i]))
  df_errors_PWA$ID[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    mrt$ID[i]
  df_errors_PWA$SoSci_ID[
    df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
    mrt$SoSci_ID[i]
}

```

```
df_errors_PWA$Proband_in[
  df_errors_PWA$OR02_01 == mrt$SoSci_ID[i]] <-
  as.numeric(as.character(mrt$Proband_in[i]))
}
```

```
## Warning: Unknown or uninitialised column: 'months_post_onset'.
```

```
sum(!(df_errors_PWA$OR02_01==df_errors_PWA$SoSci_ID), na.rm=T)
```

```
## [1] 0
```

```
write.csv(df_errors_PWA, here::here(
  "data", "additional_data",
  "CSI_online_aphasia_raw_data_for_error_analyses_incl_MRT.csv"))
```

Add tests individually and assess whether they explain additional variance

AAT: Token test

RTs Add into converging model

```
df_RT_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RT_PWA$PosOr)),
                              center = T, scale = F)
table(df_RT_PWA$PosOr.cont)
```

```
##
## -1.96955418629938 -0.969554186299384 0.0304458137006161 1.03044581370062
##          1132          1117          1103          1119
##  2.03044581370062
##          1047
```

```
mean(df_RT_PWA$PosOr.cont); sd(df_RT_PWA$PosOr.cont)
```

```
## [1] -0.0000000000000001123241
```

```
## [1] 1.40862
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##          2          3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTs_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center token test
```

```
df_RTs_PWA$TokenTest_c <- scale(df_RTs_PWA$TokenTest, center=T, scale=T)
```

```
m1_lmm_PWA_tt <- lmer(VOTlog ~ PosOr.cont*session*TokenTest_c +
  (PosOr.cont+session|subject) +
  (1|category),
  data = df_RTs_PWA,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_tt)
```

```
## The relative maximum gradient of 0.000000998 is less than our 0.001 criterion.
```

```
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_lmm_PWA_tt)
```

```
# anova(m1_lmm_PWA_tt)
```

```
#
```

```
# saveRDS(m1_lmm_PWA_tt, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_VOT_plus-T"))
```

```
# tab_model(m1_lmm_PWA_tt, transform = NULL,
```

```
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
```

```
#   title = "LMM of VOTs Predicted by Ordinal Position and Session",
```

```
#   df.method = "satterthwaite",
```

```
#   dv.labels = "Vocal Onset Time (log-transformed)",
```

```
#   #string.pred = "",
```

```
#   string.stat = "t-Value",
```

```
#   file = here::here(
```

```
#     "results", "tables",
```

```
#     "CSI_online_aphasia_PWA_control_lmm_VOT_TokenTest.html"))
```

Does the model with Token test fit the data better? -> yes!

```
# summary(m1_lmm_PWA)
```

```
# performance::model_performance(m1_lmm_PWA)
```

```
anova(m1_lmm_PWA, m1_lmm_PWA_tt)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_tt: VOTlog ~ PosOr.cont * session * TokenTest_c + (PosOr.cont + session | subject) + (1 |
```

```
##      npar    AIC    BIC logLik deviance Chisq Df Pr(>Chisq)
```

```
## m1_lmm_PWA      18 1697.5 1816.5 -830.73   1661.5
```

```
## m1_lmm_PWA_tt   24 1696.5 1855.2 -824.23   1648.5 13.004  6    0.04297 *
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Errors Add into converging model

```
df_errors_PWA$PosOr.cont <- scale(as.numeric(as.character(df_errors_PWA$PosOr)),
                                center = T, scale = F)
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center token test
df_errors_PWA$TokenTest_c <-
  scale(df_errors_PWA$TokenTest, center=T, scale=T)
```

```
m1_glmm_PWA_tt <- glmer(error_class ~ PosOr.cont*session*TokenTest_c +
                        (PosOr.cont |subject) +
                        (1|category) ,
                        data =df_errors_PWA, family = "binomial",
                        control=glmerControl(optimizer = "bobyqa",
                                              optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_glmm_PWA_tt)
```

```
## The relative maximum gradient of 0.00000284 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_glmm_PWA_tt)
# anova(m1_glmm_PWA_tt)
#
# saveRDS(m1_glmm_PWA_tt, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_error_plu
# tab_model(m1_glmm_PWA_tt,transform = NULL,
#           show.re.var = F, show.stat = T,show.r2 = F,show.icc = F,
#           title = "GLMM of errors Predicted by Ordinal Position and Session",
#           dv.labels = "Errors",
#           #string.pred = "",
#           string.stat = "z-Value",
#           file = here::here(
#             "results", "tables",
#             "CSI_online_aphasia_PWA_control_glmm_error_TokenTest.html"))
```

Does the model with Token test fit the data better? -> yes!

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_tt)
```

```
## Data: df_errors_PWA
## Models:
## m1_error: error_class ~ PosOr.cont * session + (PosOr.cont | subject) + (1 | category)
## m1_glmm_PWA_tt: error_class ~ PosOr.cont * session * TokenTest_c + (PosOr.cont | subject) + (1 | category)
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_error      10 5336.7 5405.5 -2658.3   5316.7
## m1_glmm_PWA_tt 16 5326.5 5436.5 -2647.2   5294.5 22.208  6   0.00111 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

## AAT: Naming test

RTs Add into converging model

```
df_RTs_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RTs_PWA$PosOr))),
                             center = T, scale = F)
table(df_RTs_PWA$PosOr.cont)
```

```
##
## -1.96955418629938 -0.969554186299384 0.0304458137006161 1.03044581370062
##          1132          1117          1103          1119
## 2.03044581370062
##          1047
```

```
mean(df_RTs_PWA$PosOr.cont); sd(df_RTs_PWA$PosOr.cont)
```

```
## [1] -0.0000000000000001123241
```

```
## [1] 1.40862
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##          2          3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTs_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center naming test
df_RTs_PWA$AAT_c <- scale(df_RTs_PWA$AAT, center=T, scale=T)

m1_lmm_PWA_aat <- lmer(VOTlog ~ PosOr.cont*session*AAT_c +
  (PosOr.cont+session|subject) +
  (1|category),
  data = df_RTs_PWA,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_aat)
```

```
## The relative maximum gradient of 0.0000013 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_lmm_PWA_aat)
# anova(m1_lmm_PWA_aat)
#
# saveRDS(m1_lmm_PWA_aat, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_VOT_plus-
# tab_model(m1_lmm_PWA_aat, transform = NULL,
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#   title = "LMM of VOTs Predicted by Ordinal Position and Session",
#   df.method = "satterthwaite",
#   dv.labels = "Vocal Onset Time (log-transformed)",
#   #string.pred = "",
#   string.stat = "t-Value",
#   file = here::here(
#     "results", "tables",
#     "CSI_online_aphasia_PWA_control_lmm_VOT_AachenAphase.html"))
```

Does the model with Naming test fit the data better? -> yes!

```
#summary(m1_lmm_PWA)
anova(m1_lmm_PWA, m1_lmm_PWA_aat)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
## Models:
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
## m1_lmm_PWA_aat: VOTlog ~ PosOr.cont * session * AAT_c + (PosOr.cont + session | subject) + (1 | cate
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_lmm_PWA      18 1697.5 1816.5 -830.73  1661.5
## m1_lmm_PWA_aat   24 1695.9 1854.6 -823.93  1647.9 13.609  6    0.03432 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Errors Add into converging model



```
df_errors_PWA$PosOr.cont <- scale(as.numeric(as.character(df_errors_PWA$PosOr)),
                                center = T, scale = F)

# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center naming test
df_errors_PWA$AAT_c <- scale(df_errors_PWA$AAT, center=T, scale=T)
```

```
m1_glmm_PWA_aat <- glmer(error_class ~ PosOr.cont*session*AAT_c +
                        (PosOr.cont |subject) +
                        (1|category) ,
                        data =df_errors_PWA, family = "binomial",
                        control=glmerControl(optimizer = "bobyqa",
                                              optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_glmm_PWA_aat)
```

```
## The relative maximum gradient of 0.00000131 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_glmm_PWA_aat)
# anova(m1_glmm_PWA_aat)
#
# saveRDS(m1_glmm_PWA_aat, file = here::here(
#   "results", "tables", "CSI_online_aphasia_PWA_lmm_error_plus-AAT.RDS"))
# tab_model(m1_glmm_PWA_aat, transform = NULL,
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#   title = "GLMM of errors Predicted by Ordinal Position and Session",
#   dv.labels = "Errors",
#   #string.pred = "",
#   string.stat = "z-Value",
#   file = here::here(
#     "results", "tables",
#     "CSI_online_aphasia_PWA_control_glmm_error_AAT.html"))
```

Does the model with Naming subtest fit the data better? -> yes!

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_aat)
```

```
## Data: df_errors_PWA
## Models:
## m1_error: error_class ~ PosOr.cont * session + (PosOr.cont | subject) + (1 | category)
## m1_glmm_PWA_aat: error_class ~ PosOr.cont * session * AAT_c + (PosOr.cont | subject) + (1 | category)
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_error      10 5336.7 5405.5 -2658.3   5316.7
## m1_glmm_PWA_aat 16 5318.5 5428.6 -2643.3   5286.5 30.169  6 0.0000365 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

### AAT: Spontaneous speech test

RTs Add into converging model

```
df_RTs_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RTs_PWA$PosOr))),
                             center = T, scale = F)
table(df_RTs_PWA$PosOr.cont)
```

```
##
## -1.96955418629938 -0.969554186299384 0.0304458137006161 1.03044581370062
##          1132          1117          1103          1119
## 2.03044581370062
##          1047
```

```
mean(df_RTs_PWA$PosOr.cont); sd(df_RTs_PWA$PosOr.cont)
```

```
## [1] -0.0000000000000001123241
```

```
## [1] 1.40862
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##          2          3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTs_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center spontaneous speech test
df_RTSPWA$AAT_spontansprache_c <-
  scale(df_RTSPWA$AAT_spontansprache, center=T, scale=T)
```

```
m1_lmm_PWA_aat_spontansprache <- lmer(
  VOTlog ~ PosOr.cont*session*AAT_spontansprache_c +
    (PosOr.cont+session|subject) +
    (1|category),
  data = df_RTSPWA,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_aat_spontansprache)
```

```
## The relative maximum gradient of 0.0000112 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Model converges
```

```
# summary(m1_lmm_PWA_aat_spontansprache)
# anova(m1_lmm_PWA_aat_spontansprache)
#
# saveRDS(m1_lmm_PWA_spontansprache, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lm
# tab_model(m1_lmm_aat_spontansprache, transform = NULL,
#           show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#           title = "LMM of VOTs Predicted by Ordinal Position and Session",
#           df.method = "satterthwaite",
#           dv.labels = "Vocal Onset Time (log-transformed)",
#           #string.pred = "",
#           string.stat = "t-Value",
#           file = here::here(
#             "results", "tables", "CSI_online_aphasia_PWA_control_lmm_VOT_AachenAphase_Spontansprache.
```

Does the model with Token test fit the data better? -> no, only a trend.

```
#summary(m1_lmm_PWA)
anova(m1_lmm_PWA, m1_lmm_PWA_aat_spontansprache)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTSPWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_aat_spontansprache: VOTlog ~ PosOr.cont * session * AAT_spontansprache_c + (PosOr.cont +
```

```
##           npar    AIC    BIC logLik deviance Chisq Df
## m1_lmm_PWA           18 1697.5 1816.5 -830.73   1661.5
## m1_lmm_PWA_aat_spontansprache 24 1697.7 1856.5 -824.87   1649.7 11.732  6
##           Pr(>Chisq)
```

```
## m1_lmm_PWA
```

```
## m1_lmm_PWA_aat_spontansprache    0.06822 .
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Errors Add into converging model

```
df_errors_PWA$PosOr.cont <-  
  scale(as.numeric(as.character(df_errors_PWA$PosOr)),  
        center = T, scale = F)  
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding  
c<-contr.treatment(3)  
my.coding<-matrix(rep(1/3, 6), ncol=2)  
my.simple<-c-my.coding  
my.simple
```

```
##           2           3  
## 1 -0.3333333 -0.3333333  
## 2  0.6666667 -0.3333333  
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple  
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center spontanous speech test
```

```
df_errors_PWA$AAT_spontansprache_c <-  
  scale(df_errors_PWA$AAT_spontansprache, center=T, scale=T)
```

```
m1_glmm_PWA_aat_spontan <- glmer(error_class ~ PosOr.cont*session*  
                                AAT_spontansprache_c +  
                                (PosOr.cont |subject) +  
                                (1|category) ,  
                                data =df_errors_PWA, family = "binomial",  
                                control=glmerControl(optimizer = "bobyqa",  
                                                       optCtrl = list(maxfun = 2e5)))  
didLmerConverge(m1_glmm_PWA_aat_spontan)
```

```
## The relative maximum gradient of 0.0000073 is less than our 0.001 criterion.  
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_glmm_PWA_aat_spontan)  
# anova(m1_glmm_PWA_aat_spontan)  
#  
# saveRDS(m1_glmm_PWA_aat_spontan, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_1_10_2019.RDS"))  
# tab_model(m1_glmm_PWA_aat_spontan,transform = NULL,  
#           show.re.var = F, show.stat = T,show.r2 = F,show.icc = F,  
#           title = "GLMM of errors Predicted by Ordinal Position and Session",  
#           dv.labels = "Errors",  
#           #string.pred = "",  
#           string.stat = "z-Value",  
#           file = here::here("results", "tables", "CSI_online_aphasia_PWA_control_glmm_error_AAT_spontansprache.RDS"))
```

Does the model with spontanous speech test fit the data better? -> yes!

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_aat_spontan)
```

```
## Data: df_errors_PWA
## Models:
## m1_error: error_class ~ PosOr.cont * session + (PosOr.cont | subject) + (1 | category)
## m1_glmm_PWA_aat_spontan: error_class ~ PosOr.cont * session * AAT_spontansprache_c + (PosOr.cont | subject) + (1 | category)
##               npar      AIC      BIC  logLik deviance  Chisq Df
## m1_error           10 5336.7 5405.5 -2658.3   5316.7
## m1_glmm_PWA_aat_spontan 16 5335.9 5446.0 -2652.0   5303.9 12.753 6
##               Pr(>Chisq)
## m1_error
## m1_glmm_PWA_aat_spontan 0.04713 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

## LEMO

**RTs** Add into converging model

```
df_RTs_PWA$PosOr.cont <-  
  scale(as.numeric(as.character(df_RTs_PWA$PosOr))),  
        center = T, scale = F)  
table(df_RTs_PWA$PosOr.cont)
```

```
##
## -1.96955418629938 -0.969554186299384 0.0304458137006161 1.03044581370062
##          1132          1117          1103          1119
## 2.03044581370062
##          1047
```

```
mean(df_RT$PWA$PosOr.cont); sd(df_RT$PWA$PosOr.cont)
```

```
## [1] -0.000000000000000001123241
```

```
## [1] 1.40862
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##          2          3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTSPWA$session)<-my.simple
levels(df_RTSPWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center LEMO test
```

```
df_RTSPWA$LEMO_c <- scale(df_RTSPWA$LEMO, center=T, scale=T)
```

```
m1_lmm_PWA_lemo <- lmer(VOTlog ~ PosOr.cont*session*LEMO_c +
  (PosOr.cont+session|subject) +
  (1|category),
  data = df_RTSPWA,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_lemo)
```

```
## The relative maximum gradient of 0.00000141 is less than our 0.001 criterion.
```

```
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_lmm_PWA_lemo)
```

```
# anova(m1_lmm_PWA_lemo)
```

```
#
```

```
# saveRDS(m1_lmm_PWA_lemo, file = here::here(
```

```
# "results", "tables", "CSI_online_aphasia_PWA_lmm_VOT_plus-LEMO.RDS"))
```

```
# tab_model(m1_lmm_PWA_lemo, transform = NULL,
```

```
# show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
```

```
# title = "LMM of VOTs Predicted by Ordinal Position and Session",
```

```
# df.method = "satterthwaite",
```

```
# dv.labels = "Vocal Onset Time (log-transformed)",
```

```
# #string.pred = "",
```

```
# string.stat = "t-Value",
```

```
# file = here::here(
```

```
# "results", "tables",
```

```
# "CSI_online_aphasia_PWA_control_lmm_VOT_LEMO.html"))
```

Does the model with LEMO fit the data better? -> no! (but a trend)

```
#summary(m1_lmm_PWA)
```

```
anova(m1_lmm_PWA, m1_lmm_PWA_lemo)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTSPWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_lemo: VOTlog ~ PosOr.cont * session * LEMO_c + (PosOr.cont + session | subject) + (1 | category)
```

```
## npar AIC BIC logLik deviance Chisq Df Pr(>Chisq)
```

```
## m1_lmm_PWA 18 1697.5 1816.5 -830.73 1661.5
```

```
## m1_lmm_PWA_lemo 24 1698.7 1857.5 -825.34 1650.7 10.776 6 0.09554 .
```

```
## ---
```

```
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

**Errors** Add into converging model

```
df_errors_PWA$PosOr.cont <- scale(as.numeric(as.character(df_errors_PWA$PosOr)),
                                   center = T, scale = F)

# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center LEMO test
df_errors_PWA$LEMO_c <- scale(df_errors_PWA$LEMO, center=T, scale=T)
```

*Compute further contrasts*

```
m1_glmm_PWA_lemo <- glmer(error_class ~ PosOr.cont*session*LEMO_c +
                          (PosOr.cont |subject) +
                          (1|category) ,
                          data=df_errors_PWA, family = "binomial",
                          control=glmerControl(optimizer = "bobyqa",
                                                  optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_glmm_PWA_lemo)
```

```
## The relative maximum gradient of 0.00000715 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

**## Warnings can be ignored**

```
# summary(m1_glmm_PWA_lemo)
# anova(m1_glmm_PWA_lemo)
#
# saveRDS(m1_glmm_PWA_lemo, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_error_p
# tab_model(m1_glmm_PWA_lemo,transform = NULL,
#           show.re.var = F, show.stat = T,show.r2 = F,show.icc = F,
#           title = "GLMM of errors Predicted by Ordinal Position and Session",
#           dv.labels = "Errors",
#           #string.pred = "",
#           string.stat = "z-Value",
#           file = here::here(
#             "results", "tables",
#             "CSI_online_aphasia_PWA_control_glmm_error_Lemo.html"))
```

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_lemo)
```

Time since stroke

```
df_RTs_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RTs_PWA$PosOr)),
                                center = T, scale = F)
table(df_RTs_PWA$PosOr.cont)
```

```
mean(df_RTs_PWA$PosOr.cont)
```

```
sd(df_RTs_PWA$PosOr.cont)
```

```
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
contrasts(df_RT_S_PWA$session)<-my.simple
levels(df_RT_S_PWA$session)
```

88



```
## Center months post onset
df_RTs_PWA$months_post_onset_c <- scale(df_RTs_PWA$months_post_onset,
                                         center=T, scale=T)
```

```
m1_lmm_PWA_MPO <- lmer(VOTlog ~ PosOr.cont*session*months_post_onset_c +
                      (PosOr.cont+session|subject) +
                      (1|category),
                      data = df_RTs_PWA,
                      control=lmerControl(optimizer = "bobyqa",
                                           optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_MPO)
```

```
## The relative maximum gradient of 0.00000365 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored

# summary(m1_lmm_PWA_MPO)
# anova(m1_lmm_PWA_MPO)
#
# saveRDS(m1_lmm_PWA_MPO, file = here::here(
#   "results", "tables", "CSI_online_aphasia_PWA_lmm_VOT_plus-MPO.RDS"))
# tab_model(m1_lmm_PWA_MPO, transform = NULL,
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#   title = "LMM of VOTs Predicted by Ordinal Position and Session",
#   df.method = "satterthwaite",
#   dv.labels = "Vocal Onset Time (log-transformed)",
#   #string.pred = "",
#   string.stat = "t-Value",
#   file = here::here(
#     "results", "tables",
#     "CSI_online_aphasia_PWA_control_lmm_VOT_MPO.html"))
```

Does the model with MPO fit the data better? -> no!

```
#summary(m1_lmm_PWA)
anova(m1_lmm_PWA, m1_lmm_PWA_MPO)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
## m1_lmm_PWA_MPO: VOTlog ~ PosOr.cont * session * months_post_onset_c + (PosOr.cont + session | subject)
##      npar    AIC    BIC logLik deviance  Chisq Df Pr(>Chisq)
## m1_lmm_PWA      18 1697.5 1816.5 -830.73   1661.5
## m1_lmm_PWA_MPO   24 1703.4 1862.2 -827.69   1655.4 6.0782  6    0.4145
```

**Errors** Add into converging model

```
df_errors_PWA$PosOr.cont <-
  scale(as.numeric(as.character(df_errors_PWA$PosOr)),
        center = T, scale = F)

# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center months post onset
df_errors_PWA$MPO_c <-
  scale(df_errors_PWA$months_post_onset, center=T, scale=T)
```

```
m1_glmm_PWA_MPO <- glmer(error_class ~ PosOr.cont*session*MPO_c +
  (PosOr.cont |subject) +
  (1|category) ,
  data =df_errors_PWA, family = "binomial",
  control=glmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_glmm_PWA_MPO)
```

```
## The relative maximum gradient of 0.000006 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_glmm_PWA_MPO)
# anova(m1_glmm_PWA_MPO)
#
# saveRDS(m1_glmm_PWA_MPO, file = here::here(
#   "results", "tables", "CSI_online_aphasia_PWA_lmm_error_plus-MPO.RDS"))
# tab_model(m1_glmm_PWA_MPO, transform = NULL,
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#   title =
#     "GLMM of errors Predicted by Ordinal Position and Session",
#   #df.method = "satterthwaite",
#   dv.labels = "Errors",
#   #string.pred = "",
#   string.stat = "z-Value",
#   file = here::here(
#     "results", "tables",
#     "CSI_online_aphasia_PWA_control_glmm_error_MPO.html"))
```

Does the model with MPO fit the data better? -> no!

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_MPO)
```

```
## Data: df_errors_PWA
## Models:
## m1_error: error_class ~ PosOr.cont * session + (PosOr.cont | subject) + (1 | category)
## m1_glmm_PWA_MPO: error_class ~ PosOr.cont * session * MPO_c + (PosOr.cont | subject) + (1 | category)
##               npar      AIC      BIC  logLik deviance  Chisq Df Pr(>Chisq)
## m1_error              10 5336.7 5405.5 -2658.3   5316.7
## m1_glmm_PWA_MPO      16 5341.8 5451.9 -2654.9   5309.8 6.8914 6      0.331
```

Lesion size

```
df_RTs_PWA$LHoverall_c <- scale(df_RTs_PWA$LHoverall, center=T, scale=F)

m1_lmm_PWA_LH <- lmer(VOTlog ~ PosOr.cont*session*LHoverall_c +
  (PosOr.cont+session|subject) +
  (1|category),
  data = df_RTs_PWA,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))

didLmerConverge(m1_lmm_PWA_LH)
```

RTs

```
## The relative maximum gradient of 0.00000407 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
# summary(m1_lmm_PWA_LH)
# anova(m1_lmm_PWA_LH)
#
# saveRDS(m1_lmm_PWA_LH, file = here::here("results", "tables",
#   "CSI_online_aphasia_PWA_lmm_VOT_plus-Lesion-size.RDS"))
# tab_model(m1_lmm_PWA_LH, transform = NULL,
#   show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#   title = "LMM of VOTs Predicted by Ordinal Position and Session",
#   df.method = "satterthwaite",
#   dv.labels = "Vocal Onset Time (log-transformed)",
#   #string.pred = "",
#   string.stat = "t-Value",
#   file = here::here(
#     "results", "tables",
#     "CSI_online_aphasia_PWA_control_lmm_VOT_Lesion-size.html"))
```

Does the model with lesion size fit the data better? -> no!

```
#summary(m1_lmm_PWA)
anova(m1_lmm_PWA, m1_lmm_PWA_LH)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
## Models:
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
## m1_lmm_PWA_LH: VOTlog ~ PosOr.cont * session * LHoverall_c + (PosOr.cont + session | subject) + (1 |
##               npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_lmm_PWA      18 1697.5 1816.5 -830.73 1661.5
## m1_lmm_PWA_LH   24 1704.3 1863.1 -828.15 1656.3 5.1739 6 0.5217
```

Errors Add into converging model

```
df_errors_PWA$PosOr.cont <- scale(as.numeric(as.character(df_errors_PWA$PosOr))),
                                center = T, scale = F)
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session)<-my.simple
levels(df_errors_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center lesion size
df_errors_PWA$LHoverall_c <- scale(df_errors_PWA$LHoverall, center=T, scale=T)
```

```
m1_glmm_PWA_LH <- glmer(error_class ~ PosOr.cont*session*LHoverall_c +
                        (PosOr.cont |subject) +
                        (1|category) ,
                        data =df_errors_PWA, family = "binomial",
                        control=glmerControl(optimizer = "bobyqa",
                                              optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_glmm_PWA_LH)
```

```
## The relative maximum gradient of 0.00000659 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored

# summary(m1_glmm_PWA_LH)
# anova(m1_glmm_PWA_LH)
#
# saveRDS(m1_glmm_PWA_LH, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_error_plu
# tab_model(m1_glmm_PWA_LH, transform = NULL,
#           show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
#           title = "GLMM of errors Predicted by Ordinal Position and Session",
#           dv.labels = "Errors",
#           #string.pred = "",
#           string.stat = "z-Value",
#           file = here::here(
#             "results", "tables",
#             "CSI_online_aphasia_PWA_control_glmm_error_LH.html"))
```

Does the model with Token test fit the data better? -> yes!

```
#summary(m1_lmm_PWA)
anova(m1_error, m1_glmm_PWA_LH)
```

```
## Data: df_errors_PWA
## Models:
## m1_error: error_class ~ PosOr.cont * session + (PosOr.cont | subject) + (1 | category)
## m1_glmm_PWA_LH: error_class ~ PosOr.cont * session * LHoverall_c + (PosOr.cont | subject) + (1 | cat
##           npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_error           10 5336.7 5405.5 -2658.3   5316.7
## m1_glmm_PWA_LH     16 5333.9 5444.0 -2651.0   5301.9 14.746  6    0.02232 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Add covariates explaining significant variance in a single model

RTs Add Token Test and Naming Test into converging model.

```
cor.test(df_RTs_PWA$AAT_c, df_RTs_PWA$TokenTest_c)
```

```
##
## Pearson's product-moment correlation
##
## data: df_RTs_PWA$AAT_c and df_RTs_PWA$TokenTest_c
## t = 110.24, df = 5516, p-value < 0.00000000000000022
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
##  0.8209312 0.8374132
## sample estimates:
##      cor
## 0.8293525
```

```
df_RTs_PWA$PosOr.cont <- scale(as.numeric(as.character(df_RTs_PWA$PosOr)),
                               center = T, scale = F)
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_RTs_PWA$session)<-my.simple
levels(df_RTs_PWA$session)
```

```
## [1] "1" "2" "3"
```

```
## Center token test and Naming test
df_RTs_PWA$TokenTest_c <- scale(df_RTs_PWA$TokenTest, center=T, scale=T)
df_RTs_PWA$AAT_c <- scale(df_RTs_PWA$AAT, center=T, scale=T)

m1_lmm_PWA_tt_aat <- lmer(VOTlog ~ PosOr.cont*session*(TokenTest_c*AAT_c)+
                          (PosOr.cont+session|subject) +
                          (1|category),
                          data = df_RTs_PWA,
                          control=lmerControl(optimizer = "bobyqa",
                                                optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1_lmm_PWA_tt_aat)
```

```
## The relative maximum gradient of 0.000124 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
summary(m1_lmm_PWA_tt_aat)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: VOTlog ~ PosOr.cont * session * (TokenTest_c * AAT_c) + (PosOr.cont +
## session | subject) + (1 | category)
## Data: df_RTs_PWA
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1810.1
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.4968 -0.6792 -0.1915  0.5042  5.0319
##
```

```

## Random effects:
##   Groups   Name                Variance Std.Dev. Corr
##   category (Intercept) 0.0092600 0.09623
##   subject  (Intercept) 0.0409836 0.20244
##           PosOr.cont  0.0001357 0.01165   0.27
##           session2    0.0005339 0.02311  -0.55  0.39
##           session3    0.0029467 0.05428  -0.61  0.09  0.05
##   Residual                0.0761189 0.27590
## Number of obs: 5518, groups:  category, 24; subject, 20
##
## Fixed effects:
##                                     Estimate Std. Error      df
## (Intercept)                      7.194167    0.056486   20.594370
## PosOr.cont                       0.016263    0.004697   21.433722
## session2                       -0.071053    0.013778   17.687842
## session3                       -0.078038    0.018663   20.704486
## TokenTest_c                     -0.026982    0.073995   16.095249
## AAT_c                          -0.198863    0.091339   16.428960
## PosOr.cont:session2             0.015077    0.008743  5424.195608
## PosOr.cont:session3             0.008715    0.008385  5431.728865
## TokenTest_c:AAT_c              -0.048308    0.030970   16.515486
## PosOr.cont:TokenTest_c          -0.001060    0.006471   21.750345
## PosOr.cont:AAT_c                0.006637    0.009542   33.501731
## session2:TokenTest_c            -0.014041    0.018817   18.561124
## session3:TokenTest_c            0.003742    0.025955   20.863974
## session2:AAT_c                  -0.026912    0.028832   25.851015
## session3:AAT_c                  -0.010841    0.036113   30.139853
## PosOr.cont:TokenTest_c:AAT_c     0.004082    0.003375   39.082828
## session2:TokenTest_c:AAT_c      -0.019027    0.010650   33.041850
## session3:TokenTest_c:AAT_c      -0.015318    0.012639   34.144950
## PosOr.cont:session2:TokenTest_c -0.014488    0.012062  5423.457225
## PosOr.cont:session3:TokenTest_c -0.012646    0.012000  5424.747740
## PosOr.cont:session2:AAT_c        -0.005411    0.019067  5418.272739
## PosOr.cont:session3:AAT_c        -0.006923    0.018310  5438.091709
## PosOr.cont:session2:TokenTest_c:AAT_c -0.004311    0.006971  5070.771048
## PosOr.cont:session3:TokenTest_c:AAT_c -0.004446    0.006325  5375.875481
##                                     t value      Pr(>|t|)
## (Intercept)                    127.361 < 0.0000000000000002 ***
## PosOr.cont                      3.462         0.002280 **
## session2                       -5.157         0.0000698 ***
## session3                       -4.181         0.000432 ***
## TokenTest_c                     -0.365         0.720121
## AAT_c                          -2.177         0.044363 *
## PosOr.cont:session2             1.724         0.084677 .
## PosOr.cont:session3             1.039         0.298667
## TokenTest_c:AAT_c              -1.560         0.137757
## PosOr.cont:TokenTest_c          -0.164         0.871368
## PosOr.cont:AAT_c                0.696         0.491501
## session2:TokenTest_c            -0.746         0.464916
## session3:TokenTest_c            0.144         0.886732
## session2:AAT_c                  -0.933         0.359248
## session3:AAT_c                  -0.300         0.766084
## PosOr.cont:TokenTest_c:AAT_c     1.210         0.233685
## session2:TokenTest_c:AAT_c      -1.787         0.083187 .

```

```
## session3:TokenTest_c:AAT_c          -1.212          0.233862
## Pos0r.cont:session2:TokenTest_c      -1.201          0.229720
## Pos0r.cont:session3:TokenTest_c      -1.054          0.292032
## Pos0r.cont:session2:AAT_c            -0.284          0.776599
## Pos0r.cont:session3:AAT_c            -0.378          0.705356
## Pos0r.cont:session2:TokenTest_c:AAT_c -0.618          0.536333
## Pos0r.cont:session3:TokenTest_c:AAT_c -0.703          0.482137
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
##
## Correlation matrix not shown by default, as p = 24 > 12.
## Use print(x, correlation=TRUE) or
##      vcov(x)          if you need it
```

```
anova(m1_lmm_PWA_tt_aat)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##
##              Sum Sq Mean Sq NumDF  DenDF F value
## Pos0r.cont      0.91237  0.91237    1    21.4 11.9861
## session         2.58647  1.29323    2    19.7 16.9897
## TokenTest_c      0.01012  0.01012    1    16.1  0.1330
## AAT_c           0.36082  0.36082    1    16.4  4.7403
## Pos0r.cont:session 0.22815  0.11408    2 5433.5  1.4986
## TokenTest_c:AAT_c 0.18520  0.18520    1    16.5  2.4331
## Pos0r.cont:TokenTest_c 0.00204  0.00204    1    21.8  0.0268
## Pos0r.cont:AAT_c  0.03683  0.03683    1    33.5  0.4838
## session:TokenTest_c 0.05496  0.02748    2    19.8  0.3610
## session:AAT_c     0.06634  0.03317    2    29.6  0.4358
## Pos0r.cont:TokenTest_c:AAT_c 0.11138  0.11138    1    39.1  1.4632
## session:TokenTest_c:AAT_c 0.27243  0.13622    2    36.2  1.7895
## Pos0r.cont:session:TokenTest_c 0.12624  0.06312    2 5424.5  0.8292
## Pos0r.cont:session:AAT_c 0.01157  0.00578    2 5418.3  0.0760
## Pos0r.cont:session:TokenTest_c:AAT_c 0.04416  0.02208    2 5239.2  0.2901
##
##              Pr(>F)
## Pos0r.cont      0.00228 **
## session         0.00005137 ***
## TokenTest_c      0.72012
## AAT_c           0.04436 *
## Pos0r.cont:session 0.22352
## TokenTest_c:AAT_c 0.13776
## Pos0r.cont:TokenTest_c 0.87137
## Pos0r.cont:AAT_c  0.49150
## session:TokenTest_c 0.70148
## session:AAT_c     0.65084
## Pos0r.cont:TokenTest_c:AAT_c 0.23369
## session:TokenTest_c:AAT_c 0.18151
## Pos0r.cont:session:TokenTest_c 0.43645
## Pos0r.cont:session:AAT_c 0.92684
## Pos0r.cont:session:TokenTest_c:AAT_c 0.74821
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```



```
performance::model_performance(m1_lmm_PWA_tt_aat)
```

```
## # Indices of model performance
##
## AIC          |      AICc |      BIC | R2 (cond.) | R2 (marg.) | ICC | RMSE | Sigma
## -----
## 1882.101 | 1882.587 | 2120.269 |      0.472 |      0.117 | 0.401 | 0.274 | 0.276
```

```
saveRDS(m1_lmm_PWA_tt_aat, file = here::here("results", "tables",
"CSI_online_aphasia_PWA_lmm_VOT_plus-TokenTest-plus-AachenAphasia.RDS"))
tab_model(m1_lmm_PWA_tt_aat, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title = "LMM of VOTs Predicted by Ordinal Position and Session",
  df.method = "satterthwaite",
  dv.labels = "Vocal Onset Time (log-transformed)",
  #string.pred = "",
  string.stat = "t-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_PWA_control_lmm_VOT-TokenTestAachenAphase.html"))
```

LMM of VOTs Predicted by Ordinal Position and Session

Vocal Onset Time (log-transformed)

Predictors

Estimates

CI

t-Value

p

(Intercept)

7.19

7.08 – 7.31

127.36

<0.001

PosOr cont

0.02

0.01 – 0.03

3.46

0.002

session [2]

-0.07

-0.10 – -0.04

-5.16  
 <0.001  
 session [3]  
 -0.08  
 -0.12 – -0.04  
 -4.18  
 <0.001  
 TokenTest c  
 -0.03  
 -0.18 – 0.13  
 -0.36  
 0.720  
 AAT c  
 -0.20  
 -0.39 – -0.01  
 -2.18  
 0.044  
 PosOr cont  $\times$  session [2]  
 0.02  
 -0.00 – 0.03  
 1.72  
 0.085  
 PosOr cont  $\times$  session [3]  
 0.01  
 -0.01 – 0.03  
 1.04  
 0.299  
 TokenTest c  $\times$  AAT c  
 -0.05  
 -0.11 – 0.02  
 -1.56  
 0.138  
 PosOr cont  $\times$  TokenTest c  
 -0.00  
 -0.01 – 0.01  
 -0.16

0.871  
 PosOr cont  $\times$  AAT c  
 0.01  
 -0.01 – 0.03  
 0.70  
 0.492  
 session [2]  $\times$  TokenTest c  
 -0.01  
 -0.05 – 0.03  
 -0.75  
 0.465  
 session [3]  $\times$  TokenTest c  
 0.00  
 -0.05 – 0.06  
 0.14  
 0.887  
 session [2]  $\times$  AAT c  
 -0.03  
 -0.09 – 0.03  
 -0.93  
 0.359  
 session [3]  $\times$  AAT c  
 -0.01  
 -0.08 – 0.06  
 -0.30  
 0.766  
 (PosOr cont  $\times$  TokenTestc)  $\times$  AAT c  
 0.00  
 -0.00 – 0.01  
 1.21  
 0.234  
 (session [2]  $\times$  TokenTestc)  $\times$  AAT c  
 -0.02  
 -0.04 – 0.00  
 -1.79  
 0.083

(session [3]  $\times$  TokenTestc)  $\times$  AAT c  
 -0.02  
 -0.04 – 0.01  
 -1.21  
 0.234  
 (PosOr cont  $\times$  session[2])  $\times$  TokenTest c  
 -0.01  
 -0.04 – 0.01  
 -1.20  
 0.230  
 (PosOr cont  $\times$  session[3])  $\times$  TokenTest c  
 -0.01  
 -0.04 – 0.01  
 -1.05  
 0.292  
 (PosOr cont  $\times$  session[2])  $\times$  AAT c  
 -0.01  
 -0.04 – 0.03  
 -0.28  
 0.777  
 (PosOr cont  $\times$  session[3])  $\times$  AAT c  
 -0.01  
 -0.04 – 0.03  
 -0.38  
 0.705  
 (PosOr cont  $\times$  session [2]  $\times$  TokenTest c)  $\times$  AAT c  
 -0.00  
 -0.02 – 0.01  
 -0.62  
 0.536  
 (PosOr cont  $\times$  session [3]  $\times$  TokenTest c)  $\times$  AAT c  
 -0.00  
 -0.02 – 0.01  
 -0.70  
 0.482  
 N subject

20

N category

24

Observations

5518

Main effect of Naming Test. Trend between Ordinal position and Session 2-1 x Token Test x Naming and Ordinal position x Session2-1

Does the model with Naming and Token test fit the data better? -> no (Trend)! Does the model with Naming and Token test fit the data better than the model only with Naming? -> no! => The variance explained by the token Test is also explained by the naming test Does the model with Naming test fit the data better than the main model? -> yes!

```
#summary(m1_lmm_PWA)
```

```
anova(m1_lmm_PWA, m1_lmm_PWA_tt_aat)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_tt_aat: VOTlog ~ PosOr.cont * session * (TokenTest_c * AAT_c) + (PosOr.cont + session | subject)
```

```
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
```

```
## m1_lmm_PWA          18 1697.5 1816.5 -830.73    1661.5
```

```
## m1_lmm_PWA_tt_aat    36 1706.5 1944.6 -817.23    1634.5 27.003 18    0.07893 .
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
anova(m1_lmm_PWA_aat, m1_lmm_PWA_tt_aat)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
```

```
## Models:
```

```
## m1_lmm_PWA_aat: VOTlog ~ PosOr.cont * session * AAT_c + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_tt_aat: VOTlog ~ PosOr.cont * session * (TokenTest_c * AAT_c) + (PosOr.cont + session | subject)
```

```
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
```

```
## m1_lmm_PWA_aat      24 1695.9 1854.6 -823.93    1647.9
```

```
## m1_lmm_PWA_tt_aat    36 1706.5 1944.6 -817.23    1634.5 13.394 12    0.341
```

```
anova(m1_lmm_PWA, m1_lmm_PWA_aat)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs_PWA
```

```
## Models:
```

```
## m1_lmm_PWA: VOTlog ~ PosOr.cont * session + (PosOr.cont + session | subject) + (1 | category)
```

```
## m1_lmm_PWA_aat: VOTlog ~ PosOr.cont * session * AAT_c + (PosOr.cont + session | subject) + (1 | category)
```

```
##          npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
```

```
## m1_lmm_PWA          18 1697.5 1816.5 -830.73    1661.5
```

```
## m1_lmm_PWA_aat      24 1695.9 1854.6 -823.93    1647.9 13.609 6    0.03432 *
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
(means_final<- df_RTs_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "category",
    withinvars = c("session", "PosOr"),
    betweenvars = c("subject", "AAT"), na.rm = T))
```

## Plot Naming test

```
## Automatically converting the following non-factors to factors: AAT
```

```
## Warning in qt(conf.interval/2 + 0.5, datac$N - 1): NaNs produced
```

##	subject	AAT	session	PosOr	N	VOT	sd	se	ci
## 1	101	98	1	1	21	1358.8342	334.4313	72.97888	152.23128
## 2	101	98	1	2	21	1430.7892	502.1845	109.58564	228.59165
## 3	101	98	1	3	23	1413.1229	519.2279	108.26651	224.53099
## 4	101	98	1	4	23	1279.2801	295.1891	61.55118	127.64933
## 5	101	98	1	5	23	1350.1123	495.6944	103.35943	214.35434
## 6	101	98	2	1	21	1236.0914	302.2888	65.96482	137.60020
## 7	101	98	2	2	24	1326.5282	394.2046	80.46668	166.45802
## 8	101	98	2	3	24	1264.7366	358.0604	73.08876	151.19563
## 9	101	98	2	4	24	1265.4449	309.4372	63.16360	130.66386
## 10	101	98	2	5	23	1350.5869	304.4667	63.48570	131.66127
## 11	101	98	3	1	22	1416.6396	352.1802	75.08507	156.14795
## 12	101	98	3	2	24	1383.0282	295.8206	60.38413	124.91408
## 13	101	98	3	3	24	1395.3616	291.3443	59.47040	123.02390
## 14	101	98	3	4	24	1375.4866	306.0538	62.47298	129.23520
## 15	101	98	3	5	24	1448.2782	295.9528	60.41111	124.96990
## 16	102	99	1	1	23	1422.7249	225.5446	47.02930	97.53280
## 17	102	99	1	2	23	1414.3154	251.7954	52.50297	108.88450
## 18	102	99	1	3	24	1428.2095	448.5557	91.56105	189.40846
## 19	102	99	1	4	24	1369.3762	238.9167	48.76867	100.88568
## 20	102	99	1	5	24	1557.6679	538.5309	109.92716	227.40166
## 21	102	99	2	1	23	1362.6814	320.0028	66.72519	138.37957
## 22	102	99	2	2	23	1352.6659	142.4267	29.69803	61.58994
## 23	102	99	2	3	23	1311.2218	176.2680	36.75441	76.22399
## 24	102	99	2	4	24	1331.5429	278.0828	56.76341	117.42406
## 25	102	99	2	5	24	1335.4179	226.0472	46.14170	95.45138
## 26	102	99	3	1	22	1306.8330	125.3060	26.71533	55.55758
## 27	102	99	3	2	24	1313.3345	177.1961	36.16999	74.82333
## 28	102	99	3	3	24	1241.7095	149.4035	30.49685	63.08755
## 29	102	99	3	4	23	1221.7000	107.7878	22.47530	46.61092
## 30	102	99	3	5	23	1317.8740	231.2996	48.22929	100.02143
## 31	103	97	1	1	21	1361.0269	562.2646	122.69620	255.93980
## 32	103	97	1	2	16	1405.8564	609.2341	152.30854	324.63796
## 33	103	97	1	3	14	1328.5140	284.6623	76.07919	164.35911
## 34	103	97	1	4	13	1229.9043	255.3610	70.82440	154.31311
## 35	103	97	1	5	14	1699.2952	746.5394	199.52104	431.03900
## 36	103	97	2	1	17	1059.3012	243.1891	58.98202	125.03629
## 37	103	97	2	2	20	1289.7725	450.1449	100.65546	210.67430
## 38	103	97	2	3	15	1522.8085	569.9557	147.16192	315.63093

## 39	103	97	2	4 17	1443.1595	717.8321	174.09986	369.07521
## 40	103	97	2	5 15	1386.7726	328.5558	84.83275	181.94816
## 41	103	97	3	1 18	1186.1687	468.7756	110.49148	233.11664
## 42	103	97	3	2 14	1099.7207	521.9427	139.49506	301.36076
## 43	103	97	3	3 17	1375.7002	458.5532	111.21548	235.76629
## 44	103	97	3	4 18	1384.9941	558.6514	131.67539	277.81080
## 45	103	97	3	5 16	1560.5688	611.2170	152.80426	325.69457
## 46	104	42	1	1 10	1468.3396	246.4016	77.91903	176.26509
## 47	104	42	1	2 11	1691.7417	399.8614	120.56276	268.63057
## 48	104	42	1	3 12	1725.2447	431.3717	124.52629	274.08051
## 49	104	42	1	4 7	1441.4886	527.8736	199.51745	488.20162
## 50	104	42	1	5 5	1614.7065	487.4739	218.00494	605.27875
## 51	104	42	2	1 12	1035.0665	388.5741	112.17169	246.88821
## 52	104	42	2	2 12	1322.7785	552.9101	159.61139	351.30229
## 53	104	42	2	3 10	1314.1556	275.2344	87.03676	196.89083
## 54	104	42	2	4 12	1356.2325	363.5779	104.95589	231.00635
## 55	104	42	2	5 8	1393.5998	349.2836	123.49041	292.00843
## 56	104	42	3	1 8	936.5166	178.8433	63.23066	149.51675
## 57	104	42	3	2 13	1045.0030	532.7783	147.76610	321.95468
## 58	104	42	3	3 15	1448.6131	631.5807	163.07342	349.75771
## 59	104	42	3	4 12	1363.5948	475.8995	137.38035	302.37210
## 60	104	42	3	5 7	1166.0978	296.0612	111.90063	273.81098
## 61	105	91	1	1 23	1278.9679	378.5265	78.92823	163.68714
## 62	105	91	1	2 22	1494.3695	433.7760	92.48136	192.32551
## 63	105	91	1	3 19	1487.5053	355.1332	81.47315	171.16875
## 64	105	91	1	4 23	1518.1817	505.4801	105.39990	218.58600
## 65	105	91	1	5 17	1578.3854	289.7805	70.28209	148.99138
## 66	105	91	2	1 22	1187.2017	250.4083	53.38723	111.02482
## 67	105	91	2	2 22	1120.1581	229.1538	48.85576	101.60113
## 68	105	91	2	3 24	1361.6607	373.0931	76.15732	157.54341
## 69	105	91	2	4 22	1462.1650	491.2600	104.73698	217.81248
## 70	105	91	2	5 20	1427.1733	435.0271	97.27502	203.59895
## 71	105	91	3	1 24	1216.7441	342.5561	69.92398	144.64876
## 72	105	91	3	2 23	1197.1853	286.6926	59.77954	123.97517
## 73	105	91	3	3 23	1303.6391	408.6771	85.21507	176.72524
## 74	105	91	3	4 21	1388.2115	528.1858	115.25959	240.42729
## 75	105	91	3	5 22	1367.0737	407.8340	86.95049	180.82345
## 76	106	94	1	1 14	1501.7248	608.7942	162.70709	351.50730
## 77	106	94	1	2 14	1555.0141	698.3146	186.63242	403.19484
## 78	106	94	1	3 11	1289.5354	494.3328	149.04695	332.09731
## 79	106	94	1	4 13	1761.3040	587.0137	162.80831	354.72883
## 80	106	94	1	5 12	1312.3281	495.3372	142.99154	314.72226
## 81	106	94	2	1 15	1429.7351	542.5796	140.09346	300.47059
## 82	106	94	2	2 17	1303.2390	788.9694	191.35319	405.65065
## 83	106	94	2	3 17	1155.0023	343.8604	83.39839	176.79669
## 84	106	94	2	4 17	1262.1727	462.2090	112.10214	237.64592
## 85	106	94	2	5 13	1740.9447	674.4934	187.07082	407.59231
## 86	106	94	3	1 21	1129.6410	305.2924	66.62027	138.96744
## 87	106	94	3	2 16	1151.1251	364.1948	91.04870	194.06571
## 88	106	94	3	3 21	1438.3866	619.6676	135.22255	282.06930
## 89	106	94	3	4 15	1119.3104	557.6370	143.98125	308.80907
## 90	106	94	3	5 17	1361.5606	623.4413	151.20673	320.54395
## 91	107	93	1	1 19	1259.4564	240.0093	55.06190	115.68076
## 92	107	93	1	2 23	1343.6728	241.3333	50.32147	104.36035

## 93	107	93	1	3	21	1388.6323	202.2287	44.12992	92.05340
## 94	107	93	1	4	23	1580.5209	530.0543	110.52396	229.21266
## 95	107	93	1	5	18	1537.8752	343.6372	80.99607	170.88677
## 96	107	93	2	1	23	1300.9721	320.2956	66.78624	138.50618
## 97	107	93	2	2	23	1271.6666	331.2548	69.07140	143.24531
## 98	107	93	2	3	24	1330.3263	438.0095	89.40832	184.95520
## 99	107	93	2	4	23	1465.8063	454.6168	94.79416	196.59106
## 100	107	93	2	5	22	1373.2215	370.4001	78.96957	164.22621
## 101	107	93	3	1	23	1211.1407	164.9986	34.40459	71.35074
## 102	107	93	3	2	24	1299.6179	380.6672	77.70338	160.74168
## 103	107	93	3	3	23	1291.7542	278.2545	58.02008	120.32627
## 104	107	93	3	4	23	1345.1355	316.6392	66.02383	136.92505
## 105	107	93	3	5	21	1322.7340	304.3807	66.42131	138.55242
## 106	108	99	1	1	22	1438.9657	405.9183	86.54208	179.97410
## 107	108	99	1	2	22	1275.0738	420.6970	89.69290	186.52659
## 108	108	99	1	3	22	1629.5510	547.5762	116.74364	242.78169
## 109	108	99	1	4	19	1398.0983	398.5282	91.42864	192.08444
## 110	108	99	1	5	17	1525.8691	426.0546	103.33342	219.05707
## 111	108	99	2	1	23	1237.0282	298.1722	62.17320	128.93932
## 112	108	99	2	2	23	1339.0127	297.7694	62.08921	128.76514
## 113	108	99	2	3	23	1373.2258	484.9160	101.11199	209.69342
## 114	108	99	2	4	23	1236.3170	342.8446	71.48803	148.25711
## 115	108	99	2	5	21	1521.5263	486.2544	106.10942	221.34036
## 116	108	99	3	1	24	1154.2816	187.9833	38.37194	79.37840
## 117	108	99	3	2	20	1223.6215	254.7277	56.95884	119.21621
## 118	108	99	3	3	22	1331.1782	408.2782	87.04520	181.02040
## 119	108	99	3	4	24	1310.7399	388.2077	79.24257	163.92574
## 120	108	99	3	5	19	1376.1429	391.7063	89.86360	188.79641
## 121	109	52	1	1	5	1553.7081	684.2034	305.98507	849.55074
## 122	109	52	1	2	4	1678.2281	376.5009	188.25047	599.09701
## 123	109	52	1	3	3	1174.4947	1047.8762	604.99161	2603.06879
## 124	109	52	1	4	6	1548.3169	255.5026	104.30850	268.13354
## 125	109	52	1	5	2	1369.1947	562.0209	397.40876	5049.55701
## 126	109	52	2	1	2	1274.4031	466.5656	329.91172	4191.92584
## 127	109	52	2	2	4	1086.4697	484.8184	242.40922	771.45432
## 128	109	52	2	3	4	1293.5114	393.9115	196.95576	626.80112
## 129	109	52	2	4	3	1312.8725	592.5290	342.09679	1471.92367
## 130	109	52	2	5	5	1406.8581	470.9505	210.61547	584.76230
## 131	109	52	3	1	5	1063.5614	655.2707	293.04598	813.62607
## 132	109	52	3	2	5	1439.2347	326.4862	146.00907	405.38617
## 133	109	52	3	3	5	1250.1781	689.2695	308.25070	855.84113
## 134	109	52	3	4	7	1310.9876	685.1531	258.96353	633.66094
## 135	109	52	3	5	7	1375.6471	456.2471	172.44521	421.95822
## 136	110	100	1	1	22	1257.7886	359.3965	76.62359	159.34748
## 137	110	100	1	2	19	1514.5425	550.3031	126.24819	265.23761
## 138	110	100	1	3	21	1334.1082	411.9154	89.88732	187.50166
## 139	110	100	1	4	17	1526.6584	450.0413	109.15105	231.38990
## 140	110	100	1	5	20	1694.7038	537.7702	120.24907	251.68420
## 141	110	100	2	1	23	1507.9951	583.6788	121.70544	252.40163
## 142	110	100	2	2	22	1311.4739	382.5842	81.56723	169.62833
## 143	110	100	2	3	23	1148.0501	171.1203	35.68106	73.99799
## 144	110	100	2	4	22	1276.1592	346.0953	73.78776	153.45006
## 145	110	100	2	5	22	1382.7185	476.3793	101.56440	211.21474
## 146	110	100	3	1	24	1243.3291	243.5664	49.71779	102.84908



## 147	110 100	3	2 24	1362.4957	531.6914	108.53104	224.51357
## 148	110 100	3	3 23	1294.4569	299.5477	62.46000	129.53412
## 149	110 100	3	4 23	1282.5385	286.9295	59.82893	124.07761
## 150	110 100	3	5 22	1265.8550	282.2211	60.16975	125.12985
## 151	111 96	1	1 21	1302.4626	428.0049	93.39832	194.82549
## 152	111 96	1	2 20	1415.6848	336.3217	75.20382	157.40339
## 153	111 96	1	3 18	1676.8457	560.6042	132.13568	278.78192
## 154	111 96	1	4 22	1442.8978	355.8347	75.86422	157.76829
## 155	111 96	1	5 19	1450.4708	488.6445	112.10273	235.51910
## 156	111 96	2	1 22	1200.5480	442.8777	94.42184	196.36096
## 157	111 96	2	2 19	1348.6471	452.2510	103.75349	217.97800
## 158	111 96	2	3 19	1277.7434	364.0641	83.52204	175.47330
## 159	111 96	2	4 24	1153.7975	269.9575	55.10485	113.99306
## 160	111 96	2	5 23	1202.3603	407.1926	84.90553	176.08329
## 161	111 96	3	1 21	1335.7529	486.6526	106.19630	221.52161
## 162	111 96	3	2 20	1275.1954	344.1587	76.95622	161.07122
## 163	111 96	3	3 18	1471.8820	433.2202	102.11099	215.43535
## 164	111 96	3	4 23	1351.5992	400.8776	83.58876	173.35247
## 165	111 96	3	5 22	1491.5915	511.9152	109.14070	226.97050
## 166	112 28	1	1 8	1316.5080	563.7412	199.31263	471.29948
## 167	112 28	1	2 5	1526.7209	454.1961	203.12268	563.95898
## 168	112 28	1	3 2	1076.8031	471.1768	333.17228	4233.35518
## 169	112 28	1	4 5	1423.9047	449.4000	200.97779	558.00381
## 170	112 28	1	5 2	1845.2852	217.5909	153.85997	1954.97634
## 171	112 28	2	1 7	1253.1491	350.4492	132.45733	324.11141
## 172	112 28	2	2 8	1492.6312	508.3645	179.73400	425.00338
## 173	112 28	2	3 4	1582.2843	425.4618	212.73088	677.00461
## 174	112 28	2	4 1	1352.9281	NA	NA	NaN
## 175	112 28	2	5 2	1714.9906	530.0052	374.77029	4761.90806
## 176	112 28	3	1 12	1138.1022	386.9141	111.69248	245.83349
## 177	112 28	3	2 7	1153.2813	321.1385	121.37893	297.00355
## 178	112 28	3	3 5	1428.7531	436.7453	195.31845	542.29097
## 179	112 28	3	4 4	1370.4906	223.2388	111.61939	355.22271
## 180	112 28	3	5 6	1369.6596	268.2209	109.50071	281.48054
## 181	113 100	1	1 21	1310.5205	443.3600	96.74909	201.81506
## 182	113 100	1	2 17	1439.9194	483.2373	117.20226	248.45769
## 183	113 100	1	3 17	1318.5734	339.0773	82.23831	174.33744
## 184	113 100	1	4 23	1399.5255	449.1382	93.65179	194.22193
## 185	113 100	1	5 20	1443.0444	418.9173	93.67275	196.05932
## 186	113 100	2	1 20	1201.2809	154.8110	34.61680	72.45379
## 187	113 100	2	2 23	1254.5001	384.4238	80.15790	166.23731
## 188	113 100	2	3 21	1244.8037	213.3766	46.56258	97.12784
## 189	113 100	2	4 19	1548.4409	454.7210	104.32014	219.16848
## 190	113 100	2	5 20	1512.8014	420.9777	94.13347	197.02362
## 191	113 100	3	1 18	1333.6522	250.8663	59.12976	124.75289
## 192	113 100	3	2 21	1243.2475	236.1940	51.54175	107.51421
## 193	113 100	3	3 22	1396.6814	445.0887	94.89323	197.34128
## 194	113 100	3	4 24	1209.4381	187.7392	38.32211	79.27532
## 195	113 100	3	5 19	1505.9964	548.9517	125.93816	264.58626
## 196	114 97	1	1 21	1484.1272	552.6513	120.59841	251.56388
## 197	114 97	1	2 15	1556.1974	587.5475	151.70412	325.37297
## 198	114 97	1	3 15	1458.5554	532.1168	137.39198	294.67648
## 199	114 97	1	4 17	1301.5413	353.8481	85.82077	181.93190
## 200	114 97	1	5 19	1394.6748	418.2269	95.94782	201.57889

## 201	114 97	2	1 20	1136.6087	245.9145	54.98815	115.09153
## 202	114 97	2	2 17	1215.5708	246.5963	59.80839	126.78812
## 203	114 97	2	3 19	1277.2423	253.1440	58.07522	122.01151
## 204	114 97	2	4 20	1466.7039	449.8238	100.58367	210.52404
## 205	114 97	2	5 18	1233.0174	291.5303	68.71434	144.97459
## 206	114 97	3	1 21	1133.5303	239.4278	52.24744	108.98625
## 207	114 97	3	2 22	1518.9333	667.0300	142.21127	295.74452
## 208	114 97	3	3 21	1272.4256	401.2322	87.55605	182.63872
## 209	114 97	3	4 22	1374.3754	373.6283	79.65783	165.65753
## 210	114 97	3	5 20	1495.3315	586.9165	131.23852	274.68538
## 211	115 100	1	1 21	1573.0226	481.1330	104.99184	219.00914
## 212	115 100	1	2 22	1477.9638	302.1047	64.40895	133.94573
## 213	115 100	1	3 23	1676.7618	447.1677	93.24092	193.36982
## 214	115 100	1	4 23	1354.8829	275.5391	57.45388	119.15206
## 215	115 100	1	5 19	1478.5661	267.1714	61.29332	128.77249
## 216	115 100	2	1 23	1335.1289	375.6216	78.32252	162.43096
## 217	115 100	2	2 21	1444.7999	552.2098	120.50207	251.36291
## 218	115 100	2	3 24	1376.3193	416.3729	84.99176	175.81885
## 219	115 100	2	4 22	1159.6730	174.2527	37.15079	77.25930
## 220	115 100	2	5 22	1259.2721	236.9885	50.52613	105.07483
## 221	115 100	3	1 22	1185.6920	409.7421	87.35730	181.66946
## 222	115 100	3	2 23	1263.2928	508.4072	106.01023	219.85177
## 223	115 100	3	3 24	1137.7360	232.3564	47.42956	98.11552
## 224	115 100	3	4 24	1383.9026	371.9953	75.93322	157.07984
## 225	115 100	3	5 22	1222.9151	319.3913	68.09446	141.61019
## 226	116 100	1	1 23	1349.4370	273.5274	57.03441	118.28212
## 227	116 100	1	2 22	1422.4348	339.1662	72.31048	150.37787
## 228	116 100	1	3 20	1520.7922	402.9043	90.09214	188.56503
## 229	116 100	1	4 22	1411.9017	245.3698	52.31302	108.79088
## 230	116 100	1	5 24	1496.7804	335.8464	68.55435	141.81548
## 231	116 100	2	1 24	1210.7387	256.9263	52.44486	108.49047
## 232	116 100	2	2 24	1276.5304	259.1567	52.90013	109.43226
## 233	116 100	2	3 24	1226.1971	272.0759	55.53726	114.88757
## 234	116 100	2	4 23	1371.8827	298.0578	62.14936	128.88988
## 235	116 100	2	5 24	1493.0721	515.0257	105.12917	217.47627
## 236	116 100	3	1 24	1262.7804	272.8139	55.68790	115.19919
## 237	116 100	3	2 24	1335.8637	236.6758	48.31124	99.93941
## 238	116 100	3	3 23	1334.7807	263.4028	54.92328	113.90390
## 239	116 100	3	4 23	1270.1552	209.5029	43.68437	90.59584
## 240	116 100	3	5 24	1345.6971	198.5101	40.52071	83.82348
## 241	117 100	1	1 19	1403.0974	415.2946	95.27512	200.16559
## 242	117 100	1	2 17	1339.9588	247.1947	59.95353	127.09581
## 243	117 100	1	3 21	1555.5001	550.5829	120.14704	250.62233
## 244	117 100	1	4 20	1423.8212	374.6269	83.76912	175.33078
## 245	117 100	1	5 21	1579.0680	586.8863	128.06908	267.14743
## 246	117 100	2	1 21	1291.3708	448.2158	97.80872	204.02541
## 247	117 100	2	2 23	1265.4818	369.6322	77.07365	159.84097
## 248	117 100	2	3 23	1346.1346	413.1105	86.13949	178.64238
## 249	117 100	2	4 22	1230.5466	261.3275	55.71521	115.86612
## 250	117 100	2	5 21	1384.1038	405.2388	88.43035	184.46248
## 251	117 100	3	1 23	1316.1883	469.1563	97.82584	202.87838
## 252	117 100	3	2 22	1219.4350	226.2870	48.24454	100.33002
## 253	117 100	3	3 24	1409.7018	433.5256	88.49305	183.06182
## 254	117 100	3	4 22	1259.2501	430.0137	91.67922	190.65738

## 255	117	100	3	5	24	1303.9518	327.6630	66.88394	138.35997
## 256	118	100	1	1	21	1382.3957	527.3595	115.07927	240.05116
## 257	118	100	1	2	21	1522.9463	619.2724	135.13632	281.88942
## 258	118	100	1	3	21	1532.9058	549.0874	119.82070	249.94161
## 259	118	100	1	4	21	1514.7571	629.7051	137.41293	286.63834
## 260	118	100	1	5	17	1378.0469	481.2649	116.72387	247.44356
## 261	118	100	2	1	21	1135.4206	474.2366	103.48690	215.86990
## 262	118	100	2	2	24	1220.0276	321.5133	65.62862	135.76315
## 263	118	100	2	3	23	1215.3544	335.6795	69.99401	145.15870
## 264	118	100	2	4	21	1293.3228	367.7129	80.24152	167.38088
## 265	118	100	2	5	23	1432.7240	572.8981	119.45750	247.73970
## 266	118	100	3	1	23	1273.8291	416.3052	86.80564	180.02387
## 267	118	100	3	2	24	1427.4026	616.6584	125.87487	260.39201
## 268	118	100	3	3	23	1236.0785	411.9566	85.89889	178.14340
## 269	118	100	3	4	21	1316.0199	467.8253	102.08786	212.95154
## 270	118	100	3	5	20	1454.8378	642.8706	143.75023	300.87270
## 271	119	83	1	1	19	1389.3999	431.9863	99.10445	208.21072
## 272	119	83	1	2	18	1349.1446	435.3157	102.60489	216.47740
## 273	119	83	1	3	18	1408.7464	483.9850	114.07636	240.68008
## 274	119	83	1	4	18	1339.8588	466.4117	109.93430	231.94110
## 275	119	83	1	5	17	1329.4041	362.4648	87.91062	186.36220
## 276	119	83	2	1	21	1543.9834	373.2356	81.44670	169.89483
## 277	119	83	2	2	22	1278.1155	484.0949	103.20939	214.63567
## 278	119	83	2	3	16	1424.1952	392.3671	98.09177	209.07766
## 279	119	83	2	4	21	1502.5358	418.0943	91.23567	190.31427
## 280	119	83	2	5	15	1654.3117	356.3750	92.01563	197.35391
## 281	119	83	3	1	21	1408.9437	439.2475	95.85166	199.94306
## 282	119	83	3	2	22	1097.6799	330.6858	70.50246	146.61789
## 283	119	83	3	3	21	1241.5090	330.0779	72.02890	150.24965
## 284	119	83	3	4	21	1210.6017	338.0194	73.76189	153.86460
## 285	119	83	3	5	22	1244.0312	502.9982	107.23957	223.01690
## 286	120	75	1	1	8	1250.6518	369.9371	130.79251	309.27514
## 287	120	75	1	2	13	1677.0523	612.9922	170.01344	370.42746
## 288	120	75	1	3	12	1204.3829	356.7538	102.98594	226.67053
## 289	120	75	1	4	18	1420.0321	490.9063	115.70773	244.12197
## 290	120	75	1	5	12	1465.3693	643.4496	185.74791	408.82840
## 291	120	75	2	1	15	1273.0214	503.6087	130.03121	278.88920
## 292	120	75	2	2	15	1185.5242	315.6730	81.50642	174.81388
## 293	120	75	2	3	10	1650.1187	759.4871	240.17092	543.30436
## 294	120	75	2	4	18	1317.0788	459.1972	108.23381	228.35337
## 295	120	75	2	5	14	1562.7185	586.0235	156.62137	338.35990
## 296	120	75	3	1	19	1175.8661	206.2909	47.32637	99.42901
## 297	120	75	3	2	14	1216.7220	378.7311	101.22013	218.67280
## 298	120	75	3	3	18	1156.6040	312.5545	73.66981	155.42971
## 299	120	75	3	4	10	1562.5556	557.6170	176.33399	398.89520
## 300	120	75	3	5	13	1428.6633	520.7045	144.41746	314.65860

```

override.linetype<-c("dashed")
(plot_rt_repetition_PWA_session1 <- means_final %>%
  filter(session=="1") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=AAT, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
    fun=mean, geom="line", size = 0.5) +

```

```


scale_linetype_manual(values=c("dashed"))+
scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
                             "#fb8479", "#fa6153",
                             "#f93e2d", "#f81b07",
                             "#d21706", "#ac1305",
                             "#860f04", "#5f0b03",
                             "#390602", "#130201"))+

geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = AAT), width =.1) +
apatheme+
scale_y_continuous(limits = c(600, 2400),
                   breaks =seq(800,2400, by = 200)) +
labs(x="Ordinal Position ",y = "RT (ms)", colour="Session",
     linetype="Session",
     title = "Session 1") +
theme(
  axis.title.y = element_text(margin = margin(0,10,0,0)),
  axis.title.x = element_text(margin = margin(10,0,0,0)),
  legend.key.width = unit(1, "cm"),
  legend.position="none")+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```


(plot_rt_repetition_PWA_session2 <- means_final %>%
  filter(session=="2") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=AAT, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
                                "#fb8479", "#fa6153",
                                "#f93e2d", "#f81b07",
                                "#d21706", "#ac1305",
                                "#860f04", "#5f0b03",
                                "#390602", "#130201"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = AAT), width =.1) +
  apatheme+
  scale_y_continuous(limits = c(600, 2400),
    breaks =seq(800,2400, by = 200)) +
  labs(x="Ordinal Position ",y ="RT (ms)", colour="Session",
    linetype="Session",
    title = "Session 2") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none"))

```

## Scale for linetype is already present.


## Adding another scale for linetype, which will replace the existing scale.

## Session 2



```
(plot_rt_repetition_PWA_session3 <- means_final %>%
  filter(session=="3") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=AAT, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
    "#fb8479", "#fa6153",
    "#f93e2d", "#f81b07",
    "#d21706", "#ac1305",
    "#860f04", "#5f0b03",
    "#390602", "#130201"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = AAT), width = .1) +
  apatheme+
  scale_y_continuous(limits = c(600, 2400),
    breaks =seq(800,2400, by = 200)) +
  labs(x="Ordinal Position ",y ="RT (ms)", colour="Naming score",
    # linetype="Session",
    title = "Session 3") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="right")+
  scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
## Adding another scale for linetype, which will replace the existing scale.
```



```
plots <- cowplot::plot_grid(plot_rt_repetition_PWA_session1,
                             plot_rt_repetition_PWA_session2,
                             plot_rt_repetition_PWA_session3,
                             nrow = 1, ncol=3, rel_widths = c(0.81,0.81,1),
                             margin(1,1,1,1),
                             labels = c("B", "C", "D"), label_size = 34,
                             label_fontfamily = "Helvetica", label_y = 1.01,
                             label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_PWA_AAT_scores.pdf"
ggsave(plots, filename =
        here::here("results", "figures", filename),
        width = 25, height = 13, units = "cm",
        dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

```
#### Trying to understand the interaction:
# median split of means final
median(as.numeric(as.character(means_final$AAT)))
```

```
## [1] 97
```

```
means_final %>%
  mutate(med_split=case_when(as.numeric(as.character(AAT)) >
                             median(as.numeric(as.character(
                               means_final$AAT))) ~"high",
                             as.numeric(as.character(AAT)) <
                             median(as.numeric(as.character(
                               means_final$AAT))) ~ "low",
                             as.numeric(as.character(AAT)) ==
                             median(as.numeric(as.character(
                               means_final$AAT))) ~
                               "median"),
                             mean_split=case_when(
                               as.numeric(as.character(AAT)) >
                               mean(as.numeric(as.character(
                                 means_final$AAT))) ~ "high",
                               as.numeric(as.character(AAT)) <
                               mean(as.numeric(as.character(
                                 means_final$AAT))) ~ "low",
                               as.numeric(as.character(AAT)) ==
                               mean(as.numeric(as.character(
                                 means_final$AAT))) ~ "median")) ->
    means_final

means_final %>% group_by(med_split) %>% summarise(mean=mean(VOT),
                                                    sd = sd(VOT))
```

```
## # A tibble: 3 x 3
##   med_split mean    sd
##   <chr>      <dbl> <dbl>
## 1 high      1356.  113.
## 2 low       1364.  169.
## 3 median    1355.  153.
```

```
means_final %>% group_by(mean_split) %>% summarise(mean=mean(VOT),
                                                    sd = sd(VOT))
```

```
## # A tibble: 2 x 3
##   mean_split mean    sd
##   <chr>      <dbl> <dbl>
## 1 high      1357.  128.
## 2 low       1366.  186.
```


```
(means_final<- df_RTs_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySE(.,measurevar="VOT",
                   groupvars = c("subject","AAT"), na.rm = T))
```



##	subject	AAT	N	VOT	sd	se	ci
## 1	101	98	345	775.3710	380.0659	20.46206	40.24650
## 2	102	99	351	886.8604	292.5880	15.61719	30.71535
## 3	103	97	245	1355.3306	560.3643	35.80036	70.51719
## 4	104	42	154	1745.7143	508.6572	40.98876	80.97700
## 5	105	91	327	1586.3639	436.7228	24.15083	47.51114
## 6	106	94	233	1639.8584	592.6691	38.82705	76.49867
## 7	107	93	333	1300.3393	379.0231	20.77034	40.85806
## 8	108	99	324	1264.6759	434.0358	24.11310	47.43856
## 9	109	52	67	2169.3731	617.2171	75.40507	150.55108
## 10	110	100	327	1220.1957	449.9797	24.88394	48.95336
## 11	111	96	311	1837.2637	464.0219	26.31227	51.77323
## 12	112	28	78	1705.7179	569.9750	64.53696	128.50951
## 13	113	100	305	1151.9082	401.5656	22.99358	45.24672
## 14	114	97	287	1278.4530	486.1275	28.69520	56.48056
## 15	115	100	335	1465.9582	430.1200	23.49997	46.22659
## 16	116	100	348	1238.8707	350.2938	18.77772	36.93247
## 17	117	100	323	1336.9969	427.5771	23.79103	46.80548
## 18	118	100	324	1414.3981	539.9319	29.99621	59.01262
## 19	119	83	292	1560.5582	483.6372	28.30273	55.70400
## 20	120	75	209	1469.4641	537.0199	37.14644	73.23179

```
(plot_rt_PWA_AAT <- means_final %>%
  ggplot(., aes(x=AAT, y=VOT)) +
  geom_point(size = 2)+
  scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
                                "#fb8479", "#fa6153",
                                "#f93e2d", "#f81b07",
                                "#d21706", "#ac1305",
                                "#860f04", "#5f0b03",
                                "#390602", "#130201"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = AAT), width =.1) +
  apatheme+
  scale_y_continuous(limits = c(600, 2400),
                     breaks =seq(800,2400, by = 200)) +
  labs(x="Naming test percentile score ",y ="RT (ms)", colour="Naming score",
       # linetype="Session",
       title = "Mean RTs across sessions and\nordinal positions by Naming test score") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  scale_linetype(guide="none"))
```

## Mean RTs across sessions and ordinal positions by Naming test score



```
filename <- "CSI_online_aphasia_spoken_plot_PWA_AAT.pdf"
ggsave(plot_rt_PWA_AAT, filename =
  here::here("results", "figures", filename),
  width = 15, height = 10, units = "cm",
  dpi = 300, device = cairo_pdf)

plots2 <- cowplot::plot_grid(plot_rt_PWA_AAT, plots,
  nrow = 1, ncol=2, rel_widths = c(0.81,0.81,1),
  rel_height = c(4,1),
  margin(1.5,1.5,1.5,1.5),
  labels = c("A", ""),label_size = 34,
  #label_fontfamily = "Helvetica",
  label_y = 1.01,
  label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class numeric into a
## grob.
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_PWA_AAT_summary_plot.pdf"
ggsave(plots2, filename =
  here::here("results", "figures", filename),
```

```
width = 25, height = 20, units = "cm",  
dpi = 300, device = cairo_pdf)
```

Errors Add into converging model

```
cor.test(df_errors_PWA$TokenTest_c, df_errors_PWA$LHoverall_c)
```

```
##  
## Pearson's product-moment correlation  
##  
## data: df_errors_PWA$TokenTest_c and df_errors_PWA$LHoverall_c  
## t = -44.023, df = 7176, p-value < 0.00000000000000022  
## alternative hypothesis: true correlation is not equal to 0  
## 95 percent confidence interval:  
## -0.4791506 -0.4427161  
## sample estimates:  
## cor  
## -0.4611277
```

```
cor.test(df_errors_PWA$AAT_c, df_errors_PWA$LHoverall_c)
```

```
##  
## Pearson's product-moment correlation  
##  
## data: df_errors_PWA$AAT_c and df_errors_PWA$LHoverall_c  
## t = -55.609, df = 7176, p-value < 0.00000000000000022  
## alternative hypothesis: true correlation is not equal to 0  
## 95 percent confidence interval:  
## -0.5647379 -0.5323978  
## sample estimates:  
## cor  
## -0.5487731
```

```
cor.test(df_errors_PWA$AAT_c, df_errors_PWA$TokenTest_c)
```

```
##  
## Pearson's product-moment correlation  
##  
## data: df_errors_PWA$AAT_c and df_errors_PWA$TokenTest_c  
## t = 151.84, df = 7176, p-value < 0.00000000000000022  
## alternative hypothesis: true correlation is not equal to 0  
## 95 percent confidence interval:  
## 0.8676779 0.8786656  
## sample estimates:  
## cor  
## 0.8732828
```

```
cor.test(df_errors_PWA$AAT_spontansprache, df_errors_PWA$TokenTest_c)
```

```
##
## Pearson's product-moment correlation
##
## data: df_errors_PWA$AAT_spontansprache and df_errors_PWA$TokenTest_c
## t = 66.274, df = 7176, p-value < 0.00000000000000022
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
## 0.6016264 0.6303336
## sample estimates:
## cor
## 0.6161846
```

```
# m1_glmm_PWA_all <- glmer(error_class ~
#                               PosOr.cont*session*TokenTest_c*AAT_c*LHoverall_c +
#                               (PosOr.cont |subject) +
#                               (1|category) ,
#                               data=df_errors_PWA, family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa",
#                               optCtrl = list(maxfun = 2e5)))
# m1_glmm_PWA_all <- afex::lmer_alt(error_class ~
#                               PosOr.cont*session*(TokenTest_c*AAT_c*
#                               AAT_spontansprache_c*
#                               LHoverall_c) +
#                               (PosOr.cont |subject) +
#                               (1|category) ,
#                               data=df_errors_PWA, family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa",
#                               optCtrl = list(maxfun = 2e5)))

m1_glmm_PWA_all <- afex::lmer_alt(error_class ~
                                PosOr.cont*session*(TokenTest_c+AAT_c+
                                AAT_spontansprache_c+
                                LHoverall_c) +
                                (PosOr.cont |subject) +
                                (1|category) ,
                                data=df_errors_PWA, family = "binomial",
                                control=glmerControl(optimizer = "bobyqa",
                                optCtrl = list(maxfun = 2e5)))

# m1_glmm_PWA_all <- afex::lmer_alt(error_class ~
#                               PosOr.cont*session*(TokenTest_c*AAT_c*
#                               LHoverall_c) +
#                               (PosOr.cont |subject) +
#                               (1|category) ,
#                               data=df_errors_PWA, family = "binomial",
#                               control=glmerControl(optimizer = "bobyqa",
#                               optCtrl = list(maxfun = 2e5)))

didLmerConverge(m1_glmm_PWA_all)
```

```
## The relative maximum gradient of 0.0000465 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## Warnings can be ignored
```

```
summary(m1_glmm_PWA_all)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
##   Family: binomial   ( logit )
## Formula:
## error_class ~ PosOr.cont * session * (TokenTest_c + AAT_c + AAT_spontansprache_c +
##   LHoverall_c) + (1 + re1.PosOr.cont | subject) + (1 | category)
##   Data: data
## Control: glmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
##      AIC      BIC    logLik deviance df.resid
##  5329.1   5563.0  -2630.5   5261.1     7144
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.9219 -0.3912 -0.2415 -0.1200  9.8488
##
## Random effects:
##   Groups   Name                Variance Std.Dev. Corr
##   category (Intercept)         0.349037 0.5908
##   subject  (Intercept)         0.661274 0.8132
##           re1.PosOr.cont 0.007276 0.0853   0.05
## Number of obs: 7178, groups:  category, 24; subject, 20
##
## Fixed effects:
##
##              Estimate Std. Error z value
## (Intercept)    -1.868138   0.223130  -8.372
## PosOr.cont         0.091736   0.036639   2.504
## session2        -0.444675   0.089118  -4.990
## session3        -0.736607   0.092820  -7.936
## TokenTest_c     -0.078771   0.404053  -0.195
## AAT_c           -1.134324   0.402664  -2.817
## AAT_spontansprache_c -0.071116   0.239747  -0.297
## LHoverall_c      0.002373   0.222665   0.011
## PosOr.cont:session2 -0.049177   0.062922  -0.782
## PosOr.cont:session3 -0.042042   0.065504  -0.642
## PosOr.cont:TokenTest_c -0.082566   0.063911  -1.292
## PosOr.cont:AAT_c   -0.062287   0.062476  -0.997
## PosOr.cont:AAT_spontansprache_c 0.093650   0.047339   1.978
## PosOr.cont:LHoverall_c -0.054721   0.038568  -1.419
## session2:TokenTest_c -0.033723   0.150716  -0.224
## session3:TokenTest_c -0.198145   0.154573  -1.282
## session2:AAT_c     -0.044075   0.155617  -0.283
## session3:AAT_c      0.053915   0.156123   0.345
## session2:AAT_spontansprache_c -0.017978   0.113045  -0.159
## session3:AAT_spontansprache_c 0.233157   0.121585   1.918
## session2:LHoverall_c 0.127220   0.102052   1.247
## session3:LHoverall_c 0.176587   0.102239   1.727
## PosOr.cont:session2:TokenTest_c -0.085100   0.106578  -0.798
## PosOr.cont:session3:TokenTest_c -0.218500   0.109560  -1.994
```

```

## Pos0r.cont:session2:AAT_c          0.154716    0.110082    1.405
## Pos0r.cont:session3:AAT_c          0.292621    0.110689    2.644
## Pos0r.cont:session2:AAT_spontansprache_c -0.024067    0.079779   -0.302
## Pos0r.cont:session3:AAT_spontansprache_c -0.070096    0.085723   -0.818
## Pos0r.cont:session2:LHoverall_c     0.112933    0.072131    1.566
## Pos0r.cont:session3:LHoverall_c     0.042705    0.072236    0.591
##                                     Pr(>|z|)
## (Intercept)                        < 0.0000000000000002 ***
## Pos0r.cont                          0.01229 *
## session2                           0.00000060468889586 ***
## session3                           0.000000000000000209 ***
## TokenTest_c                        0.84543
## AAT_c                              0.00485 **
## AAT_spontansprache_c               0.76675
## LHoverall_c                        0.99150
## Pos0r.cont:session2                0.43448
## Pos0r.cont:session3                0.52098
## Pos0r.cont:TokenTest_c             0.19640
## Pos0r.cont:AAT_c                   0.31878
## Pos0r.cont:AAT_spontansprache_c    0.04790 *
## Pos0r.cont:LHoverall_c             0.15596
## session2:TokenTest_c               0.82295
## session3:TokenTest_c               0.19988
## session2:AAT_c                     0.77700
## session3:AAT_c                     0.72984
## session2:AAT_spontansprache_c      0.87364
## session3:AAT_spontansprache_c      0.05516 .
## session2:LHoverall_c               0.21254
## session3:LHoverall_c               0.08413 .
## Pos0r.cont:session2:TokenTest_c    0.42459
## Pos0r.cont:session3:TokenTest_c    0.04611 *
## Pos0r.cont:session2:AAT_c          0.15989
## Pos0r.cont:session3:AAT_c          0.00820 **
## Pos0r.cont:session2:AAT_spontansprache_c 0.76290
## Pos0r.cont:session3:AAT_spontansprache_c 0.41352
## Pos0r.cont:session2:LHoverall_c    0.11742
## Pos0r.cont:session3:LHoverall_c    0.55440
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

##
## Correlation matrix not shown by default, as p = 30 > 12.
## Use print(x, correlation=TRUE) or
##     vcov(x)           if you need it

```

```
anova(m1_glmm_PWA_all)
```

```

## Analysis of Variance Table
##
##      npar Sum Sq Mean Sq F value
## Pos0r.cont      1  8.624    8.624  8.6237
## session          2 62.788   31.394 31.3940
## TokenTest_c      1 34.852   34.852 34.8517
## AAT_c            1  8.540    8.540  8.5397

```

```
## AAT_spontansprache_c      1  0.207   0.207  0.2073
## LHoverall_c              1  0.001   0.001  0.0013
## Pos0r.cont:session       2  0.667   0.333  0.3333
## Pos0r.cont:TokenTest_c   1  2.824   2.824  2.8242
## Pos0r.cont:AAT_c         1  0.180   0.180  0.1801
## Pos0r.cont:AAT_spontansprache_c 1  5.376   5.376  5.3759
## Pos0r.cont:LHoverall_c   1  2.205   2.205  2.2053
## session:TokenTest_c      2  4.480   2.240  2.2402
## session:AAT_c            2  1.148   0.574  0.5740
## session:AAT_spontansprache_c 2  4.964   2.482  2.4820
## session:LHoverall_c      2  3.168   1.584  1.5840
## Pos0r.cont:session:TokenTest_c 2  0.550   0.275  0.2752
## Pos0r.cont:session:AAT_c  2  6.627   3.314  3.3137
## Pos0r.cont:session:AAT_spontansprache_c 2  0.666   0.333  0.3329
## Pos0r.cont:session:LHoverall_c 2  2.469   1.234  1.2344
```

```
performance::model_performance(m1_glmm_PWA_all)
```

```
## # Indices of model performance
```

```
##
## AIC      |      AICc |      BIC | R2 (cond.) | R2 (marg.) | ICC | RMSE | Sigma | Log_loss | Score_
## -----
## 5329.073 | 5329.406 | 5562.952 | 0.452 | 0.284 | 0.235 | 0.331 | 1.000 | 0.354 | -
```

```
saveRDS(m1_glmm_PWA_all, file = here::here("results", "tables", "CSI_online_aphasia_PWA_lmm_error_TokenTest_Naming_Lesionsize.html"),
tab_model(m1_glmm_PWA_tt, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title =
    "GLMM of errors Predicted by Ordinal Position and Session",
  dv.labels = "Errors",
  #string.pred = "",
  string.stat = "z-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_PWA_control_glmm_error_TokenTest_Naming_Lesionsize.html"))
```

GLMM of errors Predicted by Ordinal Position and Session

Errors

Predictors

Log-Odds

CI

z-Value

p

(Intercept)

-1.87

-2.37 – -1.37

-7.33  
 <0.001  
 PosOr cont  
 0.09  
 0.01 – 0.17  
 2.14  
 0.032  
 session [2]  
 -0.43  
 -0.61 – -0.26  
 -4.96  
 <0.001  
 session [3]  
 -0.74  
 -0.92 – -0.56  
 -8.01  
 <0.001  
 TokenTest c  
 -1.12  
 -1.55 – -0.68  
 -5.03  
 <0.001  
 PosOr cont  $\times$  session [2]  
 -0.05  
 -0.17 – 0.07  
 -0.77  
 0.441  
 PosOr cont  $\times$  session [3]  
 -0.05  
 -0.18 – 0.08  
 -0.75  
 0.451  
 PosOr cont  $\times$  TokenTest c  
 -0.05  
 -0.12 – 0.02  
 -1.45



0.146  
 session [2] × TokenTest c  
 -0.15  
 -0.30 – -0.01  
 -2.07  
 0.038  
 session [3] × TokenTest c  
 -0.12  
 -0.26 – 0.03  
 -1.55  
 0.120  
 (PosOr cont × session[2]) × TokenTest c  
 -0.03  
 -0.13 – 0.07  
 -0.59  
 0.558  
 (PosOr cont × session[3]) × TokenTest c  
 -0.04  
 -0.14 – 0.07  
 -0.71  
 0.478  
 N subject  
 20  
 N category  
 24  
 Observations  
 7178

```
# Odds Ratio:
x <- data.frame(summary(m1_glmm_PWA_all)$coefficients)
x$Odds_Ratio <- plogis(x$Estimate)
x %>% dplyr::select(Estimate, Odds_Ratio) %>%
  mutate(Estimate=round(Estimate,2),
         Odds_Ratio=round(Odds_Ratio,2))
```

##	Estimate	Odds_Ratio
## (Intercept)	-1.87	0.13
## PosOr.cont	0.09	0.52
## session2	-0.44	0.39
## session3	-0.74	0.32
## TokenTest_c	-0.08	0.48

```
## AAT_c -1.13 0.24
## AAT_spontansprache_c -0.07 0.48
## LHoverall_c 0.00 0.50
## Pos0r.cont:session2 -0.05 0.49
## Pos0r.cont:session3 -0.04 0.49
## Pos0r.cont:TokenTest_c -0.08 0.48
## Pos0r.cont:AAT_c -0.06 0.48
## Pos0r.cont:AAT_spontansprache_c 0.09 0.52
## Pos0r.cont:LHoverall_c -0.05 0.49
## session2:TokenTest_c -0.03 0.49
## session3:TokenTest_c -0.20 0.45
## session2:AAT_c -0.04 0.49
## session3:AAT_c 0.05 0.51
## session2:AAT_spontansprache_c -0.02 0.50
## session3:AAT_spontansprache_c 0.23 0.56
## session2:LHoverall_c 0.13 0.53
## session3:LHoverall_c 0.18 0.54
## Pos0r.cont:session2:TokenTest_c -0.09 0.48
## Pos0r.cont:session3:TokenTest_c -0.22 0.45
## Pos0r.cont:session2:AAT_c 0.15 0.54
## Pos0r.cont:session3:AAT_c 0.29 0.57
## Pos0r.cont:session2:AAT_spontansprache_c -0.02 0.49
## Pos0r.cont:session3:AAT_spontansprache_c -0.07 0.48
## Pos0r.cont:session2:LHoverall_c 0.11 0.53
## Pos0r.cont:session3:LHoverall_c 0.04 0.51
```

Plot errors and Tests

```
(means_final<- df_errors_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "error_class", idvar = "category",
    withinvars = c("session", "Pos0r"),
    betweenvars = c("subject", "AAT", "TokenTest",
      "AAT_spontansprache"),
    na.rm = T))
```

## Automatically converting the following non-factors to factors: AAT, TokenTest, AAT\_spontansprache

```
## subject AAT TokenTest AAT_spontansprache session Pos0r N error_class
## 1 101 98 97 3 1 1 23 0.275139242
## 2 101 98 97 3 1 2 23 0.275139242
## 3 101 98 97 3 1 3 24 0.230953597
## 4 101 98 97 3 1 4 23 0.188182721
## 5 101 98 97 3 1 5 23 0.194393901
## 6 101 98 97 3 2 1 23 0.275139242
## 7 101 98 97 3 2 2 24 0.189286931
## 8 101 98 97 3 2 3 24 0.189286931
## 9 101 98 97 3 2 4 24 0.189286931
## 10 101 98 97 3 2 5 24 0.230953597
## 11 101 98 97 3 3 1 24 0.230953597
## 12 101 98 97 3 3 2 24 0.189286931
## 13 101 98 97 3 3 3 24 0.189286931
## 14 101 98 97 3 3 4 24 0.189286931
```

## 15	101	98	97	3	3	5 24	0.189286931
## 16	102	99	99	4	1	1 24	0.231350423
## 17	102	99	99	4	1	2 24	0.231350423
## 18	102	99	99	4	1	3 24	0.189683756
## 19	102	99	99	4	1	4 24	0.189683756
## 20	102	99	99	4	1	5 24	0.189683756
## 21	102	99	99	4	2	1 24	0.231350423
## 22	102	99	99	4	2	2 24	0.231350423
## 23	102	99	99	4	2	3 24	0.231350423
## 24	102	99	99	4	2	4 24	0.189683756
## 25	102	99	99	4	2	5 24	0.189683756
## 26	102	99	99	4	3	1 24	0.273017089
## 27	102	99	99	4	3	2 24	0.189683756
## 28	102	99	99	4	3	3 24	0.189683756
## 29	102	99	99	4	3	4 24	0.231350423
## 30	102	99	99	4	3	5 24	0.231350423
## 31	103	97	95	4	1	1 24	0.028572645
## 32	103	97	95	4	1	2 24	0.236905978
## 33	103	97	95	4	1	3 24	0.320239311
## 34	103	97	95	4	1	4 24	0.361905978
## 35	103	97	95	4	1	5 24	0.320239311
## 36	103	97	95	4	2	1 24	0.195239311
## 37	103	97	95	4	2	2 24	0.070239311
## 38	103	97	95	4	2	3 24	0.236905978
## 39	103	97	95	4	2	4 24	0.195239311
## 40	103	97	95	4	2	5 24	0.195239311
## 41	103	97	95	4	3	1 24	0.153572645
## 42	103	97	95	4	3	2 24	0.320239311
## 43	103	97	95	4	3	3 24	0.195239311
## 44	103	97	95	4	3	4 24	0.153572645
## 45	103	97	95	4	3	5 24	0.236905978
## 46	104	42	39	3	1	1 24	0.189683756
## 47	104	42	39	3	1	2 24	0.189683756
## 48	104	42	39	3	1	3 24	0.189683756
## 49	104	42	39	3	1	4 24	0.356350423
## 50	104	42	39	3	1	5 24	0.439683756
## 51	104	42	39	3	2	1 24	0.189683756
## 52	104	42	39	3	2	2 24	0.106350423
## 53	104	42	39	3	2	3 24	0.273017089
## 54	104	42	39	3	2	4 24	0.189683756
## 55	104	42	39	3	2	5 24	0.314683756
## 56	104	42	39	3	3	1 24	0.231350423
## 57	104	42	39	3	3	2 24	0.064683756
## 58	104	42	39	3	3	3 24	0.064683756
## 59	104	42	39	3	3	4 24	0.189683756
## 60	104	42	39	3	3	5 24	0.231350423
## 61	105	91	79	4	1	1 24	0.175794867
## 62	105	91	79	4	1	2 24	0.217461534
## 63	105	91	79	4	1	3 24	0.259128200
## 64	105	91	79	4	1	4 24	0.175794867
## 65	105	91	79	4	1	5 24	0.425794867
## 66	105	91	79	4	2	1 24	0.217461534
## 67	105	91	79	4	2	2 24	0.217461534
## 68	105	91	79	4	2	3 24	0.134128200

## 69	105	91	79	4	2	4 24	0.217461534
## 70	105	91	79	4	2	5 24	0.259128200
## 71	105	91	79	4	3	1 24	0.134128200
## 72	105	91	79	4	3	2 24	0.175794867
## 73	105	91	79	4	3	3 24	0.175794867
## 74	105	91	79	4	3	4 24	0.259128200
## 75	105	91	79	4	3	5 24	0.175794867
## 76	106	94	86	3	1	1 24	0.267461534
## 77	106	94	86	3	1	2 24	0.309128200
## 78	106	94	86	3	1	3 24	0.350794867
## 79	106	94	86	3	1	4 24	0.309128200
## 80	106	94	86	3	1	5 24	0.350794867
## 81	106	94	86	3	2	1 24	0.267461534
## 82	106	94	86	3	2	2 24	0.142461534
## 83	106	94	86	3	2	3 24	0.184128200
## 84	106	94	86	3	2	4 24	0.184128200
## 85	106	94	86	3	2	5 24	0.309128200
## 86	106	94	86	3	3	1 24	0.017461534
## 87	106	94	86	3	3	2 24	0.184128200
## 88	106	94	86	3	3	3 24	0.017461534
## 89	106	94	86	3	3	4 24	0.142461534
## 90	106	94	86	3	3	5 24	0.184128200
## 91	107	93	97	4	1	1 24	0.236905978
## 92	107	93	97	4	1	2 24	0.195239311
## 93	107	93	97	4	1	3 24	0.278572645
## 94	107	93	97	4	1	4 24	0.195239311
## 95	107	93	97	4	1	5 24	0.361905978
## 96	107	93	97	4	2	1 24	0.195239311
## 97	107	93	97	4	2	2 24	0.195239311
## 98	107	93	97	4	2	3 24	0.153572645
## 99	107	93	97	4	2	4 24	0.195239311
## 100	107	93	97	4	2	5 24	0.236905978
## 101	107	93	97	4	3	1 24	0.153572645
## 102	107	93	97	4	3	2 24	0.153572645
## 103	107	93	97	4	3	3 24	0.195239311
## 104	107	93	97	4	3	4 24	0.195239311
## 105	107	93	97	4	3	5 24	0.278572645
## 106	108	99	93	4	1	1 24	0.181152010
## 107	108	99	93	4	1	2 24	0.222818677
## 108	108	99	93	4	1	3 24	0.222818677
## 109	108	99	93	4	1	4 24	0.306152010
## 110	108	99	93	4	1	5 24	0.347818677
## 111	108	99	93	4	2	1 24	0.181152010
## 112	108	99	93	4	2	2 24	0.181152010
## 113	108	99	93	4	2	3 24	0.181152010
## 114	108	99	93	4	2	4 24	0.181152010
## 115	108	99	93	4	2	5 23	0.226277959
## 116	108	99	93	4	3	1 24	0.139485343
## 117	108	99	93	4	3	2 24	0.222818677
## 118	108	99	93	4	3	3 24	0.222818677
## 119	108	99	93	4	3	4 24	0.139485343
## 120	108	99	93	4	3	5 24	0.264485343
## 121	109	52	58	3	1	1 23	0.241598870
## 122	109	52	58	3	1	2 24	0.207739311

## 123	109	52	58	3	1	3 24	0.291072645
## 124	109	52	58	3	1	4 23	0.157747938
## 125	109	52	58	3	1	5 24	0.332739311
## 126	109	52	58	3	2	1 24	0.332739311
## 127	109	52	58	3	2	2 24	0.249405978
## 128	109	52	58	3	2	3 24	0.249405978
## 129	109	52	58	3	2	4 24	0.249405978
## 130	109	52	58	3	2	5 24	0.249405978
## 131	109	52	58	3	3	1 24	0.166072645
## 132	109	52	58	3	3	2 24	0.207739311
## 133	109	52	58	3	3	3 23	0.095636137
## 134	109	52	58	3	3	4 24	0.166072645
## 135	109	52	58	3	3	5 23	0.008679615
## 136	110	100	97	4	1	1 24	0.214683756
## 137	110	100	97	4	1	2 24	0.298017089
## 138	110	100	97	4	1	3 24	0.256350423
## 139	110	100	97	4	1	4 24	0.423017089
## 140	110	100	97	4	1	5 24	0.298017089
## 141	110	100	97	4	2	1 24	0.173017089
## 142	110	100	97	4	2	2 24	0.173017089
## 143	110	100	97	4	2	3 24	0.173017089
## 144	110	100	97	4	2	4 24	0.173017089
## 145	110	100	97	4	2	5 24	0.214683756
## 146	110	100	97	4	3	1 24	0.131350423
## 147	110	100	97	4	3	2 24	0.131350423
## 148	110	100	97	4	3	3 24	0.173017089
## 149	110	100	97	4	3	4 24	0.173017089
## 150	110	100	97	4	3	5 24	0.214683756
## 151	111	96	99	4	1	1 24	0.209128200
## 152	111	96	99	4	1	2 24	0.250794867
## 153	111	96	99	4	1	3 24	0.334128200
## 154	111	96	99	4	1	4 24	0.167461534
## 155	111	96	99	4	1	5 24	0.292461534
## 156	111	96	99	4	2	1 24	0.167461534
## 157	111	96	99	4	2	2 24	0.292461534
## 158	111	96	99	4	2	3 24	0.292461534
## 159	111	96	99	4	2	4 24	0.084128200
## 160	111	96	99	4	2	5 24	0.125794867
## 161	111	96	99	4	3	1 24	0.209128200
## 162	111	96	99	4	3	2 24	0.250794867
## 163	111	96	99	4	3	3 24	0.292461534
## 164	111	96	99	4	3	4 24	0.125794867
## 165	111	96	99	4	3	5 24	0.125794867
## 166	112	28	15	3	1	1 24	0.073474965
## 167	112	28	15	3	1	2 23	0.234559532
## 168	112	28	15	3	1	3 23	0.349944148
## 169	112	28	15	3	1	4 23	0.238142905
## 170	112	28	15	3	1	5 20	0.323255184
## 171	112	28	15	3	2	1 24	0.115141631
## 172	112	28	15	3	2	2 24	0.115141631
## 173	112	28	15	3	2	3 24	0.240141631
## 174	112	28	15	3	2	4 24	0.365141631
## 175	112	28	15	3	2	5 24	0.365141631
## 176	112	28	15	3	3	1 24	-0.051525035

## 177	112 28	15	3	3	2 24	0.156808298
## 178	112 28	15	3	3	3 24	0.240141631
## 179	112 28	15	3	3	4 24	0.281808298
## 180	112 28	15	3	3	5 24	0.198474965
## 181	113 100	99	4	1	1 24	0.214683756
## 182	113 100	99	4	1	2 24	0.298017089
## 183	113 100	99	4	1	3 24	0.214683756
## 184	113 100	99	4	1	4 24	0.131350423
## 185	113 100	99	4	1	5 24	0.214683756
## 186	113 100	99	4	2	1 24	0.214683756
## 187	113 100	99	4	2	2 24	0.131350423
## 188	113 100	99	4	2	3 24	0.214683756
## 189	113 100	99	4	2	4 24	0.298017089
## 190	113 100	99	4	2	5 24	0.256350423
## 191	113 100	99	4	3	1 24	0.256350423
## 192	113 100	99	4	3	2 24	0.214683756
## 193	113 100	99	4	3	3 24	0.173017089
## 194	113 100	99	4	3	4 24	0.089683756
## 195	113 100	99	4	3	5 24	0.298017089
## 196	114 97	86	3	1	1 24	0.144048835
## 197	114 97	86	3	1	2 24	0.394048835
## 198	114 97	86	3	1	3 24	0.394048835
## 199	114 97	86	3	1	4 24	0.310715502
## 200	114 97	86	3	1	5 24	0.227382169
## 201	114 97	86	3	2	1 24	0.185715502
## 202	114 97	86	3	2	2 24	0.310715502
## 203	114 97	86	3	2	3 24	0.227382169
## 204	114 97	86	3	2	4 24	0.185715502
## 205	114 97	86	3	2	5 24	0.269048835
## 206	114 97	86	3	3	1 23	0.097499491
## 207	114 97	86	3	3	2 24	0.102382169
## 208	114 97	86	3	3	3 24	0.144048835
## 209	114 97	86	3	3	4 24	0.102382169
## 210	114 97	86	3	3	5 22	0.111653453
## 211	115 100	83	4	1	1 24	0.284128200
## 212	115 100	83	4	1	2 24	0.200794867
## 213	115 100	83	4	1	3 24	0.159128200
## 214	115 100	83	4	1	4 24	0.159128200
## 215	115 100	83	4	1	5 24	0.367461534
## 216	115 100	83	4	2	1 24	0.200794867
## 217	115 100	83	4	2	2 24	0.242461534
## 218	115 100	83	4	2	3 24	0.159128200
## 219	115 100	83	4	2	4 24	0.242461534
## 220	115 100	83	4	2	5 24	0.200794867
## 221	115 100	83	4	3	1 24	0.242461534
## 222	115 100	83	4	3	2 24	0.200794867
## 223	115 100	83	4	3	3 24	0.159128200
## 224	115 100	83	4	3	4 24	0.159128200
## 225	115 100	83	4	3	5 24	0.242461534
## 226	116 100	83	3	1	1 24	0.228572645
## 227	116 100	83	3	1	2 24	0.270239311
## 228	116 100	83	3	1	3 24	0.270239311
## 229	116 100	83	3	1	4 24	0.270239311
## 230	116 100	83	3	1	5 24	0.186905978

## 231	116 100	83	3	2	1 24	0.186905978
## 232	116 100	83	3	2	2 24	0.186905978
## 233	116 100	83	3	2	3 24	0.186905978
## 234	116 100	83	3	2	4 24	0.228572645
## 235	116 100	83	3	2	5 24	0.186905978
## 236	116 100	83	3	3	1 24	0.186905978
## 237	116 100	83	3	3	2 24	0.186905978
## 238	116 100	83	3	3	3 24	0.228572645
## 239	116 100	83	3	3	4 24	0.228572645
## 240	116 100	83	3	3	5 24	0.186905978
## 241	117 100	99	4	1	1 24	0.289683756
## 242	117 100	99	4	1	2 24	0.414683756
## 243	117 100	99	4	1	3 24	0.248017089
## 244	117 100	99	4	1	4 24	0.248017089
## 245	117 100	99	4	1	5 24	0.206350423
## 246	117 100	99	4	2	1 24	0.206350423
## 247	117 100	99	4	2	2 24	0.164683756
## 248	117 100	99	4	2	3 24	0.164683756
## 249	117 100	99	4	2	4 24	0.206350423
## 250	117 100	99	4	2	5 24	0.248017089
## 251	117 100	99	4	3	1 24	0.164683756
## 252	117 100	99	4	3	2 24	0.206350423
## 253	117 100	99	4	3	3 24	0.123017089
## 254	117 100	99	4	3	4 24	0.206350423
## 255	117 100	99	4	3	5 24	0.123017089
## 256	118 100	99	4	1	1 24	0.250794867
## 257	118 100	99	4	1	2 24	0.209128200
## 258	118 100	99	4	1	3 24	0.250794867
## 259	118 100	99	4	1	4 24	0.250794867
## 260	118 100	99	4	1	5 24	0.375794867
## 261	118 100	99	4	2	1 24	0.250794867
## 262	118 100	99	4	2	2 24	0.125794867
## 263	118 100	99	4	2	3 24	0.167461534
## 264	118 100	99	4	2	4 24	0.250794867
## 265	118 100	99	4	2	5 24	0.167461534
## 266	118 100	99	4	3	1 24	0.167461534
## 267	118 100	99	4	3	2 24	0.125794867
## 268	118 100	99	4	3	3 24	0.167461534
## 269	118 100	99	4	3	4 24	0.167461534
## 270	118 100	99	4	3	5 24	0.292461534
## 271	119 83	74	4	1	1 24	0.180358359
## 272	119 83	74	4	1	2 23	0.237872162
## 273	119 83	74	4	1	3 24	0.305358359
## 274	119 83	74	4	1	4 24	0.263691692
## 275	119 83	74	4	1	5 24	0.263691692
## 276	119 83	74	4	2	1 24	0.138691692
## 277	119 83	74	4	2	2 24	0.138691692
## 278	119 83	74	4	2	3 24	0.305358359
## 279	119 83	74	4	2	4 24	0.180358359
## 280	119 83	74	4	2	5 24	0.388691692
## 281	119 83	74	4	3	1 24	0.180358359
## 282	119 83	74	4	3	2 24	0.138691692
## 283	119 83	74	4	3	3 24	0.180358359
## 284	119 83	74	4	3	4 24	0.180358359

## 285	119	83	74	4	3	5 24	0.138691692
## 286	120	75	21	3	1	1 24	0.317064708
## 287	120	75	21	3	1	2 24	0.275398042
## 288	120	75	21	3	1	3 24	0.317064708
## 289	120	75	21	3	1	4 24	0.067064708
## 290	120	75	21	3	1	5 24	0.317064708
## 291	120	75	21	3	2	1 24	0.192064708
## 292	120	75	21	3	2	2 24	0.150398042
## 293	120	75	21	3	2	3 24	0.400398042
## 294	120	75	21	3	2	4 24	0.067064708
## 295	120	75	21	3	2	5 24	0.233731375
## 296	120	75	21	3	3	1 24	0.025398042
## 297	120	75	21	3	3	2 24	0.192064708
## 298	120	75	21	3	3	3 23	0.023379408
## 299	120	75	21	3	3	4 24	0.358731375
## 300	120	75	21	3	3	5 24	0.275398042
##	sd	se	ci				
## 1	0.26416256	0.055081702	0.11423246				
## 2	0.27785430	0.057936626	0.12015321				
## 3	0.19259716	0.039313732	0.08132665				
## 4	0.05087420	0.010608003	0.02199965				
## 5	0.04381574	0.009136214	0.01894735				
## 6	0.27617995	0.057587501	0.11942917				
## 7	0.05007002	0.010220500	0.02114272				
## 8	0.05007002	0.010220500	0.02114272				
## 9	0.05007002	0.010220500	0.02114272				
## 10	0.19259716	0.039313732	0.08132665				
## 11	0.20809817	0.042477861	0.08787215				
## 12	0.05007002	0.010220500	0.02114272				
## 13	0.05007002	0.010220500	0.02114272				
## 14	0.05007002	0.010220500	0.02114272				
## 15	0.05007002	0.010220500	0.02114272				
## 16	0.21171683	0.043216517	0.08940018				
## 17	0.19650149	0.040110699	0.08297530				
## 18	0.06374282	0.013011448	0.02691623				
## 19	0.06374282	0.013011448	0.02691623				
## 20	0.06374282	0.013011448	0.02691623				
## 21	0.21171683	0.043216517	0.08940018				
## 22	0.21171683	0.043216517	0.08940018				
## 23	0.16183472	0.033034374	0.06833681				
## 24	0.06374282	0.013011448	0.02691623				
## 25	0.06374282	0.013011448	0.02691623				
## 26	0.23844953	0.048673306	0.10068841				
## 27	0.06374282	0.013011448	0.02691623				
## 28	0.06374282	0.013011448	0.02691623				
## 29	0.16183472	0.033034374	0.06833681				
## 30	0.16183472	0.033034374	0.06833681				
## 31	0.33435403	0.068249730	0.14118532				
## 32	0.44333886	0.090496166	0.18720558				
## 33	0.45770001	0.093427624	0.19326977				
## 34	0.50667559	0.103424721	0.21395034				
## 35	0.50295881	0.102666037	0.21238088				
## 36	0.43285329	0.088355809	0.18277792				
## 37	0.38591488	0.078774546	0.16295756				



```

## 38 0.43627762 0.089054797 0.18422388
## 39 0.43996949 0.089808396 0.18578282
## 40 0.49321658 0.100677413 0.20826710
## 41 0.43923360 0.089658183 0.18547208
## 42 0.48408060 0.098812538 0.20440931
## 43 0.49321658 0.100677413 0.20826710
## 44 0.45995619 0.093888164 0.19422247
## 45 0.42910020 0.087589712 0.18119312
## 46 0.44619973 0.091080139 0.18841362
## 47 0.49251646 0.100534501 0.20797146
## 48 0.43205537 0.088192933 0.18244098
## 49 0.50188568 0.102446985 0.21192774
## 50 0.43918450 0.089648160 0.18545135
## 51 0.38652912 0.078899927 0.16321693
## 52 0.49878216 0.101813482 0.21061723
## 53 0.42844632 0.087456240 0.18091702
## 54 0.47322185 0.096596007 0.19982406
## 55 0.47198975 0.096344505 0.19930379
## 56 0.49605066 0.101255916 0.20946382
## 57 0.45694548 0.093273606 0.19295115
## 58 0.42159610 0.086057943 0.17802442
## 59 0.41743201 0.085207952 0.17626608
## 60 0.47034193 0.096008145 0.19860798
## 61 0.15751258 0.032152121 0.06651173
## 62 0.28158025 0.057477329 0.11890091
## 63 0.30432811 0.062120715 0.12850649
## 64 0.20843165 0.042545933 0.08801297
## 65 0.44752213 0.091350071 0.18897202
## 66 0.28158025 0.057477329 0.11890091
## 67 0.30283626 0.061816193 0.12787654
## 68 0.09964568 0.020340089 0.04207668
## 69 0.28158025 0.057477329 0.11890091
## 70 0.28318410 0.057804713 0.11957816
## 71 0.09964568 0.020340089 0.04207668
## 72 0.15751258 0.032152121 0.06651173
## 73 0.22283387 0.045485774 0.09409449
## 74 0.30432811 0.062120715 0.12850649
## 75 0.23636014 0.048246811 0.09980613
## 76 0.49300665 0.100634561 0.20817845
## 77 0.46309637 0.094529151 0.19554845
## 78 0.45477871 0.092831315 0.19203621
## 79 0.44948402 0.091750542 0.18980046
## 80 0.54201494 0.110638336 0.22887284
## 81 0.47373201 0.096700141 0.20003948
## 82 0.42583090 0.086922368 0.17981262
## 83 0.44208201 0.090239613 0.18667486
## 84 0.38981822 0.079571312 0.16460580
## 85 0.47631986 0.097228384 0.20113224
## 86 0.36655137 0.074821984 0.15478107
## 87 0.43500038 0.088794080 0.18368455
## 88 0.31159721 0.063604515 0.13157596
## 89 0.44017532 0.089850411 0.18586974
## 90 0.35652984 0.072776349 0.15054935
## 91 0.26032840 0.053139312 0.10992704

```

## 92 0.22885001 0.046713812 0.09663488  
## 93 0.28158025 0.057477329 0.11890091  
## 94 0.22885001 0.046713812 0.09663488  
## 95 0.38285144 0.078149223 0.16166398  
## 96 0.18368121 0.037493769 0.07756177  
## 97 0.22885001 0.046713812 0.09663488  
## 98 0.09081336 0.018537200 0.03834712  
## 99 0.22885001 0.046713812 0.09663488  
## 100 0.22166943 0.045248083 0.09360279  
## 101 0.09081336 0.018537200 0.03834712  
## 102 0.09081336 0.018537200 0.03834712  
## 103 0.16591445 0.033867146 0.07005953  
## 104 0.22885001 0.046713812 0.09663488  
## 105 0.31292328 0.063875197 0.13213591  
## 106 0.22845068 0.046632300 0.09646626  
## 107 0.27406555 0.055943396 0.11572773  
## 108 0.27406555 0.055943396 0.11572773  
## 109 0.37406234 0.076355155 0.15795267  
## 110 0.39730809 0.081100174 0.16776849  
## 111 0.19941754 0.040705934 0.08420664  
## 112 0.21442606 0.043769536 0.09054418  
## 113 0.18318344 0.037392164 0.07735158  
## 114 0.21442606 0.043769536 0.09054418  
## 115 0.27965050 0.058311161 0.12092995  
## 116 0.08217039 0.016772961 0.03469751  
## 117 0.29586194 0.060392565 0.12493154  
## 118 0.26248952 0.053580448 0.11083960  
## 119 0.08217039 0.016772961 0.03469751  
## 120 0.31680172 0.064666881 0.13377363  
## 121 0.34298663 0.071517656 0.14831854  
## 122 0.44883802 0.091618677 0.18952767  
## 123 0.33469683 0.068319705 0.14133008  
## 124 0.43300244 0.090287251 0.18724430  
## 125 0.27550136 0.056236480 0.11633402  
## 126 0.36304493 0.074106236 0.15330043  
## 127 0.39358441 0.080340082 0.16619612  
## 128 0.39358441 0.080340082 0.16619612  
## 129 0.37923251 0.077410512 0.16013584  
## 130 0.37570648 0.076690765 0.15864693  
## 131 0.42244457 0.086231137 0.17838270  
## 132 0.43222093 0.088226727 0.18251089  
## 133 0.45822238 0.095545972 0.19815022  
## 134 0.40199564 0.082057017 0.16974787  
## 135 0.44054150 0.091859252 0.19050443  
## 136 0.28921254 0.059035262 0.12212374  
## 137 0.36301589 0.074100309 0.15328817  
## 138 0.34038859 0.069481529 0.14373349  
## 139 0.41817532 0.085359680 0.17657995  
## 140 0.37974057 0.077514219 0.16035038  
## 141 0.20329837 0.041498106 0.08584537  
## 142 0.21803992 0.044507213 0.09207018  
## 143 0.18740077 0.038253021 0.07913240  
## 144 0.21803992 0.044507213 0.09207018  
## 145 0.25497128 0.052045794 0.10766493

## 146 0.08693064 0.017744642 0.03670759  
## 147 0.08693064 0.017744642 0.03670759  
## 148 0.21803992 0.044507213 0.09207018  
## 149 0.20329837 0.041498106 0.08584537  
## 150 0.28921254 0.059035262 0.12212374  
## 151 0.30720585 0.062708131 0.12972165  
## 152 0.36513656 0.074533188 0.15418365  
## 153 0.39509370 0.080648164 0.16683344  
## 154 0.28740228 0.058665744 0.12135934  
## 155 0.37887633 0.077337807 0.15998544  
## 156 0.22703341 0.046343000 0.09586780  
## 157 0.37058885 0.075646132 0.15648595  
## 158 0.36211174 0.073915750 0.15290638  
## 159 0.12785727 0.026098756 0.05398939  
## 160 0.24643770 0.050303884 0.10406151  
## 161 0.37955879 0.077477113 0.16027362  
## 162 0.38176834 0.077928136 0.16120663  
## 163 0.37058885 0.075646132 0.15648595  
## 164 0.25873291 0.052813634 0.10925333  
## 165 0.24643770 0.050303884 0.10406151  
## 166 0.45775172 0.093438178 0.19329160  
## 167 0.38670665 0.080633911 0.16722450  
## 168 0.30412939 0.063415362 0.13151541  
## 169 0.43961919 0.091666939 0.19010560  
## 170 0.27114954 0.060630879 0.12690189  
## 171 0.42747381 0.087257726 0.18050636  
## 172 0.44025589 0.089866858 0.18590376  
## 173 0.35696806 0.072865801 0.15073439  
## 174 0.35421482 0.072303798 0.14957180  
## 175 0.32138039 0.065601498 0.13570704  
## 176 0.45773774 0.093435325 0.19328570  
## 177 0.39820525 0.081283306 0.16814733  
## 178 0.36556447 0.074620534 0.15436434  
## 179 0.38522945 0.078634632 0.16266813  
## 180 0.39528600 0.080687417 0.16691464  
## 181 0.28342770 0.057854438 0.11968102  
## 182 0.38353807 0.078289380 0.16195392  
## 183 0.31458672 0.064214745 0.13283832  
## 184 0.21845495 0.044591931 0.09224544  
## 185 0.29418097 0.060049439 0.12422173  
## 186 0.28342770 0.057854438 0.11968102  
## 187 0.24524463 0.050060350 0.10355772  
## 188 0.29418097 0.060049439 0.12422173  
## 189 0.35842420 0.073163034 0.15134927  
## 190 0.40279176 0.082219523 0.17008404  
## 191 0.37067031 0.075662761 0.15652035  
## 192 0.28342770 0.057854438 0.11968102  
## 193 0.28547480 0.058272299 0.12054543  
## 194 0.14996549 0.030611577 0.06332487  
## 195 0.36698650 0.074910805 0.15496481  
## 196 0.37209081 0.075952719 0.15712017  
## 197 0.47407026 0.096769186 0.20018231  
## 198 0.45933570 0.093761506 0.19396045  
## 199 0.42826240 0.087418697 0.18083935

## 200 0.41662251 0.085042714 0.17592426  
## 201 0.35529221 0.072523718 0.15002674  
## 202 0.44949107 0.091751981 0.18980343  
## 203 0.44693400 0.091230021 0.18872368  
## 204 0.34835663 0.071107999 0.14709810  
## 205 0.42398940 0.086546474 0.17903502  
## 206 0.28284247 0.058976733 0.12231026  
## 207 0.30946437 0.063169149 0.13067534  
## 208 0.31809510 0.064930890 0.13431978  
## 209 0.30946437 0.063169149 0.13067534  
## 210 0.27662304 0.058976230 0.12264778  
## 211 0.32778772 0.066909388 0.13841262  
## 212 0.17853692 0.036443696 0.07538953  
## 213 0.08307413 0.016957436 0.03507913  
## 214 0.08307413 0.016957436 0.03507913  
## 215 0.37767907 0.077093417 0.15947988  
## 216 0.21047041 0.042962092 0.08887386  
## 217 0.24326682 0.049656631 0.10272257  
## 218 0.08307413 0.016957436 0.03507913  
## 219 0.26758383 0.054620320 0.11299074  
## 220 0.22474201 0.045875271 0.09490023  
## 221 0.26758383 0.054620320 0.11299074  
## 222 0.19515791 0.039836442 0.08240796  
## 223 0.08307413 0.016957436 0.03507913  
## 224 0.08307413 0.016957436 0.03507913  
## 225 0.26758383 0.054620320 0.11299074  
## 226 0.19302449 0.039400959 0.08150709  
## 227 0.27275655 0.055676198 0.11517499  
## 228 0.27275655 0.055676198 0.11517499  
## 229 0.27275655 0.055676198 0.11517499  
## 230 0.04949713 0.010103559 0.02090080  
## 231 0.04949713 0.010103559 0.02090080  
## 232 0.04949713 0.010103559 0.02090080  
## 233 0.04949713 0.010103559 0.02090080  
## 234 0.20849373 0.042558604 0.08803918  
## 235 0.04949713 0.010103559 0.02090080  
## 236 0.04949713 0.010103559 0.02090080  
## 237 0.04949713 0.010103559 0.02090080  
## 238 0.19302449 0.039400959 0.08150709  
## 239 0.19302449 0.039400959 0.08150709  
## 240 0.04949713 0.010103559 0.02090080  
## 241 0.39316758 0.080254996 0.16602011  
## 242 0.44021452 0.089858412 0.18588629  
## 243 0.33621939 0.068630496 0.14197300  
## 244 0.31720832 0.064749877 0.13394533  
## 245 0.29369672 0.059950592 0.12401725  
## 246 0.26004658 0.053081786 0.10980804  
## 247 0.20776839 0.042410544 0.08773289  
## 248 0.19224079 0.039240987 0.08117617  
## 249 0.26004658 0.053081786 0.10980804  
## 250 0.33621939 0.068630496 0.14197300  
## 251 0.20776839 0.042410544 0.08773289  
## 252 0.27172671 0.055465982 0.11474013  
## 253 0.09283325 0.018949508 0.03920004

```
## 254 0.27172671 0.055465982 0.11474013
## 255 0.09283325 0.018949508 0.03920004
## 256 0.33124345 0.067614786 0.13987184
## 257 0.27746014 0.056636313 0.11716114
## 258 0.33124345 0.067614786 0.13987184
## 259 0.33124345 0.067614786 0.13987184
## 260 0.43687042 0.089175801 0.18447420
## 261 0.31192926 0.063672293 0.13171617
## 262 0.07793044 0.015907485 0.03290714
## 263 0.20090805 0.041010184 0.08483603
## 264 0.34048994 0.069502219 0.14377629
## 265 0.20090805 0.041010184 0.08483603
## 266 0.20090805 0.041010184 0.08483603
## 267 0.07793044 0.015907485 0.03290714
## 268 0.22975292 0.046898118 0.09701615
## 269 0.22975292 0.046898118 0.09701615
## 270 0.38051217 0.077671721 0.16067620
## 271 0.34272581 0.069958612 0.14472042
## 272 0.39125102 0.081581476 0.16918963
## 273 0.45371729 0.092614654 0.19158801
## 274 0.43660875 0.089122388 0.18436371
## 275 0.39667748 0.080971451 0.16750221
## 276 0.30096982 0.061435208 0.12708841
## 277 0.30096982 0.061435208 0.12708841
## 278 0.41543375 0.084800059 0.17542229
## 279 0.31082014 0.063445895 0.13124783
## 280 0.45147088 0.092156108 0.19063943
## 281 0.31436831 0.064170164 0.13274610
## 282 0.29046799 0.059291531 0.12265388
## 283 0.33019921 0.067401632 0.13943090
## 284 0.33354130 0.068083832 0.14084214
## 285 0.27957195 0.057067385 0.11805288
## 286 0.41026926 0.083745863 0.17324152
## 287 0.43038964 0.087852918 0.18173761
## 288 0.40262847 0.082186193 0.17001509
## 289 0.49884304 0.101825910 0.21064294
## 290 0.52251662 0.106658259 0.22063942
## 291 0.38119054 0.077810193 0.16096265
## 292 0.46021639 0.093941278 0.19433234
## 293 0.50940369 0.103981593 0.21510231
## 294 0.43925364 0.089662274 0.18548055
## 295 0.45219333 0.092303578 0.19094450
## 296 0.36996861 0.075519525 0.15622404
## 297 0.37295449 0.076129015 0.15748487
## 298 0.44881004 0.093583363 0.19408002
## 299 0.41517373 0.084746983 0.17531249
## 300 0.43754591 0.089313685 0.18475943
```

```
override.linetype<-c("dashed")
(plot_error_repetition_PWA_session1_Naming <-
  means_final %>% filter(session=="1") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
```

```


        fun=mean, geom="line", size = 0.5) +
scale_linetype_manual(values=c("dashed"))+
scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
                             "#fb8479", "#fa6153",
                             "#f93e2d", "#f81b07",
                             "#d21706", "#ac1305",
                             "#860f04", "#5f0b03",
                             "#390602", "#130201"))+

geom_errorbar(
  aes(ymin=error_class-se, ymax=error_class+se, group = AAT),
  width =.1) +
apatheme+
scale_y_continuous(limits = c(0, 0.5),
                   breaks =seq(0,0.5, by = 0.1)) +
labs(x="Ordinal Position ",y ="Errors", colour="Session",
     linetype="Session",
     title = "Day 1") +
theme(
  axis.title.y = element_text(margin = margin(0,10,0,0)),
  axis.title.x = element_text(margin = margin(10,0,0,0)),
  legend.key.width = unit(1, "cm"),
  legend.position="none")+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.




```
(plot_error_repetition_PWA_session2_Naming <- means_final %>%
  filter(session=="2") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
    "#fb8479", "#fa6153",
    "#f93e2d", "#f81b07",
    "#d21706", "#ac1305",
    "#860f04", "#5f0b03",
    "#390602", "#130201"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = AAT), width =.1) +
  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
    breaks =seq(0,0.5, by = 0.1)) +
  labs(x="Ordinal Position ",y ="Errors",
    colour="Session", linetype="Session",
    title = "Day 2") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
```

```
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
```

```
## Adding another scale for linetype, which will replace the existing scale.
```



```
(plot_error_repetition_PWA_session3_Naming <- means_final %>%
  filter(session=="3") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = AAT)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT, color=AAT),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#feedec", "#fdcac6", "#fca7a0",
    "#fb8479", "#fa6153",
    "#f93e2d", "#f81b07",
    "#d21706", "#ac1305",
    "#860f04", "#5f0b03",
    "#390602", "#130201"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = AAT), width = .1) +
  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
```



```

breaks =seq(0,0.5, by = 0.1)) +
labs(x="Ordinal Position ",y ="Errors", colour="Naming\npercentile",
# linetype="Session",
title = "Day 8") +
theme(
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"),
legend.position="right")+
scale_linetype(guide="none"))


```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.

## Warning: Removed 1 rows containing non-finite values ('stat\_summary()').

## Warning: Removed 1 rows containing missing values ('geom\_point()').



```

(plot_error_repetition_PWA_session1_Token <-
means_final %>% filter(session=="1") %>%
ggplot(., aes(x=PosOr, y=error_class, group=subject, color = TokenTest)) +
geom_point(size = 2)+
stat_summary(aes(linetype=TokenTest, color=TokenTest),
fun=mean, geom="line", size = 0.5) +

```


```

scale_linetype_manual(values=c("dashed"))+
scale_colour_manual(values=c("#f2ecfd", "#d7c5f9", "#bd9ef5",
                             "#a378f1", "#8851ee",
                             "#6e2aea", "#5915d4",
                             "#4911ae", "#380e87",
                             "#280a61", "#18063a",
                             "#080213"))+
geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se, group = TokenTest),
              width = .1) +
apatheme+
scale_y_continuous(limits = c(0, 0.5),
                   breaks =seq(0,0.5, by = 0.1)) +
labs(x="Ordinal Position ",y ="Errors", colour="Session",
     linetype="Session",
     title = "Day 1") +
theme(
  axis.title.y = element_text(margin = margin(0,10,0,0)),
  axis.title.x = element_text(margin = margin(10,0,0,0)),
  legend.key.width = unit(1, "cm"),
  legend.position="none")+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.




```
(plot_error_repetition_PWA_session2_Token <- means_final %>%
  filter(session=="2") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = TokenTest)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=TokenTest, color=TokenTest),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#f2ecfd", "#d7c5f9", "#bd9ef5",
    "#a378f1", "#8851ee",
    "#6e2aea", "#5915d4",
    "#4911ae", "#380e87",
    "#280a61", "#18063a",
    "#080213"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = TokenTest), width =.1) +
  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
    breaks =seq(0,0.5, by = 0.1)) +
  labs(x="Ordinal Position ",y ="Errors",
    colour="Session", linetype="Session",
    title = "Day 2") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  )
```

```
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
```

```
## Adding another scale for linetype, which will replace the existing scale.
```



```
(plot_error_repetition_PWA_session3_Token <- means_final %>%
  filter(session=="3") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = TokenTest)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=TokenTest, color=TokenTest),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#f2ecfd", "#d7c5f9", "#bd9ef5",
    "#a378f1", "#8851ee",
    "#6e2aea", "#5915d4",
    "#4911ae", "#380e87",
    "#280a61", "#18063a",
    "#080213"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = TokenTest), width = .1) +
  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
```

```

breaks =seq(0,0.5, by = 0.1)) +
labs(x="Ordinal Position ",y ="Errors", colour="Token test\npercentile",
# linetype="Session",
title = "Day 8") +
theme(
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"),
legend.position="right")+
scale_linetype(guide="none"))


```

```

## Scale for linetype is already present.
## Adding another scale for linetype, which will replace the existing scale.

## Warning: Removed 1 rows containing non-finite values ('stat_summary()').
## Removed 1 rows containing missing values ('geom_point()').

```



```

(plot_error_repetition_PWA_session1_Speech <-
means_final %>% filter(session=="1") %>%
ggplot(., aes(x=PosOr, y=error_class, group=subject,
color = AAT_spontansprache)) +
geom_point(size = 2)+
stat_summary(aes(linetype=AAT_spontansprache,
color=AAT_spontansprache),

```

```


    fun=mean, geom="line", size = 0.5) +
scale_linetype_manual(values=c("dashed"))+
scale_colour_manual(values=c("#76ff76", "#008900"))+
geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = AAT_spontansprache),
    width =.1) +

apatheme+
scale_y_continuous(limits = c(0, 0.5),
    breaks =seq(0,0.5, by = 0.1)) +
labs(x="Ordinal Position ",y ="Errors", colour="Session",
    linetype="Session",
    title = "Day 1") +
theme(
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"),
legend.position="none")+
guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```


(plot_error_repetition_PWA_session2_Speech <- means_final %>%
  filter(session=="2") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = AAT_spontansprache)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT_spontansprache, color=AAT_spontansprache),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#76ff76", "#008900"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = AAT_spontansprache), width =.1) +

  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
    breaks =seq(0,0.5, by = 0.1)) +
  labs(x="Ordinal Position ",y ="Errors",
    colour="Session", linetype="Session",
    title = "Day 2") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none"))

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.




```
(plot_error_repetition_PWA_session3_Speech <- means_final %>%
  filter(session=="3") %>%
  ggplot(., aes(x=PosOr, y=error_class, group=subject, color = AAT_spontansprache)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=AAT_spontansprache, color=AAT_spontansprache),
    fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("dashed"))+
  scale_colour_manual(values=c("#76ff76", "#008900"))+
  geom_errorbar(aes(ymin=error_class-se, ymax=error_class+se,
    group = AAT_spontansprache), width =.1) +
  apatheme+
  scale_y_continuous(limits = c(0, 0.5),
    breaks =seq(0,0.5, by = 0.1)) +
  labs(x="Ordinal Position ",y ="Errors",
    colour="Spontaneous\nspeech\nscore",
    # linetype="Session",
    title = "Day 8") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="right")+
  scale_linetype(guide="none"))
```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```
## Warning: Removed 1 rows containing non-finite values ('stat_summary()').
## Removed 1 rows containing missing values ('geom_point()').
```



```
plots <- cowplot::plot_grid(plot_error_repetition_PWA_session1_Naming,
                             plot_error_repetition_PWA_session2_Naming,
                             plot_error_repetition_PWA_session3_Naming,
                             plot_error_repetition_PWA_session1_Token,
                             plot_error_repetition_PWA_session2_Token,
                             plot_error_repetition_PWA_session3_Token,
                             plot_error_repetition_PWA_session1_Speech,
                             plot_error_repetition_PWA_session2_Speech,
                             plot_error_repetition_PWA_session3_Speech,
                             nrow = 3, ncol=3,
                             rel_widths = c(0.81,0.81,1,0.81,0.81,1,0.81,0.81,1),
                             margin(1,1,1,1),
                             labels = c("A", "", "", "B", "", "", "C", "", ""),
                             label_size = 34,
                             label_fontfamily = "Helvetica", label_y = 1.01,
                             label_x=-0.03)
```

```
## Warning: Removed 1 rows containing non-finite values ('stat_summary()').
## Removed 1 rows containing missing values ('geom_point()').
```

```
## Warning: Removed 1 rows containing non-finite values ('stat_summary()').
```

```
## Warning: Removed 1 rows containing missing values ('geom_point()').
```

```
## Warning: Removed 1 rows containing non-finite values ('stat_summary()').
```

```
## Warning: Removed 1 rows containing missing values ('geom_point()').
```

```
## Warning in as_grob.default(plot): Cannot convert object of class  
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_PWA_Error_Test_scores.pdf"  
ggsave(plots, filename =  
  here::here("results", "figures", filename),  
  width = 25, height = 39, units = "cm",  
  dpi = 300, device = cairo_pdf)  
filename_png <- "CSI_online_aphasia_spoken_plot_PWA_Error_Test_scores.png"  
ggsave(plots, filename =  
  here::here("results", "figures", filename_png),  
  width = 25, height = 39, units = "cm",  
  dpi = 300)  
#embedFonts(file = here::here("results", "figures", filename))  
#  
# # Naming percenile scores: median split of means final  
# median(as.numeric(as.character(means_final$AAT)))  
# means_final %>%  
#   mutate(med_split=case_when(as.numeric(as.character(AAT)) >  
#     median(as.numeric(as.character(means_final$AAT))) ~ "high",  
#     as.numeric(as.character(AAT)) <  
#       median(as.numeric(as.character(means_final$AAT))) ~ "low",  
#     as.numeric(as.character(AAT)) == median(as.numeric(as.character(  
#       means_final$AAT))) ~  
#       "median"),  
#   mean_split=case_when(as.numeric(as.character(AAT)) >  
#     mean(as.numeric(as.character(means_final$AAT))) ~  
#     "high",  
#     as.numeric(as.character(AAT)) < mean(as.numeric(as.character(  
#       means_final$AAT))) ~ "low",  
#     as.numeric(as.character(AAT)) == mean(as.numeric(as.character(  
#       means_final$AAT))) ~ "median")) -> means_final  
#  
# means_final %>% group_by(session, med_split, PosOr) %>%  
#   summarise(mean=mean(error_class), sd = sd(error_class))  
# means_final %>% group_by(session, mean_split, PosOr) %>%  
#   summarise(mean=mean(error_class), sd = sd(error_class))  
#  
#  
# # Token Test percenile scores: median split of means final  
# median(as.numeric(as.character(means_final$TokenTest)))  
# means_final %>% mutate(med_split=case_when(  
#   as.numeric(as.character(TokenTest)) >  
#     median(as.numeric(as.character(means_final$TokenTest))) ~ "high",  
#   as.numeric(as.character(TokenTest)) <  
#     median(as.numeric(as.character(means_final$TokenTest))) ~ "low",  
#   as.numeric(as.character(TokenTest)) ==
```

```

#   median(as.numeric(as.character( means_final$TokenTest))) ~ "median"),
#   mean_split=case_when(
#     as.numeric(as.character(TokenTest)) >
#       mean(as.numeric(as.character(means_final$TokenTest))) ~ "high",
#     as.numeric(as.character(TokenTest)) <
#       mean(as.numeric(as.character( means_final$TokenTest))) ~ "low",
#     as.numeric(as.character(TokenTest)) ==
#       mean(as.numeric(as.character(means_final$TokenTest))) ~ "median")) ->
#   means_final
#
# means_final %>% group_by(session, med_split, PosOr) %>%
#   summarise(mean=mean(error_class), sd = sd(error_class))
# means_final %>% group_by(session, mean_split, PosOr) %>%
#   summarise(mean=mean(error_class),sd = sd(error_class))
#
# # Spontaneous speech scores: median split of means final
# median(as.numeric(as.character(means_final$AAT_spontansprache)))
# means_final %>%
#   mutate(med_split=case_when(
#     as.numeric(as.character(AAT_spontansprache)) >
#       median(as.numeric(as.character(
#         means_final$AAT_spontansprache))) ~ "high",
#     as.numeric(as.character(AAT_spontansprache)) <
#       median(as.numeric(as.character(
#         means_final$AAT_spontansprache))) ~ "low",
#     as.numeric(as.character(AAT_spontansprache)) ==
#       median(as.numeric(as.character(
#         means_final$AAT_spontansprache))) ~ "median"),
#     mean_split=case_when(
#       as.numeric(as.character(AAT_spontansprache)) >
#         mean(as.numeric(as.character(
#           means_final$AAT_spontansprache))) ~ "high"
#       as.numeric(as.character(AAT_spontansprache)) <
#         mean(as.numeric(as.character(
#           means_final$AAT_spontansprache))) ~ "low",
#       as.numeric(as.character(AAT_spontansprache)) ==
#         mean(as.numeric(as.character(
#           means_final$AAT_spontansprache))) ~ "median")) -> means_final
#
# means_final %>% group_by(med_split, PosOr) %>%
#   summarise(mean=mean(error_class), sd = sd(error_class))
# means_final %>% group_by(mean_split, PosOr) %>%
#   summarise(mean=mean(error_class), sd = sd(error_class))
#
# #### Nested models
# #
# # summary(afex::lmer_alt(error_class ~
# #   session/(PosOr.cont*(TokenTest_c+AAT_c+
# #     AAT_spontansprache_c+
# #     LHoverall_c)) +
# #   (PosOr.cont |subject) +
# #   (1|category) ,
# #   data =df_errors_PWA, family = "binomial",

```

```
# # control=glmerControl(optimizer = "bobyqa",
# # optCtrl = list(maxfun = 2e5)))
```

```
# library(sjPlot)
# library(sjmisc)
# library(ggplot2)
# Change labels of sessions and re-compute model
override.linetypea<-c("longdash", "dashed")
override.linetypeb<-c("longdash", "dashed", "dotted")
df_errors_PWA <- df_errors_PWA %>%
  mutate(session_day = case_when(session=="1" ~ "Day 1",
                                session=="2" ~ "Day 2",
                                session=="3" ~ "Day 8")) %>%
  mutate(session_day=factor(session_day, levels=c("Day 1", "Day 2", "Day 8")))
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

Plot mean CSI effect by Session and test

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(df_errors_PWA$session_day)<-my.simple
levels(df_errors_PWA$session_day)
```

```
## [1] "Day 1" "Day 2" "Day 8"
```

```
contrasts(df_errors_PWA$session_day)
```

```
##           2           3
## Day 1 -0.3333333 -0.3333333
## Day 2  0.6666667 -0.3333333
## Day 8 -0.3333333  0.6666667
```

```
m1_glmm_PWA_all <-
  afex::lmer_alt(error_class ~
    PosOr.cont*session_day*
    (TokenTest_c+AAT_c+AAT_spontansprache_c+LHoverall_c) +
    (PosOr.cont |subject) + (1|category),
    df_errors_PWA, family = "binomial",
    control=glmerControl(optimizer = "bobyqa",
                        optCtrl = list(maxfun = 2e5)))
# df_errors_PWA # data frame
# summary(m1_glmm_PWA_all)
```

```

## Plot the significant interaction effects
# PosOr.cont:AAT_spontansprache_c
plot1 <- plot_model(m1_glmm_PWA_all,
  type = "pred",
  #transform=NULL,
  terms = c("PosOr.cont", "AAT_spontansprache_c"),
  mrt.values="all",
  title=c("Model prediction of 2-way interaction:\nOrdinal position X spontaneous speech (SEM :
  linetype=override.linetypea) +
  scale_x_continuous(breaks = c(-1.99860685427696,
    -0.998606854276957,
    0.00139314572304272,
    1.00139314572304,
    2.00139314572304),
    labels= c(1,2,3,4,5)) +
  xlab("Ordinal position") +
  ylab("Percentage of errors") +
  scale_colour_manual(name = "Centered\nSEM score",
    labels=c("-1.23", " 0.81"),
    values=c("#6495ed", "#8b0a50")) +

  scale_fill_manual(name = "Centered\nSEM score",
    labels=c("-1.23", " 0.81"),
    values=c("#6495ed", "#8b0a50")) +

  # guides(color=guide_legend(
  #   override.aes=list(linetype=override.linetypea)))+
theme_bw()+
theme(plot.title=element_text(size=22,hjust = .5),
  # panel.grid.major=element_blank(),
  # panel.grid.minor=element_blank(),
  #panel.border=element_blank(),
  #axis.line=element_line(),
  text=element_text(size=16),
  axis.title.y = element_text(margin = margin(0,10,0,0)),
  axis.title.x = element_text(margin = margin(10,0,0,0)),
  legend.key.width = unit(1, "cm"),
  legend.position="right")

```

## Scale for colour is already present.  
 ## Adding another scale for colour, which will replace the existing scale.

```

ggsave(plot1, filename =
  here::here("results", "figures",
    "CSI_online_aphasia_spoken_plot_error_by_OrdPos_by_SEM.pdf"),
  width = 15,#25
  height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)

# PosOr.cont:session_day3:TokenTest_c
plot2 <- plot_model(m1_glmm_PWA_all,
  type = "pred",
  #transform=NULL,

```

```

    terms = c("PosOr.cont", "TokenTest_c", "session_day"),
    mrt.values="quart",
    title=c("Model prediction of 3-way interaction:\nOrdinal position X token test (TT in AAT) X
scale_x_continuous(breaks = c(-1.99860685427696,
                                -0.998606854276957,
                                0.00139314572304272,
                                1.00139314572304,
                                2.00139314572304),
                    labels= c(1,2,3,4,5)) +
xlab("Ordinal position") +
ylab("Percentage of errors") +
scale_colour_manual(name = "Centered\nTT score",
                    # labels=c("-1.23", " 0.81"),
                    values=c("#ff1493", "#00cdcd",
                             "#2f4f4f")) +
scale_fill_manual(name = "Centered\nTT score",
                  # labels=c("-1.23", " 0.81"),
                  values=c("#ff1493", "#00cdcd",
                           "#2f4f4f")) +
theme_bw()+
theme(plot.title=element_text(size=22,hjust = .5),
      # panel.grid.major=element_blank(),
      # panel.grid.minor=element_blank(),
      #panel.border=element_blank(),
      #axis.line=element_line(),
      text=element_text(size=16),
      axis.title.y = element_text(margin = margin(0,10,0,0)),
      axis.title.x = element_text(margin = margin(10,0,0,0)),
      legend.key.width = unit(1, "cm"),
      legend.position="right")


```

## Scale for colour is already present.

## Adding another scale for colour, which will replace the existing scale.

plot2

## Model prediction of 3-way interaction: ordinal position X token test (TT in AAT) X session



```
ggsave(plot2, filename =
  here::here("results", "figures",
    "CSI_online_aphasia_spoken_plot_error_by_OrdPos_by_Session_by_TT.pdf"),
  width = 25,
  height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)

# PosOr.cont:session_day3:AAT_c
plot3 <- plot_model(m1_glmm_PWA_all,
  type = "pred",
  #transform=NULL,
  terms = c("PosOr.cont", "AAT_c", "session_day"),
  mrt.values="quart", ci.lvl = .95,
  title=c("Model prediction of 3-way interaction:\nOrdinal position X overall naming (NAM in A
  scale_x_continuous(breaks = c(-1.99860685427696,
    -0.998606854276957,
    0.00139314572304272,
    1.00139314572304,
    2.00139314572304),
    labels= c(1,2,3,4,5)) +
  xlab("Ordinal position") +
  ylab("Percentage of errors") +
  scale_colour_manual(name = "Centered\nNAM score",
    # labels=c("-1.23", " 0.81"),
    values=c("#66cdaa", "#0000ff",
      "#cd3333")) +
```

```

scale_fill_manual(name = "Centered\nTT score",
                  # labels=c("-1.23", " 0.81"),
                  values=c("#66cdaa", "#0000ff",
                           "#cd3333")) +


theme_bw() +
theme(plot.title=element_text(size=22,hjust = .5),
      # panel.grid.major=element_blank(),
      # panel.grid.minor=element_blank(),
      #panel.border=element_blank(),
      #axis.line=element_line(),
      text=element_text(size=16),
      axis.title.y = element_text(margin = margin(0,10,0,0)),
      axis.title.x = element_text(margin = margin(10,0,0,0)),
      legend.key.width = unit(1, "cm"),
      legend.position="right")

```

## Scale for colour is already present.  
 ## Adding another scale for colour, which will replace the existing scale.

plot3

## Model prediction of 3–way interaction: position X overall naming (NAM in AAT) X sessi



```

ggsave(plot3, filename =
  here::here("results", "figures",
             "CSI_online_aphasia_spoken_plot_error_by_OrdPos_by_Session_by_NAM.pdf"),

```



```

width = 25,
height = 13, units = "cm",
dpi = 300, device = cairo_pdf)

plotgrid <- cowplot::plot_grid(plot1, plot3, plot2,
  nrow = 3, ncol=1, rel_widths = c(0.3,1,1),
  margin(1,1,1,1),
  labels = c("A", "B", "C"),label_size = 34,
  label_y = 1.01,
  label_x=-0.01)

## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.

#plotgrid
ggsave(plotgrid, filename =
  here::here("results", "figures",
    "CSI_online_aphasia_spoken_plot_error_by_covariates_plotgrid.pdf"),
width = 25,
height = 25, units = "cm",
dpi = 300, device = cairo_pdf)
ggsave(plotgrid, filename =
  here::here("results", "figures",
    "CSI_online_aphasia_spoken_plot_error_by_covariates_plotgrid.png"),
width = 25,
height = 25, units = "cm",
dpi = 300)

```

---

## Additional (pre-planned) analyses

### Preregistered analyses with GLMM

We deviated from our preregistered analyses because SEs seemed suspiciously small.

*Check fit of normal vs gamma distribution in histograms, q-q-plots and using objective criteria:*

1) Fit normal and gamma distributions to the reaction time data

```

library(fitdistrplus)

## Loading required package: MASS

##
## Attaching package: 'MASS'

## The following object is masked from 'package:dplyr':
##
##   select

## Loading required package: survival

```

```
## Warning: package 'survival' was built under R version 4.3.2
```

```
fit.normal<- fitdist(df_RT$s$VOT, distr = "norm", method = "mle")
summary(fit.normal)
```

```
## Fitting of the distribution ' norm ' by maximum likelihood
## Parameters :
##      estimate Std. Error
## mean 1256.4520   4.029886
## sd   449.7363   2.849560
## Loglikelihood: -93756.26   AIC: 187516.5   BIC: 187531.4
## Correlation matrix:
##      mean sd
## mean    1  0
## sd      0  1
```

```
#plot(fit.normal)
```

```
fit.normal_PWA<- fitdist(df_RT$s_PWA$VOT, distr = "norm", method = "mle")
summary(fit.normal_PWA)
```

```
## Fitting of the distribution ' norm ' by maximum likelihood
## Parameters :
##      estimate Std. Error
## mean 1352.928   7.160560
## sd   531.897   5.063163
## Loglikelihood: -42463.15   AIC: 84930.31   BIC: 84943.54
## Correlation matrix:
##      mean sd
## mean    1  0
## sd      0  1
```

```
#plot(fit.normal_PWA)
```

```
fit.gamma <- fitdist(df_RT$s$VOT, distr = "gamma", method = "mle")
summary(fit.gamma)
```

```
## Fitting of the distribution ' gamma ' by maximum likelihood
## Parameters :
##      estimate      Std. Error
## shape 9.303155467 0.09618813487
## rate  0.007404132 0.00007718889
## Loglikelihood: -92203.61   AIC: 184411.2   BIC: 184426.1
## Correlation matrix:
##      shape      rate
## shape 1.0000000 0.9610023
## rate  0.9610023 1.0000000
```

```
#plot(fit.gamma)
```

```
fit.gamma_PWA <- fitdist(df_RT$s_PWA$VOT, distr = "gamma", method = "mle")
summary(fit.gamma_PWA)
```

```
## Fitting of the distribution ' gamma ' by maximum likelihood
## Parameters :
##      estimate      Std. Error
## shape 7.228017511 0.10366210322
## rate  0.005343025 0.00007644925
## Loglikelihood: -41893.43   AIC:  83790.86   BIC:  83804.09
## Correlation matrix:
##      shape      rate
## shape 1.0000000 0.9414491
## rate  0.9414491 1.0000000
```

```
#plot(fit.gamma_PWA)
```

```
# library(actuar)
# fit.invgamma <- fitdist(df_RTs$VOT, distr = "invgamma", method = "mle")
# summary(fit.invgauss)
# #plot(fit.invgauss)
#
# fit.invgamma_PWA <- fitdist(df_RTs_PWA$VOT, distr = "invgamma", method = "mle")
# summary(fit.invgamma_PWA)
# #plot(fit.invgauss_PWA)
```

```
library(actuar)
```

```
##
## Attaching package: 'actuar'
```

```
## The following objects are masked from 'package:stats':
##
##      sd, var
```

```
## The following object is masked from 'package:grDevices':
##
##      cm
```

```
fit.invgauss <- fitdist(
  df_RTs$VOT, distr = "invgauss", start = list(mean = 5, shape = 1),
  method = "mle")
```

```
## Warning in checkparamlist(arg_startfix$start.arg, arg_startfix$fix.arg, : Some
## parameter names have no starting/fixed value but have a default value:
## dispersion.
```

```
summary(fit.invgauss)
```

```
## Fitting of the distribution ' invgauss ' by maximum likelihood
## Parameters :
##      estimate Std. Error
## mean  1256.267   3.737018
## shape 11394.058 151.349229
```

```
## Loglikelihood: -91804.31   AIC: 183612.6   BIC: 183627.5
## Correlation matrix:
##           mean      shape
## mean  1.000000000 0.002057613
## shape 0.002057613 1.000000000
```

```
#plot(fit.invgauss)
```

```
fit.invgauss_PWA <- fitdist(df_RTs_PWA$VOT, distr = "invgauss",
                           start = list(mean = 5, shape = 1),
                           method = "mle")
```

```
## Warning in checkparamlist(arg_startfix$start.arg, arg_startfix$fix.arg, : Some
## parameter names have no starting/fixed value but have a default value:
## dispersion.
```

```
## Warning in sqrt(diag(varcovar)): NaNs produced
```

```
## Warning in sqrt(1/diag(V)): NaNs produced
```


```
## Warning in cov2cor(varcovar): diag(.) had 0 or NA entries; non-finite result is
## doubtful
```

```
summary(fit.invgauss_PWA)
```


```
## Fitting of the distribution ' invgauss ' by maximum likelihood
## Parameters :
##           estimate Std. Error
## mean  99734.213      NaN
## shape 1176.467    22.41566
## Loglikelihood: -47351.68   AIC: 94707.36   BIC: 94720.59
## Correlation matrix:
##           mean shape
## mean      1      NaN
## shape  NaN      1
```

```
#plot(fit.invgauss_PWA)
```

```
MASS::boxcox(df_RTs_PWA$VOT~df_RTs_PWA$PosOr_cont*df_RTs_PWA$session)
```



```
MASS::boxcox(df_RTs$VOT~df_RTs$PosOr_cont*df_RTs$session*df_RTs$group)
```




```
fit.transf <- fitdist(log(df_RTs$VOT), distr = "norm",method = "mle")
fit.transf_PWA <- fitdist(log(df_RTs_PWA$VOT),
                           distr = "norm",method = "mle")
```

- 2) Compare the fit of the two distributions  
Visually compare fit of both distributions in histogram


```
denscomp(list(fit.gamma, fit.invgauss))
```

## Histogram and theoretical densities



```
denscomp(list(fit.transf))
```


## Histogram and theoretical densities



```
denscomp(list(fit.gamma_PWA, fit.invgauss_PWA))
```




## Histogram and theoretical densities




```
denscomp(list(fit.transf_PWA))
```

## Histogram and theoretical densities




Visually compare fit of both distributions in Q-Q-plots


```
qqcomp(list(fit.gamma, fit.invgauss))
```




```
qqcomp(list(fit.transf))
```



```
qqcomp(list(fit.gamma_PWA))#, fit.invgauss_PWA))
```



```
qqcomp(list(fit.transf_PWA))
```



Compare information criteria

```
gofstat(list(fit.gamma, fit.invgauss, fit.normal),
        fitnames = c("Gamma", "Inverse Gaussian", "Normal"))
```

```
## Goodness-of-fit statistics
##
##          Gamma Inverse Gaussian    Normal
## Kolmogorov-Smirnov statistic  0.08343887      0.06232548  0.127563
## Cramer-von Mises statistic    30.32364092     16.58123861  75.033011
## Anderson-Darling statistic   176.46689389     96.39448742 433.186766
##
## Goodness-of-fit criteria
##
##          Gamma Inverse Gaussian    Normal
## Akaike's Information Criterion 184411.2      183612.6 187516.5
## Bayesian Information Criterion 184426.1      183627.5 187531.4
```

```
gofstat(list(fit.gamma_PWA, fit.invgauss_PWA, fit.normal_PWA),
        fitnames = c("Gamma", "Inverse Gaussian", "Normal" ))
```

```
## Goodness-of-fit statistics
##
##          Gamma Inverse Gaussian    Normal
## Kolmogorov-Smirnov statistic  0.06892153      0.4539719  0.1180601
## Cramer-von Mises statistic    8.06338088     375.0566303  25.8912637
## Anderson-Darling statistic   45.03214204     1728.3004897 147.8033420
##
```

```
## Goodness-of-fit criteria
##
##               Gamma Inverse Gaussian   Normal
## Akaike's Information Criterion 83790.86      94707.36 84930.31
## Bayesian Information Criterion 83804.09      94720.59 84943.54
```

**Conclusion:** . Overall, (inverse) gamma fits the data better than a normal model with uncontrolled data and an inverse Gaussian distribution for both the entire data set and the PWA group only. The inverse Gamma is not yet implemented in glmer. Therefore we will use the Gamma distribution.

```
# m1 <- glmer(VOT ~ PosOr.cont*session +
#             (PosOr.cont*session/subject) +
#             (PosOr.cont*session/category),
#             data = df_RTs_PWA,
#             family =Gamma(link ="identity"),
#             control=glmerControl(optimizer = "bobyqa"))
```

**PWA only - Ordinal position x session** Model fails to converge -> reduce

```
# 1) Increase optimizer iterations
# m1 <- glmer(VOT ~ PosOr.cont*session +
#             (PosOr.cont*session/subject) +
#             (PosOr.cont*session/category),
#             data = df_RTs_PWA,
#             family =Gamma(link ="identity"),
#             control=glmerControl(optimizer = "bobyqa",
#                                   optCtrl = list(maxfun = 2e5)))
# 2) Set correlation parameters to zero
m1 <- afex::lmer_alt(VOT ~ PosOr.cont*session +
                    (PosOr.cont*session||subject) +
                    (PosOr.cont*session||category),
                    data = df_RTs_PWA,
                    family =Gamma(link ="identity"),
                    control=glmerControl(optimizer = "bobyqa",
                                          optCtrl = list(maxfun = 2e5)))
didLmerConverge(m1)
```

```
## The relative maximum gradient of 0.0000625 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## The warnings can be safely ignored
```

```
# inspect model
summary(m1)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: Gamma ( identity )
## Formula: VOT ~ PosOr.cont * session + (1 + re1.PosOr.cont + re1.session2 +
##          re1.session3 + re1.PosOr.cont_by_session2 + re1.PosOr.cont_by_session3 ||
```

```

##      subject) + (1 + re2.Pos0r.cont + re2.session2 + re2.session3 +
##      re2.Pos0r.cont_by_session2 + re2.Pos0r.cont_by_session3 ||      category)
## Data: data
## Control: glmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
##      AIC      BIC    logLik deviance df.resid
## 80877.2 81002.9 -40419.6 80839.2      5499
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.9676 -0.6347 -0.2620  0.3412  6.9889
##
## Random effects:
## Groups      Name                                Variance  Std.Dev.
## category    re2.Pos0r.cont_by_session3         1388.0844   37.2570
## category.1  re2.Pos0r.cont_by_session2         1746.8469   41.7953
## category.2  re2.session3                       2080.6296   45.6139
## category.3  re2.session2                       1856.3737   43.0857
## category.4  re2.Pos0r.cont                      234.6941   15.3197
## category.5  (Intercept)                        5374.8827   73.3136
## subject     re1.Pos0r.cont_by_session3          600.7064   24.5093
## subject.1   re1.Pos0r.cont_by_session2          965.2678   31.0688
## subject.2   re1.session3                       3742.7243   61.1778
## subject.3   re1.session2                       2955.8420   54.3677
## subject.4   re1.Pos0r.cont                      361.3693   19.0097
## subject.5   (Intercept)                       20917.7899  144.6298
## Residual                                         0.1001   0.3164
## Number of obs: 5518, groups:  category, 24; subject, 20
##
## Fixed effects:
##              Estimate Std. Error t value      Pr(>|z|)
## (Intercept)    1545.112     4.381 352.700 < 0.0000000000000002 ***
## Pos0r.cont       31.556     5.918   5.333    0.0000000968 ***
## session2      -112.882     4.345 -25.979 < 0.0000000000000002 ***
## session3      -144.043     5.425 -26.552 < 0.0000000000000002 ***
## Pos0r.cont:session2    14.551     3.782   3.847     0.000119 ***
## Pos0r.cont:session3     9.690     6.903   1.404     0.160386
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##              (Intr) Ps0r.c sessn2 sessn3 Ps0.:2
## Pos0r.cont   -0.237
## session2     -0.090  0.058
## session3      0.083 -0.109 -0.029
## Ps0r.cnt:s2  -0.065  0.057  0.015 -0.028
## Ps0r.cnt:s3   0.018 -0.287  0.125  0.106  0.084

```

```
anova(m1)
```

```

## Analysis of Variance Table
##              npar Sum Sq Mean Sq F value
## Pos0r.cont      1 2.2286 2.22856 22.2599
## session         2 5.7970 2.89852 28.9518

```



```
## PosOr.cont:session      2 0.1159 0.05794  0.5788
```

```
# save model output
saveRDS(m1, file = here::here("results", "tables",
                              "CSI_online_aphasia_PWA_glmm_cont.RDS"))
tab_model(m1, transform = NULL,
          show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
          title = "GLMM (Gamma distribution) of VOTs Predicted by Ordinal Position and Session, PWA only",
          dv.labels = "Vocal Onset Time",
          #string.pred = "",
          string.stat = "t-Value",
          file = here::here(
            "results", "tables", "CSI_online_aphasia_PWA_glmm_cont.html"))
```

GLMM (Gamma distribution) of VOTs Predicted by Ordinal Position and Session, PWA only

Vocal Onset Time

Predictors

Estimates

CI

t-Value

p

(Intercept)

1545.11

1536.52 – 1553.70

352.70

<0.001

PosOr cont

31.56

19.96 – 43.16

5.33

<0.001

session [2]

-112.88

-121.40 – -104.36

-25.98

<0.001

session [3]

-144.04

-154.68 – -133.41

-26.55

```

<0.001
PosOr cont × session [2]
14.55
7.14 – 21.97
3.85
<0.001
PosOr cont × session [3]
9.69
-3.84 – 23.22
1.40
0.160
N subject
20
N category
24
Observations
5518

```

**Analyses with Ordinal position x Session x Group** Make sure contrasts are correctly defined

```
contrasts(df_RTs$session)
```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667

```

```
levels(df_RTs$session)
```

```
## [1] "1" "2" "3"

```

```
## Define contrast of group
contrasts(df_RTs$group)
```

```
##           2-1
## control -0.5
## PWA      0.5

```

```
levels(df_RTs$group)
```

```
## [1] "control" "PWA"

```

Compute model

```
# m2 <- glmer(VOT ~ PosOr.cont*session*group +
#             (PosOr.cont*session/subject) +
#             (PosOr.cont*session*group/category),
#             data = df_RTs,
#             family = Gamma(link = "identity"),
#             control = glmerControl(optimizer = "bobyqa"))
```

Model fails to converge -> reduce

```
# 1) Increase optimizer iterations
# m2 <- glmer(VOT ~ PosOr.cont*session*group +
#             (PosOr.cont*session/subject) +
#             (PosOr.cont*session*group/category),
#             data = df_RTs,
#             family = Gamma(link = "identity"),
#             control = glmerControl(optimizer = "bobyqa",
#                                     optCtrl = list(maxfun = 2e5)))
# 2) Set correlation parameters to zero
m2 <- afex::lmer_alt(VOT ~ PosOr.cont*session*group +
                    (PosOr.cont*session||subject) +
                    (PosOr.cont*session*group||category),
                    data = df_RTs,
                    family = Gamma(link = "identity"),
                    control = glmerControl(optimizer = "bobyqa",
                                            optCtrl = list(maxfun = 2e5)))
didLmerConverge(m2)
```

```
## The relative maximum gradient of 0.000238 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

```
## The warnings can be safely ignored
```

```
# inspect model
summary(m2)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: Gamma ( identity )
## Formula:
## VOT ~ PosOr.cont * session * group + (1 + re1.PosOr.cont + re1.session2 +
## re1.session3 + re1.PosOr.cont_by_session2 + re1.PosOr.cont_by_session3 ||
## subject) + (1 + re2.PosOr.cont + re2.session2 + re2.session3 +
## re2.group2.1 + re2.PosOr.cont_by_session2 + re2.PosOr.cont_by_session3 +
## re2.PosOr.cont_by_group2.1 + re2.session2_by_group2.1 + re2.session3_by_group2.1 +
## re2.PosOr.cont_by_session2_by_group2.1 + re2.PosOr.cont_by_session3_by_group2.1 ||
## category)
## Data: data
## Control: glmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
##      AIC      BIC    logLik deviance df.resid
## 178422.0 178652.4 -89180.0 178360.0     12424
##
```

```

## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.5240 -0.6220 -0.2386  0.3365  8.0705
##
## Random effects:
##      Groups      Name              Variance  Std.Dev.
##  subject      (Intercept)        11534.92084 107.4007
##  subject.1    re1.Pos0r.cont         230.18085  15.1717
##  subject.2    re1.session2          3987.89997  63.1498
##  subject.3    re1.session3          3759.80311  61.3172
##  subject.4    re1.Pos0r.cont_by_session2  799.75422  28.2799
##  subject.5    re1.Pos0r.cont_by_session3  337.48878  18.3709
##  category     (Intercept)         3218.47862  56.7316
##  category.1    re2.Pos0r.cont         107.70350  10.3780
##  category.2    re2.session2          675.10353  25.9828
##  category.3    re2.session3          671.62800  25.9158
##  category.4    re2.group2.1         1350.46946  36.7487
##  category.5    re2.Pos0r.cont_by_session2  201.22400  14.1853
##  category.6    re2.Pos0r.cont_by_session3  294.15346  17.1509
##  category.7    re2.Pos0r.cont_by_group2.1  180.28554  13.4270
##  category.8    re2.session2_by_group2.1  3093.25604  55.6170
##  category.9    re2.session3_by_group2.1  2663.70627  51.6111
##  category.10   re2.Pos0r.cont_by_session2_by_group2.1 2197.76058  46.8803
##  category.11   re2.Pos0r.cont_by_session3_by_group2.1 1097.63575  33.1306
##  Residual                                0.08145   0.2854
## Number of obs: 12455, groups:  subject, 40; category, 24
##
## Fixed effects:
##                                Estimate Std. Error t value      Pr(>|z|)
## (Intercept)                   1390.793     2.531 549.448 < 0.0000000000000002
## Pos0r.cont                     22.805     3.054   7.466 0.00000000000000824
## session2                      -98.052     3.804 -25.779 < 0.0000000000000002
## session3                     -125.369     3.869 -32.401 < 0.0000000000000002
## group2-1                      338.070     2.909 116.195 < 0.0000000000000002
## Pos0r.cont:session2             6.167     2.323   2.655      0.00794
## Pos0r.cont:session3             5.634     6.493   0.868      0.38552
## Pos0r.cont:group2-1            15.687     2.325   6.747 0.0000000000151152
## session2:group2-1             -30.708     3.306  -9.287 < 0.0000000000000002
## session3:group2-1             -42.597     3.231 -13.186 < 0.0000000000000002
## Pos0r.cont:session2:group2-1    17.956     2.722   6.598 0.0000000000417505
## Pos0r.cont:session3:group2-1     6.852     2.409   2.844      0.00446
##
## (Intercept)                    ***
## Pos0r.cont                      ***
## session2                        ***
## session3                        ***
## group2-1                        ***
## Pos0r.cont:session2             **
## Pos0r.cont:session3
## Pos0r.cont:group2-1            ***
## session2:group2-1              ***
## session3:group2-1              ***
## Pos0r.cont:session2:group2-1 ***
## Pos0r.cont:session3:group2-1 **

```

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##          (Intr) Ps0r.c sessn2 sessn3 grp2-1 Ps0.:2 Ps0.:3 P0.:2- s2:2-1
## Pos0r.cont -0.091
## session2    0.116 -0.162
## session3    -0.047  0.306 -0.507
## group2-1    -0.019 -0.172 -0.081 -0.052
## Ps0r.cnt:s2 -0.044 -0.099 -0.046  0.027  0.199
## Ps0r.cnt:s3  0.112 -0.423  0.321 -0.571  0.252  0.030
## Ps0r.cn:2-1 -0.252  0.050 -0.354  0.259 -0.015  0.094 -0.275
## sssn2:gr2-1 -0.049  0.094 -0.425  0.381  0.098  0.032 -0.286  0.058
## sssn3:gr2-1 -0.085  0.023 -0.432  0.218  0.047  0.055 -0.093  0.262  0.119
## Ps0r.:2:2-1  0.209 -0.124 -0.180  0.107  0.166  0.064  0.183 -0.064  0.176
## Ps0r.:3:2-1  0.135 -0.085  0.033  0.048  0.104 -0.011  0.011 -0.181  0.159
##          s3:2-1 P0.:2:
## Pos0r.cont
## session2
## session3
## group2-1
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## Ps0r.cn:2-1
## sssn2:gr2-1
## sssn3:gr2-1
## Ps0r.:2:2-1  0.140
## Ps0r.:3:2-1 -0.157  0.195
```

```
anova(m2)
```

```
## Analysis of Variance Table
##              npar Sum Sq Mean Sq F value
## Pos0r.cont          1 2.4993  2.4993 30.6836
## session              2 8.7004  4.3502 53.4068
## group                1 7.2716  7.2716 89.2723
## Pos0r.cont:session    2 0.0633  0.0317  0.3886
## Pos0r.cont:group      1 0.3947  0.3947  4.8462
## session:group         2 0.2507  0.1254  1.5390
## Pos0r.cont:session:group 2 0.0888  0.0444  0.5449
```

```
# save model output
saveRDS(m2, file = here::here("results", "tables",
                              "CSI_online_aphasia_SessionxGroup_glmm_cont.RDS"))
tab_model(m2, transform = NULL,
           show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
           title = "GLMM (Gamma distribution) of VOTs Predicted by Ordinal Position, Session and Group",
           dv.labels = "Vocal Onset Time",
           #string.pred = "",
           string.stat = "t-Value",
           file = here::here(
             "results", "tables",
             "CSI_online_aphasia_SessionxGroup_glmm_cont.html"))
```

# GLMM (Gamma distribution) of VOTs Predicted by Ordinal Position, Session and Group

Vocal Onset Time

Predictors

Estimates

CI

t-Value

p

(Intercept)

1390.79

1385.83 – 1395.76

549.45

<0.001

PosOr cont

22.80

16.82 – 28.79

7.47

<0.001

session [2]

-98.05

-105.51 – -90.60

-25.78

<0.001

session [3]

-125.37

-132.95 – -117.78

-32.40

<0.001

group2-1

338.07

332.37 – 343.77

116.20

<0.001

PosOr cont × session [2]

6.17

1.61 – 10.72

2.65  
 0.008  
 PosOr cont  $\times$  session [3]  
 5.63  
 -7.09 – 18.36  
 0.87  
 0.386  
 PosOr.cont:group2-1  
 15.69  
 11.13 – 20.25  
 6.75  
 <0.001  
 session2:group2-1  
 -30.71  
 -37.19 – -24.23  
 -9.29  
 <0.001  
 session3:group2-1  
 -42.60  
 -48.93 – -36.26  
 -13.19  
 <0.001  
 PosOr.cont:session2:group2-1  
 17.96  
 12.62 – 23.29  
 6.60  
 <0.001  
 PosOr.cont:session3:group2-1  
 6.85  
 2.13 – 11.57  
 2.84  
 0.004  
 N subject  
 40  
 N category  
 24  
 Observations  
 12455

**Control analyses without PWA 1 and 17** The procedure deviated slightly in two participants. PWA1 had the same array in sessions 1 and 2 and was tested a day too late in session 2, PWA17 was tested a day too late in session 3. Here, we conduct control analyses without these two participants to test whether the data are affected.

RTs

Plotting

```
(means_final<- df_RT %>%
  filter(category != "Filler") %>%
  filter(subject != 101 & subject != 117) %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("session", "PosOr"),
    betweenvars = "group", na.rm = T))
```

##	group	session	PosOr	N	VOT	sd	se	ci
## 1	control	1	1	461	1309.126	386.6087	18.00616	35.38453
## 2	control	1	2	456	1289.949	368.6706	17.26458	33.92821
## 3	control	1	3	446	1364.816	419.3224	19.85549	39.02218
## 4	control	1	4	457	1341.318	375.5740	17.56861	34.52548
## 5	control	1	5	456	1359.540	395.4900	18.52052	36.39636
## 6	control	2	1	466	1216.815	327.2233	15.15832	29.78730
## 7	control	2	2	462	1256.861	364.0399	16.93667	33.28264
## 8	control	2	3	464	1225.331	289.9285	13.45959	26.44945
## 9	control	2	4	466	1256.116	296.8703	13.75225	27.02425
## 10	control	2	5	454	1278.405	329.4120	15.46007	30.38236
## 11	control	3	1	469	1211.518	323.1567	14.92199	29.32239
## 12	control	3	2	471	1184.996	282.9187	13.03621	25.61646
## 13	control	3	3	467	1220.181	305.2131	14.12358	27.75378
## 14	control	3	4	470	1244.625	306.1228	14.12039	27.74706
## 15	control	3	5	472	1275.156	349.0940	16.06835	31.57453
## 16	PWA	1	1	322	1291.359	470.8797	26.24110	51.62626
## 17	PWA	1	2	307	1372.601	525.3676	29.98431	59.00153
## 18	PWA	1	3	293	1385.028	501.7716	29.31381	57.69314
## 19	PWA	1	4	314	1358.021	481.5093	27.17314	53.46511
## 20	PWA	1	5	278	1404.586	536.9389	32.20346	63.39460
## 21	PWA	2	1	333	1180.871	446.1987	24.45154	48.09948
## 22	PWA	2	2	339	1199.500	450.7117	24.47930	48.15096
## 23	PWA	2	3	323	1224.846	440.9998	24.53789	48.27482
## 24	PWA	2	4	332	1270.946	471.2779	25.86473	50.87999
## 25	PWA	2	5	311	1326.022	508.4508	28.83160	56.73038
## 26	PWA	3	1	350	1140.621	363.0123	19.40383	38.16314
## 27	PWA	3	2	340	1193.366	475.6980	25.79835	50.74500
## 28	PWA	3	3	348	1224.618	444.0864	23.80553	46.82129
## 29	PWA	3	4	338	1234.189	446.2534	24.27299	47.74565
## 30	PWA	3	5	322	1283.698	483.1446	26.92460	52.97096

```
override.linetype<-c("solid", "dashed", "dotted")
(plot_rt_repetition_PWA <- means_final %>% filter(group=="PWA") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2) +
  stat_summary(aes(linetype=session),
    fun=mean, geom="line", size = 0.5) +
```



```


scale_linetype_manual(values=c("solid", "dashed", "dotted"))+
scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
              width = .1) +

apatheme+
scale_y_continuous(limits = c(1120, 1450),
                   breaks = seq(1150, 1450, by = 50)) +
labs(x="Ordinal Position ", y="RT (ms)", colour="Session",
     linetype="Session",
     title = "Patients with Aphasia") +
theme(
  axis.title.y = element_text(margin = margin(0, 10, 0, 0)),
  axis.title.x = element_text(margin = margin(10, 0, 0, 0)),
  legend.key.width = unit(1, "cm"),
  legend.position="none")+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```

(plot_rt_repetition_control <- means_final %>%
  filter(group=="control") %>%

```

```


ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean, geom="line", size = 0.5) +
  scale_linetype_manual(values=c("solid", "dashed", "dotted"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
    width =.1) +

  apatheme+
  scale_y_continuous(limits = c(1120, 1450),
    breaks =seq(1150,1450, by = 50)) +
  labs(x="Ordinal Position ",y ="RT (ms)", colour="Session",
    linetype="Session",
    title = "Control Group") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"))+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.



```
plots <- cowplot::plot_grid(plot_rt_repetition_PWA,
                             plot_rt_repetition_control,
                             nrow = 1, ncol=2, rel_widths = c(0.81,1),
                             margin(1,1,1,1),
                             labels = c("A", "B"),label_size = 34,
                             label_y = 1.01,
                             label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <-
  "CSI_online_aphasia_spoken_plot_rt_by_repetition_without_101-117.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 25, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

Statistical analyses

```
df_RTs_red <- df_RTs %>% filter(subject != "101" & subject != "117") %>%
  droplevels()
df_RTs_red$PosOr.cont <- scale(as.numeric(as.character(df_RTs_red$PosOr)),
                               center = T, scale = F)

# m2_f <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#   (PosOr.cont*session||subject) +
#   (PosOr.cont*session*group||category),
#   data = df_RTs_red,
#   control=lmerControl(optimizer = "bobyqa",
#     optCtrl = list(maxfun = 2e5)))
# m2_f <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#   (PosOr.cont*session||subject) +
#   (PosOr.cont+session*group-session||category),
#   data = df_RTs_red,
#   control=lmerControl(optimizer = "bobyqa",
#     optCtrl = list(maxfun = 2e5)))
m2_f <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
  (PosOr.cont+session||subject) +
  (PosOr.cont+group||category),
  data = df_RTs_red,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))

# m2_f <- lmer(lVOT ~ PosOr.cont*session*group +
#   (PosOr.cont+session/subject) +
#   (PosOr.cont+group/category),
#   data = df_RTs_red,
#   control=lmerControl(optimizer = "bobyqa",
#     optCtrl = list(maxfun = 2e5)))
summary(m2_f)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
```

```

## lmerModLmerTest]
## Formula:
## lVOT ~ PosOr.cont * session * group + (1 + re1.PosOr.cont + re1.session2 +
##      re1.session3 || subject) + (1 + re2.PosOr.cont + re2.groupPWA ||
##      category)
## Data: data
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 566
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -5.0588 -0.6700 -0.1747  0.4856  4.7417
##
## Random effects:
##      Groups      Name      Variance  Std.Dev.
## subject      (Intercept)  0.02712626 0.164701
## subject.1 re1.PosOr.cont  0.00011070 0.010521
## subject.2 re1.session2    0.00278164 0.052741
## subject.3 re1.session3    0.00224735 0.047406
## category     (Intercept)  0.00879305 0.093771
## category.1 re2.PosOr.cont  0.00002853 0.005341
## category.2 re2.groupPWA    0.00104258 0.032289
## Residual                        0.05875025 0.242385
## Number of obs: 11787, groups:  subject, 38; category, 24
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)    7.085116    0.041816   51.242816 169.436
## PosOr.cont      0.013363    0.004422  104.743190   3.022
## session2     -0.063178    0.013800   35.126977  -4.578
## session3     -0.079132    0.012778   33.206693  -6.193
## groupPWA       0.210482    0.054569   37.088668   3.857
## PosOr.cont:session2 -0.001952    0.005059 11557.848779  -0.386
## PosOr.cont:session3  0.002122    0.005032 11552.244382   0.422
## PosOr.cont:groupPWA  0.003169    0.006681  138.528159   0.474
## session2:groupPWA   -0.021305    0.020707   38.666337  -1.029
## session3:groupPWA   -0.026097    0.019192   36.812204  -1.360
## PosOr.cont:session2:groupPWA  0.012872    0.007959 11587.162798   1.617
## PosOr.cont:session3:groupPWA  0.002883    0.007903 11588.134367   0.365
##
##              Pr(>|t|)
## (Intercept) < 0.0000000000000002 ***
## PosOr.cont      0.003160 **
## session2     0.000056588 ***
## session3     0.000000534 ***
## groupPWA       0.000442 ***
## PosOr.cont:session2  0.699649
## PosOr.cont:session3  0.673249
## PosOr.cont:groupPWA  0.635994
## session2:groupPWA   0.309918
## session3:groupPWA   0.182169
## PosOr.cont:session2:groupPWA  0.105839
## PosOr.cont:session3:groupPWA  0.715293
## ---

```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) Ps0r.c sessn2 sessn3 grpPWA Ps0r.:2 Ps0r.:3 P0r.:PW s2:PWA
## Pos0r.cont -0.001
## session2   -0.045  0.003
## session3   -0.048  0.003  0.147
## groupPWA   -0.606  0.001  0.034  0.037
## Ps0r.cnt:s2  0.001 -0.573 -0.004 -0.003 -0.001
## Ps0r.cnt:s3  0.001 -0.577 -0.003 -0.007 -0.001  0.504
## Ps0r.cn:PWA  0.001 -0.622 -0.002 -0.002  0.003  0.380  0.382
## sssn2:grPWA  0.030 -0.002 -0.666 -0.098 -0.060  0.003  0.002 -0.005
## sssn3:grPWA  0.032 -0.002 -0.098 -0.666 -0.066  0.002  0.004 -0.006  0.169
## Ps0r.:2:PWA -0.001  0.365  0.002  0.002 -0.002 -0.636 -0.320 -0.609  0.006
## Ps0r.:3:PWA -0.001  0.367  0.002  0.004 -0.002 -0.321 -0.637 -0.616  0.004
##      s3:PWA P0r.:2:
## Pos0r.cont
## session2
## session3
## groupPWA
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## Ps0r.cn:PWA
## sssn2:grPWA
## sssn3:grPWA
## Ps0r.:2:PWA  0.004
## Ps0r.:3:PWA  0.005  0.515
```

```
didLmerConverge(m2_f)
```

```
## The relative maximum gradient of 0.000000349 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.
```

Error rates

```
df_errors_red <- df_errors %>%
  filter(subject != "101" & subject != "117") %>%
  filter(group=="PWA") %>%
  droplevels()
df_errors_red$Pos0r.cont <-
  scale(as.numeric(as.character(df_errors_red$Pos0r)),
        center = T, scale = F)
# m2_f <- afex::lmer_alt(error_class ~ Pos0r.cont*session +
#                        (Pos0r.cont*session||subject) +
#                        (Pos0r.cont*session||category),
#                        data = df_errors_red,
#                        family="binomial",
#                        control=glmerControl(optimizer = "bobyqa",
#                                             optCtrl = list(maxfun = 2e5)))
# m2_f <- afex::lmer_alt(error_class ~ Pos0r.cont*session*group +
#                        (Pos0r.cont||subject) +
#                        (Pos0r.cont+group||category),
#                        data = df_errors_red,
```

```

#           family="binomial",
#           control=glmerControl(optimizer = "bobyqa",
#                                optCtrl = list(maxfun = 2e5)))
# m2_f <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                        (PosOr.cont*session||subject) +
#                        (PosOr.cont*session*group-session||category),
#                        data = df_RTs_red,
#                        control=lmerControl(optimizer = "bobyqa",
#                                             optCtrl = list(maxfun = 2e5)))
m2_f <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
                      (PosOr.cont+session||subject) +
                      (PosOr.cont+group||category),
                      data = df_RTs_red,
                      control=lmerControl(optimizer = "bobyqa",
                                           optCtrl = list(maxfun = 2e5)))
# m2_f <- lmer(lVOT ~ PosOr.cont*session*group +
#              (PosOr.cont+session|subject) +
#              (PosOr.cont+group|category),
#              data = df_RTs_red,
#              control=lmerControl(optimizer = "bobyqa",
#                                   optCtrl = list(maxfun = 2e5)))
summary(m2_f)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula:
## lVOT ~ PosOr.cont * session * group + (1 + re1.PosOr.cont + re1.session2 +
##    re1.session3 || subject) + (1 + re2.PosOr.cont + re2.groupPWA ||
##    category)
## Data: data
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 566
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -5.0588 -0.6700 -0.1747  0.4856  4.7417
##
## Random effects:
##   Groups      Name                Variance  Std.Dev.
##   subject    (Intercept)          0.02712626 0.164701
##   subject.1  re1.PosOr.cont        0.00011070 0.010521
##   subject.2  re1.session2          0.00278164 0.052741
##   subject.3  re1.session3          0.00224735 0.047406
##   category   (Intercept)          0.00879305 0.093771
##   category.1 re2.PosOr.cont        0.00002853 0.005341
##   category.2 re2.groupPWA          0.00104258 0.032289
##   Residual                        0.05875025 0.242385
## Number of obs: 11787, groups:  subject, 38; category, 24
##
## Fixed effects:
##
##              Estimate  Std. Error      df t value
## (Intercept)    7.085116    0.041816  51.242816 169.436

```

```

## Pos0r.cont          0.013363      0.004422    104.743190    3.022
## session2            -0.063178      0.013800     35.126977   -4.578
## session3            -0.079132      0.012778     33.206693   -6.193
## groupPWA            0.210482      0.054569     37.088668    3.857
## Pos0r.cont:session2 -0.001952      0.005059   11557.848779   -0.386
## Pos0r.cont:session3  0.002122      0.005032   11552.244382    0.422
## Pos0r.cont:groupPWA  0.003169      0.006681    138.528159    0.474
## session2:groupPWA    -0.021305      0.020707     38.666337   -1.029
## session3:groupPWA    -0.026097      0.019192     36.812204   -1.360
## Pos0r.cont:session2:groupPWA 0.012872      0.007959   11587.162798    1.617
## Pos0r.cont:session3:groupPWA 0.002883      0.007903   11588.134367    0.365
##                                     Pr(>|t|)
## (Intercept)          < 0.0000000000000002 ***
## Pos0r.cont           0.003160 **
## session2             0.000056588 ***
## session3             0.000000534 ***
## groupPWA             0.000442 ***
## Pos0r.cont:session2  0.699649
## Pos0r.cont:session3  0.673249
## Pos0r.cont:groupPWA  0.635994
## session2:groupPWA    0.309918
## session3:groupPWA    0.182169
## Pos0r.cont:session2:groupPWA 0.105839
## Pos0r.cont:session3:groupPWA 0.715293
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) Ps0r.c sessn2 sessn3 grpPWA Ps0.:2 Ps0.:3 PO.:PW s2:PWA
## Pos0r.cont -0.001
## session2   -0.045  0.003
## session3   -0.048  0.003  0.147
## groupPWA   -0.606  0.001  0.034  0.037
## Ps0r.cnt:s2  0.001 -0.573 -0.004 -0.003 -0.001
## Ps0r.cnt:s3  0.001 -0.577 -0.003 -0.007 -0.001  0.504
## Ps0r.cn:PWA  0.001 -0.622 -0.002 -0.002  0.003  0.380  0.382
## sssn2:grPWA  0.030 -0.002 -0.666 -0.098 -0.060  0.003  0.002 -0.005
## sssn3:grPWA  0.032 -0.002 -0.098 -0.666 -0.066  0.002  0.004 -0.006  0.169
## Ps0r.:2:PWA -0.001  0.365  0.002  0.002 -0.002 -0.636 -0.320 -0.609  0.006
## Ps0r.:3:PWA -0.001  0.367  0.002  0.004 -0.002 -0.321 -0.637 -0.616  0.004
##      s3:PWA PO.:2:
## Pos0r.cont
## session2
## session3
## groupPWA
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## Ps0r.cn:PWA
## sssn2:grPWA
## sssn3:grPWA
## Ps0r.:2:PWA  0.004
## Ps0r.:3:PWA  0.005  0.515

```

```
didLmerConverge(m2_f)
```

```
## The relative maximum gradient of 0.000000349 is less than our 0.001 criterion.  
## You can safely ignore any warnings about a claimed convergence failure.
```

### Comparison to verbal CSI with young participants Load data

Load data from both the verbal online CSI experiment (Stark et al., 2022)

```
load(here::here("data", "verbal_CSI_young_starketal2022",  
               "CSI_online_verbal_df_full.RData"))  
df_young <- df_full
```

Combine both data frames into one

- 1) Subset relevant columns and give identical names

```
df_young <- df_young %>%  
  dplyr::select(VP, Item, subcat, VOT, correct, Pos) %>%  
  dplyr::rename(subject = VP, item = Item,  
                category = subcat, PosOr=Pos) %>%  
  mutate(group="young") %>%  
  mutate(session="young group")  
  
x <- df_RT_s %>%  
  dplyr::select(subject, group, session, item, category, VOT, PosOr)
```

- 2) Give subjects from both experiments different names

```
df_young <- df_young %>% mutate(subject = subject + 300)
```

- 3) Put columns into correct format

```
df_young <- df_young %>%  
  mutate(subject = as.factor(subject)) %>%  
  mutate(item = as.character(item)) %>%  
  mutate(category = as.factor(category)) %>%  
  mutate(VOT = as.numeric(VOT)) %>%  
  mutate(PosOr = as.factor(PosOr)) %>%  
  filter(!is.na(correct) & correct != 0) %>%  
  dplyr::select(-correct) %>%  
  droplevels()
```

- 4) Bind both data frames into one

```
df_combi <- bind_rows(x, df_young)
```

- 5) Give identical category names in both experiments



```
df_combi <- df_combi %>% dplyr::mutate(category = case_when(
  category == "Buero" ~ "Büro",
  category == "Gebaeude" ~ "Gebäude",
  category == "Gemuese" ~ "Gemüse",
  category == "Koerperteile" ~ "Körperteile",
  category == "Kueche" ~ "Küche",
  category == "Suessigkeiten" ~ "Süssigkeiten",
  category == "Trinkgefaesse" ~ "Trinkgefässe",
  category == "Voegel" ~ "Vögel",
  TRUE ~ as.character(category))) %>%
  mutate(category == as.factor(category)) %>% droplevels()
table(df_combi$category)
```

```
##
## Aufbewahrung    Bauernhof    Blumen      Büro      Filler1    Filler2
##      652         681         567        657        586        581
##      Fische      Gebäude      Gemüse    Heimwerker  Huftiere    Insekten
##      669         628         678        658        693        657
## Instrumente     Jacken      Kochen    Körperteile  Küche       Obst
##      651         595         652        696        649        709
## Raubtiere       Schmuck     Sitzen     Strasse  Süssigkeiten Trinkgefässe
##      629         610         652        692        687        652
##      Vögel       Wasser
##      684         621
```

5) Drop filler trials

```
df_combi <- df_combi %>% filter(category != "Filler" &
  category != "Filler1" & category != "Filler2") %>%
  droplevels()
```

6) Export combined data frame for post-hoc power plot

```
write.csv(df_combi, here::here("data", "CSI_online_young_PWA_old_combined.csv"))
```

Descriptives

```
(descriptives <- df_combi %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("PosOr", "session"),
    betweenvars = "group",
    na.rm = T))
```

## Automatically converting the following non-factors to factors: group, session

```
##      group PosOr    session    N      VOT      sd      se      ci
## 1 control     1         1 461 1236.721 383.2024 17.847516 35.07277
## 2 control     1         2 466 1144.410 324.3402 15.024768 29.52485
## 3 control     1         3 469 1139.114 320.3094 14.790516 29.06404
## 4 control     2         1 456 1217.544 365.4223 17.112469 33.62928
```

## 5	control	2	2	462	1184.456	360.8324	16.787443	32.98939
## 6	control	2	3	471	1112.591	280.4260	12.921349	25.39076
## 7	control	3	1	446	1292.412	415.6279	19.680549	38.67837
## 8	control	3	2	464	1152.927	287.3740	13.341002	26.21641
## 9	control	3	3	467	1147.777	302.5239	13.999138	27.50925
## 10	control	4	1	457	1268.913	372.2649	17.413816	34.22128
## 11	control	4	2	466	1183.711	294.2546	13.631082	26.78615
## 12	control	4	3	470	1172.220	303.4256	13.995981	27.50259
## 13	control	5	1	456	1287.135	392.0054	18.357336	36.07568
## 14	control	5	2	454	1206.000	326.5096	15.323856	30.11466
## 15	control	5	3	472	1202.752	346.0182	15.926780	31.29634
## 16	PWA	1	1	362	1220.274	459.3182	24.141226	47.47510
## 17	PWA	1	2	375	1108.467	435.1172	22.469357	44.18211
## 18	PWA	1	3	395	1083.626	370.4159	18.637649	36.64168
## 19	PWA	2	1	345	1291.769	513.4978	27.645791	54.37606
## 20	PWA	2	2	386	1127.932	439.4589	22.367867	43.97847
## 21	PWA	2	3	386	1123.099	453.0649	23.060394	45.34007
## 22	PWA	3	1	337	1314.130	510.4865	27.807971	54.69965
## 23	PWA	3	2	370	1152.440	431.8690	22.451801	44.14953
## 24	PWA	3	3	396	1163.716	438.2590	22.023345	43.29763
## 25	PWA	4	1	357	1274.240	464.6651	24.592687	48.36521
## 26	PWA	4	2	378	1185.207	453.1751	23.308811	45.83156
## 27	PWA	4	3	384	1162.566	433.5719	22.125623	43.50289
## 28	PWA	5	1	322	1329.476	533.6370	29.738428	58.50684
## 29	PWA	5	2	355	1247.699	492.1252	26.119292	51.36849
## 30	PWA	5	3	370	1212.513	465.4573	24.197971	47.58322
## 31	young	1	young group	670	1144.019	250.5367	9.679078	19.00503
## 32	young	2	young group	651	1171.140	269.5845	10.565851	20.74732
## 33	young	3	young group	662	1202.806	282.1272	10.965186	21.53079
## 34	young	4	young group	650	1200.640	283.4120	11.116334	21.82832
## 35	young	5	young group	631	1264.514	307.4940	12.241145	24.03838

Plotting

Plot RTs by Session and ordinal position for both experiments

```

override.linetype<-c("solid", "dashed", "dotted", "longdash")
(plot_rt_repetition_PWA <- descriptives %>%
  filter(group=="PWA" | group=="young") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
    geom="line", size = 0.5) +
  scale_linetype_manual(values=c("solid", "dashed",
    "dotted", "longdash"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000", "gray"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
    width =.1) +
  apatheme +
  scale_y_continuous(limits = c(1040, 1450),
    breaks =seq(1050,1450, by = 50)) +
  labs(x="Ordinal Position ",y ="RT (ms)", colour="Session",
    linetype="Session",
    title = "PWA vs Young Group") +

```

```


theme(
  axis.title.y = element_text(margin = margin(0,10,0,0)),
  axis.title.x = element_text(margin = margin(10,0,0,0)),
  legend.key.width = unit(1, "cm"),
  legend.position="none")+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.

## PWA vs Young Group



```

(plot_rt_repetition_control <- descriptives %>%
  filter(group=="control" | group=="young") %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
    geom="line", size = 0.5) +
  scale_linetype_manual(values=c("solid", "dashed", "dotted", "longdash"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000", "gray"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
    width =.1) +
  apatheme+
  scale_y_continuous(limits = c(1040, 1450),

```

```


breaks =seq(1050,1450, by = 50)) +
labs(x="Ordinal Position ",y ="RT (ms)", colour="Session",
linetype="Session",
title = "Control vs Young Group") +
theme(
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"))+
guides(color=guide_legend(
override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none")

```

```
## Scale for linetype is already present.
```

```
## Adding another scale for linetype, which will replace the existing scale.
```

## Control vs Young Group



```

plots <- cowplot::plot_grid(
  plot_rt_repetition_PWA,plot_rt_repetition_control,
  nrow = 1, ncol=2, rel_widths = c(0.7,1), #rel_height = c(1,1),
  margin(1,1,1,1),
  labels = c("A", "B"),label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x=-0.03)

```

```

## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunit_v2 into a grob.

```

```
filename <- "CSI_online_aphasia_spoken_comparison-to-young.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 25, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

## Appendix

### List of stimuli

```
df %>% arrange(category) %>%
  group_by(category, item, correct, AR) %>% count()
```

## # A tibble: 1,657 x 5

## # Groups: category, item, correct, AR [1,657]

##	category	item	correct	AR	n
##	<chr>	<chr>	<chr>	<chr>	<int>
## 1	Aufbewahrung	kleiderschrank	0	Br [e.o.r.]	1
## 2	Aufbewahrung	kleiderschrank	0	Greu [e.o.r.]	1
## 3	Aufbewahrung	kleiderschrank	0	Kreider [e.o.r.]	1
## 4	Aufbewahrung	kleiderschrank	0	NR	9
## 5	Aufbewahrung	kleiderschrank	0	Schra e Schra e	1
## 6	Aufbewahrung	kleiderschrank	1	<NA>	11
## 7	Aufbewahrung	kleiderschrank	1.1	Holzschrank	1
## 8	Aufbewahrung	kleiderschrank	1.1	Schrank	92
## 9	Aufbewahrung	kleiderschrank	1.1	Schrank Gleicher Schrank	1
## 10	Aufbewahrung	kleiderschrank	1.2	Schran Schank	1

## # i 1,647 more rows

### Response times and error rates by participant and category

RTs by subject Line graph for each participant:

```
modeloutput <- coef(m2)$subject
means_final_subject <- df_RTs %>%
  summarySEwithin(., "VOT", withinvars = c("subject", "PosOr", "session"),
    betweenvars="group")
means_final <- df_RTs %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("PosOr"),
    na.rm = T)

for(i in 1:nrow(means_final_subject)) {
  means_final_subject$grandmean[i] <-
    means_final$VOT[means_final$PosOr == means_final_subject$PosOr[i]] -
    means_final$VOT[means_final$PosOr == 1]
```

```

means_final_subject$normalizedRT[i] <-
  means_final_subject$VOT[i] -
  means_final_subject$VOT[means_final_subject$subject ==
    means_final_subject$subject[i] &
    means_final_subject$PosOr == 1 &
    means_final_subject$session == 1]

# prepare for ordering
means_final_subject$effect[i] <-
  round(modeloutput$PosOr.cont[means_final_subject$subject[i]] +
    modeloutput$re1.PosOr.cont[means_final_subject$subject[i]] +
    modeloutput$re2.PosOr.cont[means_final_subject$subject[i]],2)
}

means_final_subject <- means_final_subject[
  order(desc(means_final_subject$group),
    desc(means_final_subject$effect)),]
means_final_subject$effect <-
  as.factor(round(means_final_subject$effect, 2))
means_final_subject$effect <-
  factor(means_final_subject$effect,
    levels=rev(levels(means_final_subject$effect )))

# add participant number
means_final_subject <- means_final_subject %>%
  mutate(subject_en = case_when(
    group == "PWA" ~ paste0("PWA ",
      substr(as.character(
        means_final_subject$subject), 2,3),
      "\n(",effect,")",sep=''),
    group == "control" ~ paste0("Control ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(",effect,")",sep='')) %>%
  mutate(subject_en = case_when(subject_en=="PWA 04\n(29.1)" ~
    "PWA 04\n(29.10)",
    subject_en=="PWA 16\n(24.3)" ~
    "PWA 16\n(24.30)",
    subject_en=="Participant 12\n(38.3)" ~
    "Participant 12\n(38.30)",
    subject_en=="Control 12\n(17.5)" ~
    "Control 12\n(17.50)",
    TRUE~subject_en)) %>%
  mutate(subject_en=factor(subject_en,levels=c(
    "PWA 03\n(42.36)","PWA 05\n(37.11)","PWA 20\n(33.71)",
    "PWA 13\n(32.42)","PWA 07\n(29.28)","PWA 08\n(29.13)",
    "PWA 04\n(29.10)","PWA 12\n(27.84)","PWA 16\n(24.30)",
    "PWA 18\n(23.59)","PWA 06\n(23.31)", "PWA 09\n(19.86)",
    "PWA 14\n(18.04)","PWA 11\n(16.91)","PWA 17\n(16.18)",
    "PWA 10\n(12.79)","PWA 19\n(10.94)","PWA 02\n(4.11)",
    "PWA 01\n(0.71)","PWA 15\n(0.02)","Control 09\n(44.58)",
    "Control 17\n(41.22)","Control 10\n(34.06)","Control 20\n(29.22)",
    "Control 02\n(26.54)","Control 07\n(26.11)","Control 01\n(23.97)",

```


```

    "Control 05\n(22.77)", "Control 03\n(22.53)", "Control 15\n(21.83)",
    "Control 19\n(21.75)", "Control 13\n(21.66)", "Control 14\n(20.13)",
    "Control 04\n(19.86)", "Control 08\n(17.97)", "Control 12\n(17.50)",
    "Control 11\n(13.73)", "Control 06\n(12.86)", "Control 16\n(12.39)",
    "Control 18\n(9.51)" )))

# Plotting
(plot_rt_subject <- means_final_subject %>%
  ggplot(., aes(x=PosOr,y=normalizedRT,
               color=session, group=session, na.rm=T)) +
  geom_point(size =1, color = 'black') +
  geom_line(aes(x=PosOr,y=normalizedRT, color=session, linetype="c"),
            size = 0.5) +
  geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
            group = 1,size = 0.8)+
  geom_errorbar(aes(ymin=normalizedRT-se, ymax=normalizedRT+se),
                width =.1) +
  scale_color_manual(name="Session",
                    values=c(
                      "#0072B2", "#E69F00", "#000000", "dark gray"),
                    labels=c(
                      "1", "2", "3",
                      "Grand Mean (across subjects, sessions, groups)")) +
  scale_linetype_manual(name="", values=c("c"="solid", "d"="dashed"),
                       labels=c("Participant mean",
                                "Grand Mean"))+

  apatheme+
  labs(x="Ordinal Position", y = "Normalized RTs (ms)") +
  facet_wrap(means_final_subject$subject_en, scales='free', ncol=8)+
  scale_y_continuous(limits = c(-800, 800),
                    breaks = c(-600,-400,-200,0,200,400,600)) +
  scale_x_discrete(breaks=c(1,2,3,4,5))+
  theme(legend.position = "bottom"))

```



— 2 — 3 — Grand Mean (across subjects, sessions, groups) — Partici

```
filename <- "CSI_online_aphasia_effect_by_participant.pdf"
ggsave(plot_rt_subject, filename =
  here::here("results", "figures", filename),
  width = 34, height = 26, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))

## save for exploratory analyses:
means_final_subject_RTs <- means_final_subject
```

Get an idea of the variance of the ordinal position effect between groups

```
# # sd of ordinal position effects based on model estimate
# means_final_subject %>% group_by(group, session) %>%
#   summarise(mean_effect=mean(effect), sd_effect=sd(effect))
# means_final_subject %>%
#   summarySEwithin(., "effect", withinvars = c("PosOr", "session"),
#     betweenvars="group")
# # sd of raw ordinal position effect
# means_final_subject <- means_final_subject %>% arrange(subject, group, session, PosOr)
# for(i in 1:nrow(means_final_subject)) {
#   if(means_final_subject$PosOr[i]==1){
#     means_final_subject$raw_ordpos[i] <- NA
#   } else {
#     means_final_subject$raw_ordpos[i] <-
```



```

#       means_final_subject$VOT[i] - means_final_subject$VOT[i-1]
#   }
# }
# means_final_subject %>%
#   summarySEwithin(., "raw_ordpos", withinvars = c("session"),
#                   betweenvars="group", na.rm=T)

```

**RTs by category** Line graph for each category:

```

modeloutput <- coef(m2)$category
means_final_category <- df_RTs %>%
  summarySEwithin(., "VOT", withinvars =
    c("category", "PosOr", "session"))

```

## Automatically converting the following non-factors to factors: category

```

means_final <- df_RTs %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "category",
    withinvars = c("PosOr"),
    na.rm = T)

for(i in 1:nrow(means_final_category)) {
  means_final_category$grandmean[i] <-
    means_final$VOT[means_final$PosOr == means_final_category$PosOr[i]] -
    means_final$VOT[means_final$PosOr == 1]
  means_final_category$normalizedRT[i] <-
    means_final_category$VOT[i] -
    means_final_category$VOT[means_final_category$category == means_final_category$category[i] & means_
      means_final_category$session == 1]

  # prepare for ordering
  means_final_category$effect[i] <-
    modeloutput$PosOr.cont[means_final_category$category[i]] +
    modeloutput$re2.PosOr.cont[means_final_category$category[i]]
}

means_final_category <- means_final_category[
  order(desc(means_final_category$effect)),]
means_final_category$effect <-
  as.factor(round(means_final_category$effect, 2))
means_final_category$effect <-
  factor(means_final_category$effect,
    levels=rev(levels(means_final_category$effect)))
means_final_category$category <- factor(
  means_final_category$category, levels=c(
    "Insekten", "Sitzen", "Kochen", "Jacken",
    "Obst", "Trinkgefäße", "Wasser", "Heimwerker",
    "Küche", "Fische", "Aufbewahrung",
    "Büro", "Bauernhof", "Raubtiere", "Huftiere", "Gemüse",
    "Körperteile", "Vögel", "Instrumente", "Blumen",
    "Gebäude", "Schmuck", "Strasse", "Süssigkeiten"))

# order category levels by effect size

```

```

means_final_category$category <- factor(
  means_final_category$category, levels=c(
    "Gebäude", "Schmuck", "Raubtiere", "Sitzen", "Jacken",
    "Blumen", "Huftiere", "Wasser", "Trinkgefässe", "Küche",
    "Insekten", "Büro", "Bauernhof", "Strasse", "Kochen",
    "Gemüse", "Körperteile", "Fische", "Heimwerker", "Aufbewahrung",
    "Obst", "Vögel", "Instrumente", "Süssigkeiten"))
# give categories English names and combine with effect size
means_final_category <- means_final_category %>%
  mutate(category_en = case_when(
    category == "Aufbewahrung" ~ paste0(
      "Storage\n\n(", effect, ")", sep=''),
    category == "Bauernhof" ~ paste0(
      "Farming\ntools\n(", effect, ")", sep=''),
    category == "Blumen" ~ paste0(
      "Flowers\n\n(", effect, ")", sep=''),
    category == "Büro" ~ paste0(
      "Office\ntools\n(", effect, ")", sep=''),
    category == "Fische" ~ paste0(
      "Fish\n\n(", effect, ")", sep=''),
    category == "Gebäude" ~ paste0(
      "Buildings\n\n(", effect, ")", sep=''),
    category == "Gemüse" ~ paste0(
      "Vegetables\n\n(", effect, ")", sep=''),
    category == "Heimwerker" ~ paste0(
      "Carpenter.s\ntools\n(", effect, ")", sep=''),
    category == "Huftiere" ~ paste0(
      "Hoofed\nanimals\n(", effect, ")", sep=''),
    category == "Insekten" ~ paste0(
      "Insects\n\n(", effect, ")", sep=''),
    category == "Instrumente" ~ paste0(
      "Instru-\nments\n(", effect, ")", sep=''),
    category == "Jacken" ~ paste0(
      "Jackets\n\n(", effect, ")", sep=''),
    category == "Kochen" ~ paste0(
      "Cooking\nequipment\n(", effect, ")", sep=''),
    category == "Körperteile" ~ paste0(
      "Body parts\n\n(", effect, ")", sep=''),
    category == "Küche" ~ paste0(
      "Kitchen\nfurniture\n(", effect, ")", sep=''),
    category == "Obst" ~ paste0(
      "Fruits\n\n(", effect, ")", sep=''),
    category == "Raubtiere" ~ paste0(
      "Predators\n\n(", effect, ")", sep=''),
    category == "Schmuck" ~ paste0(
      "Jewelry\n\n(", effect, ")", sep=''),
    category == "Sitzen" ~ paste0(
      "Seating\nfurniture\n(", effect, ")", sep=''),
    category == "Strasse" ~ paste0(
      "Street\nvehicles\n(", effect, ")", sep=''),
    category == "Süssigkeiten" ~ paste0(
      "Sweets\n\n(", effect, ")", sep=''),
    category == "Trinkgefässe" ~ paste0(


```

```

    "Drinking\\nvessels\\n(", effect, ")", sep=''),
category == "Vögel" ~ paste0(
  "Birds\\n\\n(", effect, ")", sep=''),
category == "Wasser" ~ paste0(
  "Water\\nvehicles\\n(", effect, ")", sep='')))) %>%
mutate(category_en = case_when(category_en=="Insects\\n\\n(35.4)" ~
  "Insects\\n\\n(35.40)",
  category_en=="Jackets\\n\\n(27.9)" ~
  "Jackets\\n\\n(27.90)" ,
  TRUE~category_en)) %>%
mutate(category_en=factor(category_en,levels=c(
  "Insects\\n\\n(35.40)", "Seating\\nfurniture\\n(33.45)",
  "Cooking\\nequipment\\n(28.45)", "Jackets\\n\\n(27.90)",
  "Fruits\\n\\n(27.77)", "Drinking\\nvessels\\n(26.47)",
  "Water\\nvehicles\\n(26.44)", "Carpenter.s\\ntools\\n(26.18)",
  "Kitchen\\nfurniture\\n(25.76)", "Fish\\n\\n(23.97)",
  "Storage\\n\\n(23.56)", "Office\\ntools\\n(23.13)",
  "Farming\\ntools\\n(22.55)", "Predators\\n\\n(21.51)",
  "Hoofed\\nanimals\\n(21.18)", "Vegetables\\n\\n(20.73)" ,
  "Body parts\\n\\n(19.93)", "Birds\\n\\n(19.33)",
  "Instru-\\nments\\n(18.27)", "Flowers\\n\\n(15.53)",
  "Buildings\\n\\n(13.56)", "Jewelry\\n\\n(12.87)",
  "Street\\nvehicles\\n(12.76)", "Sweets\\n\\n(11.11)"))))

# Plotting
(plot_rt_category <- means_final_category %>%
  ggplot(., aes(x=PosOr,y=normalizedRT, color=session,
    group=session, na.rm=T)) +
  geom_point(size =1) +
  geom_line(aes(x=PosOr,y=normalizedRT, color=session, linetype="c"),
    size = 0.5) +
  geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
    group = 1,size = 0.8)+
  geom_errorbar(aes(ymin=normalizedRT-se, ymax=normalizedRT+se),
    width =.1) +
  scale_color_manual(name="Session",
    values=c("#0072B2", "#E69F00", "#000000",
      "dark gray"),
    labels=c("1", "2", "3", "Grand Mean")) +
  scale_linetype_manual(name="",values=c("c"="solid","d"="dashed"),
    labels=c("Category mean (across groups)",
      "Grand Mean"))+
  apatheme+
  labs(x="Ordinal Position",y ="Normalized RTs (ms)") +
  facet_wrap(means_final_category$category_en, scales='free', ncol=8)+
  scale_y_continuous(limits = c(-800, 800),
    breaks = c(-600,-400,-200,0,200,400,600)) +
  scale_x_discrete(breaks=c(1,2,3,4,5))+
  theme(legend.position = "bottom"))

```



1 — 1 — 2 — 3 — Grand Mean — Category mean (across groups)

```
filename <- "CSI_online_aphasia_effect_by_category.pdf"
ggsave(plot_rt_category, filename =
  here::here("results", "figures", filename),
  width = 26, height = 20, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

Combine both

```
plots <- cowplot::plot_grid(plot_rt_subject, plot_rt_category,
  nrow = 2, ncol = 1, #rel_widths = c(1,1),
  rel_heights = c(1,0.6),
  margin(1,1,1,1),
  labels = c("A", "B"), label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x = 0)
```

```
## Warning: Removed 1 rows containing missing values ('geom_point()').
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_RT_s-by-category-and-subject.pdf"
ggsave(plots, filename =
```

```

    here::here("results", "figures", filename),
    width = 30, height = 50, units = "cm",
    dpi = 300, device = cairo_pdf)

```

Errors by subject Line graph for each participant:

```

m2_error <- readRDS(here::here(
  "results", "tables",
  "CSI_online_aphasia_SessionxGroup_glmml_errors.RDS"))
modeloutput <- coef(m2_error)$subject
means_final_subject <- df_errors %>%
  summarySEwithin(
    .,"error_class",withinvars = c("subject","PosOr", "session"),
    betweenvars="group")
means_final<- df_errors %>%
  Rmisc::summarySEwithin(., "error_class",idvar = "subject",
    withinvars = c("PosOr"),
    na.rm = T)

for(i in 1:nrow(means_final_subject)) {
  means_final_subject$grandmean[i] <-
    means_final$error_class[means_final$PosOr ==
      means_final_subject$PosOr[i]] -
    means_final$error_class[means_final$PosOr== 1]
  means_final_subject$normalizedRT[i] <-
    means_final_subject$error_class[i] -
    means_final_subject$error_class[means_final_subject$subject ==
      means_final_subject$subject[i] &
      means_final_subject$PosOr == 1 &
      means_final_subject$session == 1]

  # prepare for ordering
  means_final_subject$effect[i] <-
    modeloutput$PosOr.cont[means_final_subject$subject[i]] #+
    # modeloutput$re1.PosOr.cont[means_final_subject$subject[i]]
}

means_final_subject <- means_final_subject[order(desc(means_final_subject$group), desc(means_final_subj
means_final_subject$effect <-
  as.factor(round(means_final_subject$effect, 2))
means_final_subject$effect <-
  factor(means_final_subject$effect,
    levels=rev(levels(means_final_subject$effect )))

# add participant number
means_final_subject <- means_final_subject %>%
  mutate(effect=round(as.numeric(as.character(effect)),2)) %>%
  mutate(subject_en = case_when(
    group == "PWA" & as.numeric(as.character(effect)) == 0.10~
      paste0("PWA ",
        substr(as.character(means_final_subject$subject), 2,3),
        "\n(",effect,"0)",sep=''),
    group == "control" & as.numeric(as.character(effect)) == 0.10~

```

```

paste0("Control ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(",effect,"0)",sep=''),
group == "PWA" & as.numeric(as.character(effect)) >= 0.01~
paste0("PWA ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(",effect,")",sep=''),
group == "control"& as.numeric(as.character(effect)) >= 0.01 ~
paste0("Control ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(",effect,")",sep=''),
group == "PWA" & as.numeric(as.character(effect)) < 0.01~
paste0("PWA ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(< .01)",sep=''),
group == "control"& as.numeric(as.character(effect)) < 0.01 ~
paste0("Control ",
      substr(as.character(means_final_subject$subject), 2,3),
      "\n(< .01)",sep='')) %>%
mutate(subject_en=factor(subject_en))
# mutate(subject_en=factor(subject_en, levels=c(
#   "PWA 12\n(0.24)", "PWA 07\n(0.16)", "PWA 05\n(0.16)", "PWA 08\n(0.16)",
#   "PWA 10\n(0.13)", "PWA 18\n(0.12)", "PWA 04\n(0.12)", "PWA 19\n(0.12)",
#   "PWA 03\n(0.10)", "PWA 06\n(0.07)", "PWA 15\n(0.06)", "PWA 20\n(0.05)",
#   "PWA 16\n(0.05)", "PWA 14\n(0.03)", "PWA 13\n(0.03)", "PWA 02\n(< .01)",
#   "PWA 17\n(< .01)", "PWA 09\n(< .01)", "PWA 01\n(< .01)", "PWA 11\n(< .01)",
#   "Control 02\n(0.13)", "Control 05\n(0.13)", "Control 07\n(0.11)",
#   "Control 15\n(0.10)", "Control 10\n(0.10)", "Control 16\n(0.09)",
#   "Control 01\n(0.09)", "Control 04\n(0.08)", "Control 20\n(0.08)",
#   "Control 09\n(0.07)", "Control 19\n(0.07)", "Control 12\n(0.07)",
#   "Control 06\n(0.07)", "Control 14\n(0.06)", "Control 08\n(0.05)",
#   "Control 13\n(0.04)", "Control 11\n(0.03)", "Control 17\n(0.03)",
#   "Control 03\n(0.02)", "Control 18\n(0.01)"))))


# Plotting
(plot_error_subject <- means_final_subject %>%
  mutate(session=case_when(session=="1" ~ "day 1",
    session=="2" ~ "day 2",
    session=="3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr,y=normalizedRT, color=session,
    group=session, na.rm=T)) +
  geom_point(size =1, color = 'black') +
  geom_line(aes(x=PosOr,y=normalizedRT, color=session, linetype="c"),
    size = 0.5) +
  geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
    group = 1,size = 0.8)+
  geom_errorbar(aes(ymin=normalizedRT-se, ymax=normalizedRT+se), width =.1) +
  scale_color_manual(name="Session",
    values=c("#0072B2", "#E69F00", "#000000",
      "dark gray"),
    labels=c("1", "2", "3",
      "Grand Mean (across subjects, sessions, groups)")) +
  scale_linetype_manual(name="",values=c("c"="solid","d"="dashed"),

```

```

labels=c("Participant mean",
         "Grand Mean"))+
apatheme+
labs(x="Ordinal Position",y ="Error Rate") +
facet_wrap(means_final_subject$subject_en, scales='free', ncol=8)+
scale_y_continuous(limits = c(-0.5, 0.5),
                   breaks = c(-0.4,-0.2,0,0.2,0.4)) +
scale_x_discrete(breaks=c(1,2,3,4,5))+
theme(legend.position = "bottom")

```



— 2 — 3 — Grand Mean (across subjects, sessions, groups) — Participant mean

```

filename <- "CSI_online_aphasia_errors_by_participant.pdf"
ggsave(plot_error_subject, filename =
  here::here("results", "figures", filename),
  width = 34, height = 26, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))

## save for exploratory analyses:
means_final_subject_errors <- means_final_subject

```

Errors by category Line graph for each participant:

```

m2_error <- readRDS(here::here(
  "results", "tables",

```

```

"CSI_online_aphasia_SessionxGroup_glmml_errors.RDS"))
modeloutput <- coef(m2_error)$category
means_final_category <- df_errors %>%
  summarySEwithin(., "error_class",
    withinvars = c("category", "PosOr", "session"))

## Automatically converting the following non-factors to factors: category

means_final <- df_errors %>%
  Rmisc::summarySEwithin(., "error_class", idvar = "category",
    withinvars = c("PosOr", "#", "session"),
    #betweenvars = "group",
    na.rm = T)

for(i in 1:nrow(means_final_category)) {
  means_final_category$grandmean[i] <-
    means_final$error_class[means_final$PosOr ==
      means_final_category$PosOr[i]] -
    means_final$error_class[means_final$PosOr == 1]
  means_final_category$normalized_error[i] <-
    means_final_category$error_class[i] -
    means_final_category$error_class[
      means_final_category$category == means_final_category$category[i] &
      means_final_category$PosOr == 1 &
      means_final_category$session == 1]

  # prepare for ordering
  means_final_category$effect[i] <-
    modeloutput$PosOr.cont[means_final_category$category[i]]# +
    # modeloutput$re1.PosOr.cont+
    # modeloutput$re2.group2.1[means_final_category$category[i]]
}

means_final_category <-
  means_final_category[order(desc(means_final_category$effect)),]
means_final_category$effect <-
  as.factor(round(means_final_category$effect, 2))
means_final_category$effect <-
  factor(means_final_category$effect,
    levels=rev(levels(means_final_category$effect)))

means_final_category$category <- factor(
  means_final_category$category, levels=c(
    "Insekten", "Sitzen", "Kochen", "Jacken",
    "Obst", "Trinkgefäße", "Wasser", "Heimwerker",
    "Küche", "Fische", "Aufbewahrung",
    "Büro", "Bauernhof", "Raubtiere", "Huftiere", "Gemüse",
    "Körperteile", "Vögel", "Instrumente", "Blumen",
    "Gebäude", "Schmuck", "Strasse", "Süssigkeiten"))

# give categories English names and combine with effect size
means_final_category <- means_final_category %>%
  mutate(category_en =
    case_when(

```



```

category == "Aufbewahrung" ~ "Storage",
category == "Bauernhof" ~ "Farming\ntools",
category == "Blumen" ~ "Flowers",
category == "Büro" ~ "Office\ntools",
category == "Fische" ~ "Fish",
category == "Gebäude" ~ "Buildings",
category == "Gemüse" ~ "Vegetables",
category == "Heimwerker" ~ "Carpenter.s\ntools",
category == "Huftiere" ~ "Hoofed\nanimals",
category == "Insekten" ~ "Insects",
category == "Instrumente" ~ "Instruments",
category == "Jacken" ~ "Jackets",
category == "Kochen" ~ "Cooking\nequipment",
category == "Körperteile" ~ "Body part",
category == "Küche" ~ "Kitchen\nfurniture",
category == "Obst" ~ "Fruits",
category == "Raubtiere" ~ "Predators",
category == "Schmuck" ~ "Jewelry",
category == "Sitzen" ~ "Seating\nfurniture",
category == "Strasse" ~ "Street\nvehicles",
category == "Süssigkeiten" ~ "Sweets",
category == "Trinkgefässe" ~ "Drinking\nvessels",
category == "Vögel" ~ "Birds",
category == "Wasser" ~ "Water\nvehicles")) %>%
# mutate(category_en = case_when(
#   as.numeric(as.character(effect)) == 0.10~ paste0(category_en, " ",
#   #   "\n(",effect,"0)",sep=''),
#   as.numeric(as.character(effect)) >= 0.01~ paste0(category_en, " ",
#   #   "\n(",effect,")",sep=''),
#   as.numeric(as.character(effect)) < 0.01~ paste0(category_en, " ",
#   #   "\n(< .01)",sep=''),
#   TRUE ~ paste0(category_en, " ",
#   #   "\n(",effect,")",sep='')))) %>%
mutate(category_en=factor(category_en))


# Plotting
(plot_error_category <- means_final_category %>%
  mutate(session=case_when(session=="1" ~ "day 1",
    session=="2" ~ "day 2",
    session=="3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr,y=normalized_error, color=session, group=session, na.rm=T)) +
  geom_point(size =1, color = 'black') +
  geom_line(aes(x=PosOr,y=normalized_error, color=session,
    linetype="c"),
    size = 0.5) +
  geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
    group = 1,size = 0.8)+
  geom_errorbar(aes(ymin=normalized_error-se, ymax=normalized_error+se),
    width =.1) +
  scale_color_manual(name="Session",
    values=c("#0072B2", "#E69F00", "#000000",
      "dark gray"),
    labels=c("1", "2", "3",

```

```

    "Grand Mean (across categories, sessions, groups)")) +
  scale_linetype_manual(name="", values=c("c"="solid", "d"="dashed"),
    labels=c("Category mean",
      "Grand Mean")))+
  apatheme+
  labs(x="Ordinal Position", y="Error Rate") +
  facet_wrap(means_final_category$category_en, scales='free', ncol=8)+
  scale_y_continuous(limits = c(-0.5, 0.5),
    breaks = c(-0.4, -0.2, 0, 0.2, 0.4)) +
  scale_x_discrete(breaks=c(1,2,3,4,5))+
  theme(legend.position = "bottom")

```



- 2 — 3 — Grand Mean (across categories, sessions, groups) — Cate

```

filename <- "CSI_online_aphasia_errors_by_category.pdf"
ggsave(plot_error_category, filename =
  here::here("results", "figures", filename),
  width = 26, height = 20, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))

```

Combine both

```

plots <- cowplot::plot_grid(plot_error_subject, plot_error_category,
  nrow = 2, ncol=1,
  rel_heights = c(1,0.6),
  margin(1,1,1,1),

```

```

labels = c("A", "B"), label_size = 34,
          label_fontfamily = "Helvetica", label_y = 1.01,
          label_x=0)

```

```

## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.

```

```

filename <- "CSI_online_aphasia_spoken_errors-by-category-and-subject.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 30, height = 50, units = "cm",
  dpi = 300, device = cairo_pdf)

```

## Exploratory nested model with group and ordinal position nested into session

Take the same random structure as in the main model

```

# m2_lmm_n <- lmer(lVOT ~ group/session/PosOr.cont +
#                 (PosOr.cont+session|subject) +
#                 (PosOr.cont+group|category),
#                 data = df_RTs,
#                 control=lmerControl(optimizer = "bobyqa",
#                                     optCtrl = list(maxfun = 2e5)))
# summary(m2_lmm_n)

m2_lmm_n <- lmer(lVOT ~ session/(group*PosOr.cont) +
  (PosOr.cont+session|subject) +
  (PosOr.cont+group|category),
  data = df_RTs,
  control=lmerControl(optimizer = "bobyqa",
                      optCtrl = list(maxfun = 2e5)))
summary(m2_lmm_n)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ session/(group * PosOr.cont) + (PosOr.cont + session |
##          subject) + (PosOr.cont + group | category)
## Data: df_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1158.2
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -4.8980 -0.6647 -0.1747  0.4804  5.6443
##
## Random effects:
##   Groups   Name                Variance  Std.Dev. Corr
##   subject  (Intercept)  0.03572288  0.189005
##           PosOr.cont    0.00010406  0.010201  0.18
##           session2      0.00339912  0.058302 -0.13  0.24

```

```

##          session3    0.00406332 0.063744 -0.49  0.26  0.64
## category (Intercept) 0.00884984 0.094074
##          Pos0r.cont  0.00002358 0.004856 0.07
##          group2-1    0.00090450 0.030075 0.08  0.16
## Residual              0.06154884 0.248090
## Number of obs: 12455, groups:  subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)      7.116562   0.035604  58.495842 199.884
## session2        -0.076082   0.010856  38.393028  -7.009
## session3        -0.089211   0.011561  36.616625  -7.717
## session1:group2-1  0.172863   0.065639  38.187285   2.634
## session2:group2-1  0.147257   0.062950  38.261949   2.339
## session3:group2-1  0.152784   0.055622  38.529375   2.747
## session1:Pos0r.cont 0.014161   0.003397 104.345986   4.168
## session2:Pos0r.cont 0.018796   0.003349  98.553423   5.612
## session3:Pos0r.cont 0.017810   0.003310  94.964792   5.380
## session1:group2-1:Pos0r.cont 0.001525   0.006499 151.024051   0.235
## session2:group2-1:Pos0r.cont 0.014830   0.006398 141.844633   2.318
## session3:group2-1:Pos0r.cont 0.004620   0.006317 136.892022   0.731
##
##              Pr(>|t|)
## (Intercept)      < 0.0000000000000002 ***
## session2          0.00000002267 ***
## session3          0.00000000345 ***
## session1:group2-1  0.0121 *
## session2:group2-1  0.0246 *
## session3:group2-1  0.0091 **
## session1:Pos0r.cont 0.00006349491 ***
## session2:Pos0r.cont 0.00000018378 ***
## session3:Pos0r.cont 0.00000053431 ***
## session1:group2-1:Pos0r.cont 0.8148
## session2:group2-1:Pos0r.cont 0.0219 *
## session3:group2-1:Pos0r.cont 0.4658
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##          (Intr) sessn2 sessn3 ss1:2-1 ss2:2-1 ss3:2-1 s1:P0. s2:P0. s3:P0.
## session2   -0.096
## session3   -0.361  0.612
## sssn1:gr2-1  0.006 -0.009 -0.009
## sssn2:gr2-1  0.006  0.008  0.000  0.944
## sssn3:gr2-1  0.006  0.000  0.006  0.941  0.952
## sssn1:Ps0r.  0.084  0.095  0.108  0.006  0.005  0.006
## sssn2:Ps0r.  0.085  0.102  0.113  0.004  0.006  0.006  0.323
## sssn3:Ps0r.  0.085  0.101  0.114  0.004  0.005  0.007  0.326  0.331
## ss1:2-1:P0.  0.001 -0.004 -0.003  0.057  0.094  0.115  0.112  0.009  0.007
## ss2:2-1:P0.  0.001  0.005  0.002  0.057  0.096  0.117  0.009  0.088  0.008
## ss3:2-1:P0.  0.001  0.002  0.005  0.058  0.097  0.118  0.007  0.008  0.079
##
##          s1:2-1: s2:2-1:
## session2
## session3
## sssn1:gr2-1

```

```
## sssn2:gr2-1
## sssn3:gr2-1
## sssn1:PsOr.
## sssn2:PsOr.
## sssn3:PsOr.
## ss1:2-1:P0.
## ss2:2-1:P0. 0.259
## ss3:2-1:P0. 0.261 0.266
```

---

## Exploratory analyses

We conducted several exploratory analyses to assess the stability of our effects, especially because we deviated from the pre-planned GLMMs for RT analyses.

Here, we report additional analyses that were suggested by reviewers

### Inspecting participants with long or short time since onset of lesion

Subject 112 was tested 4 months after onset, subject 103 was tested 7 months after onset, and subject 120 was tested 259 months after onset

```
means_final_subject_RTs_r <-
  means_final_subject_RTs %>% filter(subject %in%
                                     c(112, 103, 120)) %>%
  droplevels() %>%
  mutate(subject_en_mpo=case_when(
    subject_en=="PWA 03\n(42.36)"~"PWA 03 (7 MPO)\n(42.36ms)",
    subject_en=="PWA 20\n(33.71)"~"PWA 20 (259 MPO)\n(33.71ms)",
    subject_en=="PWA 12\n(27.84)"~"PWA 12 (4 MPO)\n(27.84ms)",
  )) %>%
  mutate(subject_en_mpo=factor(subject_en_mpo, levels =
    c("PWA 12 (4 MPO)\n(27.84ms)",
      "PWA 03 (7 MPO)\n(42.36ms)",
      "PWA 20 (259 MPO)\n(33.71ms)"))))

means_final_subject_errors_r <-
  means_final_subject_errors %>%
  filter(subject %in% c(112, 103, 120)) %>% droplevels() %>%
  mutate(subject_en_mpo=case_when(
    subject_en=="PWA 03\n(0.10)"~"PWA 03 (7 MPO)\n(0.10)",
    subject_en=="PWA 20\n(0.06)"~"PWA 20 (259 MPO)\n(0.06)",
    subject_en=="PWA 12\n(0.27)"~"PWA 12 (4 MPO)\n(0.27)",
  )) %>%
  mutate(subject_en_mpo=factor(subject_en_mpo, levels =
    c("PWA 12 (4 MPO)\n(0.27)",
      "PWA 03 (7 MPO)\n(0.10)",
      "PWA 20 (259 MPO)\n(0.06)"))))
```

```


### change grand mean to mean group effect
modeloutput <- coef(m2)$subject

## extract plots
(plot_rt_subject_r <- means_final_subject_RTs_r %>%
  ggplot(., aes(x=PosOr,y=normalizedRT,
               color=session, group=session, na.rm=T)) +
  geom_point(size =1, color = 'black') +
  geom_line(aes(x=PosOr,y=normalizedRT, color=session,
               linetype="c"),
            size = 0.5) +
  # geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
  #           group = 1,size = 0.8)+
  geom_errorbar(aes(ymin=normalizedRT-se, ymax=normalizedRT+se),
               width =.1) +
  guides(linetype="none") +
  scale_color_manual(name="Session",
                    values=c(
                      "#0072B2", "#E69F00", "#000000",
                      "dark gray"),
                    labels=c(
                      "1", "2", "3")) + #,
  # "Grand Mean (across subjects, sessions, groups)")) +
  # scale_linetype_manual(name="", values=c("c"="solid", "d"="dashed"),
  # labels=c("Participant mean",
  # "Grand Mean")))+
  apatheme+
  labs(x="Ordinal Position", y = "Normalized RTs (ms)") +
  facet_wrap(means_final_subject_RTs_r$subject_en_mpo,
            scales='free', ncol=3)+
  scale_y_continuous(limits = c(-800, 800),
                    breaks = c(-600,-400,-200,0,200,400,600)) +
  scale_x_discrete(breaks=c(1,2,3,4,5))+
  theme(legend.position = "bottom"))

```


Extract by participant plots for these participants and plot

```
## Warning: Removed 1 rows containing missing values ('geom_point()').
```



```
(plot_error_subject_r <- means_final_subject_errors_r %>%
  mutate(session=case_when(session=="1" ~ "day 1",
    session=="2" ~ "day 2",
    session=="3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr,y=normalizedRT, color=session,
    group=session, na.rm=T)) +
  geom_point(size =1, color = 'black') +
  geom_line(aes(x=PosOr,y=normalizedRT, color=session, linetype="c"),
    size = 0.5) +
  geom_errorbar(aes(ymin=normalizedRT-se, ymax=normalizedRT+se), width =.1) +
  # geom_line(aes(x=PosOr,y=grandmean, color="b", linetype="d"),
  #   group = 1,size = 0.8)+
  scale_color_manual(name="Session",
    breaks=c("day 1", "day 2", "day 8"), #, "b"),
    values=c("#0072B2", "#E69F00", "#000000"),#,
    # "dark gray"),
    labels=c("1", "2", "3")) + #,
    # "Grand Mean (across subjects, sessions, groups)")) +
  #scale_linetype_manual(name="",
    #values=c("c"="solid", "d"="dashed"),
    #labels=c("Participant mean",
    # "Grand Mean")))+
  apatheme+
  labs(x="Ordinal Position",y ="Error Rate") +
  facet_wrap(means_final_subject_errors_r$subject_en_mpo, scales='free', ncol=3)+
  scale_y_continuous(limits = c(-0.5, 0.5),
```

```
breaks = c(-0.4,-0.2,0,0.2,0.4)) +
scale_x_discrete(breaks=c(1,2,3,4,5))+
guides(linetype="none") +
theme(legend.position = "bottom"))
```



```
## combine both
plots <- cowplot::plot_grid(plot_rt_subject_r, plot_error_subject_r,
  nrow = 2, ncol=1,
  rel_heights = c(1,1),
  margin(1,1,1,1),
  labels = c("A", "B"), label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x=0)
```

```
## Warning: Removed 1 rows containing missing values ('geom_point()').
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_errors-by-category-and-subject_MPO.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 25, height = 20, units = "cm",
  dpi = 300, device = cairo_pdf)
```



```
mean(as.numeric(as.character(
  means_final_subject_RTs$effect[
    means_final_subject_RTs$group=="PWA"])), na.rm=T)
```

Get descriptives based on model data

```
## [1] 21.5855
```

```
sd(as.numeric(as.character(
  means_final_subject_RTs$effect[
    means_final_subject_RTs$group=="PWA"])), na.rm=T)
```

```
## [1] 11.47912
```

```
mean(as.numeric(as.character(
  means_final_subject_errors$effect[
    means_final_subject_RTs$group=="PWA"
])), na.rm=T)
```

```
## [1] 0.06
```

```
sd(as.numeric(as.character(
  means_final_subject_errors$effect[means_final_subject_RTs$group=="PWA"])), na.rm=T)
```

```
## [1] 0.08493555
```

Absence of CSI effect for fillers?

```
# load preprocessed data
input = "aphasia_final.csv"
d <- read.csv2(here::here("data","transient_data_files", input), sep=",") #>% select(-"X")

# select only fillers
d <- d %>% filter(category=="Filler")

## Add filler subcategories
# "The 24 categories were distributed across eight blocks of
# three categories each. To each block, five filler items
# were added, resulting in eight blocks of 20 items."
d <- d %>%
  mutate(filler_block = case_when(
    trial <= 20 ~ "block1",
    trial > 20 & trial <= 40 ~ "block2",
    trial > 40 & trial <= 60 ~ "block3",
    trial > 60 & trial <= 80 ~ "block4",
    trial > 80 & trial <= 100 ~ "block5",
```

```

trial > 100 & trial <= 120 ~ "block6",
trial > 120 & trial <= 140 ~ "block7",
trial > 140 & trial <= 160 ~ "block8"))
table(d$filler_block)

```

## Preparation

```

##
## block1 block2 block3 block4 block5 block6 block7 block8
##      600      600      600      600      600      600      600      600

```

```

## Add ordinal position
d <- d %>% group_by(subject, session, filler_block) %>%
  add_count() %>%
  dplyr::mutate(PosOr = seq(1:n)) %>%
  dplyr::select(-n)

```

```

## Warning: There were 960 warnings in 'dplyr::mutate()'.
## The first warning was:
## i In argument: 'PosOr = seq(1:n)'.
## i In group 1: 'subject = 101', 'session = 1', 'filler_block = "block1"'.
## Caused by warning in '1:n':
## ! numerical expression has 5 elements: only the first used
## i Run 'dplyr::last_dplyr_warnings()' to see the 959 remaining warnings.

```

```

table(df$PosOr)

```

```

##
##      1      2      3      4      5
## 2880 2880 2880 2880 2880

```

```

# d %>% group_by(subject, session, filler_block) %>% count(PosOr)
# table(df$PosOr, df$session, df$subject)

```

```

# factorize columns
d$VOT <- as.numeric(as.character(d$VOT))
is.numeric(d$VOT)

```

```

## [1] TRUE

```

```

d$PosOr <- as.factor(d$PosOr)
d$group <- as.factor(d$type)
d$subject <- as.factor(d$subject)
d$session <- as.factor(d$session)

```

```

# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple

```

```
##           2           3
## 1 -0.3333333 -0.3333333
## 2  0.6666667 -0.3333333
## 3 -0.3333333  0.6666667
```

```
contrasts(d$session)<-my.simple
levels(d$session)
```

```
## [1] "1" "2" "3"
```

```
## Define contrast of group
contrasts(d$group) <- MASS::contr.sdif(2)
levels(d$group)
```

```
## [1] "control" "PWA"
```

```
## Define Ordinal position as continuous predictor variable
d$PosOr_cont <- as.numeric(scale(as.numeric(
  as.character(d$PosOr)),
  center = T, scale = F))
```

```
## Errors and correct responses
```

```
# Correct responses start with 1. We will consider all responses in 1.1-1.3 for analyses of response t
```

```
d$error[is.na(d$VOT)] <- "99"
d$correct[is.na(d$VOT)] <- "0"
```

```
## Two trials were forgotten to be classified, but AR == 99 --> technical error?
```

```
d$error[is.na(d$correct) & d$AR == "99"] <- "99"
d$correct[is.na(d$correct) & d$AR == "99"] <- "0"
sum(is.na(d$correct))
```

```
## [1] 0
```

```
## NR and 0.4 are the same -> replace this
```

```
d$error[d$error=="NR"] <- "4"
```

```
## Rename broken names
```

```
# unique(df$error)
```

```
d$error <- stringr::str_replace(d$error, ";;;;;;;;", "")
```

```
d$error <- stringr::str_replace(d$error, "ok", "") # subject 113, session 2, trial 121 (Couch)
```

```
df$error <- gsub("?", NA, df$error, fixed = TRUE)
```

```
# unique(df$error)
```

```
# unique(df$correct)
```

```
d$correct <- stringr::str_replace(d$correct, ";;;;;;;;", "")
```

```
# unique(df$correct)
```

```
d$error[d$correct == 0 & is.na(d$error)] <- 1 # phonet. paraphrasia > 25 %
```

```
## Subset data for reaction time and error analyses and delete fillers
```

```
# As correct reaction times will be considered:
```

```
# 1 - correct.
```

```

# 1.1 - correct with alternative response.
# 1.2 - correct with phonematic paraphasia (<=25% of the word).
# 1.3 - correct with correct article [*].
d %>% mutate(correct_class = case_when(
  correct == 1 ~ 1,
  correct == 1.1 ~ 1,
  correct == 1.2 ~ 1,
  correct == 1.3 ~ 1,
  correct == 1.4 ~ 0,
  correct == 0 ~ 0)) -> d

### Save data frame for RT analyses: Only correct responses
d_RTs <- d %>% filter(correct_class == 1)
print(paste0("Amount of trials that went into RT analyses of Filler trials: ",
  nrow(d_RTs)))

```

```
## [1] "Amount of trials that went into RT analyses of Filler trials: 4218"
```

```
table(d_RTs$group)
```

```
##
## control      PWA
##      2348      1870
```

```

# Subset data frame for error analyses
# As errors on the participant side will be considered:
# 1 - wrong with phonematic paraphasia (> 25 % of the word).
# 2 - wrong: semantic paraphasia (word in the experiment).
# 3 - wrong: semantic paraphasia (word not in the experiment).
# 4 - wrong: null reaction.
# 5 - wrong: replacement without connection to the word (word in the experiment).
# 6 - wrong: replacement without connection to the word (word not in the experiment).
# 7 - superordinate word.
# 8 - neologism.
# 9 - etc.

d %>% mutate(error_class = case_when(
  error == 1 | error == 2 | error == 3 |
    error == 4 | error == 5 | error == 6 | error == 7 |
    error == 8 | error == 9 ~ 1,
  error == 99 | is.na(error) ~ 0)) -> d

#### Subset data for error analyses: All trials excluding technical errors, invalid RTs and fillers
d_errors <- d %>% filter((error != "99" | is.na(error)))

print(paste0("Amount of trials that went into error analyses: ",
  nrow(d_errors)))

```

```
## [1] "Amount of trials that went into error analyses: 4771"
```

```
print(paste0("Amount of these trials with errors analyses: ",
            nrow(d_errors[d_errors$error_class==1,])))
```

```
## [1] "Amount of these trials with errors analyses: 491"
```

```
table(d_errors$group)
```

```
##
## control      PWA
##      2372      2399
```

```
(means_final<-
  d %>% filter(correct_class == 1) %>%
  filter(category == "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
                        withinvars = c("session", "PosOr"),
                        betweenvars = "group", na.rm = T))
```

## Plotting of VOTs

##	group	session	PosOr	N	VOT	sd	se	ci
## 1	control	1	1	157	1237.344	298.7901	23.84605	47.10280
## 2	control	1	2	158	1229.314	320.2176	25.47515	50.31823
## 3	control	1	3	155	1217.212	251.7419	20.22040	39.94515
## 4	control	1	4	154	1224.877	270.7734	21.81954	43.10647
## 5	control	1	5	156	1213.521	268.7514	21.51733	42.50507
## 6	control	2	1	155	1124.055	210.6816	16.92235	33.42991
## 7	control	2	2	158	1154.887	222.5629	17.70615	34.97300
## 8	control	2	3	156	1168.960	239.1948	19.15091	37.83046
## 9	control	2	4	158	1150.262	200.6234	15.96074	31.52548
## 10	control	2	5	154	1215.952	294.2336	23.71002	46.84128
## 11	control	3	1	154	1152.081	232.6809	18.74996	37.04224
## 12	control	3	2	156	1171.249	242.4956	19.41518	38.35251
## 13	control	3	3	159	1131.397	226.2960	17.94644	35.44587
## 14	control	3	4	159	1133.064	184.0503	14.59614	28.82871
## 15	control	3	5	159	1170.278	257.3952	20.41277	40.31709
## 16	PWA	1	1	126	1284.737	407.1925	36.27560	71.79391
## 17	PWA	1	2	122	1262.389	462.3727	41.86126	82.87541
## 18	PWA	1	3	115	1312.944	494.5014	46.11249	91.34850
## 19	PWA	1	4	115	1239.336	414.7010	38.67107	76.60709
## 20	PWA	1	5	118	1313.645	492.6735	45.35427	89.82176
## 21	PWA	2	1	118	1117.702	406.7237	37.44195	74.15182
## 22	PWA	2	2	132	1156.443	406.4393	35.37600	69.98216
## 23	PWA	2	3	126	1129.120	324.7708	28.93289	57.26177
## 24	PWA	2	4	128	1091.962	365.5339	32.30894	63.93355
## 25	PWA	2	5	124	1175.063	442.5136	39.73889	78.66070
## 26	PWA	3	1	135	1093.505	368.7910	31.74048	62.77713
## 27	PWA	3	2	127	1139.945	403.6176	35.81527	70.87736
## 28	PWA	3	3	128	1128.958	396.9119	35.08238	69.42171
## 29	PWA	3	4	135	1152.840	408.6211	35.16850	69.55717
## 30	PWA	3	5	121	1127.213	353.1359	32.10326	63.56222

```

override.linetype<-c("longdash", "dashed", "dotted")
(plot_rt_repetition_PWA <- means_final %>% filter(group=="PWA") %>%
  mutate(session=case_when(session == "1" ~ "day 1",
                           session == "2" ~ "day 2",
                           session == "3" ~ "day 8"))) %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
              geom="line", size = 0.5) +
  scale_linetype_manual(values=c("longdash", "dashed", "dotted"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
              width =.1) +


  apatheme+
  scale_y_continuous(limits = c(1020, 1450),
                    breaks =seq(1050,1450, by = 50)) +
  labs(x="Ordinal Position ",y = "VOT (ms)", colour="Session",
       linetype="Session",
       title = "Filler Trials of PWA") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none")

```

## Scale for linetype is already present.

## Adding another scale for linetype, which will replace the existing scale.


# Filler Trials of PWA



```
(plot_rt_repetition_control <- means_final %>%
  filter(group=="control") %>%
  mutate(session=case_when(session == "1" ~ "day 1",
                           session == "2" ~ "day 2",
                           session == "3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
              geom="line", size = 0.5) +
  scale_linetype_manual(values=c("longdash", "dashed", "dotted"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
              width =.1) +
  apatheme+
  scale_y_continuous(limits = c(1020, 1450),
                    breaks =seq(1050,1450, by = 50)) +
  labs(x="Ordinal Position ",y ="VOT (ms)", colour="Session", linetype="Session",
       title = "Filler Trials of Control Group") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"))+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
  scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
## Adding another scale for linetype, which will replace the existing scale.
```

## Filler Trials of Control Group



```
plots <- cowplot::plot_grid(
  plot_rt_repetition_PWA, plot_rt_repetition_control,
  nrow = 1, ncol=2, rel_widths = c(0.81,1), #rel_height = c(1,1),
  margin(1,1,1,1),
  labels = c("A", "B"), label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_rt_by_repetition_FILLERS.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
  width = 25, height = 13, units = "cm",
  dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))
```

Inferential statistics of VOTs Preparation



```
d_RTs$PosOr.cont <-
  scale(as.numeric(as.character(d_RTs$PosOr)),
        center = T, scale = F)
# *Compute further contrasts*
# define contrasts of session: compare 1 to 2 and 1 to 3, intercept is the grand mean => simple coding
c<-contr.treatment(3)
my.coding<-matrix(rep(1/3, 6), ncol=2)
my.simple<-c-my.coding
my.simple
```

```
contrasts(d_RTs$session)<-my.simple
levels(d_RTs$session)
```

```
## Define contrast of group
contrasts(d_RTs$group) <- MASS::contr.sdif(2)
levels(d_RTs$group)
```

```
# *didLMERconverge function*
## This function provides a better convergence check for lme4 v>1.0 models, which have a nasty habit of
didLmerConverge = function(lmerModel){
  relativeMaxGradient=signif(max(abs(with(
    lmerModel@optinfo$derivs,solve(Hessian,gradient))))),3)
  if (relativeMaxGradient < 0.001) {
    cat(sprintf("\tThe relative maximum gradient of %s is less than our 0.001 criterion.\n\tYou can safely ignore this message.\n"))
  }
  else {
    cat(sprintf("The relative maximum gradient of %s exceeds our 0.001 criterion.\nThis looks like a real problem.\n"))
  }
}

#### Transform RTs: log transformation as in main analyses
d_RTs$lvOT <- log(d_RTs$VOT)
```

```
library(lmerTest)
# m2_lmm <- lmer(lVOT ~ PosDr.cont*session*group +
#               (PosDr.cont*session/subject),
#               data = d_RT,
#               control=lmerControl(optimizer = "bobyqa"))
# didLmerConverge(m2_lmm)
```

```

# Model fails to converge --> Reduce
# 1) Increase optimizer iterations
# m2_lmm <- lmer(lVOT ~ PosOr.cont*session*group +
#               (PosOr.cont*session|subject),
#               data = d_RTs,
#               control=lmerControl(optimizer = "bobyqa",
#                                   optCtrl = list(maxfun = 2e5)))
# didLmerConverge(m2_lmm)

# 2) Omit correlation parameters as model still fails to converge
# m2_lmm <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                         (PosOr.cont*session||subject),
#                         data = d_RTs,
#                         control=lmerControl(optimizer = "bobyqa",
#                                             optCtrl = list(maxfun = 2e5)))

# 3) Model fit is still singular -> Further reduce the model
# m2_lmm <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                         (PosOr.cont+session||subject),
#                         data = d_RTs,
#                         control=lmerControl(optimizer = "bobyqa",
#                                             optCtrl = list(maxfun = 2e5)))
# m2_lmm <- afex::lmer_alt(lVOT ~ PosOr.cont*session*group +
#                         (session||subject),
#                         data = d_RTs,
#                         control=lmerControl(optimizer = "bobyqa",
#                                             optCtrl = list(maxfun = 2e5)))
# 4) Does the model also converge when correlation parameters are included - yes!
m2_lmm <- lmer(lVOT ~ PosOr.cont*session*group +
              (session|subject),
              data = d_RTs,
              control=lmerControl(optimizer = "bobyqa",
                                  optCtrl = list(maxfun = 2e5)))

# rePCA(m2_lmm)
didLmerConverge(m2_lmm)

```

```

## The relative maximum gradient of 0.000000727 is less than our 0.001 criterion.
## You can safely ignore any warnings about a claimed convergence failure.

```

```

## Warnings can be ignored

```

```

summary(m2_lmm)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ PosOr.cont * session * group + (session | subject)
## Data: d_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: -391.4
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max

```

```

## -2.7368 -0.6288 -0.1654 0.4322 5.1883
##
## Random effects:
## Groups Name Variance Std.Dev. Corr
## subject (Intercept) 0.038296 0.19569
## session2 0.003026 0.05500 -0.06
## session3 0.005456 0.07386 -0.48 0.60
## Residual 0.049623 0.22276
## Number of obs: 4218, groups: subject, 40
##
## Fixed effects:
## Estimate Std. Error df t value
## (Intercept) 7.057860 0.031172 37.669431 226.417
## Pos0r.cont 0.003775 0.002449 4104.169425 1.542
## session2 -0.079458 0.012316 37.786634 -6.451
## session3 -0.084154 0.014550 37.884349 -5.784
## group2-1 0.196398 0.062344 37.669431 3.150
## Pos0r.cont:session2 0.008929 0.006029 4104.476679 1.481
## Pos0r.cont:session3 0.003490 0.005986 4105.352910 0.583
## Pos0r.cont:group2-1 -0.001560 0.004897 4104.169426 -0.318
## session2:group2-1 -0.055915 0.024633 37.786634 -2.270
## session3:group2-1 -0.046108 0.029101 37.884349 -1.584
## Pos0r.cont:session2:group2-1 -0.015678 0.012058 4104.476680 -1.300
## Pos0r.cont:session3:group2-1 0.003927 0.011973 4105.352910 0.328
## Pr(>|t|)
## (Intercept) < 0.0000000000000002 ***
## Pos0r.cont 0.12325
## session2 0.000000141 ***
## session3 0.000001139 ***
## group2-1 0.00319 **
## Pos0r.cont:session2 0.13866
## Pos0r.cont:session3 0.55990
## Pos0r.cont:group2-1 0.75014
## session2:group2-1 0.02900 *
## session3:group2-1 0.12141
## Pos0r.cont:session2:group2-1 0.19359
## Pos0r.cont:session3:group2-1 0.74291
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) Ps0r.c sessn2 sessn3 grp2-1 Ps0.:2 Ps0.:3 P0.:2- s2:2-1
## Pos0r.cont 0.001
## session2 -0.039 -0.004
## session3 -0.389 -0.002 0.555
## group2-1 0.004 0.002 0.001 -0.002
## Ps0r.cnt:s2 -0.001 -0.002 0.001 0.003 0.000
## Ps0r.cnt:s3 0.000 -0.014 0.003 0.004 0.001 0.505
## Ps0r.cn:2-1 0.002 0.116 -0.003 0.002 0.001 -0.005 -0.013
## sssn2:gr2-1 0.001 -0.003 0.081 0.038 -0.039 0.002 0.004 -0.004
## sssn3:gr2-1 -0.002 0.002 0.038 0.056 -0.389 0.003 0.008 -0.002 0.555
## Ps0r.:2:2-1 0.000 -0.005 0.002 0.003 -0.001 0.123 0.065 -0.002 0.001
## Ps0r.:3:2-1 0.001 -0.013 0.004 0.008 0.000 0.065 0.115 -0.014 0.003
## s3:2-1 P0.:2:

```

```
## PosOr.cont
## session2
## session3
## group2-1
## PsOr.cnt:s2
## PsOr.cnt:s3
## PsOr.cn:2-1
## sssn2:gr2-1
## sssn3:gr2-1
## PsOr.:2:2-1 0.003
## PsOr.:3:2-1 0.004 0.505
```

```
anova(m2_lmm)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##
##          Sum Sq Mean Sq NumDF   DenDF F value    Pr(>F)
## PosOr.cont      0.11793  0.11793      1 4104.2   2.3764    0.123255
## session         2.41377  1.20688      2   38.2  24.3210 0.000000154 ***
## group           0.49246  0.49246      1   37.7   9.9240    0.003191 **
## PosOr.cont:session 0.11067  0.05534      2 4104.4   1.1151    0.327971
## PosOr.cont:group   0.00503  0.00503      1 4104.2   0.1014    0.750137
## session:group      0.26327  0.13164      2   38.2   2.6527    0.083409 .
## PosOr.cont:session:group 0.14854  0.07427      2 4104.4   1.4967    0.224000
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
saveRDS(m2_lmm, file = here::here("results", "tables", "CSI_online_aphasia_PosOrSessionxGroup_lmm_VOT_1",
tab_model(m2_lmm, transform = NULL,
  show.re.var = F, show.stat = T, show.r2 = F, show.icc = F,
  title = "LMM of VOTs of Filler trials Predicted by Ordinal Position and Session",
  dv.labels = "Vocal Onset Time (log-transformed)",
  #string.pred = "",
  df.method = "satterthwaite",
  string.stat = "t-Value",
  file = here::here(
    "results", "tables",
    "CSI_online_aphasia_spoken_SessionxGroup_lmm_VOT_FILLERS.html"))
```

LMM of VOTs of Filler trials Predicted by Ordinal Position and Session

Vocal Onset Time (log-transformed)

Predictors

Estimates

CI

t-Value

p

(Intercept)

7.06

6.99 – 7.12  
 226.42  
 <0.001  
 PosOr cont  
 0.00  
 -0.00 – 0.01  
 1.54  
 0.123  
 session [2]  
 -0.08  
 -0.10 – -0.05  
 -6.45  
 <0.001  
 session [3]  
 -0.08  
 -0.11 – -0.05  
 -5.78  
 <0.001  
 group2-1  
 0.20  
 0.07 – 0.32  
 3.15  
 0.003  
 PosOr cont × session [2]  
 0.01  
 -0.00 – 0.02  
 1.48  
 0.139  
 PosOr cont × session [3]  
 0.00  
 -0.01 – 0.02  
 0.58  
 0.560  
 PosOr.cont:group2-1  
 -0.00  
 -0.01 – 0.01

```

-0.32
0.750
session2:group2-1
-0.06
-0.11 - -0.01
-2.27
0.029
session3:group2-1
-0.05
-0.11 - 0.01
-1.58
0.121
PosOr.cont:session2:group2-1
-0.02
-0.04 - 0.01
-1.30
0.194
PosOr.cont:session3:group2-1
0.00
-0.02 - 0.03
0.33
0.743
N subject
40
Observations
4218

```

```

## Check model
# performance::check_model(m2_lmm)
# ggResidpanel::resid_panel(m2_lmm, smoother = TRUE,
                             # qqbands = TRUE, type = "pearson")

```

**Main model with category block as covariate** Add “block” variable for trials of individual participants

```

df_RTs <- df_RTs %>%
  mutate(filler_block = case_when(
    trial <= 20 ~ 1,
    trial > 20 & trial <= 40 ~ 2,
    trial > 40 & trial <= 60 ~ 3,
    trial > 60 & trial <= 80 ~ 4,
    trial > 80 & trial <= 100 ~ 5,

```

```

trial > 100 & trial <= 120 ~ 6,
trial > 120 & trial <= 140 ~ 7,
trial > 140 & trial <= 160 ~ 8))
# use as centered continuous variable
df_RTs$filler_block_c <-
  scale(df_RTs$filler_block, center=T, scale=F)

```

Add to converging model

```

m2_lmm_control <- lmer(lVOT ~
  PosOr.cont*session*group*filler_block_c +
  (PosOr.cont+session|subject) +
  (PosOr.cont+group|category),
  data = df_RTs,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(
      maxfun = 2e5)))
summary(m2_lmm_control)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ PosOr.cont * session * group * filler_block_c + (PosOr.cont +
## session | subject) + (PosOr.cont + group | category)
## Data: df_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1267.8
##
## Scaled residuals:
##   Min       1Q   Median       3Q      Max
## -4.9413 -0.6604 -0.1718  0.4775  5.6569
##
## Random effects:
##   Groups   Name                Variance  Std.Dev. Corr
##   subject  (Intercept)  0.03577866  0.189152
##            PosOr.cont    0.00010267  0.010133  0.18
##            session2      0.00339497  0.058266 -0.13  0.25
##            session3      0.00404501  0.063600 -0.49  0.27  0.64
##   category (Intercept)  0.00874730  0.093527
##            PosOr.cont    0.00002298  0.004794  0.10
##            group2-1      0.00090366  0.030061  0.06  0.21
## Residual                0.06152928  0.248051
## Number of obs: 12455, groups:  subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate      Std. Error
## (Intercept)    7.1166377    0.0355631
## PosOr.cont      0.0168851    0.0024766
## session2     -0.0758537    0.0108508
## session3     -0.0891813    0.0115410
## group2-1      0.1578366    0.0603215
## filler_block_c  0.0028800    0.0011690
## PosOr.cont:session2  0.0046453    0.0039247

```

```

## Pos0r.cont:session3          0.0037132      0.0038953
## Pos0r.cont:group2-1         0.0069304      0.0045497
## session2:group2-1          -0.0251090      0.0217017
## session3:group2-1          -0.0198596      0.0230820
## Pos0r.cont:filler_block_c   -0.0005891      0.0007235
## session2:filler_block_c      0.0054085      0.0024334
## session3:filler_block_c      0.0026637      0.0024132
## group2-1:filler_block_c      0.0011232      0.0021901
## Pos0r.cont:session2:group2-1 0.0132400      0.0078495
## Pos0r.cont:session3:group2-1 0.0029669      0.0077908
## Pos0r.cont:session2:filler_block_c -0.0020722      0.0017197
## Pos0r.cont:session3:filler_block_c -0.0029060      0.0017016
## Pos0r.cont:group2-1:filler_block_c -0.0006622      0.0013896
## session2:group2-1:filler_block_c 0.0057401      0.0048733
## session3:group2-1:filler_block_c 0.0015736      0.0048220
## Pos0r.cont:session2:group2-1:filler_block_c 0.0003111      0.0034432
## Pos0r.cont:session3:group2-1:filler_block_c 0.0013833      0.0034003
##                               df t value
## (Intercept)                58.3818764 200.113
## Pos0r.cont                  29.9245813   6.818
## session2                   38.4343494  -6.991
## session3                   36.6227844  -7.727
## group2-1                   38.5604588   2.617
## filler_block_c             11895.6821369   2.464
## Pos0r.cont:session2        12249.6910925   1.184
## Pos0r.cont:session3        12250.8770133   0.953
## Pos0r.cont:group2-1        37.1498889   1.523
## session2:group2-1          38.4339969  -1.157
## session3:group2-1          36.6227637  -0.860
## Pos0r.cont:filler_block_c   415.4699244  -0.814
## session2:filler_block_c    12234.0714453   2.223
## session3:filler_block_c    12250.7940892   1.104
## group2-1:filler_block_c     1213.4440408   0.513
## Pos0r.cont:session2:group2-1 12247.7180439   1.687
## Pos0r.cont:session3:group2-1 12250.2037653   0.381
## Pos0r.cont:session2:filler_block_c 12255.4780239  -1.205
## Pos0r.cont:session3:filler_block_c 12138.4041122  -1.708
## Pos0r.cont:group2-1:filler_block_c 12241.3921513  -0.477
## session2:group2-1:filler_block_c 12248.8057815   1.178
## session3:group2-1:filler_block_c 12253.0730201   0.326
## Pos0r.cont:session2:group2-1:filler_block_c 11992.8602949   0.090
## Pos0r.cont:session3:group2-1:filler_block_c 12253.2741177   0.407
##                               Pr(>|t|)
## (Intercept)                < 0.0000000000000002 ***
## Pos0r.cont                  0.00000014742 ***
## session2                   0.00000002385 ***
## session3                   0.00000000333 ***
## group2-1                   0.0126 *
## filler_block_c             0.0138 *
## Pos0r.cont:session2        0.2366
## Pos0r.cont:session3        0.3405
## Pos0r.cont:group2-1        0.1362
## session2:group2-1          0.2544
## session3:group2-1          0.3952

```



```
## Pos0r.cont:filler_block_c 0.4160
## session2:filler_block_c 0.0263 *
## session3:filler_block_c 0.2697
## group2-1:filler_block_c 0.6082
## Pos0r.cont:session2:group2-1 0.0917 .
## Pos0r.cont:session3:group2-1 0.7033
## Pos0r.cont:session2:filler_block_c 0.2282
## Pos0r.cont:session3:filler_block_c 0.0877 .
## Pos0r.cont:group2-1:filler_block_c 0.6337
## session2:group2-1:filler_block_c 0.2389
## session3:group2-1:filler_block_c 0.7442
## Pos0r.cont:session2:group2-1:filler_block_c 0.9280
## Pos0r.cont:session3:group2-1:filler_block_c 0.6841
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

##
## Correlation matrix not shown by default, as p = 24 > 12.
## Use print(x, correlation=TRUE) or
##      vcov(x)          if you need it
```

## Comparing PWA tested in the clinic and at home

```
read.csv2(here::here("data", "additional_data",
                     "questionnaire-test_data.csv")) -> tests
df_RTs_PWA$test_location <- NA
for(i in 1:length(unique(df_RTs_PWA$subject))){
  df_RTs_PWA$test_location[
    df_RTs_PWA$subject==unique(df_RTs_PWA$subject)[i]] <-
    tests$Ort.zu.Hause..1...in.Klinik..2.[
    tests$Proband.in==unique(df_RTs_PWA$subject)[i]]
}

# 1 = home testes, 2 = tested in clinic
df_RTs_PWA <- df_RTs_PWA %>% mutate(test_location=case_when(
  test_location==1~"home",
  test_location==2~"clinic")) %>%
  mutate(test_location=factor(test_location, levels=c("home", "clinic")))

# descriptives
(means_final<- df_RTs_PWA %>%
  filter(category != "Filler") %>%
  Rmisc::summarySEwithin(., "VOT", idvar = "subject",
    withinvars = c("Pos0r", "session"),
    betweenvars = "test_location", na.rm = T))
```

```
##      test_location Pos0r session    N      VOT      sd      se      ci
## 1      home      1      1 127 1346.199 422.3752 37.47974 74.17130
## 2      home      1      2 132 1273.638 426.7381 37.14278 73.47729
## 3      home      1      3 138 1215.905 428.6614 36.49009 72.15663
## 4      home      2      1 125 1429.225 453.0344 40.52063 80.20168
```

## 5	home	2	2	133	1279.128	483.4542	41.92079	82.92347
## 6	home	2	3	134	1217.631	421.1310	36.38017	71.95857
## 7	home	3	1	115	1516.877	505.2941	47.11892	93.34221
## 8	home	3	2	124	1342.945	466.1062	41.85757	82.85449
## 9	home	3	3	132	1332.938	463.9254	40.37953	79.88033
## 10	home	4	1	123	1471.126	494.8829	44.62208	88.33387
## 11	home	4	2	129	1357.914	476.7573	41.97614	83.05696
## 12	home	4	3	135	1346.080	483.0407	41.57352	82.22519
## 13	home	5	1	97	1480.381	507.7860	51.55785	102.34153
## 14	home	5	2	116	1425.451	516.4443	47.95065	94.98100
## 15	home	5	3	126	1342.039	464.5974	41.38963	81.91521
## 16	clinic	1	1	235	1394.079	484.1078	31.57971	62.21689
## 17	clinic	1	2	243	1261.039	446.2997	28.63014	56.39608
## 18	clinic	1	3	257	1253.911	340.6824	21.25118	41.84940
## 19	clinic	2	1	220	1459.885	552.2705	37.23407	73.38296
## 20	clinic	2	2	253	1287.994	421.7362	26.51433	52.21791
## 21	clinic	2	3	252	1313.327	472.3141	29.75299	58.59734
## 22	clinic	3	1	222	1447.442	519.4234	34.86141	68.70335
## 23	clinic	3	2	246	1292.562	419.4500	26.74316	52.67583
## 24	clinic	3	3	264	1314.615	431.6229	26.56455	52.30626
## 25	clinic	4	1	234	1410.285	454.0671	29.68329	58.48196
## 26	clinic	4	2	249	1334.080	447.4857	28.35825	55.85372
## 27	clinic	4	3	249	1305.202	410.8462	26.03632	51.28050
## 28	clinic	5	1	225	1489.114	552.1233	36.80822	72.53468
## 29	clinic	5	2	239	1394.637	487.2906	31.52021	62.09422
## 30	clinic	5	3	244	1383.710	472.4320	30.24436	59.57456

```
# plot
override.linetype<-c("longdash", "dashed", "dotted")
(plot_rt_repetition_home <- means_final %>% filter(test_location=="home") %>%
  mutate(session=case_when(session == "1" ~ "day 1",
                             session == "2" ~ "day 2",
                             session == "3" ~ "day 8")) %>%

  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2)+
  stat_summary(aes(linetype=session),fun=mean,
               geom="line", size = 0.5) +
  scale_linetype_manual(values=c("longdash", "dashed", "dotted"))+
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000"))+
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
               width =.1) +


  apatheme+
  scale_y_continuous(limits = c(1120, 1650),
                     breaks =seq(1150,1650, by = 50)) +
  labs(x="Ordinal Position ",y ="VOT (ms)", colour="Session",
       linetype="Session",
       title = "PWA tested at home") +
  theme(
    axis.title.y = element_text(margin = margin(0,10,0,0)),
    axis.title.x = element_text(margin = margin(10,0,0,0)),
    legend.key.width = unit(1, "cm"),
    legend.position="none")+
  guides(color=guide_legend(
    override.aes=list(linetype=override.linetype)))+
```

```
scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
```

```
## Adding another scale for linetype, which will replace the existing scale.
```

## PWA tested at home




```
(plot_rt_repetition_clinic <- means_final %>%
  filter(test_location=="clinic") %>%
  mutate(session=case_when(session == "1" ~ "day 1",
                           session == "2" ~ "day 2",
                           session == "3" ~ "day 8")) %>%
  ggplot(., aes(x=PosOr, y=VOT, group=session, color = session)) +
  geom_point(size = 2) +
  stat_summary(aes(linetype=session), fun=mean,
              geom="line", size = 0.5) +
  scale_linetype_manual(values=c("longdash", "dashed", "dotted")) +
  scale_color_manual(values=c("#0072B2", "#E69F00", "#000000")) +
  geom_errorbar(aes(ymin=VOT-se, ymax=VOT+se, group = session),
              width = .1) +
  apatheme +
  scale_y_continuous(limits = c(1120, 1650),
                    breaks = seq(1150, 1650, by = 50)) +
  labs(x="Ordinal Position", y="VOT (ms)", colour="Session", linetype="Session",
       title = "PWA tested in clinic") +
  theme(
```

```
axis.title.y = element_text(margin = margin(0,10,0,0)),
axis.title.x = element_text(margin = margin(10,0,0,0)),
legend.key.width = unit(1, "cm"))+
guides(color=guide_legend(
  override.aes=list(linetype=override.linetype)))+
scale_linetype(guide="none"))
```

```
## Scale for linetype is already present.
```

```
## Adding another scale for linetype, which will replace the existing scale.
```

## PWA tested in clinic



```
plots <- cowplot::plot_grid(
  plot_rt_repetition_home, plot_rt_repetition_clinic,
  nrow = 1, ncol=2, rel_widths = c(0.81,1), #rel_height = c(1,1),
  margin(1,1,1,1),
  labels = c("A", "B"), label_size = 34,
  label_fontfamily = "Helvetica", label_y = 1.01,
  label_x=-0.03)
```

```
## Warning in as_grob.default(plot): Cannot convert object of class
## marginsimpleUnitunit_v2 into a grob.
```

```
filename <- "CSI_online_aphasia_spoken_plot_rt_homevsclinic.pdf"
ggsave(plots, filename =
  here::here("results", "figures", filename),
```

```

width = 25, height = 13, units = "cm",
dpi = 300, device = cairo_pdf)
#embedFonts(file = here::here("results", "figures", filename))

```

```

## model
contrasts(df_RTs_PWA$test_location) <- MASS::contr.sdif(2)
levels(df_RTs_PWA$test_location)

```

```
## [1] "home" "clinic"
```

```

# use converging model and add test_location as predictor
## fixed structure
m1_lmm_PWA_location <- lmer(VOTlog ~ test_location*(PosOr.cont*session) +
                             (PosOr.cont+session|subject) +
                             (1|category),
                             data = df_RTs_PWA,
                             control=lmerControl(optimizer = "bobyqa",
                                                    optCtrl = list(maxfun = 2e5)))
summary(m1_lmm_PWA_location)

```

```

## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: VOTlog ~ test_location * (PosOr.cont * session) + (PosOr.cont +
##      session | subject) + (1 | category)
##      Data: df_RTs_PWA
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1731.4
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.4937 -0.6783 -0.1854  0.5093  5.1042
##
## Random effects:
##      Groups      Name              Variance Std.Dev. Corr
##      category (Intercept) 0.0092411 0.09613
##      subject  (Intercept) 0.0432058 0.20786
##                PosOr.cont 0.0001311 0.01145  0.22
##                session2   0.0009489 0.03080 -0.44 -0.01
##                session3   0.0033828 0.05816 -0.63 -0.07  0.28
## Residual                0.0761010 0.27586
## Number of obs: 5518, groups:  category, 24; subject, 20
##
## Fixed effects:
##
##              Estimate Std. Error      df
## (Intercept)    7.224581   0.051538 24.098573
## test_location2-1 -0.287603   0.095310 18.047629
## PosOr.cont        0.021490   0.003917 17.802761
## session2        -0.086762   0.012219 15.325272
## session3        -0.103111   0.016666 18.352910
## PosOr.cont:session2  0.009888   0.006943 5437.311688
## PosOr.cont:session3  0.004646   0.006869 5437.400089
## test_location2-1:PosOr.cont -0.007095   0.007833 17.798044

```

```

## test_location2-1:session2          -0.012742    0.024436   15.321425
## test_location2-1:session3          0.037982    0.033326   18.341805
## test_location2-1:Pos0r.cont:session2 0.009872    0.013887  5437.175137
## test_location2-1:Pos0r.cont:session3 0.004143    0.013734  5437.249047
##                                     t value      Pr(>|t|)
## (Intercept)                        140.178 < 0.0000000000000002 ***
## test_location2-1                   -3.018      0.00738 **
## Pos0r.cont                          5.486      0.00003412 ***
## session2                           -7.101      0.00000321 ***
## session3                           -6.187      0.00000706 ***
## Pos0r.cont:session2                 1.424      0.15446
## Pos0r.cont:session3                 0.676      0.49885
## test_location2-1:Pos0r.cont         -0.906      0.37715
## test_location2-1:session2          -0.521      0.60952
## test_location2-1:session3           1.140      0.26908
## test_location2-1:Pos0r.cont:session2 0.711      0.47717
## test_location2-1:Pos0r.cont:session3 0.302      0.76292
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) ts_2-1 Ps0r.c sessn2 sessn3 Ps0.:2 Ps0.:3 ts_2-1:P0. t_2-1:2
## tst_lctn2-1 -0.187
## Pos0r.cont   0.138 -0.033
## session2    -0.235  0.051 -0.007
## session3    -0.466  0.103 -0.044  0.375
## Ps0r.cnt:s2 -0.001  0.001 -0.024  0.019  0.010
## Ps0r.cnt:s3 -0.002  0.002 -0.042  0.014  0.013  0.526
## tst_2-1:P0. -0.030  0.149 -0.295  0.005  0.017  0.011  0.024
## tst_lc2-1:2  0.047 -0.254  0.005 -0.299 -0.107 -0.027 -0.019 -0.007
## tst_lc2-1:3  0.095 -0.504  0.017 -0.107 -0.260 -0.014 -0.017 -0.044      0.375
## t_2-1:P0.:2  0.001 -0.001  0.011 -0.027 -0.014 -0.330 -0.177 -0.024      0.018
## t_2-1:P0.:3  0.002 -0.002  0.024 -0.019 -0.017 -0.177 -0.324 -0.042      0.014
##      t_2-1:3 t_2-1:P0.:2
## tst_lctn2-1
## Pos0r.cont
## session2
## session3
## Ps0r.cnt:s2
## Ps0r.cnt:s3
## tst_2-1:P0.
## tst_lc2-1:2
## tst_lc2-1:3
## t_2-1:P0.:2  0.010
## t_2-1:P0.:3  0.013  0.526

```

```

## random structure
m1_lmm_PWA_location2 <- lmer(VOTlog ~ (Pos0r.cont*session) +
                             (Pos0r.cont+session|subject) +
                             (test_location|category),
                             data = df_RT_S_PWA,
                             control=lmerControl(optimizer = "bobyqa",
                                                    optCtrl = list(maxfun = 2e5)))

```

```
## boundary (singular) fit: see help('isSingular')
```

```
summary(m1_lmm_PWA_location2) # model does not converge and test_location explains least variance
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: VOTlog ~ (PosOr.cont * session) + (PosOr.cont + session | subject) +
## (test_location | category)
## Data: df_RTs_PWA
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1698.9
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.5191 -0.6861 -0.1837  0.5152  5.0874
##
## Random effects:
## Groups Name Variance Std.Dev. Corr
## category (Intercept) 0.0086220 0.09285
## test_location2-1 0.0004396 0.02097 1.00
## subject (Intercept) 0.0612978 0.24758
## PosOr.cont 0.0001267 0.01125 0.35
## session2 0.0009234 0.03039 -0.25 0.09
## session3 0.0034611 0.05883 -0.67 -0.14 0.19
## Residual 0.0759800 0.27564
## Number of obs: 5518, groups: category, 24; subject, 20
##
## Fixed effects:
## Estimate Std. Error df t value
## (Intercept) 7.197088 0.058800 23.491270 122.400
## PosOr.cont 0.020659 0.003705 17.705800 5.576
## session2 -0.087833 0.011606 16.110144 -7.568
## session3 -0.098606 0.016190 17.686389 -6.090
## PosOr.cont:session2 0.011482 0.006547 5438.018353 1.754
## PosOr.cont:session3 0.005429 0.006491 5440.059343 0.836
## Pr(>|t|)
## (Intercept) < 0.0000000000000002 ***
## PosOr.cont 0.00002885 ***
## session2 0.00000108 ***
## session3 0.00001011 ***
## PosOr.cont:session2 0.0796 .
## PosOr.cont:session3 0.4030
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) PsOr.c sessn2 sessn3 Ps0.:2
## PosOr.cont 0.223
## session2 -0.138 0.036
## session3 -0.515 -0.077 0.332
## PsOr.cnt:s2 0.000 -0.021 0.004 0.003
## PsOr.cnt:s3 0.000 -0.035 0.003 0.003 0.522
## optimizer (bobyqa) convergence code: 0 (OK)
```

```
## boundary (singular) fit: see help('isSingular')
```

## Assessing the variance of the ordinal position effect between groups

**VOTs** Compute a nested model on the VOT model

```
m1_VOTs <- readRDS(file =
  here::here(
    "results", "tables",
    "CSI_online_aphasia_SessionxGroup_control_lmm_VOT.RDS"))
#summary(m1_VOTs)
#m1_VOTs@call

## Use this structure for a nested model:
m1_VOTs_nested <- lmer(lVOT ~ group/session/PosOr.cont +
  (PosOr.cont+session|subject) +
  (PosOr.cont+group|category),
  data = df_RTs,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
summary(m1_VOTs_nested)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ group/session/PosOr.cont + (PosOr.cont + session | subject) +
##          (PosOr.cont + group | category)
##      Data: df_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1158.2
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -4.8980 -0.6647 -0.1747  0.4804  5.6443
##
## Random effects:
##   Groups   Name                Variance  Std.Dev. Corr
##  subject  (Intercept)  0.03572329  0.189006
##           PosOr.cont    0.00010406  0.010201  0.18
##           session2      0.00339921  0.058303 -0.13  0.24
##           session3      0.00406340  0.063745 -0.49  0.26  0.64
##  category  (Intercept)  0.00884966  0.094073
##           PosOr.cont    0.00002358  0.004856  0.07
##           group2-1      0.00090450  0.030075  0.08  0.16
## Residual                    0.06154884  0.248090
## Number of obs: 12455, groups:  subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)    7.116562   0.035604 58.495156 199.883
## group2-1        0.157635   0.060276 38.561678   2.615
## groupcontrol:session2 -0.063279   0.014959 35.588407  -4.230
## groupPWA:session2    -0.088885   0.015736 41.218683  -5.649
```



```

## groupcontrol:session3      -0.079172    0.016016   34.253327  -4.943
## groupPWA:session3         -0.099251    0.016677   39.015066  -5.951
## groupcontrol:session1:Pos0r.cont  0.013399    0.004431  115.483152   3.024
## groupPWA:session1:Pos0r.cont    0.014924    0.004957  164.783105   3.011
## groupcontrol:session2:Pos0r.cont  0.011381    0.004423  114.610795   2.573
## groupPWA:session2:Pos0r.cont    0.026211    0.004831  148.762370   5.426
## groupcontrol:session3:Pos0r.cont  0.015500    0.004390  111.385092   3.531
## groupPWA:session3:Pos0r.cont    0.020120    0.004753  142.968524   4.233
##                               Pr(>|t|)
## (Intercept)                < 0.0000000000000002 ***
## group2-1                    0.012659 *
## groupcontrol:session2       0.000156 ***
## groupPWA:session2           0.000001345 ***
## groupcontrol:session3       0.000019994 ***
## groupPWA:session3           0.000000604 ***
## groupcontrol:session1:Pos0r.cont  0.003074 **
## groupPWA:session1:Pos0r.cont    0.003016 **
## groupcontrol:session2:Pos0r.cont  0.011351 *
## groupPWA:session2:Pos0r.cont    0.000000229 ***
## groupcontrol:session3:Pos0r.cont  0.000604 ***
## groupPWA:session3:Pos0r.cont    0.000041084 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##      (Intr) grp2-1 grpc:2 grPWA:2 grpc:3 grPWA:3 g:1:PO gPWA:1 g:2:PO
## group2-1      0.006
## grpcntrl:s2 -0.070  0.082
## grpPWA:sss2 -0.067 -0.079  0.000
## grpcntrl:s3 -0.259  0.307  0.613  0.000
## grpPWA:sss3 -0.251 -0.296  0.000  0.612  0.000
## grpcn:1:PO.  0.063 -0.061  0.110  0.000  0.123  0.000
## grPWA:1:PO.  0.058  0.062  0.000  0.086  0.000  0.100  0.045
## grpcn:2:PO.  0.064 -0.061  0.107  0.000  0.121  0.000  0.316  0.045
## grPWA:2:PO.  0.059  0.063  0.000  0.102  0.000  0.111  0.046  0.274  0.046
## grpcn:3:PO.  0.064 -0.061  0.109  0.000  0.119  0.000  0.318  0.045  0.319
## grPWA:3:PO.  0.060  0.064  0.000  0.099  0.000  0.116  0.047  0.276  0.047
##      gPWA:2: g:3:PO
## group2-1
## grpcntrl:s2
## grpPWA:sss2
## grpcntrl:s3
## grpPWA:sss3
## grpcn:1:PO.
## grPWA:1:PO.
## grpcn:2:PO.
## grPWA:2:PO.
## grpcn:3:PO.  0.046
## grPWA:3:PO.  0.284  0.047

```

```
as.data.frame(effects=allEffects(m1_VOTs_nested))
```

```


## Warning in Analyze.model(focal.predictors, mod, xlevels, default.levels, : the
## predictor Pos0r.cont is a one-column matrix that was converted to a vector

```

```
## $'group:session:PosOr.cont'
##      group session PosOr.cont      fit      se      lower      upper
## 1  control      1      -2.00 7.058431 0.05023269 6.959967 7.156895
## 2    PWA      1      -2.00 7.228244 0.05070769 7.128849 7.327638
## 3  control      2      -2.00 6.999187 0.04819351 6.904720 7.093653
## 4    PWA      2      -2.00 7.116784 0.04862002 7.021481 7.212086
## 5  control      3      -2.00 6.975058 0.04340011 6.889987 7.060128
## 6    PWA      3      -2.00 7.118601 0.04380863 7.032729 7.204473
## 7  control      1      -1.00 7.071830 0.04989989 6.974018 7.169641
## 8    PWA      1      -1.00 7.243167 0.05026643 7.144637 7.341697
## 9  control      2      -1.00 7.010568 0.04799961 6.916481 7.104655
## 10   PWA      2      -1.00 7.142995 0.04834359 7.048234 7.237756
## 11 control      3      -1.00 6.990557 0.04322436 6.905831 7.075284
## 12   PWA      3      -1.00 7.138721 0.04355954 7.053337 7.224104
## 13 control      1       0.02 7.085496 0.04996453 6.987558 7.183435
## 14   PWA      1       0.02 7.258390 0.05031788 7.159759 7.357020
## 15 control      2       0.02 7.022177 0.04822077 6.927657 7.116697
## 16   PWA      2       0.02 7.169731 0.04855766 7.074550 7.264911
## 17 control      3       0.02 7.006367 0.04350313 6.921094 7.091640
## 18   PWA      3       0.02 7.159243 0.04383823 7.073313 7.245172
## 19 control      1       1.00 7.098627 0.05040966 6.999816 7.197438
## 20   PWA      1       1.00 7.273015 0.05084307 7.173355 7.372675
## 21 control      2       1.00 7.033330 0.04882653 6.937623 7.129038
## 22   PWA      2       1.00 7.195418 0.04922923 7.098921 7.291915
## 23 control      3       1.00 7.021556 0.04419867 6.934920 7.108193
## 24   PWA      3       1.00 7.178960 0.04460355 7.091530 7.266390
## 25 control      1       2.00 7.112025 0.05124054 7.011586 7.212465
## 26   PWA      1       2.00 7.287939 0.05184473 7.186315 7.389562
## 27 control      2       2.00 7.044712 0.04982719 6.947043 7.142381
## 28   PWA      2       2.00 7.221629 0.05036602 7.122904 7.320354
## 29 control      3       2.00 7.037056 0.04532024 6.948221 7.125891
## 30   PWA      3       2.00 7.199080 0.04586156 7.109184 7.288975
```

```
plot(effects::allEffects(m1_VOTs_nested))
```

```
## Warning in Analyze.model(focal.predictors, mod, xlevels, default.levels, : the
## predictor PosOr.cont is a one-column matrix that was converted to a vector
```



```
## Check whether the by-group slope causes the SEs being similar between groups
m1_VOTs_nested2 <- lmer(lVOT ~ group/session/PosOr.cont +
  (PosOr.cont+session|subject) +
  (PosOr.cont|category),
  data = df_RTs,
  control=lmerControl(optimizer = "bobyqa",
    optCtrl = list(maxfun = 2e5)))
summary(m1_VOTs_nested2)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: lVOT ~ group/session/PosOr.cont + (PosOr.cont + session | subject) +
## (PosOr.cont | category)
## Data: df_RTs
## Control: lmerControl(optimizer = "bobyqa", optCtrl = list(maxfun = 200000))
##
## REML criterion at convergence: 1176.9
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -4.8547 -0.6655 -0.1737  0.4808  5.6868
##
## Random effects:
## Groups Name Variance Std.Dev. Corr
## subject (Intercept) 0.03561229 0.188712
## PosOr.cont 0.00010428 0.010212 0.17
```

```

##          session2    0.00340190 0.058326 -0.13  0.24
##          session3    0.00406562 0.063762 -0.49  0.27  0.65
## category (Intercept) 0.00882438 0.093938
##          Pos0r.cont  0.00002319 0.004816 0.07
## Residual              0.06176389 0.248523
## Number of obs: 12455, groups:  subject, 40; category, 24
##
## Fixed effects:
##
##              Estimate Std. Error      df t value
## (Intercept)      7.116181   0.035550  58.503544 200.175
## group2-1          0.156914   0.059870  37.785294   2.621
## groupcontrol:session2 -0.063272   0.014969  35.590650  -4.227
## groupPWA:session2    -0.088634   0.015747  41.222784  -5.628
## groupcontrol:session3 -0.079181   0.016025  34.288283  -4.941
## groupPWA:session3    -0.098842   0.016687  39.053913  -5.923
## groupcontrol:session1:Pos0r.cont 0.013395   0.004435 115.666590   3.020
## groupPWA:session1:Pos0r.cont 0.014846   0.004962 165.013007   2.992
## groupcontrol:session2:Pos0r.cont 0.011378   0.004428 114.792897   2.570
## groupPWA:session2:Pos0r.cont 0.026096   0.004836 149.004889   5.396
## groupcontrol:session3:Pos0r.cont 0.015543   0.004394 111.556603   3.537
## groupPWA:session3:Pos0r.cont 0.019961   0.004759 143.192069   4.195
##
##              Pr(>|t|)
## (Intercept)    < 0.0000000000000002 ***
## group2-1          0.012563 *
## groupcontrol:session2 0.000157 ***
## groupPWA:session2    0.000001435 ***
## groupcontrol:session3 0.000020083 ***
## groupPWA:session3    0.000000659 ***
## groupcontrol:session1:Pos0r.cont 0.003110 **
## groupPWA:session1:Pos0r.cont 0.003196 **
## groupcontrol:session2:Pos0r.cont 0.011459 *
## groupPWA:session2:Pos0r.cont 0.000000263 ***
## groupcontrol:session3:Pos0r.cont 0.000591 ***
## groupPWA:session3:Pos0r.cont 0.000047661 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##          (Intr) grp2-1 grpc:2 grPWA:2 grpc:3 grPWA:3 g:1:P0 gPWA:1 g:2:P0
## group2-1      0.001
## grpcntrl:s2 -0.069  0.082
## grpPWA:sss2 -0.066 -0.079  0.000
## grpcntrl:s3 -0.258  0.307  0.614  0.000
## grpPWA:sss3 -0.250 -0.297  0.000  0.613  0.000
## grpcn:1:P0.  0.061 -0.063  0.109  0.000  0.124  0.000
## grPWA:1:P0.  0.056  0.058  0.000  0.085  0.000  0.100  0.044
## grpcn:2:P0.  0.061 -0.063  0.106  0.000  0.122  0.000  0.315  0.044
## grPWA:2:P0.  0.057  0.059  0.000  0.101  0.000  0.112  0.045  0.273  0.045
## grpcn:3:P0.  0.061 -0.063  0.108  0.000  0.120  0.000  0.317  0.044  0.318
## grPWA:3:P0.  0.057  0.059  0.000  0.098  0.000  0.116  0.046  0.275  0.046
##
##          gPWA:2: g:3:P0
## group2-1
## grpcntrl:s2
## grpPWA:sss2

```

```
## grpcntrl:s3
## grpPWA:sss3
## grpcn:1:PO.
## grPWA:1:PO.
## grpcn:2:PO.
## grPWA:2:PO.
## grpcn:3:PO. 0.046
## grPWA:3:PO. 0.283 0.046
```

```
anova(m1_VOTs_nested, m1_VOTs_nested2)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: df_RTs
## Models:
## m1_VOTs_nested2: lVOT ~ group/session/PosOr.cont + (PosOr.cont + session | subject) + (PosOr.cont | group)
## m1_VOTs_nested: lVOT ~ group/session/PosOr.cont + (PosOr.cont + session | subject) + (PosOr.cont + group | session)
##               npar      AIC      BIC logLik deviance Chisq Df Pr(>Chisq)
## m1_VOTs_nested2  26 1138.9 1332.0 -543.43  1086.9
## m1_VOTs_nested   29 1126.1 1341.6 -534.06  1068.1 18.736  3    0.00031 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
as.data.frame(effects::allEffects(m1_VOTs_nested2))
```


```
## Warning in Analyze.model(focal.predictors, mod, xlevels, default.levels, : the
## predictor PosOr.cont is a one-column matrix that was converted to a vector
```

```
## $'group:session:PosOr.cont'
##      group session PosOr.cont      fit      se      lower      upper
## 1 control      1      -2.00 7.058418 0.05017104 6.960075 7.156761
## 2 PWA          1      -2.00 7.227437 0.05048740 7.128474 7.326400
## 3 control      2      -2.00 6.999181 0.04814300 6.904814 7.093549
## 4 PWA          2      -2.00 7.116304 0.04840454 7.021424 7.211184
## 5 control      3      -2.00 6.974940 0.04335975 6.889948 7.059932
## 6 PWA          3      -2.00 7.118366 0.04358522 7.032932 7.203800
## 7 control      1      -1.00 7.071813 0.04983158 6.974135 7.169490
## 8 PWA          1      -1.00 7.242284 0.05001849 7.144240 7.340328
## 9 control      2      -1.00 7.010559 0.04794163 6.916586 7.104532
## 10 PWA         2      -1.00 7.142400 0.04809915 7.048118 7.236682
## 11 control      3      -1.00 6.990484 0.04317804 6.905848 7.075119
## 12 PWA         3      -1.00 7.138327 0.04330637 7.053440 7.223214
## 13 control      1      0.02 7.085476 0.04989082 6.987682 7.183270
## 14 PWA          1      0.02 7.257427 0.05004502 7.159331 7.355523
## 15 control      2      0.02 7.022164 0.04815657 6.927770 7.116558
## 16 PWA          2      0.02 7.169018 0.04828726 7.074367 7.263668
## 17 control      3      0.02 7.006338 0.04345219 6.921165 7.091511
## 18 PWA          3      0.02 7.158687 0.04355896 7.073305 7.244069
## 19 control      1      1.00 7.098603 0.05033216 6.999944 7.197262
## 20 PWA          1      1.00 7.271976 0.05055007 7.172890 7.371062
## 21 control      2      1.00 7.033314 0.04875779 6.937741 7.128887
## 22 PWA          2      1.00 7.194591 0.04893795 7.098666 7.290517
```

```
## 23 control      3      1.00 7.021571 0.04414478 6.935040 7.108101
## 24 PWA          3      1.00 7.178249 0.04430401 7.091406 7.265092
## 25 control      1      2.00 7.111998 0.05116065 7.011715 7.212281
## 26 PWA          1      2.00 7.286823 0.05153541 7.185805 7.387840
## 27 control      2      2.00 7.044692 0.04975533 6.947163 7.142220
## 28 PWA          2      2.00 7.220687 0.05005785 7.122566 7.318808
## 29 control      3      2.00 7.037114 0.04526483 6.948388 7.125840
## 30 PWA          3      2.00 7.198210 0.04554644 7.108932 7.287488
```

```
plot(effects::allEffects(m1_VOTs_nested2))
```

```
## Warning in Analyze.model(focal.predictors, mod, xlevels, default.levels, : the
## predictor PosOr.cont is a one-column matrix that was converted to a vector
```



```
### Analyse with bayesian approach:
# bayes_VOTs_nested <- brms::brm(lVOT ~ group/session/PosOr.cont +
#                               (PosOr.cont+session/subject) +
#                               (PosOr.cont+group/category) , data=df_RTs,
#   prior= c(prior(normal(0,100), class = Intercept),
#             prior(normal(0,100), class = sd)),
#   control=list(adapt_delta=.999, max_treedepth=12),
#   warmup = 100, #2000
#   chains=8, iter=100, # 20000
#   save_pars=save_pars(all=TRUE)
# )
```

```
#  
# save(fit_freq, file="fit_freq.Rdata")
```

Other code

---

## Session info

```
sessionInfo()
```

```
## R version 4.3.1 (2023-06-16)  
## Platform: x86_64-apple-darwin20 (64-bit)  
## Running under: macOS Sonoma 14.4  
##  
## Matrix products: default  
## BLAS: /Library/Frameworks/R.framework/Versions/4.3-x86_64/Resources/lib/libRblas.0.dylib  
## LAPACK: /Library/Frameworks/R.framework/Versions/4.3-x86_64/Resources/lib/libRlapack.dylib; LAPACK  
##  
## locale:  
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8  
##  
## time zone: Europe/Berlin  
## tzcode source: internal  
##  
## attached base packages:  
## [1] stats graphics grDevices utils datasets methods base  
##  
## other attached packages:  
## [1] actuar_3.3-2 fitdistrplus_1.1-11 survival_3.5-8  
## [4] MASS_7.3-60.0.1 flextable_0.9.2 dplyr_1.1.2  
## [7] sjPlot_2.8.14 ggplot2_3.4.2 Cairo_1.6-0  
## [10] Rmisc_1.5.1 plyr_1.8.8 lattice_0.22-6  
## [13] lmerTest_3.1-3 lme4_1.1-35.1 Matrix_1.6-5  
## [16] tidyr_1.3.0  
##  
## loaded via a namespace (and not attached):  
## [1] RColorBrewer_1.1-3 rstudioapi_0.16.0 jsonlite_1.8.7  
## [4] datawizard_0.8.0 magrittr_2.0.3 estimability_1.4.1  
## [7] farver_2.1.1 nloptr_2.0.3 rmarkdown_2.23  
## [10] ragg_1.2.5 vctrs_0.6.3 minqa_1.2.5  
## [13] askpass_1.1 effectsize_0.8.3 forcats_1.0.0  
## [16] htmltools_0.5.8.1 haven_2.5.4 curl_5.2.1  
## [19] survey_4.4-2 broom_1.0.5 sjmisc_2.8.9  
## [22] huxtable_5.5.2 pracma_2.4.4 htmlwidgets_1.6.4  
## [25] emmeans_1.8.7 plotly_4.10.4 uuid_1.1-0  
## [28] mime_0.12 lifecycle_1.0.3 iterators_1.0.14  
## [31] pkgconfig_2.0.3 sjlabelled_1.2.0 R6_2.5.1  
## [34] fastmap_1.1.1 shiny_1.7.4.1 digest_0.6.33  
## [37] numDeriv_2016.8-1.1 colorspace_2.1-0 rprojroot_2.0.3
```

## [40] textshaping_0.3.6	labeling_0.4.2	effects_4.2-2
## [43] fansi_1.0.4	abind_1.4-5	httr_1.4.7
## [46] mgcv_1.9-1	compiler_4.3.1	here_1.0.1
## [49] fontquiver_0.2.1	withr_2.5.0	doParallel_1.0.17
## [52] backports_1.4.1	DBI_1.2.3	carData_3.0-5
## [55] performance_0.10.4	highr_0.10	openssl_2.1.0
## [58] sjstats_0.18.2	gfonts_0.2.0	caTools_1.18.2
## [61] tools_4.3.1	zip_2.3.0	httpuv_1.6.11
## [64] nnet_7.3-19	qqconf_1.3.2	glue_1.6.2
## [67] nlme_3.1-164	promises_1.2.0.1	grid_4.3.1
## [70] reshape2_1.4.4	generics_0.1.3	qqplotr_0.0.6
## [73] gtable_0.3.3	ggResidpanel_0.3.0	hms_1.1.3
## [76] data.table_1.14.8	car_3.1-2	xml2_1.3.5
## [79] utf8_1.2.3	foreach_1.5.2	pillar_1.9.0
## [82] stringr_1.5.0	later_1.3.1	mitools_2.4
## [85] robustbase_0.99-3	splines_4.3.1	tidyselect_1.2.0
## [88] fontLiberation_0.1.0	expint_0.1-8	knitr_1.43
## [91] fontBitstreamVera_0.1.1	crul_1.4.0	xfun_0.39
## [94] DEoptimR_1.1-3	stringi_1.7.12	lazyeval_0.2.2
## [97] yaml_2.3.7	boot_1.3-30	evaluate_0.21
## [100] codetools_0.2-19	httpcode_0.3.0	officer_0.6.2
## [103] twosamples_2.0.1	gdtools_0.3.3	tibble_3.2.1
## [106] cli_3.6.1	xtable_1.8-4	parameters_0.21.1
## [109] systemfonts_1.0.4	pbmccapply_1.5.1	afex_1.3-0
## [112] munsell_0.5.0	modelr_0.1.11	Rcpp_1.0.11
## [115] ggeffects_1.2.3	coda_0.19-4.1	parallel_4.3.1
## [118] ellipsis_0.3.2	assertthat_0.2.1	bayestestR_0.13.1
## [121] opdisDownsampling_1.0.1	bitops_1.0-8	viridisLite_0.4.2
## [124] mvtnorm_1.2-2	scales_1.2.1	insight_0.19.3
## [127] purrr_1.0.1	crayon_1.5.2	rlang_1.1.1
## [130] cowplot_1.1.1		