

# F02\_mci\_style\_neu\_mixed\_models.R

2020-09-19

```
## MCI_STYLE_NEU MIXED MODELS SCRIPT ##
```

```
# Computes linear mixed-effects regression models with simple contrast coding for the fixed effects of semantics and  
# narrative context (the context being emotionally neutral). Thus, in each model, the estimate of the intercept is the  
# grand mean, while the estimates of the slopes contrast "treatment" levels to their respective reference levels  
# (semantics: violation - intuitive, mci - intuitive; narrative context style: fairytale - normal). The maximal random  
# effects structure is used with all by-participant and by-item random slopes and random intercepts. Correlations  
# between random effects are removed if the model fails to converge with two different numerical optimizers. Planned  
# follow-up contrasts are computed for the main effects and the effects of semantics separately within each type of  
# narrative context style.
```

```
## SETUP ## -----
```

```
# Load packages
```

```
library(MASS)           # Version 7.3-51.6  
library(lme4)           # Version 1.1-23  
library(lmerTest)       # Version 3.1-2  
library(afex)           # Version 0.27-2  
library(emmeans)       # Version 1.4.8  
library(tidyverse)     # Version 1.3.0  
library(magrittr)      # Version 1.5
```

```
# Load preprocessed data
```

```
a1 <- readRDS("EEG/export/a1.RDS")
```

```
# Remove trials with errors or invalid RTs/ERPs
```

```
a1 %<>% filter(!error) %>% na.omit()
```

```
# Center behavioral ratings (valence and arousal) around 0
```

```

a1 %<>% mutate(rating_1 = Rating1Resp - 2, rating_2 = Rating2Resp - 2)

# Define simple contrast coding for context narrative style (normal - fairytale)
#   H0(Intercept): (mu1+mu2)/2 = 0 <-> mu1+mu2 = 0
#   H0(Slope): -mu1 + mu2 = 0
#   with mu1 = mean of the normal style and mu2 = mean of the fairytale style
t(contrasts.style <- t(cbind(c("nor" = -1, "ftl" = 1))))

##      [,1]
## nor    -1
## ftl     1

contrasts(a1$style) <- ginv(contrasts.style)

# Define simple contrast coding for semantics (violation - intuitive, mci - intuitive)
#   H0(Intercept): (mu1+mu2+mu3)/3 = 0 <-> mu1+mu2+mu3 = 0
#   H0(Slope1): -1*mu1 + 1*mu2 + 0*mu3 = 0
#   H0(Slope2): -1*mu1 + 0*mu2 + 1*mu3 = 0
#   with mu1 = mean of intuitive concepts, mu2 = mean of violations, mu3 = mean of MCIs
t(contrasts.semantics <- t(cbind(c("int" = -1, "vio" = 1, "mci" = 0),
                                c("int" = -1, "vio" = 0, "mci" = 1))))

##      [,1] [,2]
## int    -1   -1
## vio     1    0
## mci     0    1

```

```

contrasts(a1$semantics) <- ginv(contrasts.semantics)

## LINEAR MIXED-EFFECTS MODELS ## -----

# Specifiy settings for optimization in lmer
control_params <- lmerControl(calc.derivs = FALSE, optimizer = "bobyqa", optCtrl = list(maxfun = 2e5))

# LMM for rating 1
mod_valence <- lmer_alt(rating_1 ~ semantics*style + (semantics*style||participant) + (semantics*style||item),
                        data = a1, control = control_params)

```

```

# LMM for rating 2
mod_arousal <- lmer_alt(rating_2 ~ semantics*style + (semantics*style||participant) + (semantics*style||item),
                      data = a1, control = control_params)

# LMM for verb-related N400
mod_N400_verb <- lmer_alt(N400_verb ~ semantics*style + (semantics*style||participant) + (semantics*style||item),
                        data = a1, control = control_params)

# LMM for picture-related N400
mod_N400_pict <- lmer_alt(N400_pict ~ semantics*style + (semantics*style||participant) + (semantics*style||item),
                        data = a1, control = control_params)

# Create a list of all four models
models <- list("RATING_1" = mod_valence, "RATING_2" = mod_arousal,
              "N400_VERB" = mod_N400_verb, "N400_PICT" = mod_N400_pict)

# F-tests (type III tests)
(tests <- map(models, anova))

```

```

## $RATING_1
## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq Mean Sq NumDF   DenDF F value Pr(>F)
## semantics    0.015486  0.007743     2   90.117  0.0562 0.9453
## style        0.246118  0.246118     1   22.151  1.7877 0.1948
## semantics:style 0.061438  0.030719     2  161.930  0.2231 0.8003
##
## $RATING_2
## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq Mean Sq NumDF   DenDF F value  Pr(>F)
## semantics    0.02041  0.01020     2   78.896  0.0519 0.94945
## style        1.15011  1.15011     1   23.074  5.8503 0.02386 *
## semantics:style 0.08628  0.04314     2   69.605  0.2194 0.80352
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## $N400_VERB
## Type III Analysis of Variance Table with Satterthwaite's method
##           Sum Sq Mean Sq NumDF   DenDF F value Pr(>F)

```

```
## semantics      49.615  24.808      2 167.039  2.1461 0.1202
## style          12.252  12.252      1  49.762  1.0599 0.3082
## semantics:style 36.095  18.047      2  58.826  1.5613 0.2184
##
## $N400_PICT
## Type III Analysis of Variance Table with Satterthwaite's method
##              Sum Sq Mean Sq NumDF  DenDF F value    Pr(>F)
## semantics      73.377  36.688      2   75.8  1.8929 0.157685
## style          134.130 134.130      1 6692.5  6.9202 0.008542 **
## semantics:style 185.370  92.685      2   82.2  4.7819 0.010851 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
## PLANNED FOLLOW-UP CONTRASTS ## -----
```

```
# Allow emmeans to compute Satterthwaites p-values
emm_options(lmer.df = "Satterthwaite", lmerTest.limit = Inf)

# Follow-up contrasts for the main effect of semantics
(means.semantics <- map(models,function(x){
  emmeans(x, trt.vs.ctrl ~ semantics, infer = TRUE, adjust = "bonferroni")$contrasts
}))
```

```
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
```

```
## $RATING_1
## contrast estimate      SE   df lower.CL upper.CL t.ratio p.value
## vio - int  0.00694 0.0218 46.5  -0.0436   0.0574  0.318  1.0000
## mci - int -0.00136 0.0216 46.7  -0.0515   0.0488 -0.063  1.0000
##
## Results are averaged over the levels of: style
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
```

```
##
## $RATING_2
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.00611 0.0227 50.9 -0.0464 0.0586 0.269 1.0000
## mci - int -0.00323 0.0243 50.9 -0.0594 0.0530 -0.133 1.0000
##
## Results are averaged over the levels of: style
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
##
## $N400_VERB
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.020 0.100 6757.9 -0.205 0.2449 0.199 1.0000
## mci - int -0.181 0.105 81.3 -0.421 0.0593 -1.719 0.1787
##
## Results are averaged over the levels of: style
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
##
## $N400_PICT
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.0229 0.192 57.2 -0.420 0.4655 0.119 1.0000
## mci - int -0.3524 0.189 40.6 -0.793 0.0884 -1.861 0.1400
##
## Results are averaged over the levels of: style
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests

# Follow-up contrasts for the main effect of context style
(means.style <- map(models, function(x){
  emmeans(x, trt.vs.ctrl ~ style, infer = TRUE, adjust = "bonferroni")$contrasts
}))
```

```
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
## NOTE: Results may be misleading due to involvement in interactions
```

```
## $RATING_1
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## ftl - nor -0.0231 0.0173 22.1 -0.0589 0.0127 -1.337 0.1948
##
```

```
## Results are averaged over the levels of: semantics
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
##
```

```
## $RATING_2
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## ftl - nor -0.0508 0.021 23.1 -0.0942 -0.00736 -2.419 0.0239
##
```

```
## Results are averaged over the levels of: semantics
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
##
```

```
## $N400_VERB
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## ftl - nor -0.0857 0.0832 49.8 -0.253 0.0815 -1.030 0.3082
##
```

```
## Results are averaged over the levels of: semantics
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
##
```

```
## $N400_PICT
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## ftl - nor 0.279 0.106 6692 0.071 0.486 2.631 0.0085
##
```

```
## Results are averaged over the levels of: semantics
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
```

```
# Follow-up contrasts for semantics within each context style
(means.nested <- map(models, function(x){
  emmeans(x, trt.vs.ctrl ~ semantics|style, infer = TRUE, adjust = "bonferroni")$contrasts
})))
```

```
## $RATING_1
## style = nor:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.00222 0.0244 72.8 -0.0536 0.0580 0.091 1.0000
## mci - int 0.00131 0.0244 72.5 -0.0546 0.0572 0.054 1.0000
##
## style = ftl:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.01167 0.0244 72.9 -0.0442 0.0675 0.478 1.0000
## mci - int -0.00403 0.0244 72.4 -0.0599 0.0518 -0.165 1.0000
##
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
##
## $RATING_2
## style = nor:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.011525 0.0262 90.0 -0.0482 0.0713 0.440 1.0000
## mci - int 0.006008 0.0282 77.0 -0.0585 0.0705 0.213 1.0000
##
## style = ftl:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.000692 0.0262 90.2 -0.0591 0.0605 0.026 1.0000
## mci - int -0.012475 0.0282 76.8 -0.0769 0.0520 -0.443 1.0000
##
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
##
## $N400_VERB
```

```

## style = nor:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int -0.0241 0.146 294.2 -0.352 0.3041 -0.165 1.0000
## mci - int -0.3805 0.156 90.7 -0.736 -0.0251 -2.440 0.0332
##
## style = ftl:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.0640 0.146 295.6 -0.265 0.3925 0.439 1.0000
## mci - int 0.0192 0.156 90.3 -0.336 0.3743 0.123 1.0000
##
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests
##
## $N400_PICT
## style = nor:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int -0.221 0.240 91.6 -0.769 0.327 -0.920 0.7198
## mci - int -0.751 0.230 87.8 -1.275 -0.227 -3.270 0.0031
##
## style = ftl:
## contrast estimate SE df lower.CL upper.CL t.ratio p.value
## vio - int 0.267 0.241 91.7 -0.281 0.815 1.110 0.5399
## mci - int 0.046 0.229 87.5 -0.477 0.569 0.201 1.0000
##
## Degrees-of-freedom method: satterthwaite
## Confidence level used: 0.95
## Conf-level adjustment: bonferroni method for 2 estimates
## P value adjustment: bonferroni method for 2 tests

# Backup results
save(models, tests, means.semantics, means.style, means.nested, file = "EEG/export/stats.RData")

# System specs and package versions
sessionInfo()

## R version 4.0.2 (2020-06-22)
## Platform: x86_64-w64-mingw32/x64 (64-bit)

```



```

## Running under: Windows 10 x64 (build 18362)
##
## Matrix products: default
##
## locale:
## [1] LC_COLLATE=German_Germany.1252 LC_CTYPE=German_Germany.1252 LC_MONETARY=German_Germany.1252 LC_NUMERIC=C
## [5] LC_TIME=German_Germany.1252
##
## attached base packages:
## [1] stats      graphics  grDevices datasets  utils      methods    base
##
## other attached packages:
## [1] magrittr_1.5      forcats_0.5.0    stringr_1.4.0    dplyr_1.0.0      purrr_0.3.4      readr_1.3.1      tidyr_1.1.0      tibble_3.0.3      gg
## [10] tidyverse_1.3.0  emmeans_1.4.8    afex_0.27-2      lmerTest_3.1-2   lme4_1.1-23      Matrix_1.2-18    MASS_7.3-51.6
##
## loaded via a namespace (and not attached):
## [1] minqa_1.2.4      colorspace_1.4-1 ellipsis_0.3.1    rio_0.5.16        estimability_1.3  fs_1.5.0          rstudioap
## [8] listenv_0.8.0    R.matlab_3.6.2    fansi_0.4.1       mvtnorm_1.1-1     lubridate_1.7.9   xml2_1.3.2        codetools
## [15] splines_4.0.2    R.methodsS3_1.8.0 knitr_1.29         eegUtils_0.5.0.9000 jsonlite_1.7.0    nloptr_1.2.2.2    broom_0.7
## [22] dbplyr_1.4.4     R.oo_1.23.0       shiny_1.5.0        compiler_4.0.2     httr_1.4.2        backports_1.1.8    lazyeval_
## [29] assertthat_0.2.1 fastmap_1.0.1     cli_2.0.2          later_1.1.0.1     htmltools_0.5.0   tools_4.0.2        gtable_0.
## [36] glue_1.4.1       reshape2_1.4.4    Rcpp_1.0.5         carData_3.0-4     cellranger_1.1.0  vctrs_0.3.2        nlme_3.1-
## [43] xfun_0.16        globals_0.12.5    Rmisc_1.5          openxlsx_4.1.5    rvest_0.3.6       mime_0.9           miniUI_0.
## [50] lifecycle_0.2.0  renv_0.12.0       statmod_1.4.34     future_1.18.0     scales_1.1.1      hms_0.5.3          promises_
## [57] parallel_4.0.2   yaml_2.2.1        curl_4.3           stringi_1.4.6     highr_0.8         boot_1.3-25        zip_2.1.1
## [64] matrixStats_0.56.0 rlang_0.4.7        pkgconfig_2.0.3    pracma_2.2.9      evaluate_0.14     lattice_0.20-41    htmlwidge
## [71] tidyselect_1.1.0 plyr_1.8.6         R6_2.4.1           generics_0.0.2     ini_0.3.1         DBI_1.1.0          mgcv_1.8-
## [78] pillar_1.4.6     haven_2.3.1        foreign_0.8-80     withr_2.2.0       abind_1.4-5       future.apply_1.6.0 modelr_0.
## [85] crayon_1.3.4     car_3.0-8          plotly_4.9.2.1     rmarkdown_2.3     grid_4.0.2        readxl_1.3.1       data.tabl
## [92] blob_1.2.1       reprex_0.3.0       digest_0.6.25      xtable_1.8-4      httpuv_1.5.4      numDeriv_2016.8-1.1 R.utils_2
## [99] signal_0.7-6     munsell_0.5.0      viridisLite_0.3.0

```