

7CS4-22-Cyber Security Lab Meenakshi Nawal

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in A Lab Manual on (7CS4-22: Cyber Security Lab) Programme: B.Tech Semester: VII Session 2022-2023 Dr. Meenakshi Nawal (Associate Professor) (Computer Science and Engineering) Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in LAB MANUAL Cyber Security Lab (7CS4-22) VERSION 1.0 AUTHOR / OWNER REVIEWED BY APPROVED BY NAME Dr. Meenakshi Nawal Prof. (Dr.) Mukesh Kumar Gupta DESIGNATION Associate Professor HOD (CSE) SIGNATURE & REVIEW DATE SIGNATURE & REVIEW DATE SIGNATURE & REVIEW DATE Department of Computer Science & Engineering, Jaipur – 302017, Rajasthan (INDIA) E-Mail: hodcs@skit.ac.in, URL: www.skit.ac.in Swami Keshvanand

Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in LAB RULES Responsibilities of Users: Users are expected to follow some obvious rules of conduct: Always: o Enter the lab on time and leave at proper time. o Wait for the previous class to leave before the next class enters. o Keep the bag outside in the respective racks. o Utilize lab hours in the corresponding. o Turn off the machine before leaving the lab unless a member of lab staff has specifically told you not to do so. o Leave the labs at least as nice as you found them. o If you notice a problem with a piece of equipment (e.g. a computer doesn't respond) or the room in general (e.g. cooling, heating, lighting) please report it to lab staff immediately. Do not attempt to fix the problem yourself. Never: o Don't abuse the equipment. o Do not adjust the heat or air conditioners. If you feel the temperature is not properly set, inform lab staff; we will attempt to maintain a balance that is healthy for people and machines. o Do not attempt to reboot a computer. Report problems to lab staff. o Do not remove or modify any software or file without permission. o Do not remove printers and machines from the network without being explicitly told to do so by lab staff. o Don't monopolize equipment. If you're going to be away from your machine for more than 10 or 15 minutes, log out before leaving. This is both for the security Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:

www.skit.ac.in of your account, and to ensure that others are able to use the lab resources while you are not.

- o Don't use internet, internet chat of any kind in your regular lab schedule.
- o Do not download or upload of MP3, JPG or MPEG files.
- o No games are allowed in the lab sessions.
- o No hardware including USB drives can be connected or disconnected in the labs without prior permission of the lab in-charge.
- o No food or drink is allowed in the lab or near any of the equipment. Aside from the fact that it leaves a mess and attracts pests, spilling anything on a keyboard or other piece of computer equipment could cause permanent, irreparable, and costly damage. (and in fact has)
- o If you need to eat or drink, take a break and do so in the canteen.
- o Don't bring any external material in the lab, except your lab record, copy and books.
- o Don't bring the mobile phones in the lab. If necessary, then keep them in silence mode.
- o Please be considerate of those around you, especially in terms of noise level. While labs are a natural place for conversations of all types, kindly keep the volume turned down. If you are having problems or questions, please go to either the faculty, lab in-charge or the lab supporting staff. They will help you. We need your full support and cooperation for smooth functioning of the lab.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

INSTRUCTIONS BEFORE ENTERING IN THE LAB

- All the students are supposed to prepare the theory regarding the next experiment/ Program.
- Students are supposed to bring their lab records as per their lab schedule.
- Previous experiment/program should be written in the lab record.
- If applicable trace

paper/graph paper must be pasted in lab record with proper labeling.

- All the students must follow the instructions, failing which he/she may not be allowed in the lab.

WHILE WORKING IN THE LAB

- Adhere to experimental schedule as instructed by the lab in-charge/faculty.
- Get the previously performed experiment/ program signed by the faculty/ lab in charge.
- Get the output of current experiment/program checked by the faculty/ lab in charge in the lab copy.
- Each student should work on his/her assigned computer at each turn of the lab.
- Take responsibility of valuable accessories.
- Concentrate on the assigned practical and don't play games.
- If anyone is caught red-handed carrying any equipment of the lab, then he/she will have to face serious consequences.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

MARKING/ASSESSMENT SYSTEM

Total Marks -100

Distribution of Marks - 60 (Sessional)

Attendance	File Work	Performance	Viva	Total
10	10	20	20	60

Distribution of Marks - 40 (End Term)

These marks depend on External Examiner.	File Work	Performance	Viva	Total
	10	20	10	40

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

RTU Lab Syllabus

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-

5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in Beyond the Syllabus 1. Implement the following SUBSTITUTION & TRANSPOSITION TECHNIQUES concepts: a) Playfair Cipher b) Hill Cipher 2. Implement the following algorithms a) RSA Algorithm b) MD5 c) SHA-1 Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in Institute Vision/Mission/Quality policy VISION To Promote Higher Learning in Advanced Technology and Industrial Research to make our Country a Global Player. MISSION (SKIT) To Promote Quality Education, Training and Research in the field of Engineering by establishing effective interface with Industry and to encourage Faculty to undertake Industry Sponsored Projects for Students. QUALITY POLICY (SKIT) We are committed to 'achievement of quality' as an integral part of our institutional policy by continuous self-evaluation and striving to improve ourselves. Institute would pursue quality in: ➤ All its endeavors like admissions, teaching-learning processes, examinations, extra and co- curricular activities, industry-institution interaction, research & development, continuing education, and consultancy. ➤ Functional areas like teaching departments, training & placement cell, library, administrative office, accounts office, hostels, canteen, security services, transport, maintenance section and all other services." Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail:

info@skit.ac.in Web: www.skit.ac.in Department Vision and Mission VISION Producing quality graduates trained in the latest tools and technologies and to be a leading department in the state and region by imparting in-depth knowledge to the students in an emerging technology in computer science & engineering. MISSION Delivering Student's resources in IT enabled domain through: ➤ Effective Industry interaction and project-based learning ➤ Motivating our graduates for Employability, entrepreneurship, research, and higher education ➤ Providing excellent engineering skills in a state-of-the-art infrastructure Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in PO/PSO-Indicator-Competency Program Outcomes/Program Specific Outcomes – Indicators - Competencies Program Outcome/Program Specific Outcome Indicator Competency PO 1: Engineering knowledge: Apply the knowledge of mathematics, science, engineering fundamentals, and an engineering specialisation for the solution of complex engineering problems. 1.1 Apply mathematical techniques such as calculus, linear algebra, and statistics to solve problems 1.2 Apply advanced mathematical techniques to model and solve computer science & engineering problems 1.3 Apply laws of natural science to an engineering problem 1.4 Apply fundamental engineering concepts to solve engineering problems 1.5 Apply computer science & engineering concepts to solve engineering problems. PO 2: Problem analysis: Identify, formulate, research literature, and analyse complex engineering problems reaching substantiated conclusions using first principles of

mathematics, natural sciences, and

engineering sciences. 2.1 Articulate problem statements and identify objectives 2.2 Identify engineering systems, variables, and parameters to solve the problems 2.3 Identify the mathematical, engineering and other relevant knowledge that applies to a given problem 2.4 Reframe complex problems into interconnected sub-problems 2.5 problems Identify, assemble and evaluate information 2.6 Identify existing processes/solution methods for solving the problem, including forming justified approximations and assumptions 2.7 Compare and contrast alternative solution processes to select the best process. 2.8 Combine scientific principles and engineering concepts to formulate model/s (mathematical or otherwise) of a system or process that is appropriate in terms of applicability and required accuracy. 2.9 Identify assumptions (mathematical and physical) necessary to allow modeling of a system at the level of accuracy required. 2.1 Apply engineering mathematics and computations to solve mathematical models 2.11 Produce and validate results through skilful use of contemporary Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in engineering tools and models 2.12 Identify sources of error in the solution process, and limitations of the solution. 2.13 Extract desired understanding and conclusions consistent with objectives and limitations of the analysis PO 3: Design/Development of Solutions: Design solutions for complex engineering problems and design system components or processes that meet the specified needs with appropriate consideration for public health and safety, and cultural, societal, and environmental considerations. 3.1

Recognize that need analysis is key to good problem definition 3.2 Elicit and document, engineering requirements from stakeholders 3.3 Synthesize engineering requirements from a review of the state-of-the-art 3.4 Extract engineering requirements from relevant engineering Codes and Standards such as IEEE, ACM, ISO etc. 3.5 Explore and synthesize engineering requirements considering health, safety risks, environmental, cultural and societal issues 3.6 Determine design objectives, functional requirements and arrive at specifications 3.7 Apply formal idea generation tools to develop multiple engineering design solutions 3.8 Build models/prototypes to develop diverse set of design solutions 3.9 Identify suitable criteria for evaluation of alternate design solutions 3.1 Apply formal decision-making tools to select optimal engineering design solutions for further development 3.11 Consult with domain experts and stakeholders to select candidate engineering design solution for further development 3.12 Refine a conceptual design into a detailed design within the existing constraints (of the resources) 3.13 Generate information through appropriate tests to improve or revise design PO 4: Conduct investigations of complex problems: Use research-based knowledge and research methods including design of experiments, analysis and interpretation of data, and synthesis of the information to provide valid conclusions. 4.1 Define a problem, its scope and importance for purposes of investigation 4.2 Examine the relevant methods, tools and techniques of experiment design, system calibration, data acquisition, analysis and presentation 4.3 Apply appropriate instrumentation and/or software tools to make measurements of physical quantities 4.4 Establish a relationship between measured data and underlying physical principles. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura,

Jaipur-302017,

INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

4.5 Design and develop experimental approach, specify appropriate equipment and procedures 4.6 Understand the importance of statistical design of experiments and choose an appropriate experimental design plan based on the study objectives 4.7 Use appropriate procedures, tools and techniques to conduct experiments and collect data 4.8 Analyze data for trends and correlations, stating possible errors and limitations 4.9 Represent data (in tabular and/or graphical forms) so as to facilitate analysis and explanation of the data, and drawing of conclusions 4.1 Synthesize information and knowledge about the problem from the raw data to reach appropriate conclusions

PO 5: Modern tool usage: Create, select, and apply appropriate techniques, resources, and modern engineering and IT tools including prediction and modelling to complex engineering activities with an understanding of the limitations.

5.1 Identify modern engineering tools, techniques and resources for engineering activities 5.2 Create/adapt/modify/extend tools and techniques to solve engineering problems 5.3 Identify the strengths and limitations of tools for (i) acquiring information, (ii) modelling and simulating, (iii) monitoring system performance, and (iv) creating engineering designs. 5.4 Demonstrate proficiency in using discipline specific tools 5.5 Discuss limitations and validate tools, techniques and resources 5.6 Verify the credibility of results from tool use with reference to the accuracy and limitations, and the assumptions inherent in their use.

PO 6: The engineer and society: Apply reasoning informed by the contextual knowledge to assess societal, health, safety, legal, and cultural issues and the consequent responsibilities

relevant to the professional engineering practice.

6.1 Identify and describe various engineering roles; particularly as pertains to protection of the public and public interest at global, regional and local level 6.2 Interpret legislation, regulations, codes, and standards relevant to your discipline and explain its contribution to the protection of the public

PO 7: Environment and sustainability: Understand 7.1 Identify risks/impacts in the life cycle of an engineering product or activity

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA

Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

the impact of the professional engineering solutions in societal and environmental contexts, and demonstrate the knowledge of, and need for sustainable development. 7.2 Understand the relationship between the technical, socio economic and environmental dimensions of sustainability 7.3 Describe management techniques for sustainable development 7.4 Apply principles of preventive engineering and sustainable development to an engineering activity or product relevant to the discipline

PO 8: Ethics: Apply ethical principles and commit to professional ethics and responsibilities and norms of the engineering practice.

8.1 Identify situations of unethical professional conduct and propose ethical alternatives 8.2 Identify tenets of the ASME professional code of ethics 8.3 Examine and apply moral & ethical principles to known case studies

PO 9: Individual and team work: Function effectively as an individual, and as a member or leader in diverse teams, and in multidisciplinary settings.

9.1 Recognize a variety of working and learning preferences; appreciate the value of diversity on a team 9.2 Implement the

norms of practice (e.g. rules, roles, charters, agendas, etc.) of effective team work, to accomplish a goal. 9.3 Demonstrate effective communication, problem solving, conflict resolution and leadership skills 9.4 Treat other team members respectfully 9.5 Listen to other members and maintain composure in difficult situations 9.6 Present results as a team, with smooth integration of contributions from all individual efforts PO 10: Communication: Communicate effectively on complex engineering activities with the engineering community and with the society at large, such as, being able to comprehend and write effective reports and design documentation, make effective presentations, and give and receive clear instructions. 10.1 Read, understand and interpret technical and non-technical information 10.2 Produce clear, well-constructed, and well-supported written engineering documents 10.3 Create flow in a document or presentation 10.4 Listen to and comprehend information, instructions, and viewpoints of others 10.5 Deliver effective oral presentations to technical and non-technical audiences 10.6 Create engineering-standard figures, reports and drawings to complement writing and presentations 10.7 Use a variety of media effectively to convey a message in a document or a presentation PO 11: Project management and finance: 11.1 Describe various economic and financial costs/benefits of an engineering activity Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in Demonstrate knowledge and understanding of the engineering and management principles and apply these to one's own work, as a member and leader in a team, to manage projects and in

multidisciplinary environments. 11.2 Analyze different forms of financial statements to evaluate the financial status of an engineering project 11.3 Analyze and select the most appropriate proposal based on economic and financial considerations. 11.4 Identify the tasks required to complete an engineering activity, and the resources required to complete the tasks. 11.5 Use project management tools to schedule an engineering project so it is completed on time and on budget. PO 12: Life-long learning: Recognise the need for, and have the preparation and ability to engage in independent and life-long learning in the broadest context of technological change. 12.1 Describe the rationale for requirement for continuing professional development 12.2 Identify deficiencies or gaps in knowledge and demonstrate an ability to source information to close this gap 12.3 Identify historic points of technological advance in engineering that required practitioners to seek education in order to stay current 12.4 Recognize the need and be able to clearly explain why it is vitally important to keep current regarding new developments in your field 12.5 Source and comprehend technical literature and other credible sources of information 12.6 Analyze sourced technical and popular information for feasibility, viability, sustainability, etc. PSO1: Core Engineering Skills: Exhibit fundamental concepts of Data Structures, Databases, Operating Systems, Computer Network, Theory of Computation, Advanced Programming and Software Engineering. PSO1.1 Possess the concepts of Data Structure and Database Management System PSO1.2 Possess the concepts of core engineering subjects including Operating System, Computer Networks and Software Engineering. PSO1.3 Apply basic programming skills to solve real world problems PSO2: Standard Software Engineering practices: Demonstrate an ability to design, develop, test, debug, deploy,

analyze, troubleshoot, maintain, manage and secure a software. PSO2.1 Apply fundamental software engineering concepts to solve real world problem PSO2.2 Possess conceptual knowledge for designing, analysing and testing a software PSO2.3 Estimate and evaluate the cost related to a Software Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in PSO3: Future Endeavors: Recognize the need to have knowledge of higher education institutions/ organizations/ companies related to computer science & engineering. PSO3.1 Identify the requirement of continuing education through postgraduation like M.Tech., MS, MBA etc. PSO3.2 List various higher education institutes and organizations related to computer science & engineering. Bloom's Taxonomy Level Descriptor Level of Attainment Keywords

- 1 Remembering Recalling from memory List, define, tell, describe, recite, recall, identify, show, label, tabulate, quote, name, who, when, where, etc.
- 2 Understanding Explaining ideas or concepts describe, explain, paraphrase, restate, associate, contrast, summarize, differentiate interpret, discuss
- 3 Applying Using information in another familiar situation Calculate, predict, apply, solve, illustrate, use, demonstrate, determine, model, experiment, show, examine, modify
- 4 Analyzing Breaking information into part to explore understandings and relationships classify, outline, break down, categorize, analyze, diagram, illustrate, infer, select
- 5 Evaluating Justifying a decision or course of action assess, decide, choose, rank, grade, test, measure, defend, recommend, convince, select, judge, support, conclude,

argue, justify, compare, summarize, evaluate

- 6 Creating Generating new ideas, products, or views to do things Design, formulate, build, invent, create, compose, generate, derive, modify, develop, integrate

** It may be noted that some of the verbs in the above table are associated with multiple Bloom's Taxonomy level. These verbs are actions that could apply to different activities. We need to keep in mind that it's the skill, action or activity we need out students to demonstrate that will determine the contextual meaning of the verb used in the assessment question. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in COs Competency Level Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in CO-PO-PSO Mapping Using Performance Indicators (PIs) Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

CO-PO-PSO Mapping: Formulation & Justification Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

INDEX

Sr. No.	Topic	Page Number
1	Lab Plan	1
2	Lab Objective and Outcome	2
3	Experiment No 1	3
4	Experiment No 2	6
5	Experiment No 3	11
6	Experiment No 4	16
7	Experiment No 5	25
8	Experiment No 6	28
9	Experiment No 7	33
10	Experiment No 8	35
11	Experiment No 9	39
12	Experiment No 10	44
13	Experiment No 11	47
14	Experiment No 12	49
15	Experiment No 13	65
16	Experiment No 14	68
17	Experiment No 15	70
18	Experiment No 16	71
19	Viva Questions	90

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

1 LAB PLAN Total number of experiments 10 Total number of turns required 10 Number of turns required for Experiment Number Turns Scheduled Day Experiment 1 1 Day 1 Experiment 2 1 Day 2 Experiment 3 1 Day 3 Experiment 4 1 Day 4 Experiment 5 1 Day 5 Experiment 6 1 Day 6 Experiment 7 1 Day 7 Experiment 8 1 Day 8 Experiment 9 1 Day 9 Experiment 10 1 Day 10 Experiment 11 1 Day 11 Experiment 12 1 Day 12 Experiment 13 1 Day 13 Experiment 14 1 Day 14 Experiment 15 1 Day 15 Experiment 16 1 Day 16 Distribution of Lab Hours: Attendance 05 minutes Explanation of features of language 15 minutes Explanation of experiment 15 minutes Performance of experiment 70 minutes Viva / Quiz / Queries 15 minutes Total 120 Minutes (2 Hrs.) Swami Keshvanand Institute of Technology, Management

& Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

2 Lab Objective and Outcome Objective The objective of this course is to impart necessary and practical knowledge of components of cyber security lab and develop skills required to build real-life based projects.

- Understand and implement the cipher techniques.
- Demonstrate the knowledge of cyber security and implement different cyber security algorithms.
- Understand the different types of attacks on the systems.
- Analyze different packet sniffing tools and identify TCP/UDP datagram.
- Installation and understanding of rootkits and snort tools and their various options.
- Demonstrate how to secure the data and create digital signature.

Course Outcomes After completion of this course, students will be able to –

- 7CS4-22.1 Apply the cryptographic algorithms for data communication.
- 7CS4-22.2 Understand implementation of various security tools and algorithms.
- 7CS4-22.3 Apply the Digital signature for secure data transmission and secure data storage.
- 7CS4-22.4 Utilize the different open-source tools for network security and analysis.
- 7CS4-22.5 Demonstrate intrusion detection system using network security tool.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

3 Experiments Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by

UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

4 d Experiment 1: Implementation of Caesar Cipher The Caesar Cipher, named after Julius Caesar of Ancient Rome, is a type of substitution cipher where each letter of the original (plaintext) message is substituted with another letter. Encrypting: But how do we decide what letter is replaced by what? That's where the key comes into play. Found in almost every encryption algorithm, the key determines how the data is encrypted. In the Caesar cipher, the key is a number from 0 to 25, because there are 26 letters in the alphabet. This means that for any given message, there are 26 different ways we can encrypt the message. For each letter, the key determines which letter is replacing the current letter, by counting down the alphabet. In the following example, let's say we wanted to encrypt the letter B with a key of 3, we would find the 3rd letter that appears after B - which is C, D, then finally E. Fig. Encryption in Caesar Cipher Algorithm Decrypting: Decrypting works in a very similar way - except this time, instead of counting "down" the alphabet, you count "up"! As an example, let's try to decrypt ELOOB using a key of 3 - because we know the result should be our original plaintext, BILLY. Let's start by aligning our alphabets: Caesar Cipher algorithm Implementation in python: class CaesarCipher(): def init (self,key,message): self.key = key self.message = message self.cipher = "" self.PlainText = "" Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

5 def encrypt(self): alpha

```
="ABCDEFGHIJKLMNOPQRSTUVWXYZ" beta = "abcdefghijklmnopqrstuvwxyz"
for char in self.message:
    if char in alpha:
        charindex = (alpha.index(char)+ self.key) % len(alpha)
        self.cipher = self.cipher + alpha[charindex]
    elif char in beta:
        charindex = (beta.index(char)+ self.key)% len(beta)
        self.cipher = self.cipher + beta[charindex]
    else:
        self.cipher = self.cipher + char
return self.cipher

def decrypt(self):
    alpha="ABCDEFGHIJKLMNOPQRSTUVWXYZ"
    beta = "abcdefghijklmnopqrstuvwxyz"
    for char in self.cipher:
        if char in alpha:
            charindex = (alpha.index(char) - self.key)% len(alpha)
            self.PlainText = self.PlainText + alpha[charindex]
        elif char in beta:
            charindex = (beta.index(char) - self.key)% len(beta)
            self.PlainText = self.PlainText + beta[charindex]
        else:
            self.PlainText = self.PlainText + char
    return self.PlainText

def main():
    message = input("Enter the Plain Text: ")
    key = int(input("Enter the key: "))
    caesar = CaesarCipher(key, message)
    CipherText = caesar.encrypt()
    print(" Cipher text of given message: ", CipherText)
    PlainText = caesar.decrypt()
    print(" Original message: ", PlainText)

if name == " main ":
    main()

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in
```

6 Experiment 2: Implementation of Rail Fence Cipher The Rail Fence cipher works by writing your message on alternate lines across the page, and then reading off each line in turn. For example, the plaintext "defend the east wall" is written as shown below, with all spaces removed. The ciphertext is then read off by writing the top row first, followed by the bottom row, to get "DFNTEATALEEDHESWL". Encryption To encrypt a message using the Rail Fence Cipher, you must write your message in zigzag

lines across the page, and then read off each row. Firstly, you need to have a key, which for this cipher is the number of rows you are going to have. You then start writing the letters of the plaintext diagonally down to the right until you reach the number of rows specified by the key. You then bounce back up diagonally until you hit the first row again. This continues until the end of the plaintext. For the plaintext we used above, "defend the east wall", with a key of 3, we get the encryption process shown below. Note that at the end of the message we have inserted two "X"s. These are called nulls, and act as placeholders. We do this to make the message fit neatly into the grid (so that there are the same number of letters on the top row, as on the bottom row. Although not necessary, it makes the decryption process a lot easier if the message has this layout. The ciphertext is read off row by row to get "DNETLEEDHESWLXFTAAX".

Decryption Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

7 The decryption process for the Rail Fence Cipher involves reconstructing the diagonal grid used to encrypt the message. We start writing the message but leaving a dash in place of the spaces yet to be occupied. Gradually, you can replace all the dashes with the corresponding letters and read off the plaintext from the table. We start by making a grid with as many rows as the key is, and as many columns as the length of the ciphertext. We then place the first letter in the top left square, and dashes diagonally downwards where the letters will be. When we get back to the top row, we place the next letter in the ciphertext. Continue like this across the row and start the next row when

you reach the end. For example, if you receive the ciphertext "TEKOOHRACIRMNREATANFTETYTGHH", encrypted with a key of 4, you start by placing the "T" in the first square. You then dash the diagonal down spaces until you get back to the top row and place the "E" here. Continuing to fill the top row you get the pattern below. The first row of the decryption process for the Rail Fence Cipher. We have a table with 4 rows because the key is 4, and 28 columns as the ciphertext has length 28. The second stage in the decryption process. The third stage in the decryption process. The fourth and final stage in the decryption process.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

8 From this we can now read the plaintext off following the diagonals to get "they are attacking from the north".

Rail Fence cipher Implementation in python:

```
class RailFenceCipher():
def init(self, message, key):
self.message = message
self.key = key
self.CipherText = ""
self.PlainText = ""
self.Matrix = []
def getmatrix(self):
self.Matrix = [[0 for col in range(len(self.message))] for row in range(self.key)]
return self.Matrix
def encrypt(self):
RailMatrix = self.getmatrix()
# Putting the message in RailMatrix diagonally
row = 0
dir_down = 0
for col in range(len(self.message)):
RailMatrix[row][col] = self.message[col]
if row == 0 or (row < self.key-1 and dir_down == 0):
dir_down = 0
row += 1
else:
row -= 1
dir_down = 1
# Reading the row to get cipher Text for sublist in RailMatrix:
for value in sublist:
if value == 0:
self.CipherText = self.CipherText
else:
self.CipherText = self.CipherText + value
```

Swami Keshvanand Institute of Technology,

Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

```

9 return self.CipherText # Decryption using Rail Fence Cipher
def decrypt(self):
    CipherMatrix = self.getmatrix()
    # mark the diagonal of ciphermatrix
    row = 0
    dir_down = 0
    for col in range(len(self.message)):
        CipherMatrix[row][col] = 1
        if row == 0 or (row < self.key-1 and dir_down == 0):
            dir_down = 0
            row += 1
        else:
            row -= 1
            dir_down = 1
    # putting the cipher text into rows of cipher Matrix
    col = 0
    for sublist in CipherMatrix:
        i = 0
        for value in sublist:
            if value == 1:
                sublist[i] = self.CipherText[col]
                col += 1
            i += 1
    # printing the Original message after decryption result
    result = []
    row = 0
    for col in range(len(self.message)):
        result.append(CipherMatrix[row][col])
        if row == 0 or (row < self.key-1 and dir_down == 0):
            dir_down = 0
            row += 1
        else:
            row -= 1
            dir_down = 1
    self.PlainText = "".join(result)
    return self.PlainText
def str(self):
    return "Input Message: {} \nInput Key: {} \nCipher Text: {} \nPlain Text: {}".format(self.message, self.key, self.CipherText, self.PlainText)

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in
10 def main():
    message = input("Enter the Plain Text: ")
    key = int(input("Enter the key: "))
    RailFence = RailFenceCipher(message, key)
    RailFence.encrypt()
    RailFence.decrypt()
    print("*****")
    print(RailFence)
    print("*****")
if name == "main ":
    main()

```

Swami

Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

11 Experiment 3: Columnar Transposition Cipher

Columnar Transposition involves writing the plaintext out in rows, and then reading the ciphertext off in columns. In its simplest form, it is the Route Cipher where the route is to read down each column in order. For example, the plaintext "a simple transposition" with 5 columns looks like the grid below

Plaintext written across 5 columns. If we now read down each column, we get the ciphertext "ALNISESTITPIMROOPASN".

Encryption We first pick a keyword for our encryption. We write the plaintext out in a grid where the number of columns is the number of letters in the keyword. We then title each column with the respective letter from the keyword. We take the letters in the keyword in alphabetical order and read down the columns in this order. If a letter is repeated, we do the one that appears first, then the next and so on. As an example, let's encrypt the message "The tomato is a plant in the nightshade family" using the keyword tomato. We get the grid given below.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

12 The plaintext is written in a grid beneath the keyword. The numbers represent the alphabetical order of the keyword, and so the order in which the columns will be read. We have written the keyword above the grid of the plaintext, and the numbers telling us which order to read the columns in. Notice

that the first "O" is 3 and the second "O" is 4, and the same thing for the two "T"s. Decryption The decryption process is significantly easier if nulls have been used to pad out the message in the encryption process. Below we shall talk about how to go about decrypting a message in both scenarios. Firstly, if nulls have been used, then you start by writing out the keyword and the alphabetical order of the letters of the keyword. You must then divide the length of the ciphertext by the length of the keyword. The answer to this is the number of rows you need to add to the grid. You then write the ciphertext down the first column until you reach the last row. The next letter becomes the first letter in the second column (by the alphabetical order of the keyword), and so on. As an example, we shall decrypt the ciphertext "ARESA SXOST HEYLO IIAIE XPENG DLLTA HTFAX TENHM WX" given the keyword potato. We start by writing out the keyword and the order of the letters. There are 42 letters in the ciphertext, and the keyword has six letters, so we need $42 \div 6 = 7$ rows. We have the keyword and the order of the letters in the keyword. We also know there are 7 rows. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 13 Now we start by filling in the columns in the order given by the alphabetical order of the keyword, starting with the column headed by "A". After the first column is entered, we have the grid shown to the right. After inserting the second column. We continue to add columns in the order specified by the keyword. After inserting the third column. The completely reconstructed grid. Now we read off the plaintext row at a time to get "potatoes are in

the nightshade family as well". Column Transposition cipher Implementation in python: Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 14

```

import math
class columnTransposition():
    def __init__(self, message, key):
        self.message = message
        self.key = key
        self.CipherText = ""
        self.PlainText = ""
    def __str__(self):
        return "Input Message: {} \nInput Key: {} \nCipher Text: {} \nPlain Text: {}".format(self.message, self.key, self.CipherText, self.PlainText)
    def encrypt(self):
        col = len(self.key)
        # fill the row of matrix using message
        row = math.ceil(len(self.message)/len(self.key))
        PlainMatrix = [
            [" " for col in range(len(self.key))] for i in range(row)
        ]
        message_index = 0
        for sublist in PlainMatrix:
            for value in range(len(self.key)):
                sublist[value] = self.message[message_index]
                if message_index < len(self.message)-1:
                    message_index += 1
                else:
                    break
        # Reading the columns to generate cipher text
        sorted_keys = sorted(self.key)
        # to arrange in order
        for i in range(col):
            col_read_index = self.key.index(sorted_keys[i])
            for row in PlainMatrix:
                self.CipherText = self.CipherText + row[col_read_index]
        Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 15
        return self.CipherText
    def decrypt(self):
        # Create the cipher text matrix and putting the cipher text row =
        math.ceil(len(self.CipherText)/len(self.key))
        CipherMatrix = [
            [" " for col in range(len(self.key))] for col

```

in range(row)] cipher_index =

```
0 sorted_keys = sorted(self.key) for i in range(len(self.key)): for row in CipherMatrix: col_select =
self.key.index(sorted_keys[i]) row[col_select] = self.CipherText[cipher_index] cipher_index += 1 #
Reading the cipher Matrix to generate original message for row in CipherMatrix: for char in row:
self.PlainText = self.PlainText + char return self.PlainText def main(): message = input("Enter the
Plain Text: ") key = input("Enter the key: ") ColTransposition = columnTransposition(message, key)
ColTransposition.encrypt() #ColTransposition.decrypt() ColTransposition.decrypt() print(
ColTransposition) if name == " main ": main() Swami Keshvanand Institute of Technology,
Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE,
Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956
Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 16
```

Experiment 4: Password Cracking Techniques- Brute force & Dictionary attack A password, also known as a PIN, passcode, or secret code, is just a secret word or phrase used for authentication, to determine the identity of a person. Nowadays when you hear the word password, you automatically assume they are talking about a website or something related to computers and other electronic devices, but computers haven't always been around, passwords have. Passwords are a big part of our daily life. We have passwords to protect our email, voicemail, phones, ATM cards, lockers, online banking, wireless networks, encrypted data etc. As you can see, we need to keep them secure because if they fall into the wrong hands, bad things will happen. Let's look at some possible outcomes that could happen if such a thing happened.

- Your bank account could be emptied to fund a large purchase
- Your sensitive email could be read by someone.
- You could be visited by the police station after your wireless network was used to illegal activity. It is extremely important

to know how to secure and create strong passwords. Password cracking is the act of recovering passwords through unconventional and usually unethical methods from data that has been stored or sent through a computer system. Password cracking is a very popular computer attack because once a high-level user password is cracked, you've got the power! There's no longer a need to search for vulnerabilities and all that other mumbojumbo needed to take over a system that we won't be discussing in this section. Also, everyone is susceptible to a password cracking attack. Unless you live in a remote, technology-absent area, you have a password for something, and there's usually something to gain from obtaining your password. Password cracking can be used for both good and evil. If I forgot my password Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 17

for a certain system or program, I might try cracking it before I completely give up on it. Now if it's for any other reason, then it probably has an evil basis and is most likely illegal as well. To show you how real and popular this form of attack is today, here are a few recent happenings.

- Password cracking was used to take over a few high-profile Twitter accounts.
- Wal-

Mart was a victim of a security breach where sensitive information was taken. Password cracking was one of the many methods used to gain entry.

10,000 cracked Hotmail passwords were publicly posted, and every day crackers continue to post new lists on forums all over the internet. • phpBB.com was hacked and their 200,000+ username/password database was dumped and made publicly available to anyone willing to download it. Of those passwords, over 80,000 were reported to have had been cracked. There are many different types of password cracking methods

1. Brute Force Attacks: A

Brute force attack uses trial-and-error to guess login info, encryption keys, or find a hidden web page. Hackers work through all possible combinations hoping to guess correctly. These attacks are done by 'brute force' meaning they use excessive forceful attempts to try and 'force' their way into your private account(s). This is an old attack method, but it's still effective and popular with hackers. Because depending on the length and complexity of the password, cracking it can take anywhere from a few seconds to many years. Here's how hackers benefit from brute force attacks:

- Profiting from ads or collecting activity data
- Stealing personal data and valuables
- Spreading malware to cause disruptions
- Hijacking your system for malicious activity
- Ruining a website's reputation

Tools Aid Brute Force Attempts

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

18 Guessing a password for a particular user or site can take a long time, so hackers have developed tools to do the job faster. Automated tools help with brute force attacks. These use rapid-fire guessing that is built to create every possible password and attempt to use them. Brute force hacking software can find a single dictionary word password within one second. Tools like these have workarounds programmed in them to:

- Work against many computer protocols (like FTP, MySQL, SMTP, and Telnet)
- Allow hackers to crack wireless modems.
- Identify weak passwords
- Decrypt passwords in encrypted storage.
- Translate words into leetspeak — "don't hack me" becomes "d0n7H4cK m3," for example.
- Run all possible combinations of characters.
- Operate dictionary attacks.

How to Defend Against Brute Force Attacks

Brute force attacks need time to run. Some attacks can take weeks or even months to provide anything usable. Most of the defenses against brute force attacks involve increasing the time required for success beyond what is technically possible, but that is not the only defense.

- Increase password length : More characters equal more time to brute force crack
- Increase password complexity : More options for each character also increase the time to brute force crack

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

19

- Limit login attempts : Brute force attacks increment a counter of failed login attempts on most directory services – a good defense against brute force attacks is to lock out users after a few failed attempts, thus nullifying a brute force attack in progress
- Implement Captcha : Captcha is a common system to verify a human is a human on websites and can stop brute force attacks in progress
- Use multi-factor authentication : Multi-factor authentication adds a second layer

of security to each login attempt that requires human intervention which can stop a brute force attack from success

Introduction to the 10 Most Popular Password Cracking Tools

1. Brutus: Brutus is one of the most popular remote online password cracking tools. It claims to be the fastest and most flexible password cracking tool. This tool is free and is only available for Windows systems. It was released back in October 2000. It supports HTTP (Basic Authentication), HTTP (HTML Form/CGI), POP3, FTP, SMB, Telnet and other types such as IMAP, NNTP, NetBus, etc. You can also create your own authentication types. This tool also supports multi-stage authentication engines and is able to

connect 60 simultaneous targets. It also has resume and load options. So, you can pause the attack process any time and then resume whenever you want to resume. This tool has not been updated for many years. Still, it can be useful for you.

2. RainbowCrack: RainbowCrack is a hash cracker tool that uses a large-scale time-memory trade off process for faster password cracking than traditional brute force tools. Time-memory trade off is a computational process in which all plain text and hash pairs are calculated by using a selected hash algorithm. After computation, results are stored in the rainbow table. This process is very time consuming. But, once the table is ready, it can crack a password much faster than brute force tools. You also do not need to generate rainbow tables by yourselves. Developers of RainbowCrack have also generated LM rainbow tables, NTLM rainbow tables, MD5 rainbow tables and Sha1 rainbow tables. Like RainbowCrack, these tables are also available for free. You can download these tables and use for your password cracking processes.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

20 Download Rainbow tables here: <http://project-rainbowcrack.com/table.htm> A few paid rainbow tables are also available, which you can buy from here: <http://project-rainbowcrack.com/buy.php> This tool is available for both Windows and Linux systems. Download Rainbow crack here: <http://project-rainbowcrack.com/>

3. Wfuzz: Wfuzz is another web application password cracking tool that tries to crack passwords with brute forcing. It can also be used to find hidden resources like directories, servlets and scripts. This tool can also identify different kind of injections

including SQL Injection, XSS Injection, LDAP Injection, etc in Web applications.

Key features of Wfuzz password cracking tool:

- Capability of injection via multiple points with multiple dictionary
- Output in colored HTML
- Post, headers, and authentication data brute forcing
- Proxy and SOCK Support, Multiple Proxy Support
- Multi-Threading
- Brute force HTTP Password
- POST and GET Brute forcing
- Time delay between requests
- Cookies fuzzing

4. Cain and Abel : Cain and Abel is a well-known password cracking tool that is capable of handling a variety of tasks. The most notable thing is that the tool is only available for Windows platforms. It can work as sniffer in the network, cracking encrypted passwords using the dictionary attack, recording VoIP conversations, brute force attacks, cryptanalysis attacks, revealing password boxes, uncovering cached passwords, decoding scrambled passwords, and analyzing routing protocols. Cain and Abel does not exploit any vulnerability or bugs. It only covers security weakness of protocols to grab the password. This tool was developed for network administrators, security professionals, forensics staff, and penetration

testers.Download here: http://www.oxid.it/ca_um/ Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 21 5. John the Ripper: John the Ripper is another well-known free open source password cracking tool for Linux, Unix and Mac OS X. A Windows version is also available. This tool can detect weak passwords. A pro version of the tool is also available, which offers better features and native packages for target operating systems. You can also download Openwall GNU/*/Linux that comes with John the Ripper.Download John

the Ripper here: <http://www.openwall.com/john/> 6. THC Hydra: THC Hydra is a fast network login password cracking tool. When it is compared with other similar tools, it shows why it is faster. New modules are easy to install in the tool. You can easily add modules and enhance the features. It is available for Windows, Linux, Free BSD, Solaris and OS X. This tool supports various network protocols. Currently it supports Asterisk, AFP, Cisco AAA, Cisco auth, Cisco enable, CVS, Firebird, FTP, HTTP-FORM-GET, HTTP-FORM-POST, HTTP-GET, HTTP-HEAD, HTTP-PROXY, HTTPS-FORM-GET, HTTPS-FORM-POST, HTTPS-GET, HTTPS-HEAD, HTTP-Proxy, ICQ, IMAP, IRC, LDAP, MS-SQL, MYSQL, NCP, NNTP, Oracle Listener, Oracle SID, Oracle, PC-Anywhere, PCNFS, POP3, POSTGRES, RDP, Rexec, Rlogin, Rsh, SAP/R3, SIP, SMB, SMTP, SMTP Enum, SNMP, SOCKS5, SSH (v1 and v2), Subversion, Teamspeak (TS2), Telnet, VMware-Auth, VNC and XMPP.Download THC Hydra here: <https://www.thc.org/thc-hydra/> If you are a developer, you can also contribute to the tool's development. 7. Medusa: Medusa is also a password cracking tool similar to THC Hydra. It claims to be a speedy parallel, modular and login brute forcing tool. It supports HTTP, FTP, CVS, AFP, IMAP, MS SQL, MYSQL, NCP, NNTP, POP3, PostgreSQL, pcAnywhere, rlogin, SMB, rsh, SMTP, SNMP, SSH, SVN, VNC, VmAuthd and Telnet. While cracking the password, host, username and password can be flexible input while performing the attack. Medusa is a command line tool, so you need to learn commands before using the tool. Efficiency of the tool depends on network connectivity. On a local system, it can test 2000 passwords per minute. With this tool, you can also perform a parallel attack. Suppose you want to crack passwords of a few email accounts simultaneously. You can specify the username list along with the password list. Read more about this Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017,

INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 22 here: <http://foofus.net/goons/jmk/medusa/medusa.html> Download Medusa here: <http://www.foofus.net/jmk/tools/medusa-2.1.1.tar.gz> 8. OphCrack: OphCrack is a free rainbow-table based password cracking tool for Windows. It is the most popular Windows password cracking tool, but can also be used on Linux and Mac systems. It cracks LM and NTLM hashes. For cracking Windows XP, Vista and Windows 7, free rainbow-tables are also available. A live CD of OphCrack is also available to simplify the cracking. One can use the Live CD of OphCrack to crack Windows-based passwords. This tool is available for free. Download OphCrack here: <http://ophcrack.sourceforge.net/> Download free and premium rainbow tables for OphCrack here:

<http://ophcrack.sourceforge.net/tables.php> 9. L0phtCrack: L0phtCrack is an alternative to OphCrack. It attempts to crack Windows password from hashes. For cracking passwords, it uses Windows workstations, network servers, primary domain controllers, and Active Directory. It also uses dictionary and brute force attacking for generating and guessing passwords. It was acquired by Symantec and discontinued in 2006. Later L0pht developers again re-acquired it and launched L0phtCrack in 2009. It also comes with a schedule routine audit feature. One can set daily, weekly or monthly audits, and it will start scanning on the scheduled time. L0phtCrack: <http://www.l0phtcrack.com/> Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 23

10 Aircrack-NG: Aircrack-NG is a WiFi password cracking tool that can crack WEP or WPA passwords. It analyzes wireless encrypted packets and then tries to crack passwords via its cracking algorithm. It uses the FMS attack along with other useful attack techniques for cracking password. It is available for Linux and Windows systems. A live CD of Aircrack is also available. If you want to use AirCrack NG for password cracking, read tutorials here: http://www.aircrack-ng.org/doku.php?id=getting_started Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 24 Download AirCrack-NG here: <http://www.aircrack-ng.org/> 2. Dictionary Attack A Dictionary Attack as an attack vector used by the attacker to break in a system, which is password protected, by putting technically every word in a dictionary as a form of password for that system. This attack vector is a form of Brute Force Attack. The dictionary can contain words from an English dictionary and also some leaked list of commonly used passwords and when combined with common character replacing with numbers, can sometimes be very effective and fast. • Difference between Brute Force and Dictionary Attack: The difference with brute force attack is that, in brute force, many possible key permutations are checked whereas, in the dictionary attack, only the words with most possibilities of success are checked and are less time consuming than brute force. • What to avoid while selecting your password: There are a few things which were very common a few years back and still exist. Most of the password cracking tools start from there. Passwords that fall into this category are most easy to crack. These are the

few password mistakes which you should avoid: o Never use a dictionary word o Avoid using your pet's name, parent name, your phone number, driver's license number or anything which is easy to guess. o Avoid using passwords with sequence or repeated characters: For Ex: 1111111, 12345678 or qwerty, asdfgh. • The longer the password, the harder it is to crack : Password length is the most important factor. If you select a small password, password cracking tools can easily crack it by using few words combinations. A longer password will take a longer time in guessing. You're your password at least 8 characters long. • Always use a combination of characters, numbers, and special characters : This is another thing which makes passwords hard to crack. Password cracking tools try the combination of one by one. Have a combination of small characters, capital letters, and special

characters. Suppose Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

25 If you have only numbers in your password. Password cracking tools only need to guess numbers from 0-9. Here only length matters. But having a password combination of a-z, A-Z, 0-9 and other special characters with a good length will make it harder to crack. This kind of password sometimes takes weeks to crack.

- Variety in passwords: One important thing you must always take care. Never use same password everywhere. Cyber criminals can steal passwords from one website and then try it on other websites too.
- The top 15 passwords on the 2017 list.
 - o 123456, Password, 12345678, qwerty, 12345, 123456789, letmein, 1234567, Football, iloveyou, admin, welcome, monkey, login, abc123
- The top 11 worst passwords of 2012:
 - o

Password, 123456, 12345678, abc123, qwerty, monkey, letmein, dragon, 111111, baseball, iloveyou

Experiment 5: Diffie Hellman key exchange algorithm

The question of key exchange was one of the first problems addressed by a cryptographic protocol. This was prior to the invention of public key cryptography. The Diffie-Hellman key agreement protocol (1976) was the first practical method for establishing a shared secret over an unsecured communication channel. In Public key encryption schemes are secure only if authenticity of the public key is assured. Diffie-Hellman key exchange is a simple public key algorithm. The protocol enables 2 users to establish a secret key using a public key scheme based on discrete algorithms. The protocol is secure only if the authenticity of the 2 participants can be established. In this scheme, there are 2 publicly known numbers:

- o A prime number q
- o An integer a that is a primitive root of q . (Note: Primitive root of a prime number P is one, whose powers module P generate all the images from 1 to $P-1$)

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in

26 Algorithm steps:

1. The first step is for Alice and Bob to agree on a large prime p and a nonzero integer g modulo p . Alice and Bob make the values of p and g public knowledge.
2. The next step is for Alice to pick a secret integer a that she does not reveal to anyone, while at the same time Bob picks an integer b that he keeps secret.
3. Alice uses their secret integers to compute: $A \equiv g^a \pmod{p}$
4. Bob uses their secret integers to compute: $B \equiv g^b \pmod{p}$
5. They next exchange these computed values; Alice sends A to Bob and Bob sends B to Alice.
6. Finally, Bob and Alice

again use their secret integers to compute.

- a. Alice uses their secret integers to compute: $A' \equiv B^a \pmod{p}$
- b. Bob uses their secret integers to compute: $B' \equiv A^b \pmod{p}$

7. The values that they compute are same i.e. $A' = B'$.

Implementation of Diffie-Hellman algorithm

```
import math
# Shared Variables (public key)
Used by Alice and Bob
sharedPrime = int(input("Enter the prime number (p): "))
# p
sharedBase = int(input("Enter the primitive root of prime number p (g): "))
# g
# Begin print("Publicly Shared Variables:")
print(" Publicly Shared Prime: ", sharedPrime)
print(" Publicly Shared Base: ", sharedBase)
```

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax:

+91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 27 # Alice Sends Bob $A = g^a \text{ mod } p$

```

aliceSecret = int(input("Alice's choose self private key (a): ")) # a
A = int(math.pow(sharedBase,aliceSecret) % sharedPrime) print( "\n Alice Sends Over Public Chanel: ",
A ) # Bob Sends Alice  $B = g^b \text{ mod } p$  bobSecret = int(input("Bob's choose self private key (b): ")) # b
B = int(math.pow(sharedBase,bobSecret) % sharedPrime) print( "Bob Sends Over Public Chanel: ",
B ) print( "*****" ) print( "Privately Calculated Shared Secret:")
# Alice Computes Shared Secret:  $s = B^a \text{ mod } p$  aliceSharedSecret = int(math.pow(B,aliceSecret) %
sharedPrime) print( " Alice Shared Secret: ", aliceSharedSecret ) # Bob Computes Shared Secret:  $s = A^b \text{ mod } p$ 
bobSharedSecret = int(math.pow(A,bobSecret) % sharedPrime) print( " Bob Shared Secret: ", bobSharedSecret )
if aliceSharedSecret is bobSharedSecret: print("Alice and Bob having same key:") else:

```

Swami Keshvanand Institute of Technology, Management & Gramothan,

Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 28 print("Generated keys are different ... Please check your code again:")

Experiment 6: Implementation of Playfair cipher The Playfair cipher starts with creating a key table. The key table is a 5×5 grid of letters that will act as the key for encrypting your plaintext. Each of the 25 letters must be unique and one letter of the alphabet is omitted from the table (as there are 25 spots and 26 letters in the alphabet). To encrypt a message, one would break the message into diagrams (groups of 2 letters) such that, for example, "HelloWorld" becomes "HE LL OW OR LD" and map them out on the key table. The two letters of the diagram are considered as the opposite corners of a rectangle in the key table. Note the relative position of the corners of this rectangle. Then apply the following 4 rules, in order, to each pair of letters in the plaintext:

1. If both letters are the same (or only one letter is left), add an "X" after the first letter
2. If the letters appear on the same row of your table, replace them with the letters to their immediate right respectively
3. If the letters appear on the same column of your table, replace them with the letters immediately below respectively
4. If the letters are not on the same row or column, replace them with the letters on the same row respectively but at the other pair of corners of the

rectangle defined by the original pair. ALGORITHM: STEP-1: Read the plain text from the user. STEP-2: Read the keyword from the user. STEP-3: Arrange the keyword without duplicates in a 5*5 matrix in the row order and fill the remaining cells with missed out letters in alphabetical order. Note that 'i' and 'j' takes the same cell. STEP-4: Group the plain text in pairs and match the corresponding corner letters by forming a rectangular grid. STEP-5: Display the obtained cipher text. PROGRAM :

```

(Playfair Cipher) #include<stdio.h> #include<conio.h> #include<string.h> #include<ctype.h> #define
MX 5 void playfair(char ch1,char ch2, char key[MX][MX]) { int i,j,w,x,y,z; FILE *out;

```

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555

E-mail: info@skit.ac.in Web: www.skit.ac.in 30 if((out=fopen("cipher.txt","a+"))==NULL) { printf("File Corrupted."); } for(i=0;i<MX;i++) { } } for(j=0;j<MX;j++) { if(ch1==key[i][j]) { w=i; x=j; } else if(ch2==key[i][j]) { y=i; z=j; //printf("%d%d %d%d",w,x,y,z); if(w==y) { x=(x+1)%5;z=(z+1)%5; printf("%c%c",key[w][x],key[y][z]); fprintf(out, "%c%c",key[w][x],key[y][z]); } else if(x==z) { } else { } w=(w+1)%5;y=(y+1)%5; printf("%c%c",key[w][x],key[y][z]); fprintf(out, "%c%c",key[w][x],key[y][z]); printf("%c%c",key[w][z],key[y][x]); fprintf(out, "%c%c",key[w][z],key[y][x]); fclose(out); } void main() { int i,j,k=0,l,m=0,n; char key[MX][MX],keyminus[25],keyst[10],str[25]={0}; char alpa[26]='A','B','C','D','E','F','G','H','I','J','K','L','M','N','O','P','Q','R','S','T','U','V','W','X','Y','Z'; clrscr(); Swami Keshvanand Institute of Technology, Management & Gramothan,

Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 31 printf("\nEnter key:"); gets(keyst); printf("\nEnter the plain text:"); gets(str); n=strlen(keyst); //convert the characters to upertext for (i=0; i<n; i++) { if(keyst[i]=='j')keyst[i]='i'; else if(keyst[i]=='J')keyst[i]='I'; keyst[i] = toupper(keyst[i]); } //convert all the characters of plaintext to upertext for (i=0; i<strlen(str); i++) { if(str[i]=='j')str[i]='i'; else if(str[i]=='J')str[i]='I'; str[i] = toupper(str[i]); } j=0; for(i=0;i<26;i++) { for(k=0;k<n;k++) { if(keyst[k]==alpa[i]) break; else if(alpa[i]=='J') break; } if(k==n) { keyminus[j]=alpa[i];j++; } } //construct key keymatrix k=0; for(i=0;i<MX;i++) { for(j=0;j<MX;j++) { if(k<n) { key[i][j]=keyst[k]; k++; } else { Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 32 key[i][j]=keyminus[m];m++; } printf("%c ",key[i][j]); } printf("\n"); } printf("\n\nEntered text :%s\nCipher Text :",str); for(i=0;i<strlen(str);i++) { if(str[i]=='J')str[i]='I'; if(str[i+1]=='\0') playfair(str[i],'X',key); else { } getch(); } OUTPUT: if(str[i+1]=='J')str[i+1]='I'; if(str[i]==str[i+1]) playfair(str[i],'X',key); else { playfair(str[i],str[i+1],key);i++; } Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC

Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 33 Experiment 7:Implementation of hill cipher Each letter is represented by a number modulo 26. Often the simple scheme A = 0, B= 1... Z = 25, is used, but this is not an essential feature of the cipher. To encrypt a message, each block of n letters is multiplied by an invertible $n \times n$ matrix, against modulus 26. To decrypt the message, each block is multiplied by the inverse of the matrix used for encryption. The matrix used for encryption is the cipher key, and it should be chosen randomly from the set of invertible $n \times n$ matrices (modulo 26). ALGORITHM: STEP-1: Read the plain text and key from the user. STEP-2: Split the plain text into groups of length three. STEP-3: Arrange the keyword in a 3×3 matrix. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 34 STEP-4: Multiply the two matrices to obtain the cipher text of length three. STEP-5: Combine all these groups to get the

```
complete cipher text. PROGRAM : (Hill Cipher) #include<stdio.h> #include<conio.h>
#include<string.h> int main(){ unsigned int a[3][3]={6,24,1},{13,16,10},{20,17,15}}; unsigned int
b[3][3]={8,5,10},{21,8,21},{21,12,8}}; int i,j, t=0; unsigned int c[20],d[20]; char msg[20]; clrscr();
printf("Enter plain text\n "); scanf("%s",msg); for(i=0;i<strlen(msg);i++) { c[i]=msg[i]-65; printf("%d
",c[i]); } for(i=0;i<3;i++) { t=0; for(j=0;j<3;j++) { t=t+(a[i][j]*c[j]); } d[i]=t%26; } printf("\nEncrypted Cipher
Text :"); for(i=0;i<3;i++) printf(" %c",d[i]+65); for(i=0;i<3;i++) { t=0;
```

```
for(j=0;j<3;j++) { t=t+(b[i][j]*d[j]); } c[i]=t%26; } printf("\nDecrypted Cipher Text :"); for(i=0;i<3;i++)
printf(" %c",c[i]+65); getch(); return 0; Swami Keshvanand Institute of Technology, Management
&Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD,
Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-
5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 35 } Experiment 8:
Implementation of RSA RSA is an algorithm used by modern computers to encrypt and decrypt
messages. It is an asymmetric cryptographic algorithm. Asymmetric means that there are two
different keys. This is also called public key cryptography, because one of them can be given to
everyone . A basic principle behind RSA is the observation that it is practical to find three very large
positive integers e, d and n such that with modular exponentiation for all integer m: (me)d = m (mod
n) The public key is represented by the integers n and e; and, the private key, by the integer d. m
represents the message. RSA involves a public key and a private key . The public key can be known
by everyone and is used for encrypting messages. The intention is that messages encrypted with the
public key can only be decrypted in a reasonable amount of time using the private key. Swami
Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura,
Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by
UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555
E-mail: info@skit.ac.in Web: www.skit.ac.in 36 ALGORITHM: STEP-1: Select two co-prime numbers
as p and q. STEP-2: Compute n as the product of p and q. STEP-3: Compute (p-1)*(q-1) and store it
in z. STEP-4: Select a random prime number e that is less
```

```
than that of z. STEP-5: Compute the private key, d as e * mod-1(z). STEP-6: The cipher text is
computed as messagee* mod n. STEP-7: Decryption is done as cipherdmod n. PROGRAM: (RSA)
#include<stdio.h> #include<conio.h> #include<stdlib.h> #include<math.h> #include<string.h> long int
p,q,n,t,flag,e[100],d[100],temp[100],j,m[100],en[100],i; char msg[100]; int prime(long int); void ce();
long int cd(long int); void encrypt(); void decrypt(); void main() { clrscr(); printf("\nENTER FIRST
PRIME NUMBER\n"); scanf("%d",&p); flag=prime(p); if(flag==0) Swami Keshvanand Institute of
Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by
AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC
Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:
www.skit.ac.in 37 { printf("\nWRONG INPUT\n"); getch(); } printf("\nENTER ANOTHER PRIME
NUMBER\n"); scanf("%d",&q); flag=prime(q); if(flag==0||p==q) { printf("\nWRONG INPUT\n"); getch();
} printf("\nENTER MESSAGE\n"); fflush(stdin); scanf("%s",msg); for(i=0;msg[i]!=NULL;i++)
m[i]=msg[i]; n=p*q; t=(p-1)*(q-1); ce(); printf("\nPOSSIBLE VALUES OF e AND d ARE\n");
for(i=0;i<j-1;i++) printf("\n%ld\t%ld",e[i],d[i]); encrypt(); decrypt(); getch(); } int prime(long int pr) { int i;
j=sqrt(pr); for(i=2;i<=j;i++) { if(pr%i==0) return 0; } return 1; } void ce() { int k; k=0; for(i=2;i<t;i++) {
```

if(t%i==0) continue; flag=prime(i); Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 38

```
if(flag==1&&i!=p&&i!=q) { e[k]=i;
```

```
flag=cd(e[k]); if(flag>0) { d[k]=flag; k++; } if(k==99) break; } } long int cd(long int x) { long int k=1;
while(1) { k=k+t; if(k%x==0) return(k/x); } } void encrypt() { long int pt,ct,key=e[0],k,len; i=0;
len=strlen(msg); while(i!=len) { pt=m[i]; pt=pt-96; k=1; for(j=0;j<key;j++) { k=k*pt; k=k%n; } temp[i]=k;
ct=k+96; en[i]=ct; i++; } en[i]=-1; printf("\nTHE ENCRYPTED MESSAGE IS\n"); for(i=0;en[i]!=-1;i++)
printf("%c",en[i]); } void decrypt() { long int pt,ct,key=d[0],k; i=0; while(en[i]!=-1) { ct=temp[i];
Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura,
Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by
UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555
E-mail: info@skit.ac.in Web: www.skit.ac.in 39 k=1; for(j=0;j<key;j++) { k=k*ct; k=k%n; } pt=k+96;
m[i]=pt; i++; } m[i]=-1; printf("\nTHE DECRYPTED MESSAGE IS\n"); for(i=0;m[i]!=-1;i++)
printf("%c",m[i]); } Experiment 9: IMPLEMENTATION OF MD5 MD5 processes a variable-length
message into a fixed-length output of 128 bits. The input message is broken up into chunks of
512-bit blocks. The message is padded so that its length is divisible by 512. The padding works as
follows: first a single bit, 1, is appended to the end of the message. This is followed by as many zeros
as are required to bring the length of the message up to 64 bits less than a multiple of 512. The
remaining bits are filled up with 64 bits representing the length of the original message, modulo
264. The main MD5 algorithm operates on a 128-bit state, divided into four 32-bit words, denoted A,
B, C, and D. These are initialized to certain fixed constants. The main algorithm then uses each
512-bit message block in turn to modify the state Swami Keshvanand Institute of Technology,
Management & Gramothan, Ramnagar,
```

Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 40

ALGORITHM: STEP-1: Read the 128-bit plain text. STEP-2: Divide into four blocks of 32-bits named as A, B, C and D. STEP-3: Compute the functions f, g, h and i with operations such as, rotations, permutations, etc., STEP-4: The output of these functions are combined together as F and performed circular shifting and then given to key round. STEP-5: Finally, right shift of 's' times are performed and the results are combined together to produce the final output.

PROGRAM: (MD5) #include <stdlib.h> #include <stdio.h> #include <string.h> #include <math.h> #include <conio.h> typedef union uwb { unsigned w; unsigned char b[4]; } MD5union; typedef unsigned DigestArray[4]; unsigned func0(unsigned abcd[]){ return (abcd[1] & abcd[2]) | (~abcd[1] & abcd[3]);} unsigned func1(unsigned abcd[]){ return (abcd[3] & abcd[1]) | (~abcd[3] & abcd[2]);} unsigned func2(unsigned abcd[]){ Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 41

```
return abcd[1] ^ abcd[2] ^ abcd[3];} unsigned func3( unsigned abcd[] ){ return abcd[2] ^ (abcd[1] | ~
```

```
abcd[3]);} typedef unsigned (*DgstFctn)(unsigned a[]); unsigned *calctable( unsigned *k) { double s,
pwr; int i; pwr = pow( 2, 32); for (i=0; i<64; i++) { s = fabs(sin(1+i)); k[i] = (unsigned)( s * pwr ); } return
k; } unsigned rol( unsigned r, short N ) { unsigned mask1 = (1<<N) -1; return
```

```
((r>>(32-N)) & mask1) | ((r<<N) & ~mask1); } unsigned *md5( const char *msg, int mlen) { static
DigestArray h0 = { 0x67452301, 0xEFCDAB89, 0x98BADCFE, 0x10325476 }; static DgstFctnff[] = {
&func0, &func1, &func2, &func3}; static short M[] = { 1, 5,3,7}; static short O[] = { 0, 1,5,0}; static short
rot0[] = { 7,12,17,22}; static short rot1[] = { 5, 9,14,20}; static short rot2[] = { 4,11,16,23}; static short
rot3[] = { 6,10,15,21}; static short *rots[] = {rot0, rot1, rot2, rot3 }; static unsigned kspace[64]; static
unsigned *k; static DigestArrayh; DigestArrayabcd; DgstFctnfctn; short m, o, g; unsigned f; short
*rotn; union Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar,
Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India
Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax:
+91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 42 { }mm; unsigned w[16]; char b[64];
int os = 0; int grp, grps, q, p; unsigned char *msg2; if (k==NULL) k= calctable(kspace); for (q=0; q<4;
q++) h[q] = h0[q]; // initialize { grps = 1 + (mlen+8)/64; msg2 = malloc( 64*grps); memcpy( msg2, msg,
mlen); msg2[mlen] = (unsigned char)0x80; q = mlen + 1; while (q < 64*grps){ msg2[q] = 0; q++ ; } {
MD5union u; u.w = 8*mlen; q -= 8; memcpy(msg2+q, &u.w, 4 ); } } for (grp=0; grp<grps; grp++) {
memcpy( mm.b, msg2+os, 64); for(q=0;q<4;q++) abcd[q] = h[q]; for (p = 0; p<4; p++) { fctn = ff[p];
rotn = rots[p]; m = M[p]; o= O[p]; for (q=0; q<16; q++) { g = (m*q + o) % 16; f = abcd[1] + rol( abcd[0]+
fctn(abcd)+k[q+16*p] + mm.w[g], rotn[q%4]); abcd[0] = abcd[3]; abcd[3] = abcd[2]; abcd[2] = abcd[1];
abcd[1] = f; }} for (p=0; p<4; p++) Swami Keshvanand Institute of Technology, Management
&Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by
```

```
AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC
Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:
www.skit.ac.in 43 h[p] += abcd[p]; os += 64; } return h;} void main() { int j,k; const char *msg = "The
quick brown fox jumps over the lazy dog"; unsigned *d = md5(msg, strlen(msg)); MD5union u;
clrscr(); printf("\t MD5 ENCRYPTION ALGORITHM IN C \n\n"); printf("Input String to be Encrypted
using MD5 : \n\t%s",msg); printf("\n\nThe MD5 code for input string is: \n"); printf("\t= 0x"); for (j=0;j<4;
j++){ u.w = d[j]; for (k=0;k<4;k++) printf("%02x",u.b[k]); } printf("\n"); printf("\n\t MD5 Encyption
Successfully Completed!!!\n\n"); getch(); system("pause"); getch();} Swami Keshvanand Institute of
Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by
AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC
Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:
www.skit.ac.in 44 Experiment 10: IMPLEMENTATION OF SHA-I In cryptography, SHA-1 (Secure
Hash Algorithm 1) is a cryptographic hash function. SHA-1 produces a 160-bit hash value known as a
message digest. The way this algorithm works is that for a message of size < 264 bits it computes a
160-bit condensed output called a message digest. The SHA-1 algorithm is designed so that it is
practically infeasible to find two input messages that hash to the same output message. A hash
functionsuch as SHA-1 is used to calculate an alphanumeric string that serves as the cryptographic
representation of a file or a piece of data. This is called a digest and can serve as a digital signature.
It is supposed to be unique and non-reversible. Swami Keshvanand Institute of Technology,
```

Management & Gramothan, Ramnagar, Jagatpura,

Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 45 ALGORITHM: STEP-1: Read the 256-bit key values. STEP-2: Divide into five equal-sized blocks named A, B, C, D and E. STEP-3: The blocks B, C and D are passed to the function F. STEP-4: The resultant value is permuted with block E. STEP-5: The block A is shifted right by 's' times and permuted with the result of step-4 STEP-6: Then it is permuted with a weight value and then with some other key pair and taken as the first block. STEP-7: Block A is taken as the second block and the block B is shifted by 's' times and taken as the third block. STEP-8: The blocks C and D are taken as the block D and E for the final output. PROGRAM: (Secure Hash Algorithm) import java.security.*; public class SHA1 { public static void main(String[] a) { try { MessageDigest md = MessageDigest.getInstance("SHA1"); System.out.println("Message digest object info: "); System.out.println(" Algorithm = " + md.getAlgorithm()); System.out.println(" Provider = " + md.getProvider()); System.out.println(" ToString = " + md.toString()); String input = ""; Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 46 md.update(input.getBytes()); byte[] output = md.digest(); System.out.println(); System.out.println("SHA1(\""+input+"") = "+bytesToHex(output)); input = "abc"; md.update(input.getBytes()); output = md.digest(); System.out.println(); System.out.println("SHA1(\""+input+"") = "+bytesToHex(output)); input =

"abcdefghijklmnpqrstuvwxy"; md.update(input.getBytes()); output = md.digest(); System.out.println(); System.out.println("SHA1(\""+input+"") = "+bytesToHex(output)); System.out.println(""); } catch (Exception e) { System.out.println("Exception: " + e); } } public static String bytesToHex(byte[] b) { Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 47 char hexDigit[] = {'0', '1', '2', '3', '4', '5', '6', '7', '8', '9', 'A', 'B', 'C', 'D', 'E', 'F'}; StringBuffer buf = new StringBuffer(); for (int j=0; j<b.length; j++) { buf.append(hexDigit[(b[j] >> 4) & 0x0f]); buf.append(hexDigit[b[j] & 0x0f]); } return buf.toString(); } } Experiment 11: Implementation of digital signature standard ALGORITHM: STEP-1: Alice and Bob are investigating a forgery case of x and y. STEP-2: X had document signed by him, but he says he did not sign that document digitally. STEP-3: Alice reads the two prime numbers p and a. STEP-4: He chooses a random co-primes alpha and beta and the x's original signature ex. STEP-5: With these values, he applies it to the elliptic curve cryptographic equation to obtain y. STEP-6: Comparing this 'y' with actual y's document, Alice concludes that y is a forgery. PROGRAM : (Digital Signature Standard) import java.util.*; import java.math.BigInteger; class dsaAlg { final static BigInteger one = new BigInteger("1"); final static BigInteger zero = new BigInteger("0"); Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956

Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 48

```

public static BigInteger getNextPrime(String ans) { BigInteger test = new BigInteger(ans); while (!test.isProbablePrime(99)) { test = test.add(one); } return test; }
public static BigInteger findQ(BigInteger n) { BigInteger start = new BigInteger("2"); while (!n.isProbablePrime(99)) { while (!((n.mod(start)).equals(zero))) { start = start.add(one); } n = n.divide(start); } return n; }
public static BigInteger getGen(BigInteger p, BigInteger q, Random r) { BigInteger h = new BigInteger(p.bitLength(), r); h = h.mod(p); return h.modPow((p.subtract(one)).divide(q), p); }
public static void main (String[] args) throws java.lang.Exception { Random randObj = new Random(); BigInteger p = getNextPrime("10600"); /* approximate prime */ BigInteger q = findQ(p.subtract(one)); BigInteger g = getGen(p,q,randObj); System.out.println("\n simulation of Digital Signature Algorithm\n"); System.out.println("\n global public key components are:\n"); System.out.println("\np is: " + p); System.out.println("\nq is: " + q); System.out.println("\ng is: " + g); BigInteger x = new BigInteger(q.bitLength(), randObj); x = x.mod(q); BigInteger y = g.modPow(x,p); BigInteger k = new BigInteger(q.bitLength(), randObj); k = k.mod(q); BigInteger r = (g.modPow(k,p)).mod(q); BigInteger hashVal = new BigInteger(p.bitLength(), randObj); BigInteger kInv = k.modInverse(q); BigInteger s = kInv.multiply(hashVal.add(x.multiply(r))); s = s.mod(q); System.out.println("\n secret information are:\n"); System.out.println("x (private) is: " + x); System.out.println("k (secret) is: " + k); System.out.println("y (public) is: " + y);

```

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-

5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 49

```

System.out.println("\nh (rndhash) is: " + hashVal); System.out.println("\n generating digital signature:\n"); System.out.println("r is : " + r); System.out.println("s is : " + s); BigInteger w = s.modInverse(q); BigInteger u1 = (hashVal.multiply(w)).mod(q); BigInteger u2 = (r.multiply(w)).mod(q); BigInteger v = (g.modPow(u1,p)).multiply(y.modPow(u2,p)); v = (v.mod(p)).mod(q); System.out.println("\n verifying digital signature (checkpoints)\n:"); System.out.println("w is : " + w); System.out.println("u1 is : " + u1); System.out.println("u2 is : " + u2); System.out.println("v is : " + v); if (v.equals(r)) { System.out.println("\n success: digital signature is verified!\n " + r); } else { System.out.println("\n error: incorrect digital signature\n "); } }

```

Experiment 12: Wireshark Tutorial The purpose of this document is to introduce the packet sniffer Wireshark. Wireshark would be used for the lab experiments. This document introduces the basic operation of a packet sniffer, installation, and a test run of Wireshark. Wireshark, a network analysis tool formerly known as Ethereal, captures packets in real time and display them in human-readable format. Wireshark includes filters, color-coding, and other features that let you dig deep into network traffic and inspect individual packets. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 50

Figure 1: Packet sniffer structure Figure 1b: Protocol Data Encapsulation PACKET SNIFFER The basic tool for observing the messages exchanged as packets on the network using a variety of protocols is called a packet sniffer .

As the name suggests, a packet sniffer captures (“sniffs”) messages being sent/received from/by your computer; it will also typically store and/or display the contents of the various protocol fields in these captured messages. A packet sniffer itself is passive. It observes messages being sent and received by applications and protocols running on your computer, but never sends packets itself. Similarly, received packets are never explicitly sent to the packet sniffer. Instead, a packet sniffer receives a copy of packets that are sent / received from/by application and protocols executing on your machine. Figure 1 shows the structure of a packet sniffer. At the right of Figure 1 are the protocols (in this case, Internet protocols) and applications (such as a web browser or ftp client) that normally run on your computer. The overall packet structure. The packet sniffer, shown within the dashed rectangle in Figure 1 is an addition to the usual software in your computer and consists of two parts. The packet capture library receives a copy of every link-layer frame that is sent from or received by your computer. Messages exchanged by higher layer protocols such as HTTP, FTP, TCP, UDP, DNS, or IP all are eventually encapsulated in link-layer frames that are transmitted over physical media such as an Ethernet cable. In Figure 1, the assumed physical media is an Ethernet, and so all upper-layer protocols are eventually encapsulated within an Ethernet frame. Capturing all link-layer frames thus gives you access to all messages sent/received from/by all protocols and applications executing in your computer. The second component of a

packet sniffer is the packet analyzer, which displays the contents of all fields within a protocol message. In order to do so, the packet analyzer must “understand” the structure of all messages exchanged by protocols. For example, suppose we are interested in displaying the various fields in messages exchanged by the HTTP protocol in Figure 1. The packet analyzer understands the format of Ethernet frames, and so can identify the IP datagram within an Ethernet frame. It also understands the IP datagram format, so that it can extract the TCP segment within the IP datagram. Finally, it understands the TCP segment structure, so it can extract the HTTP message contained in the TCP segment. Finally, it understands the HTTP protocol and so, for example, knows that the first bytes of an HTTP message will contain the string “GET,” “POST,” or “HEAD”. We will be using the Wireshark packet sniffer [<http://www.wireshark.org/>] for these labs, allowing us to display the contents of messages being sent/received from/by protocols at different levels of the protocol stack. (Technically speaking, Wireshark is a packet analyzer that uses a packet capture library in your computer). Wireshark is a free network protocol analyzer that runs on Windows, Linux/Unix, and Mac computers. It’s an ideal packet analyzer for our labs – it is stable, has a large user base and well-documented support that includes a user-guide: Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 52 http://www.wireshark.org/docs/wsug_html_chunked/), a set of well-crafted man pages at (<http://www.wireshark.org/docs/man-pages/>), and a list of very detailed FAQ (<http://www.wireshark.org/faq.html>), rich functionality that

includes the capability to analyze hundreds of protocols, and a well-designed user interface. It operates in computers using Ethernet, Token-Ring, FDDI, serial (PPP and SLIP), 802.11 wireless LANs, and ATM connections (if the OS on which it's running allows Wireshark to do so). Getting Wireshark Wireshark can be installed in any operating system, just go to <https://www.wireshark.org/download.html> Figure 2: Wireshark Download Page. You can download the version of Wireshark that matches your operating system. Running Wireshark When you run the Wireshark program, the Wireshark graphical user interface shown in Figure 2 will be displayed. Initially, no data will be displayed in the various windows. For Mac OSX users, you need to have XQuartz or X11 installed for Wireshark to work!!! Also, the first time you open Wireshark, it will take several seconds to start so be patient. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 53 Figure 3: Initial screen for Wireshark. You will need to select one of the Wireshark interfaces, if you are using your laptop connected over the WiFi, then you need to select the WiFi interface. If you are at a server, you need to select the Ethernet interface being used. In general, you can select any interface but that does not mean that traffic will flow through that interface. The network interfaces (i.e., the physical connections) that your computer has to the network are shown. The attached snapshot was taken from my computer. You may not see the exact same entries when you perform a capture in the 237 Lab. You will notice that eth0 and eth1 will be displayed. Click "Start"

for interface eth0. Packet capture will now begin - all packets being sent / received from/by your computer are now being captured by Wireshark! After you select the interface, you should click on "START". If everything goes well, you should get a view similar to Figure 2. WIRESHARK USER INTERFACE Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 54 Figure 4a: Wireshark Graphical User Interface for Windows OS. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 55 Figure 4b: Wireshark Graphical User Interface for Mac OSX. The Wireshark interface has five major components: • The command menus are standard pulldown menus located at the top window. Of interest to us now are the File and Capture menus. The File menu allows you to save captured packet data or open a file containing previously captured packet data and exit the Wireshark application. The Capture menu allows you to begin packet capture. • The packet-listing window displays a one-line summary for each packet captured, including the packet number (assigned by Wireshark; this is not a packet number contained in any protocol's header), the time at which the packet was captured, the packet's source and destination addresses, the protocol type, and protocol-specific information contained in the packet. The packet listing

can be sorted according to any of these categories by clicking on a column name. The protocol type field lists the highest-level protocol that sent or received this packet, i.e., the protocol that is the source or ultimate sink for this packet. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 56 • The packet-header details window provides details about the packet selected (highlighted) in the packet-listing window. (To select a packet in the packet-listing window, place the cursor over the packet's one-line summary in the packet-listing window and click with the left mouse button.). These details include information about the Ethernet frame and IP datagram that contains this packet. The amount of Ethernet and IP-layer detail displayed can be expanded or minimized by clicking on the right-pointing or down-pointing arrowhead to the left of the Ethernet frame or IP datagram line in the packet details window. If the packet has been carried over TCP or UDP, TCP or UDP details will also be displayed, which can similarly be expanded or minimized. Finally, details about the highest-level protocol that sent or received this packet are also provided. • The packet-contents window displays the entire contents of the captured frame, in both ASCII and hexadecimal format. • Towards the top of the Wireshark graphical user interface, is the packet display filter field, into which a protocol name or other information can be entered in order to filter the information displayed in the packet-listing window (and hence the packet-header and packet-contents windows). In the example below, we'll use the packet-display filter field to have Wireshark hide (not display) packets except those that

correspond to HTTP messages. Capturing Packets After downloading and installing Wireshark, you can launch it and click the name of an interface under Interface List to start capturing packets on that interface. For example, if you want to capture traffic on the wireless network, click your wireless interface. You can configure advanced features by clicking Capture Options, but this isn't necessary for now. Test Run The best way to learn about any new piece of software is to try it out! Do the following 1. Start up your favorite web browser. 2. Start up the Wireshark software. You will initially see a window similar to that shown in Figure 3. You need to select an interface and press Start. 2. After your browser has displayed the <http://www.gmu.edu> page, stop Wireshark packet capture by selecting stop in the Wireshark capture window. This will cause the Wireshark capture window to disappear and the main Wireshark window to display all packets Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 57 captured since you began packet capture see image below: 4. Color Coding: You'll probably see packets highlighted in green, blue, and black. Wireshark uses colors to help you identify the types of traffic at a glance. By default, green is TCP traffic, dark blue is DNS traffic, light blue is UDP traffic, and black identifies TCP packets with problems — for example, they could have been delivered out-of-order. Inspecting Packets To inspect packets, click on one of the packets and go to the bottom pane: Notice that although there is a lot of interesting information, the view of the packet is not very easy to read. Swami Keshvanand Institute of Technology, Management

&Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 58 Inspecting Packet Flows (Network Connections) 5. You now have live packet data that contains all protocol messages exchanged between your computer and other network entities! However, as you will notice the HTTP messages are not clearly shown because there are many other packets included in the packet capture. Even though the only action you took was to open your browser, there are many other programs in your computer that communicate via the network in the background. To filter the connections to the ones we want to focus on, we have to use the filtering functionality of Wireshark by typing "http" in the filtering field as shown below: Notice that we now view only the packets that are of protocol HTTP. However, we also still do not have the exact communication we want to focus on because using HTTP as a filter is not descriptive enough to allow us to find our connection to http://www.gmu.edu . We need to be more precise if we want to capture the correct set of packets. 6. One potential filter that comes to mind is to type the destination host (www.gmu.edu) directly in the filter area. Unfortunately, this will end up bringing up an error (see screenshot below) and will not work because Wireshark does not have the ability to discern which protocol fields you need to match. Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 59 7. To further filter

packets in Wireshark, we need to use a more precise filter. By setting the http.host==www.gmu.edu, we are restricting the view to packets that have as an http host the www.gmu.edu website. Notice that we need two equal signs to perform the match "==" not just one! Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 60 8. Let's try another protocol, for instance DNS, type DNS to the filter area: Do you notice that the packets are colored differently? Let's try now to find out what are those packets contain by following one of the conversations (also called network flows), select one of the packets and press the right mouse button (if you are on a Mac use the command button and click), you should see something similar to the screen below: Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 61 From the drop-down list select the "Follow UDP Stream" selection. You should be able to get something similar to the screen below: Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 62 If we close this window and change the filter back to "http.host

==www.gmu.edu” and then follow a packet from the list of packets that match that filter, we should get the something similar to the screens in the next page: Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 63 Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 64 If you close the window, notice that the filter based on the flow is still there: Besides streams we can also use the keyword “contains” to allow some freedom for searching. Let’s see how: Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 65 Also, we can use “contains” with other protocols! Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 66 Experiment 13: Installation of rootkits and study about the variety of options. Introduction: • Rootkit is a stealth type of malicious software designed to hide the existence of certain process

from normal methods of detection and enables continued privileged access to a computer. • Breaking the term rootkit into the two component words, root and kit, is a useful way to define it. Root is a UNIX/Linux term that’s the equivalent of Administrator in Windows. The word kit denotes programs that allow someone to obtain root/admin-level access to the computer by executing the programs in the kit – all of which is done without end-user consent or knowledge. • A rootkit is a type of malicious software that is activated each time your system boots up. • Rootkits are difficult to detect because they are activated before your system’s OS has completely booted up. • A rootkit often allows the installation of hidden files, processes, hidden user accounts etc. in the systems OS. • Rootkits can intercept data from terminals, network connections, and the keyboard. • Rootkits have two primary functions: remote command/control (back door) and software eavesdropping. • Rootkits allow someone executing files, accessing logs, monitoring user activity, and even changing the computer’s configuration. • The presence of a rootkit on a network was first documented in the early 1990s. At that time, Sun and Linux operating systems were the primary targets for a hacker looking to install a rootkit. • Today, rootkits are available for several operating systems, including Windows, and are ever more difficult to detect on any network. Procedure to install Rootkit Tool STEP-1: Download Rootkit Tool from GMER website www.gmer.net. STEP-2: This displays the Processes, Modules, Services, Files, Registry, RootKit / Malwares, Autostart, CMD of local host. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:

www.skit.ac.in 67 STEP-3: Select Processes menu and kill any unwanted process if any. STEP-4: Modules menu displays the various system files like .sys, .dll STEP-5: Services menu displays the complete services running with Autostart, Enable, Disable, System, Boot. STEP-6: Files menu displays full files on Hard-Disk volumes. STEP-7: Registry displays Hkey_Current_user and Hkey_Local_Machine. STEP-8: Rootkits / Malwares scans the local drives selected. STEP-9: Autostart displays the registry base Autostart applications. STEP-10: CMD allows the user to interact with command line utilities or Registry

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 68 Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 69 Experiment 14: An Intrusion detection system (SNORT) An intrusion detection system is a device, or software application that monitors a network or systems for malicious activity or policy violations. SNORT is a widely IDS/IPS. Snort runs in 3 different modes: IDS mode, Logging mode and Sniffer mode Snort Installation: visit the website www.snort.org. Follow the below steps: 1. Sudo apt install snort 2. Snort -V 3. we need to configure our HOME_NET value. 4. ifconfig 5. sudo gedit /etc/snort/snort.conf 6. Still snort have no rules 7. Verify by using the following commands 8. sudo snort -T -i wifi0 -c /etc/snort/snort.conf 9. snort -T -i wifi0 -c C:\Snort\etc\snort.conf 10. Here we are

telling Snort to test (-T) the configuration file (-c points to its location) on the wifi0 interface (enter your interface value if it's different). Rule Header • alert – Rule action. Snort will generate an alert when the set condition is met. • any – Source IP. Snort will look at all sources. • any – Source port. Snort will look at all ports. • -> – Direction. From source to destination. • \$HOME_NET – Destination IP. We are using the HOME_NET value from the snort.conf file. • any – Destination port. Snort will look at all ports on the protected network.

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 70 Rule Options • msg:"ICMP test" – Snort will include this message with the alert. • sid:1000001 – Snort rule ID. Remember all numbers < 1,000,000 are reserved, this is why we are starting with 1000001 • rev:1 – Revision number. This option allows for easier rule maintenance. • classtype:icmp-event – Categorizes the rule as an "icmp-event", one of the predefined Snort categories. This option helps with rule organization. • Again execute the test following command: IDS Mode • Display alerts on the console. • sudo snort -A console -q -c /etc/snort/snort.conf -i eht0 • snort -i 3 -c C:\Snort\etc\snort.conf -A console • -c to point the configuration file. • Specifying the interface (-i). • The -A console option prints alerts to standard output. • -q for the quit • Ping using the other command prompt. • You should see alerts generated for every ICMP Echo request and Echo reply message, with the message text we specified in the msg option

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar,

Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 71 Experiment 15: ARP Poisoning Address Resolution Protocol (ARP) is used to convert IP address to physical address. The host sends an ARP broadcast on the network, and the recipient computer responds with its MAC address. The resolved IP/MAC address is then used to communicate. ARP poisoning is sending fake MAC addresses to the switch so that it can associate the fake MAC addresses with the IP address of a computer on a network and hijack the traffic. ARP Poisoning: • ARP is used to convert IP address to physical address. • The host sends an ARP broadcast on the network, and the recipient computer responds with its MAC address. • The resolved IP/MAC address is then used to communicate. • ARP poisoning is sending fake MAC addresses to the switch so that it can associate the fake MAC addresses with the IP address of a computer on a network and hijack the traffic. • Open the command prompt and enter the following command • Arp -a • -a is the parameter to display the contents of the ARP cache. • dynamic entries are added and deleted automatically when using TCP/IP sessions with remote computers. • Static entries are added manually and are deleted when the computer is restarted, and the network interface card restarted or other activities that affect it. • ipconfig /all command to get the IP and MAC address • arp -s 192.168.0.56 74-86- ---- • arp -a • arp -d 192.168.0.56 // To delete the entry • Download ettercap for windows Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail:

info@skit.ac.in Web: www.skit.ac.in 72 Experiment 16: secure data storage, secure data transmission and for creating digital signatures (GNUPG) INSTALLING THE SOFTWARE : 1. Visit www.gpg4win.org . Click on the "Gpg4win 2.3.0" button 2. On the following screen, click the "Download Gpg4win" button. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 73 3. When the "Welcome" screen is displayed, click the "Next" button 4. When the "License Agreement" page is displayed, click the "Next" button Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 74 5. Set the check box values as specified below, then click the "Next" button 6. Set the location where you want the software to be installed. The default location is fine. Then, click the "Next" button. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 75 7. Specify where you want shortcuts to the software placed, then click the "Next" button 8. If you selected to have a GPG shortcut in your Start Menu, specify the folder in which it will be placed. The default "Gpg4win" is OK. Click the "Install" button to continue Swami Keshvanand

Institute of Technology, Management

&Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 76 9. A warning will be displayed if you have Outlook or Explorer opened. If this occurs, click the "OK" button. 10. The installation process will tell you when it is complete. Click the "Next" button Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 77 11. Once the Gpg4win setup wizard is complete, the following screen will be displayed. Click the "Finish" button 12. If you do not uncheck the "Show the README file" check box, the README file will be displayed. The window can be closed after you've reviewed it Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 78 CREATING YOUR PUBLIC AND PRIVATE KEYS GPG encryption and decryption is based upon the keys of the person who will be receiving the encrypted file or message. Any individual who wants to send the person an encrypted file or message must possess the recipient's public key certificate to encrypt the message. The recipient must have the associated private key, which is different than the public key, to be able to decrypt the file. The public and private key pair for an individual is usually generated by the individual on his or her computer using the installed

GPGprogram, called "Kleopatra" and the following procedure: 1. From your start bar, select the "Kleopatra" icon to start the Kleopatra certificate management software 2. The following screen will be displayed Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 79 3. From the "File" dropdown, click on the "New Certificate" option 4. The following screen will be displayed. Click on "Create a personal OpenPGP key pair" and the "Next" button Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141-5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 80 5. The Certificate Creation Wizard will start and display the following: Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 81 6. Enter your name and e-mail address. You may also enter an optional comment. Then, click the "Next" button 7. Review your entered values. If OK, click the "Create Key" button Swami Keshvanand Institute of Technology, Management &Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of

the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web:

www.skit.ac.in 82 8. You will be asked to enter a passphrase 9. The passphrase should follow strong password standards. After you've entered your passphrase, click the "OK" button. Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 83 10. You will be asked to re-enter the passphrase 11. Re-enter the passphrase value. Then click the "OK" button. If the passphrases match, the certificate will be created 12. Once the certificate is created, the following screen will be displayed. You can save a backup of your public and private keys by clicking the "Make a backup Of Your Key Pair" button. This backup can be used to copy certificates onto other authorized Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 84 computers. 13. If you choose to backup your key pair, you will be presented with the following screen: Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 85 14. Specify the folder and name the file. Then click the "OK" button. 15. After the key is exported, the following will be displayed. Click the "OK" button Swami Keshvanand Institute of Technology, Management

& Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 86 16. You will be returned to the "Key Pair Successfully Created" screen. Click the "Finish" button. 17. Before the program closes, you will need to confirm that you want to close the program by clicking on the "Quit Kleopatra" button Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 87 DECRYPTING AN ENCRYPTED E-MAIL THAT HAS BEEN SENT TO YOU: 1. Open the e-mail message 2. Select the GpgOL tab Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 88 3. Click the "Decrypt" button 4. A command window will open along with a window that asks for the Passphrase to your private key that will be used to decrypt the incoming message Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 89 5. Enter your passphrase and click the "OK" button 6. The results window will tell you if the decryption succeeded.

Click the "Finish" button top close the window

Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 90 7. Your unencrypted e-mail message body will be displayed 8. When you close the e-mail you will be asked if you want to save the e-mail message in its unencrypted form. For maximum security, click the "No" button. This will keep the message encrypted within the e-mail system and will require you to enter your passphrase each time you reopen the e-mail message Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 91 Viva- Questions 1. What is public-key cryptography? It is also known as asymmetric cryptography. In this type of cryptography, a key pair consists of public key and private key is used to securely exchange the message between two parties. One is used to encrypt the message and other key is used to decrypt the message. The advantage of public-key cryptography is that you only need to keep your private key secure and distribute the public key. 2. What is block cipher? Block cipher is an algorithm that converts a block of plaintext into ciphertext. It takes two inputs, n bits of fixed length of blocks and a secret key and output are n bits of ciphertext. 3. What is stream cipher? Name a most widely used stream cipher. Stream cipher is symmetric encryption algorithm with takes one bit or one byte as input and encrypted with a secret key called keystream. The keystream generator function produces keys K1, K2, K3 ... which are XORed with

plaintext P1, P2, P3 ... to produce cipher text C1, C2, C3 3. What are the differences among encoding, encryption, and hashing? Encoding: Basically, encoding is used to protect the integrity of data as it crosses through communication network to keep its original message upon arriving. It is primarily an insecure function because it is easily reversible. Encryption: Encryption is basically designed for confidentiality and data integrity and reversible only if you have the appropriate key. Hashing: With hashing the operation is one-way i.e., non-reversible. It takes an input (or message) and returns a fixed-size string, which is called the hash value. 4. What are Brute Force Attacks? Brute forcing is a mechanism which is used by an attacker to break the encryption of data by applying a set of various keys. Cryptanalyst has a set of number of keys and apply them one by one to the encryption algorithm until he gets the right key. 5. What is the difference between DSA and RSA? DSA means Digital Signature Algorithm. The basic difference between DSA and RSA is RSA can encrypt and sign, however DSA is only used for digital signature. 6. What are Digital Signatures? Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 92 Digital signature is an attachment to an electronic message used for security purpose. It is used to verify the authenticity of the sender. 7. What is message authentication? When the verifier validates the digital signature using public key of a sender, he is assured that signature has been created only by sender who possess the

corresponding secret private key and no one else. 8. What are the services provided by digital certificates? Digital certificates provide

authentication, nonrepudiation, and integrity services. 9. What are Digital certificates? Digital certificates are digital documents attesting to the binding of a public key to an individual or other entity. They allow verification of the claim that a given public key does in fact belong to a given individual. Certificates help prevent someone from using a phony key to impersonate someone else. 10. What is Secure Sockets Layer (SSL)? The Secure Sockets Layer (SSL) is a computer networking protocol that manages server authentication, client authentication and encrypted communication between servers and clients. 11. What is the technology available to ensure data privacy and integrity during transmission? 1. Controlling Access within the Network 2. Encrypting Data for Network Transmission 3. Secure Sockets Layer (SSL) Protocol 4. Firewall 12. What are the services provided by digital certificates? Digital certificates provide authentication, nonrepudiation, and integrity services 13. What is Rootkit? The term Rootkit originally referred to a collection of tools used to gain administrative access on UNIX operating systems. The collection of tools often included well-known system monitoring tools that were modified to hide the actions of an unauthorized user. An unauthorized user would replace the existing tools on the system with the modified versions preventing authorized users from discovering the security breach. Rootkit - "A tool used to protect backdoors and other tools Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 93 from detection by administrators" 14. What are called Rootkits in Windows? They refer to programs that use system hooking or modification to hide

files, processes, registry keys, and other objects to hide programs and behaviors. Windows rootkits do not necessarily include any functionality to gain administrative privileges. In fact, many Windows rootkits require administrative privileges to even function. 15. What are the basic classes of Rootkits? Two basic classes of Windows rootkits: kernel mode rootkits & user mode rootkits. 16. Why Rootkits are used? Rootkits are used by criminals for a variety of purposes, usually to turn a computer into part of a botnet, which can then, in turn, go on to infect other computers or send spam email messages. The rootkit owner can install key loggers to capture user-entered passwords for online banking and similar activities or steal the user's personal details to use for identity fraud. 17. How Rootkits stay undetected? Many rootkits infect the boot sectors of the computer's hard disk, allowing them to load before the computer's operating system. The rootkit then patches the operating system and changes common functions to hide its existence. For example, the root kit could intercept calls for a list of files in a directory, removing its own file names before showing the results to the user, so it would appear as if the directory is clean. 18. What are the Rootkit capabilities? Current Rootkit Capabilities: Rootkits Hide processes, Hide files, Hide registry entries, Hide services, Completely bypass personal firewalls, Undetectable by antivirus, Remotely undetectable, Covert channels - undetectable on the network, Defeat cryptographic hash checking, Install silently, All capabilities ever used by viruses or worms. 19. What is Intrusion Detection System (IDS)? With the development of network technologies and applications, network attacks are greatly increasing both in number and severity. As a key

technique in network security domain, Intrusion Detection System (IDS) plays vital role of detecting various kinds of attacks and secures the networks. Main purpose

of IDS is to find out intrusions among normal audit data Swami Keshvanand Institute of Technology, Management & Gramothan, Ramnagar, Jagatpura, Jaipur-302017, INDIA Approved by AICTE, Ministry of HRD, Government of India Recognized by UGC under Section 2(f) of the UGC Act, 1956 Tel. : +91-0141- 5160400 Fax: +91-0141-2759555 E-mail: info@skit.ac.in Web: www.skit.ac.in 94 and this can be considered as classification problem. 20. What are the activities of IDS? Intrusion detection systems (IDS) are an effective security technology, which can detect, prevent and possibly react to the attack. It performs monitoring of target sources of activities, such as audit and network traffic data in computer or network systems, requiring security measures, and employs various techniques for providing security services. 21. What is intrusion or intruder? Intrusion: Attempting to break into or misuse your system. Intruders may be from outside the network or legitimate users of the network. Intrusion can be a physical, system or remote intrusion. Intrusion Detection Systems look for attack signatures, which are specific patterns that usually indicate malicious or suspicious intent. 22. What is Snort? Snort is an open-source network intrusion prevention system, capable of performing real time traffic analysis and packet logging on IP networks. It can perform protocol analysis, content searching/matching, and can be used to detect a variety of attacks and probes, such as buffer overflows, stealth port scans, CGI attacks, SMB probes, OS fingerprinting attempts, and much more. 23. What are the uses of Snort? Snort has three primary uses: It can be used as a straight packet sniffer like tcpdump, a packet logger (useful for network traffic debugging, etc.), or as a full-blown network intrusion prevention system. The privacy of the Snort community is very important to source fire. 24. What are the three modes of Snort? Snort can be configured to run in three

modes: 1. Sniffer mode 2. Packet Logger mode 3. Network Intrusion Detection System Mode Sniffer mode: snort -v Print out the TCP/IP packets header on the screen. Packet Logger mode: snort -dev -l c:\log [create this directory in the C drive] and snort will automatically know to go into packet logger mode, it collects every packet it sees and places it in log directory. Network Intrusion Detection System mode: snort -d c:\log -h ipaddress/24 -c nort conf.