

FDP: NETWORK SCIENCE

Graph Models II

6 December 2018

Introduction

Watts-Strogatz Model

Properties of WS Graphs

Barabasi-Albert Model

Properties of BA Graphs

Rakhi Saxena
Deshbandhu College,
University of Delhi,
Delhi, India.

1 Introduction

2 Watts-Strogatz Model

Properties of WS Graphs

3 Barabasi-Albert Model

Properties of BA Graphs

1 Introduction

Introduction

Watts-Strogatz Model

Properties of WS Graphs

Barabasi-Albert Model

Properties of BA Graphs

2 Watts-Strogatz Model

Properties of WS Graphs

3 Barabasi-Albert Model

Properties of BA Graphs

- Hubs represent most striking difference between a random and real-world network. Raises several fundamental questions:

- Hubs represent most striking difference between a random and real-world network. Raises several fundamental questions:
- Why does the random network model of Erdős and Rényi fail to reproduce the hubs and the power laws observed in many real networks?

- Hubs represent most striking difference between a random and real-world network. Raises several fundamental questions:
- Why does the random network model of Erdős and Rényi fail to reproduce the hubs and the power laws observed in many real networks?
- How to explain the small-world property of real-world networks?

- Hubs represent most striking difference between a random and real-world network. Raises several fundamental questions:
- Why does the random network model of Erdős and Rényi fail to reproduce the hubs and the power laws observed in many real networks?
- How to explain the small-world property of real-world networks?
- Why do so different systems as the WWW or the cell converge to a similar scale-free architecture?

- Hubs represent most striking difference between a random and real-world network. Raises several fundamental questions:
- Why does the random network model of Erdős and Rényi fail to reproduce the hubs and the power laws observed in many real networks?
- How to explain the small-world property of real-world networks?
- Why do so different systems as the WWW or the cell converge to a similar scale-free architecture?

	Cellular Network	WWW
Nodes	proteins or metabolites	documents
Links	chemical reactions	hyperlinks
Purpose	production of chemicals cells needed to survive	information access and delivery
History	4 billion years of evolution	few decades old

- Researchers have developed models that can explain characteristics of real-world graphs
 - High Clustering Coefficient
 - Scale-free

- Researchers have developed models that can explain characteristics of real-world graphs
 - High Clustering Coefficient
 - Scale-free
- Watts-Strogatz (WS) Model [WS98]
 - Random graph model fails to exhibit a high clustering coefficient, but it is small-world
 - WS model tries to explicitly model high local clustering

- Researchers have developed models that can explain characteristics of real-world graphs
 - High Clustering Coefficient
 - Scale-free
- Watts-Strogatz (WS) Model [WS98]
 - Random graph model fails to exhibit a high clustering coefficient, but it is small-world
 - WS model tries to explicitly model high local clustering
- Barabási-Albert (BA) Model [BA99]
 - BA model tries to capture the scale-free degree distributions of real-world graphs via a generative process

1 Introduction

2 Watts-Strogatz Model

Properties of WS Graphs

3 Barabasi-Albert Model

Properties of BA Graphs


Watts-Strogatz Small-world Graph Model [WS98]

- Model starts with a *regular graph* of degree $2k$ with n nodes arranged in a circular layout
- Each node has edges to its k nbrs on the right and left

Watts-Strogatz Small-world Graph Model [WS98]

- Model starts with a *regular graph* of degree $2k$ with n nodes arranged in a circular layout
- Each node has edges to its k nbrs on the right and left


Watts–Strogatz Regular Graph: $n = 8$, $k = 2$



Watts-Strogatz Small-world Graph Model [WS98]

- Model starts with a *regular graph* of degree $2k$ with n nodes arranged in a circular layout
- Each node has edges to its k nbrs on the right and left

Watts–Strogatz Regular Graph: $n = 8$, $k = 2$



Navigation icons: back, forward, search, etc.

- Regular Graph has high clustering coefficient
- Surprisingly, adding a small amount of randomness leads to emergence of small-world phenomenon

WS Regular Graph: Clustering Coefficient

- Consider the subgraph G_v induced by the $2k$ neighbours of a node v

WS Regular Graph: Clustering Coefficient

- Consider the subgraph G_v induced by the $2k$ neighbours of a node v
- Clustering coefficient of v is given as

$$C(v) = \frac{m_v}{M_v} \quad (1)$$

- m_v is the actual number of edges, and M_v is the maximum possible number of edges, among the neighbours of v

WS Regular Graph: Clustering Coefficient

- Consider the subgraph G_v induced by the $2k$ neighbours of a node v
- Clustering coefficient of v is given as

$$C(v) = \frac{m_v}{M_v} \quad (1)$$

- m_v is the actual number of edges, and M_v is the maximum possible number of edges, among the neighbours of v
- Consider some node r_i at a distance of i hops ($1 \leq i \leq k$) from v to the right, considering only the backbone edge

WS Regular Graph: Clustering Coefficient

- Consider the subgraph G_v induced by the $2k$ neighbours of a node v
- Clustering coefficient of v is given as

$$C(v) = \frac{m_v}{M_v} \quad (1)$$

- m_v is the actual number of edges, and M_v is the maximum possible number of edges, among the neighbours of v
- Consider some node r_i at a distance of i hops ($1 \leq i \leq k$) from v to the right, considering only the backbone edge
- Node r_i has edges to $k - i$ of its immediate neighbours and to $k - 1$ of its left neighbours

WS Regular Graph: Clustering Coefficient

- Consider the subgraph G_v induced by the $2k$ neighbours of a node v
- Clustering coefficient of v is given as

$$C(v) = \frac{m_v}{M_v} \quad (1)$$

- m_v is the actual number of edges, and M_v is the maximum possible number of edges, among the neighbours of v
- Consider some node r_i at a distance of i hops ($1 \leq i \leq k$) from v to the right, considering only the backbone edge
- Node r_i has edges to $k - i$ of its immediate neighbours and to $k - 1$ of its left neighbours
- Due to the symmetry about v , a node l_i that is at a distance of i backbone hops from v to the left has the same number of edges
- Degree of any node that is i backbone hops away from v is given as

$$d_i = (k - i) + (k - i) = 2k - i - 1 \quad (2)$$

WS Regular Graph: Clustering Coefficient

- Each edge contributes to the degree of its two incident nodes, summing the degrees of all neighbours of v

$$2m_v = 2 \left(\sum_{i=1}^k 2k - i - 1 \right)$$

$$m_v = 2k^2 - \frac{k(k+1)}{2} - k$$

$$m_v = \frac{3}{2}k(k-1) \quad (3)$$

WS Regular Graph: Clustering Coefficient

- Each edge contributes to the degree of its two incident nodes, summing the degrees of all neighbours of v

$$2m_v = 2 \left(\sum_{i=1}^k 2k - i - 1 \right)$$

$$m_v = 2k^2 - \frac{k(k+1)}{2} - k$$

$$m_v = \frac{3}{2}k(k-1) \quad (3)$$

- Also the number of possible edges among the $2k$ neighbours of v

$$M_v = \binom{2k}{2} = \frac{2k(2k-2)}{2} = k(2k-1) \quad (4)$$

WS Regular Graph: Clustering Coefficient

- Each edge contributes to the degree of its two incident nodes, summing the degrees of all neighbours of v

$$2m_v = 2 \left(\sum_{i=1}^k 2k - i - 1 \right)$$

$$m_v = 2k^2 - \frac{k(k+1)}{2} - k$$

$$m_v = \frac{3}{2}k(k-1) \quad (3)$$

- Also the number of possible edges among the $2k$ neighbours of v

$$M_v = \binom{2k}{2} = \frac{2k(2k-2)}{2} = k(2k-1) \quad (4)$$

$$\Rightarrow C_v = \frac{m_v}{M_v} = \frac{3k-3}{4k-2} \quad (5)$$

- **Clustering coefficient** of node v given by

$$C(v) = \frac{m_v}{M_v} = \frac{3k - 3}{4k - 2} \quad (6)$$

- As k increases, clustering coefficient approaches $\frac{3}{4}$ because $C(G) = C(v) \rightarrow \frac{3}{4}$ as $k \rightarrow \infty$
- **WS graph has high clustering coefficient**

- Along the backbone, farthest node from v has a distance of at most $\frac{n}{2}$ hops
- Since each node is connected to k neighbours on either side, furthest node reachable in at most $\frac{n/2}{k}$ hops

- Along the backbone, farthest node from v has a distance of at most $\frac{n}{2}$ hops
- Since each node is connected to k neighbours on either side, furthest node reachable in at most $\frac{n/2}{k}$ hops
- Diameter of WS Regular graph

$$d(g) = \begin{cases} \lceil \frac{n}{2k} \rceil, & \text{if } n \text{ is even} \\ \lceil \frac{n-1}{2k} \rceil, & \text{if } n \text{ is odd} \end{cases}$$

- Thus diameter of regular WS graph scales linearly in the number of nodes

- Along the backbone, farthest node from v has a distance of at most $\frac{n}{2}$ hops
- Since each node is connected to k neighbours on either side, furthest node reachable in at most $\frac{n/2}{k}$ hops
- Diameter of WS Regular graph

$$d(g) = \begin{cases} \lceil \frac{n}{2k} \rceil, & \text{if } n \text{ is even} \\ \lceil \frac{n-1}{2k} \rceil, & \text{if } n \text{ is odd} \end{cases}$$

- Thus diameter of regular WS graph scales linearly in the number of nodes
- **WS Regular Graph is not small-world**

Random Perturbation of a Random Graph

Graph Models II

Rakhi Saxena

Introduction

Watts-Strogatz Model

Properties of WS Graphs

Barabasi-Albert Model

Properties of BA Graphs

- **Edge Rewiring:**

- For each edge (u, v) , with probability r , replace v with another randomly chosen node avoiding loops and duplicate edges
- WS graph has $m = kn$ total edges, after rewiring, rm of edges are random and $(1 - r)m$ are regular


- **Edge Rewiring:**

- For each edge (u, v) , with probability r , replace v with another randomly chosen node avoiding loops and duplicate edges
- WS graph has $m = kn$ total edges, after rewiring, rm of edges are random and $(1 - r)m$ are regular

- **Edge Shortcuts:**

- Add a *few* edges between random pairs of nodes, with probability r , per edge, of adding a successful edge
- Total number of random shortcut edges added to the network are $mr = knr$
- Total number of edges in the graph is
 $m + mr = (1 + r)m = (1 + r)kn$

Watts-Strogatz Graph: Shortcut Edges



$n = 20, k = 3$

◀ ◻ ▶ ◀ ◻ ▶ ◀ ◻ ▶ ◀ ◻ ▶ ◀ ◻ ▶ | Image courtesy of [ZJ14]

- Consider the shortcut approach, each vertex has degree at least $2k$
- Additionally, the shortcut edge follow a Binomial distribution
- Each node can have $n' = n - 2k - 1$ additional shortcut edges, so we take n' as the number of independent trials to add edges
- Since a node has degree $2k$, with shortcut edge probability of r , we expect roughly $2kr$ shortcuts from that node, but the node can connect to at most $n - 2k - 1$ other nodes
- \Rightarrow probability of success is

$$p = \frac{2kr}{n - 2k - 1} = \frac{2kr}{n'} \quad (7)$$

- Let X denote random variable denoting number of shortcuts for each node
- Probability of a node with j shortcut edges is given as

$$f(j) = P(X = j) = \binom{n'}{j} p^j (1 - p)^{n'-j} \quad (8)$$

- with $E[X] = n'p = 2kr$ and $p = \frac{2kr}{n-2k-1} = \frac{2kr}{n'}$
- Therefore, expected degree of each node in the network is

$$2k + E[X] = 2k + 2kr = 2k(1 + r) \quad (9)$$

- Clear that the degree distribution of the WS graph does not adhere to a powerlaw
- **WS networks are not scale-free**

- **Clustering Coefficient:**

$$C(v) \approx \frac{3(k-1)}{(1+r)(4kr+2(2k-1))} = \frac{3k-3}{4k-2+2r(2kr+4k-1)} \quad (10)$$

- Thus for small values of r clustering coefficient remains high
- **Diameter:**
- Small values of shortcut edge probability r are enough to reduce the diameter from $O(n)$ to $O(\log n)$

Watts-Strogatz Model: Diameter(circles) and Clustering Coefficient(triangles)




Image courtesy of [ZJ14]

1 Introduction

2 Watts-Strogatz Model

Properties of WS Graphs

3 Barabasi-Albert Model

Properties of BA Graphs

Barabasi-Albert Scale-Free Model [BA99]

- BA model yields a scale-free degree distribution based on *preferential attachment*

Barabasi-Albert Scale-Free Model [BA99]

- BA model yields a scale-free degree distribution based on *preferential attachment*
 - Edges from a new node are more likely to connect to higher degree nodes
- Let G_t denote graph at time t , let n_t denote number of nodes, m_t denote number of edges in G_t

Barabasi-Albert Scale-Free Model [BA99]

- BA model yields a scale-free degree distribution based on *preferential attachment*
 - Edges from a new node are more likely to connect to higher degree nodes
- Let G_t denote graph at time t , let n_t denote number of nodes, m_t denote number of edges in G_t
- **Initialization:** BA model starts with G_0 , with each node connected to its left and right neighbors in a circular layout. Thus $m_0 = n_0$

- BA model yields a scale-free degree distribution based on *preferential attachment*
 - Edges from a new node are more likely to connect to higher degree nodes
- Let G_t denote graph at time t , let n_t denote number of nodes, m_t denote number of edges in G_t
- **Initialization:** BA model starts with G_0 , with each node connected to its left and right neighbors in a circular layout. Thus $m_0 = n_0$
- **Growth and Preferential Attachment:** BA model derives a new graph G_{t+1} from G_t by adding exactly one new node u and adding $q \leq n_0$ new edges from u to q distinct nodes $v_j \in G_t$, where node v_j is chosen with probability $\pi_t(v_j)$ proportional to its degree in G_t , given as

$$\pi_i(v_t) = \frac{d_j}{\sum_{v_j \in G_t} d_j} \quad (11)$$

Example: BA Model

$$n_0 = 3, q = 2, t = 12$$

At $t = 0$, start with 3 vertices v_0, v_1 , and v_2 fully connected (shown in gray).

At $t = 1$, vertex v_3 is added, with edges to v_1 and v_2 , chosen according to the distribution

$$\pi_0(v_i) = 1/3 \text{ for } i = 0, 1, 2$$

At $t = 2$, v_4 is added. Nodes v_2 and v_3 are preferentially chosen according to the probability distribution

$$\pi_1(v_0) = \pi_1(v_3) = \frac{2}{10} = 0.2$$

$$\pi_1(v_1) = \pi_1(v_2) = \frac{3}{10} = 0.3$$




Image courtesy of [ZJ14]

- Degree of BA Graphs is given by

$$f(k) = \frac{(q+2)(q+1)q}{(k+2)(k+1)k} \cdot \frac{2}{(q+2)} = \frac{2q(q+1)}{k(k+1)(k+2)} \quad (12)$$

- For constant q and large k , degree distribution scales as $f(k) \approx k^{-3}$
- BA model yields a power-law degree distribution with $\gamma = 3$, especially for large degrees

- **Diameter:** of BA graph scales as

$$d(G_t) = O\left(\frac{\log n_t}{\log \log n_t}\right) \quad (13)$$

- suggesting that they exhibit *ultra-small-world* behaviour, when $q > 1$

- **Diameter:** of BA graph scales as

$$d(G_t) = O\left(\frac{\log n_t}{\log \log n_t}\right) \quad (13)$$

- suggesting that they exhibit *ultra-small-world* behaviour, when $q > 1$
- **Clustering Coefficient:** Expected clustering coefficient scales as

$$E[C(G_t)] = O\left(\frac{(\log n_t)^2}{n_t}\right) \quad (14)$$

- which is only slightly better than for random graphs

Example: BA Model - Degree Distribution

$n_0 = 3, q = 2, t = 997$





Image courtesy of [ZJ14]

References I

 Albert-Laszlo Barabasi and Reka Albert, *Emergence of Scaling in Random Networks*, Science **286** (1999), no. 5439, 509–512.

 Duncan J. Watts and Steven H. Strogatz, *Collective dynamics of ‘small-world’ networks*, Nature **393** (1998), 440–442.

 Mohammed J. Zaki and Wagner Meira Jr, *Data Mining and Analysis: Fundamental Concepts and Algorithms*, Cambridge University Press, New York, NY, USA, 2014.