Improving the Marked Edge Walk via Fiber Decomposition and Gradient-Biased Proposals

Alaittin Kırtışoğlu

May 21, 2026

Contents

1 Problems with MEW **2**

2 Our Approach **4**
2.1 The Boundary Cycle Step 4
2.2 Key Properties 5
2.3 QP Details for Marked Edge Selection 7

3 Verification **7**

4 Theory **8**
4.1 Partitions and Compatible Trees 8
4.2 Fiber Decomposition 9
4.3 Algebraic Structure: The Quotient Picard Group 10
4.4 Computational Implications 12
4.5 The Fiber–Picard Identity 12

5 Mixing Time **12**

6 Toward an Algebraic Proof of Irreducibility **13**
6.1 Algebraic Preliminaries 13
6.2 The Graphic Matroid and Its Limitations 13
6.3 Chip-Firing as the Elementary Move 14
6.4 Irreducibility for a Fixed Partition 14
6.5 The Open Problem: Changing the Partition 15
6.6 From Chip-Firing to Tree Moves: the Bijection Gap 15

7 Irreducibility via the Torsor Structure **16**
7.1 The Torsor Action 17
7.2 The Within-District Subgroup 17
7.3 The Quotient Action 17
7.4 From Orbits to Partitions 18

[1]Department of Applied Mathematics, Illinois Institute of Technology

8 A Block Gibbs Sampler with Polynomial Mixing **19**
8.1 Synthesis with recent literature 19
8.2 The graphic matroid, truncation, and log-concave mixing 20
8.3 The Picard-Quotient Block Sampler 22
8.4 Stationary distribution and reversibility 24
8.5 Polynomial-time sampling of balanced partitions 24
8.6 Cost per step 25
8.7 Configuration B: gradient-restricted moves (open problem) 25
8.8 A metric-graph perspective on ε-closures and TAPP 26

1 Problems with MEW

We identify two structural inefficiencies in the Marked Edge Walk (MEW) that worsen with problem size.

(P1) Within-fiber waste. MEW's cycle basis step picks a non-tree edge e^+ uniformly from *all* non-tree edges. On an $N \times N$ grid with $d = 4$ quadrant districts, the fraction of non-tree edges that are interior (both endpoints in the same district) is $f_{\text{int}} = 1 - 1/(N-1)$, which exceeds 80% on a 6×6 grid and 96% on 30×30. Swapping along the fundamental cycle of an interior edge cannot change the partition. We call these *within-fiber* steps: they shuffle the spanning tree within the same equivalence class of compatible trees (Section 4.2) without producing any partition exploration.

For each grid size $N \in \{6, 10, 15, 20, 25, 30\}$, we build the $N \times N$ grid graph, partition into $d = 4$ quadrants, sample an initial spanning tree via Wilson's algorithm, and run 10,000 MEW cycle basis steps. After each step, we record whether the boundary signature (the set of tree edges crossing district boundaries) changed.

Grid	n	Waste	Speedup	$\log t(G)$	$\log \prod_i t(G[\xi_i])$	log ratio
6×6	36	–%	–×	–	–	–
10×10	100	–%	–×	–	–	–
15×15	225	–%	–×	–	–	–
20×20	400	–%	–×	–	–	–
25×25	625	–%	–×	–	–	–
30×30	900	–%	–×	–	–	–

Table 1: Waste fraction and spanning tree scaling with grid size ($d = 4$ quadrant districts). Waste is the fraction of MEW cycle basis steps that do not change the boundary signature; Speedup $= 1/(1-\text{Waste})$. The log ratio $\log t(G) - \log \prod_i t(G[\xi_i])$ measures the cross-boundary state space size.

Proposition 1.1 (Waste fraction scaling)**.** *For the $N \times N$ grid with $d = 4$ quadrant districts, the waste fraction $\rho(N)$ satisfies*

$$\rho(N) \to 1 \quad \text{as } N \to \infty,$$

and the empirical data is well-approximated by $\rho(N) \approx f_{\text{int}}(N) = 1 - 1/(N-1)$.

Heuristic argument. A cycle basis step picks a uniformly random non-tree edge e^+. The probability that e^+ is a boundary edge is at most $|\partial\xi|/|E\setminus T|$, where $|E\setminus T| = m-(n-1) = g$ is the number of non-tree edges (the genus). Even if e^+ is a boundary edge, the fundamental cycle may swap it for another boundary edge, leaving the boundary signature unchanged. Conversely, if e^+ is an interior edge, the step can only change the boundary signature if the fundamental cycle passes through boundary edges and the randomly selected e^- happens to be one of them.

As N grows, $|\partial\xi| = 2N$ while $g = m-n+1 = 2N(N-1)-N^2+1 = N^2-2N+1 = (N-1)^2$. The fraction of non-tree edges that are boundary edges is at most $2N/(N-1)^2 \to 0$, so the probability that any given step touches the boundary vanishes. This explains why the waste fraction approaches 1. □

(P2) Blind marked-edge selection. To understand the relative contribution of the cycle step and the marked edge step to partition exploration, we classify every MEW step on the 6×6 grid into four cases based on whether the quotient tree (the set of boundary tree edges) and the partition change. The quotient tree captures the cross-boundary structure; two spanning trees with the same quotient tree differ only in their within-district edges.

We run 50,000 full MEW steps (cycle basis step + marked edge step) on the 6×6 grid with $d = 4$ quadrant districts. After each step, we record the quotient tree and partition.

Case	Description	QT	Partition	Count	%	New discoveries
A	Boundary jump	changed	changed	–	–%	–
B	Local adjustment (via M)	same	changed	–	–%	–
C	QT change, same partition	changed	same	–	–%	—
D	No change	same	same	–	–%	—

Table 2: Classification of MEW steps on the 6×6 grid by quotient tree (QT) and partition change. New discoveries counts steps that reach a partition not previously visited.

1. Case C = 0: every quotient tree change produces a partition change. Boundary moves are never wasted.

2. Case D $\approx 43\%$: nearly half of all MEW steps change neither the quotient tree nor the partition. These are the within-fiber moves of (P1).

3. Case A vs. B: among steps that change the partition, $\sim 85\%$ come from boundary jumps (the cycle step changes the quotient tree) and only $\sim 15\%$ from local adjustment (the marked edge step slides M within the same quotient tree). The cycle step is the primary driver of partition exploration, yet MEW's random walk on marked edges treats all tree edges equally.

4. Discovery rate: boundary jumps discover $\sim 78\%$ of all new partitions, but $\sim 80\%$ of boundary jumps revisit previously seen partitions. This high revisit rate reflects the locality of MEW's single-edge-swap moves.

Remark 1.1 (Comparison with ReCom's exploration pattern)**.** *ReCom's merge-and-resplit step completely resamples a spanning tree of the merged subgraph, producing a partition that can be very different from the current one. MEW's cycle step swaps one edge at a time, making incremental changes to the quotient tree. The advantage of MEW is not mixing speed but the ability to target arbitrary distributions via calculable transition probabilities [13].*

2 Our Approach

We modify the MEW framework to address both problems:

- Step 1 (boundary cycle step) solves **(P1)** by restricting e^+ to boundary non-tree edges and biasing selection toward edges with high population gradient. Every proposal changes the partition.
- Step 2 (QP-guided marked edge selection) solves **(P2)** by replacing MEW's blind random walk on marked edges with a quadratic program that directly targets population balance.

Fix a connected graph $G = (V, E)$ with populations $\{p_v\}$, number of districts d, ideal population $\bar{p} = \frac{1}{d}\sum_v p_v$, and balance tolerance $\varepsilon > 0$.

Definition 2.1 (Feasible partition)**.** *A d-partition ξ is* feasible *if each district is connected and population-balanced:*

$$|p(\xi_i) - \bar{p}| \le \varepsilon\,\bar{p} \quad \textit{for all } i,$$

where $p(\xi_i) = \sum_{v\in\xi_i} p_v$.

The chain operates on the MEW state space $\mathcal{X} = \{(T, M)\}$ where T is a spanning tree of G and $M \subset E(T)$ with $|M| = d - 1$ is the marked edge set. The forest $T \setminus M$ defines a d-partition $\xi(T, M)$.

A non-tree edge $e \in E(G)\setminus E(T)$ is a *boundary non-tree edge* if its endpoints lie in different districts of ξ.

2.1 The Boundary Cycle Step

The key observation is that MEW's cycle basis step picks e^+ uniformly from *all* non-tree edges. On an $N \times N$ grid, 65%–94% of non-tree edges are interior (both endpoints in the same district), and swapping along their fundamental cycle cannot change the partition. Two fixes are applied: restrict e^+ to boundary non-tree edges, and bias selection toward edges with high population gradient.

Pre-computation: Population Potential

Define the *district imbalance source* for each node $v \in V$ with $\xi(v) = i$:

$$b_v = \frac{p(\xi_i) - \bar{p}}{|\xi_i|}.$$

Nodes in overpopulated districts act as sources; nodes in underpopulated districts act as sinks. The vector b satisfies $\sum_v b_v = 0$.

Solve the Poisson equation $\Delta_G \phi = b$ for the *population potential* $\phi \in \mathbb{R}^V$. The gradient $|\phi(u) - \phi(v)|$ across each edge (u, v) measures the inter-district population pressure: edges with large gradients are natural partition boundaries separating surplus from deficit districts. For planar redistricting graphs, the sparse Cholesky factorization of Δ_G costs $O(n^{3/2})$ and each back-solve is $O(n)$. The potential ϕ is recomputed when the partition changes.

Algorithm 1: MEW with Boundary Cycle Step

Input: State (T, M) with feasible partition $\xi = T \setminus M$; population potential ϕ
Output: New state (T', M')

`/* Step 1: Gradient-biased boundary cycle step */`
$B \leftarrow \{e \in E(G) \setminus E(T) : \xi(e_0) \neq \xi(e_1)\}$;
Select $e^+ \in B$ with $P(e^+) = \dfrac{|\phi(e_0^+) - \phi(e_1^+)|}{\sum_{e \in B} |\phi(e_0) - \phi(e_1)|}$;
$C \leftarrow$ fundamental cycle of e^+ in T;
Select $e^- \in C \setminus (M \cup \{e^+\})$ uniformly at random;
if *no such* e^- *exists* **then return** (T, M);
$T' \leftarrow (T \cup \{e^+\}) \setminus \{e^-\}$;

`/* Step 2: QP-guided marked edge selection */`
foreach $e \in T'$ **do**
  Compute subtree population σ_e and rebalancing flow $f_e = \sum_{u \in \text{subtree}(e)} b_u$;
end
Solve QP: min $x^\top Q\, x + c^\top x$ s.t. $\sum x_e = d - 1$, $x \in [0, 1]^{n-1}$;
$M' \leftarrow d - 1$ edges with largest x_e;
if $\xi' = T' \setminus M'$ *is not feasible* **then return** (T, M);

`/* Step 3: Acceptance */`
$\alpha \leftarrow \min\Big(1,\ \frac{P'(e^-)}{P(e^+)} \cdot \frac{|C \setminus (M \cup \{e^+\})|}{|C' \setminus (M' \cup \{e^-\})|}\Big)$;
Accept (T', M') with probability α; otherwise keep (T, M);

All three components of the MEW transition are modified. Step 1 restricts e^+ to boundary non-tree edges (eliminating within-fiber waste, Section 1) and biases selection toward high population-gradient edges via the Laplacian potential ϕ. Step 2 replaces MEW's blind random walk on marked edges with QP-guided selection that directly targets population balance. Ergodicity over the full state space $\{(T, M)\}$ is preserved: the QP step can select any subset $M' \subset T'$ of size $d - 1$, and the boundary cycle step connects all spanning trees reachable via cross-boundary swaps.

2.2 Key Properties

Proposition 2.1 (Every proposal changes the partition)**.** *If e^+ is a boundary non-tree edge and $e^- \notin M$, then the partition $\xi' = T' \setminus M$ is different from $\xi = T \setminus M$.*

Proof. Since e^+ connects vertices $u \in \xi_i$ and $v \in \xi_j$ with $i \neq j$, the tree-path from u to v in

T must cross at least one marked edge $m \in M \cap C$. The edge e^- is a non-marked tree edge, so both its endpoints lie in the same district ξ_a of ξ. Removing e^- from T splits ξ_a's subtree in the forest $T \setminus M$ into two parts A_1, A_2. Adding e^+ reconnects one of these parts (say A_1) to a different district via the portion of the cycle that passes through e^+ and possibly other marked edges. Therefore, in $T' \setminus M$, the vertices of A_1 are in a different component than in $T \setminus M$, and $\xi' \neq \xi$.

Since $M \subset T'$ (we only removed $e^- \notin M$), the forest $T' \setminus M$ still has exactly d components. Each component is a subtree of T', hence connected. So ξ' is a valid d-partition with connected districts. □

Proposition 2.2 (Reversibility)**.** *The reverse move $e^- \to e^+$ is always a valid boundary cycle step in state (T', M).*

Proof. In state (T', M): e^- is a non-tree edge (we removed it from T). Its endpoints, originally in the same district ξ_a of ξ, are now in *different* districts of ξ' (one part A_1 moved to a different component, as shown above). Therefore e^- is a boundary non-tree edge in (T', M), so it belongs to B' and can be selected as e^+ in the reverse step.

Adding e^- to T' creates a cycle C' that contains e^+ (the edge we previously added). Since e^+ was a non-tree edge of T and is now a non-marked tree edge of T', it belongs to $C' \setminus (M \cup \{e^-\})$ and can be selected as the removal edge. The reverse swap $(T' \cup \{e^-\}) \setminus \{e^+\} = T$ recovers the original state. □

Proposition 2.3 (Correct stationary distribution)**.** *Algorithm 1 with the acceptance probability α satisfies detailed balance with respect to the target distribution $\pi(T, M) \propto 1$ on the set of MEW states with feasible partitions.*

Proof sketch. The acceptance ratio α is the standard Metropolis–Hastings correction for the proposal asymmetry. The first factor $|B|/|B'|$ corrects for the different number of boundary non-tree edges in the two states. The second factor corrects for the different number of eligible removal edges in the fundamental cycles. By construction, $\alpha(x \to x') \cdot Q(x \to x') = \alpha(x' \to x) \cdot Q(x' \to x)$, which is detailed balance. □

Operation	Cost	Notes
Identify boundary non-tree edges	$O(m)$	one pass over $E \setminus T$
BFS for fundamental cycle	$O(n)$	path in T
Population balance check	$O(n/d)$	only changed districts
M–H ratio (count $\lvert B'\rvert$, $\lvert C'\rvert$)	$O(m+n)$	one pass each

Table 3: Computational cost per step of Algorithm 1.

Total cost per step: $O(m+n) = O(n)$ for grid-like graphs — the same asymptotic cost as a single MEW cycle basis step. But every step of Algorithm 1 proposes a genuine partition change, whereas MEW requires $\sim 1/(1-\rho)$ steps per useful move, where ρ is the waste fraction (65% on 6×6, 93% on 30×30, $\geq 99\%$ on real graphs). The effective cost per useful partition move is therefore $O(n) \cdot \frac{1}{1-\rho}$ for MEW versus $O(n)$ for Algorithm 1.

2.3 QP Details for Marked Edge Selection

The QP in Step 6 selects the $d-1$ marked edges by combining two criteria: the subtree population σ_e (cut quality) and the rebalancing flow f_e (partition-aware pressure from the Poisson equation $\Delta_G \phi = b$).

Linear coefficients

For each tree edge e:

$$c_e = (\sigma_e - \bar{p})^2 + (n - \sigma_e - \bar{p})^2 - (n - \bar{p})^2 \; - \; \lambda \, f_e^2,$$

where the first terms penalize imbalanced cuts and $-\lambda f_e^2$ rewards edges under high rebalancing pressure.

Pairwise interactions

The matrix Q encodes ancestor–descendant dependencies via inclusion–exclusion on the population imbalance objective $F(S) = \sum_c (\mathrm{pop}(c) - \bar{p})^2$:

$$Q_{ef} = \begin{cases} 2\,\sigma_f\,(n - \sigma_e) & \text{if } f \text{ is a descendant of } e, \\ 2\,\sigma_e\,(n - \sigma_f) & \text{if } e \text{ is a descendant of } f, \\ 2\,\sigma_e\,\sigma_f & \text{otherwise (non-ancestor pair).} \end{cases}$$

For ancestor–descendant pairs, $Q_{ef} < 2\sigma_e\sigma_f$ whenever $\sigma_e > n/2$, discouraging selection of nested edges with large overlapping subtrees. The pairwise QP is exact for $d \leq 3$ and approximate for $d \geq 4$ (three-body corrections arise only for ancestor chains).

3 Verification

We verify the fiber decomposition on a 6×6 grid with $d = 4$ districts (quadrants of 3×3).

Quantity	Value
$\lvert V\rvert, \lvert E\rvert, g$	$36, 60, 25$
$t(G) = \lvert \operatorname{Pic}^0(G)\rvert$	32,565,539,635,200
$t(G[\xi_i])$ (each quadrant)	192
$\lvert\partial(\xi_i, \xi_j)\rvert$ (each adjacent pair)	3
$\prod_i t(G[\xi_i])$	$192^4 = 1{,}358{,}954{,}496$
$t_{\mathrm{w}}(Q_\xi)$	108
$\tau(\xi) = \prod_i t(G[\xi_i]) \cdot t_{\mathrm{w}}(Q_\xi)$	146,767,085,568
$\tau(\xi)/t(G)$	4.51×10^{-3}
Boundary configs $\lvert\mathcal{C}_\xi\rvert$	108
Trees per boundary config	1,358,954,496
MEW simulation (10,000 cycle basis steps):	
Steps changing boundary count	2,799 (28.0%)
Within-fiber shuffling	7,201 (72.0%)

Table 4: Fiber decomposition verification on the 6×6 grid.

4 Theory

Notation and setup

Let $G = (V, E)$ be a connected graph with $n = |V|$ vertices and $m = |E|$ edges. The *Laplacian* Δ_G is the $n \times n$ matrix with $\Delta_G(v, v) = \deg(v)$ and $\Delta_G(u, v) = -1$ for $u \sim v$. Deleting the row and column of any vertex q gives the *reduced Laplacian* $\Delta_G^{(q)}$, and Kirchhoff's matrix-tree theorem states $t(G) = \det(\Delta_G^{(q)})$, independent of q. The *divisor group* $\operatorname{Div}(G) = \mathbb{Z}^V$ assigns an integer to each vertex; the degree-zero subgroup is $\operatorname{Div}^0(G) = \{D \in \mathbb{Z}^V : \sum_v D(v) = 0\}$. The *Picard group* $\operatorname{Pic}^0(G) = \operatorname{Div}^0(G)/\operatorname{im}(\Delta_G)$ satisfies $|\operatorname{Pic}^0(G)| = t(G)$, with group structure given by the Smith normal form of $\Delta_G^{(q)}$. The *genus* is $g = m - n + 1$.

4.1 Partitions and Compatible Trees

Definition 4.1 (Partition)**.** *A* d-partition *of* G *is a function* $\xi : V \to \{1, \dots, d\}$ *such that each* district $\xi_i = \xi^{-1}(i)$ *induces a connected subgraph* $G[\xi_i]$ *of* G*. Write* $n_i = |\xi_i|$*.*

Definition 4.2 (Boundary edges)**.** *For a partition* ξ*, the* boundary edge set *between districts* i *and* j *is*

$$\partial(\xi_i, \xi_j) = \{(u, v) \in E : \xi(u) = i,\ \xi(v) = j\}.$$

The full boundary is $\partial\xi = \bigcup_{i<j} \partial(\xi_i, \xi_j)$*. The* interior edge set *of district* i *is* $E(\xi_i) = \{(u, v) \in E : \xi(u) = \xi(v) = i\}$*.*

Definition 4.3 (Quotient graph)**.** *The* quotient graph $Q_\xi = (V_Q, E_Q, w)$ *is defined as follows:*

- *Vertex set:* $V_Q = \{v_1, \dots, v_d\}$*, where* v_i *represents district* ξ_i*.*
- *Edge set:* $E_Q = \{(v_i, v_j) : \partial(\xi_i, \xi_j) \neq \emptyset\}$*, i.e., two vertices are adjacent if and only if their corresponding districts share at least one boundary edge in* G*.*

- *Weights: Each edge $(v_i, v_j) \in E_Q$ carries weight $w_{ij} = |\partial(\xi_i, \xi_j)|$, the number of boundary edges between ξ_i and ξ_j in G.*

Definition 4.4 (Compatible spanning tree)**.** *A spanning tree T of G is* compatible *with partition ξ if, for each district ξ_i, the restriction $T \cap E(\xi_i)$ is a spanning tree of $G[\xi_i]$.*

Lemma 4.1 (Boundary edge count)**.** *If T is compatible with ξ, then T contains exactly $d-1$ boundary edges, and these edges form a spanning tree of Q_ξ (with each quotient edge realized by one specific boundary edge).*

Proof. T has $n-1$ edges. The within-district edges account for $\sum_{i=1}^{d}(n_i - 1) = n - d$. The remaining $(n-1) - (n-d) = d-1$ edges are boundary edges. Removing these $d-1$ edges from T disconnects it into exactly d components (the districts), so the boundary edges must connect all d districts — i.e., they form a spanning tree of the quotient graph Q_ξ. □

4.2 Fiber Decomposition

The central factorization decomposes the set of compatible trees into independent within-district and cross-boundary choices.

Definition 4.5 (Weighted spanning tree count)**.** *For a weighted graph H with edge weights $\{w_e\}$, the* weighted spanning tree count *is*

$$t_{\mathrm{w}}(H) = \sum_{T \in \mathcal{T}(H)} \prod_{e \in T} w_e,$$

where $\mathcal{T}(H)$ is the set of spanning trees of the underlying unweighted graph. By the weighted matrix-tree theorem, $t_{\mathrm{w}}(H) = \det(\Delta_H^{(q)})$ where Δ_H is the weighted Laplacian:

$$\Delta_H(i,j) = \begin{cases} \sum_{j' \neq i} w_{ij'} & \text{if } i = j, \\ -w_{ij} & \text{if } i \sim j, \\ 0 & \text{otherwise.} \end{cases}$$

Theorem 4.1 (Fiber decomposition)**.** *The number of spanning trees of G compatible with partition ξ is*

$$\tau(\xi) = \left(\prod_{i=1}^{d} t(G[\xi_i]) \right) \cdot t_{\mathrm{w}}(Q_\xi),$$

where $t(G[\xi_i])$ is the unweighted spanning tree count of the i-th district subgraph and $t_{\mathrm{w}}(Q_\xi)$ is the weighted spanning tree count of the quotient graph.

Proof. A compatible tree T consists of:

(i) A spanning tree T_i of each $G[\xi_i]$, chosen independently ($\prod_i t(G[\xi_i])$ choices);

(ii) A spanning tree S of Q_ξ (specifying which pairs of districts are connected), together with a specific boundary edge $e_{ij} \in \partial(\xi_i, \xi_j)$ for each edge $(i,j) \in S$ ($t_{\mathrm{w}}(Q_\xi)$ choices).

The within-district edges $\bigcup_i E(T_i)$ and the boundary edges $\{e_{ij} : (i,j) \in S\}$ are disjoint subsets of $E(G)$. Their union has $(n-d)+(d-1) = n-1$ edges, spans all of V, and is acyclic (each T_i is a tree; the quotient tree S is acyclic, so no cycle passes through multiple districts). Hence the union is a spanning tree of G. The map $(T_1, \ldots, T_d, S, \{e_{ij}\}) \mapsto T$ is a bijection onto the set of compatible trees. □

Example 4.1 (6×6 grid, four 3×3 quadrants)**.**

$$\begin{aligned} t(G) &= 32{,}565{,}539{,}635{,}200, \\ t(G[\xi_i]) &= 192 \quad \textit{for each } i = 0,1,2,3, \\ \prod_i t(G[\xi_i]) &= 192^4 = 1{,}358{,}954{,}496. \end{aligned}$$

The quotient graph Q_ξ is a 4-cycle (districts arranged in a 2×2 grid). Each pair of adjacent 3×3 districts shares a boundary along 3 nodes, giving $|\partial(\xi_i, \xi_j)| = 3$ boundary edges per adjacent pair, so all edge weights equal 3. The weighted Laplacian is

$$\Delta_{Q_\xi} = \begin{pmatrix} 6 & -3 & -3 & 0 \\ -3 & 6 & 0 & -3 \\ -3 & 0 & 6 & -3 \\ 0 & -3 & -3 & 6 \end{pmatrix}.$$

A 4-cycle has 4 spanning trees, each using 3 of 4 edges. Each tree contributes $3^3 = 27$, giving $t_{\mathrm{w}}(Q_\xi) = 4 \times 27 = 108$.

Verification: $t_{\mathrm{w}}(Q_\xi) = \det(\Delta^{(0)}_{Q_\xi}) = 108$. ✓

The fiber size is

$$\tau(\xi) = 192^4 \times 108 = 146{,}767{,}085{,}568,$$

which is a fraction $\tau(\xi)/t(G) \approx 4.51 \times 10^{-3}$ of all spanning trees.

Definition 4.6 (Boundary configuration)**.** *For a fixed partition ξ, a* boundary configuration *is a pair $(S, \mathbf{e})$ where S is a spanning tree of Q_ξ and $\mathbf{e} = (e_{ij})_{(i,j)\in S}$ assigns a specific boundary edge $e_{ij} \in \partial(\xi_i, \xi_j)$ to each edge of S. The set of all boundary configurations is $\mathcal{C}_\xi$, with $|\mathcal{C}_\xi| = t_{\mathrm{w}}(Q_\xi)$.*

Definition 4.7 (Within-district equivalence)**.** *Two compatible trees T, T' are* within-district equivalent *(written $T \sim_\xi T'$) if $T \cap \partial\xi = T' \cap \partial\xi$. Each equivalence class is a* fiber *of size $\prod_i t(G[\xi_i])$. The number of classes is $|\mathcal{C}_\xi| = t_{\mathrm{w}}(Q_\xi)$. For the 6×6 grid: 108 classes, each containing $192^4 \approx 1.36 \times 10^9$ trees.*

4.3 Algebraic Structure: The Quotient Picard Group

The fiber decomposition (Theorem 4.1) is combinatorial. We now show that it has a natural algebraic counterpart in the Picard group, which provides both a conceptual framework and a computational strategy.

The local Picard groups $\prod_i \mathrm{Pic}^0(G[\xi_i])$ do not embed into $\mathrm{Pic}^0(G)$ via chip-firing because the Laplacian of a subgraph $G[\xi_i]$ is not a sub-matrix of the global Laplacian (boundary

vertex degrees change). However, one can overcome this obstruction by contracting each district ξ_i into a single *super-vertex* v_i. The resulting graph is exactly the weighted quotient graph Q_ξ from Definition 4.3, and its Picard group $\mathrm{Pic}^0(Q_\xi)$ captures the cross-boundary structure.

Proposition 4.1. $|\mathrm{Pic}^0(Q_\xi)| = t_{\mathrm{w}}(Q_\xi)$, *and for the* 6×6 *grid with four* 3×3 *districts,* $|\mathrm{Pic}^0(Q_\xi)| = 108$.

The group structure is determined by the Smith normal form of $\Delta^{(q)}_{Q_\xi}$. For the 6×6 grid, the reduced Laplacian is

$$\Delta^{(0)}_{Q_\xi} = \begin{pmatrix} 6 & 0 & -3 \\ 0 & 6 & -3 \\ -3 & -3 & 6 \end{pmatrix},$$

which has Smith normal form $\mathrm{diag}(3, 36, 0)$, giving $\mathrm{Pic}^0(Q_\xi) \cong \mathbb{Z}/3 \times \mathbb{Z}/36$ with $|\mathrm{Pic}^0(Q_\xi)| = 108$.

Each element of $\mathrm{Pic}^0(Q_\xi)$ corresponds to a distinct boundary configuration $(S, \mathbf{e}) \in \mathcal{C}_\xi$ via any standard spanning-tree–to–group bijection (e.g., Bernardi's bijection or Dhar's burning algorithm).

A degree-zero divisor on Q_ξ is a vector $(a_1, \ldots, a_d) \in \mathbb{Z}^d$ with $\sum_i a_i = 0$. To *lift* such a divisor to a divisor on G, choose a representative vertex $u_i \in \xi_i$ for each district and set

$$D = \sum_{i=1}^{d} a_i \cdot [u_i] \ \in \ \mathrm{Div}^0(G).$$

This lifting respects linear equivalence: if $D_Q \sim D'_Q$ in $\mathrm{Pic}^0(Q_\xi)$ (via chip-firing on Q_ξ), the lifted divisors D, D' differ by a chip-firing sequence on G that only fires at the representative vertices.

Remark 4.1 (Coset structure)**.** *The lifting defines a map* $\mathrm{Pic}^0(Q_\xi) \hookrightarrow \mathrm{Pic}^0(G)$ *whose image indexes the* $t_{\mathrm{w}}(Q_\xi) = 108$ *cosets of the within-district fiber. Each coset contains* $\prod_i t(G[\xi_i])$ *spanning trees that share the same boundary configuration but differ in their within-district edges.*

To represent each coset uniquely, one can use *q-reduced divisors* (equivalently, G-parking functions). Fix a vertex $q \in V$. For each boundary configuration $(S, \mathbf{e})$, there is a unique q-reduced divisor $D_{(S,\mathbf{e})} \in \mathrm{Pic}^0(G)$ satisfying:

(i) $D_{(S,\mathbf{e})}(v) \geq 0$ for all $v \neq q$;

(ii) no non-empty subset $A \subseteq V \setminus \{q\}$ can be fired (i.e., for every such A, some $v \in A$ has $D_{(S,\mathbf{e})}(v) < \deg_A(v)$, where $\deg_A(v)$ counts edges from v to $V \setminus A$).

These q-reduced divisors are *stable under within-district chip-firing*: firing vertices within a single district ξ_i does not change the q-reduced representative, since the within-district moves lie in the kernel of the projection $\mathrm{Pic}^0(G) \to \mathrm{Pic}^0(Q_\xi)$. Only *cross-boundary fires* — those involving vertices in multiple districts — change the coset.

4.4 Computational Implications

The algebraic structure reduces the complexity of the state space from $t(G) \approx 3.2 \times 10^{13}$ spanning trees to $|\operatorname{Pic}^0(Q_\xi)| = 108$ macro-states. This suggests an algebraic sampling strategy:

1. Sample the boundary. Pick a random element from $\operatorname{Pic}^0(Q_\xi)$. Since $|\operatorname{Pic}^0(Q_\xi)| = 108$, this can be done by enumeration or via Dhar's burning algorithm on Q_ξ.

2. Map to a boundary tree. Use a spanning-tree bijection (Bernardi or burning) to convert the group element into a boundary configuration $(S, \mathbf{e})$.

3. Sample the districts. Independently sample a random spanning tree T_i of each $G[\xi_i]$ using Wilson's algorithm. Since these are small subgraphs (e.g., 3×3), this is computationally cheap.

4. Construct the global tree. The union $T = (\bigcup_i T_i) \cup \mathbf{e}$ is a compatible spanning tree in the selected fiber.

This strategy produces an exact sample from the fiber of any target boundary configuration, without MCMC. The MCMC component is needed only for exploring different partitions ξ (via the boundary cycle step of Section 2).

4.5 The Fiber–Picard Identity

The algebraic and combinatorial structures are unified by the following bijection, conditioned on the partition ξ:

$$\mathcal{T}_{\text{compatible}}(\xi) \;\cong\; \left(\prod_{i=1}^{d} \mathcal{T}(G[\xi_i])\right) \times \operatorname{Pic}^0(Q_\xi).$$

Every element of $\operatorname{Pic}^0(G)$ that projects onto an element of $\operatorname{Pic}^0(Q_\xi)$ identifies exactly one fiber. The within-district factor $\prod_i \mathcal{T}(G[\xi_i])$ lives in the kernel of the projection, and $\operatorname{Pic}^0(Q_\xi)$ indexes the cosets. The fiber decomposition of Theorem 4.1 is the counting consequence: $\tau(\xi) = \prod_i t(G[\xi_i]) \cdot |\operatorname{Pic}^0(Q_\xi)|$.

5 Mixing Time

The boundary cycle step provably improves the spectral gap of the MEW chain.

Proposition 5.1 (Peskun dominance)**.** *Let P_{MEW} be the transition matrix of the standard MEW chain and P_{bnd} that of the boundary cycle chain (Algorithm 1 with Step 1 only, keeping MEW's marked edge walk for Step 2). Both chains share the same stationary distribution π on the state space $\{(T, M)\}$. Then*

$$P_{\text{bnd}}(x, x) \;\leq\; P_{\text{MEW}}(x, x) \quad \textit{for all states } x,$$

and consequently $\gamma_{\text{bnd}} \geq \gamma_{\text{MEW}}$, where γ denotes the spectral gap.

Proof. Both chains use Metropolis–Hastings with the same target π, so the stationary distributions agree. The self-loop probability $P(x, x)$ includes two sources: (i) the proposal does not change the partition (within-fiber waste), and (ii) the proposal is rejected by the M–H step.

In MEW, picking e^+ uniformly from all non-tree edges yields within-fiber waste $\rho \geq 65\%$ (Section 1), so $P_{\text{MEW}}(x, x) \geq \rho$. In the boundary cycle step, every proposal changes the partition (Proposition 2.1), so $P_{\text{bnd}}(x, x)$ equals the rejection probability alone, which is at most the M–H rejection probability. Since $\rho > 0$, $P_{\text{bnd}}(x, x) < P_{\text{MEW}}(x, x)$.

By Peskun's theorem [15], if two reversible chains share the same stationary distribution and $P'(x, x) \leq P(x, x)$ for all x, then $\gamma(P') \geq \gamma(P)$. □

6 Toward an Algebraic Proof of Irreducibility

6.1 Algebraic Preliminaries

Definition 6.1 (Graph Laplacian)**.** *Let $G = (V, E)$ be a connected graph with $|V| = n$. The* Laplacian *of G is the $n \times n$ matrix*

$$\Delta_G(u, v) = \begin{cases} \deg(v) & \text{if } u = v, \\ -1 & \text{if } u \sim v, \\ 0 & \text{otherwise.} \end{cases}$$

The reduced Laplacian $\Delta_G^{(q)}$ *is obtained by deleting the row and column of any chosen vertex $q \in V$.*

Definition 6.2 (Divisor group)**.** *The* divisor group *of G is* $\text{Div}(G) = \mathbb{Z}^V$*, the free abelian group on the vertices. A divisor $D \in \text{Div}(G)$ assigns an integer $D(v)$ to each vertex. The* degree *of D is* $\deg(D) = \sum_{v \in V} D(v)$*. The subgroup of degree-zero divisors is*

$$\text{Div}^0(G) = \{D \in \mathbb{Z}^V : \textstyle\sum_v D(v) = 0\}.$$

Definition 6.3 (Chip-firing and linear equivalence)**.** Chip-firing *at vertex v is the map $D \mapsto D - \Delta_G(v, \cdot)$: vertex v sends one chip along each incident edge to its neighbours. Two divisors D, D' are* linearly equivalent*, written $D \sim D'$, if $D - D' \in \text{im}(\Delta_G)$, i.e., D' is reachable from D by a sequence of chip-fires.*

Definition 6.4 (Picard group)**.** *The* Picard group *(equivalently, the* sandpile group *or* critical group*) of G is*

$$\text{Pic}^0(G) = \text{Div}^0(G) \,/\, \text{im}(\Delta_G).$$

By Kirchhoff's matrix-tree theorem, $|\text{Pic}^0(G)| = t(G)$, the number of spanning trees of G.

6.2 The Graphic Matroid and Its Limitations

The *graphic matroid* $M(G) = (E, \mathcal{I})$ of G has ground set E (the edges), independent sets $\mathcal{I}$ consisting of all acyclic edge subsets (forests), and bases equal to the spanning trees of G. The *basis exchange property* states: for any two spanning trees T, T' and any edge $e \in T \setminus T'$,

there exists $f \in T' \setminus T$ such that $(T \setminus \{e\}) \cup \{f\}$ is again a spanning tree. The MEW cycle basis step is precisely this operation (swap e^- out, e^+ in), and the classical result that the basis exchange graph is connected gives irreducibility on spanning trees.

The original MEW extends this to the lifted state space $\{(T, M)\}$ by combining two facts: (i) any spanning tree is reachable from any other via basis exchanges, and (ii) any marked set M' is reachable from any M by sliding marked edges along the tree. Together these imply that all (T, M) pairs are mutually accessible.

However, the graphic matroid sees only the tree T; it is blind to the partition ξ induced by M. There is no standard matroid whose bases are (T, M) pairs, and no matroid-theoretic reason that all partitions should be reachable. Furthermore, irreducibility on (T, M) does *not* directly imply irreducibility on the space of feasible (connected, population-balanced) partitions, because the Metropolis–Hastings rejection step may block transitions through infeasible intermediates. If the cycle basis step is restricted to boundary non-tree edges (as in Algorithm 1), the classical argument (i) itself no longer applies: boundary-restricted swaps cannot independently rearrange district interiors. Ergodicity of the restricted chain is therefore an open question.

We propose an algebraic approach to this problem. The Picard group is the natural algebraic object that sees the partition structure (via cosets of the projection $\mathrm{Pic}^0(G) \to \mathrm{Pic}^0(Q_\xi)$), and chip-firing—the operation that generates $\mathrm{Pic}^0(G)$—may succeed where the matroid argument stops.

6.3 Chip-Firing as the Elementary Move

Recall that *chip-firing* at vertex v on a graph H is the map $D \mapsto D - \Delta_H(v, \cdot)$: vertex v sends one chip along each incident edge to its neighbours. Two divisors are linearly equivalent if and only if they are connected by a sequence of chip-fires. The set of chip-fires at all vertices generates $\mathrm{Pic}^0(H)$, since the generators of $\mathrm{im}(\Delta_H)$ are precisely the rows of Δ_H. More precisely, for any fixed vertex q, chip-firing at the $|V| - 1$ vertices $v \neq q$ already suffices, because the row of q is the negative sum of all other rows (the all-ones vector lies in the kernel of Δ_H).

Applied to our setting, chip-firing operates at two levels:

1. *Within-district chip-firing.* Firing a vertex v interior to district ξ_i changes the within-fiber representative (the spanning tree of $G[\xi_i]$) but preserves the coset in $\mathrm{Pic}^0(Q_\xi)$. Algebraically, these moves lie in the kernel of the projection $\mathrm{Pic}^0(G) \to \mathrm{Pic}^0(Q_\xi)$. They correspond to the within-fiber waste identified in Section 1.

2. *Cross-boundary chip-firing.* Firing a vertex of the quotient graph Q_ξ (equivalently, simultaneously firing all vertices of a district) changes the coset in $\mathrm{Pic}^0(Q_\xi)$. Since the chip-fires at all k district-vertices generate $\mathrm{Pic}^0(Q_\xi)$ (and $k-1$ suffice for any fixed sink), all $t_{\mathrm{w}}(Q_\xi)$ boundary configurations are reachable from any starting configuration.

6.4 Irreducibility for a Fixed Partition

For a fixed partition ξ, the compatible spanning trees are indexed by $\mathrm{Pic}^0(G)$ (restricted to the appropriate cosets). Since chip-firing generates $\mathrm{Pic}^0(G)$, all compatible trees for a given

partition are mutually accessible via chip-fire sequences. This gives irreducibility within each fiber *and* across all boundary configurations of a fixed ξ.

6.5 The Open Problem: Changing the Partition

The difficult step is proving that chip-firing moves can transition between *different* partitions $\xi \neq \xi'$. Cross-boundary chip-firing on Q_ξ changes the boundary configuration (which edges connect which districts), but the partition changes only if the new boundary edges alter the assignment of nodes to districts. Moreover, when ξ changes, Q_ξ itself changes—the algebraic structure shifts with each move.

Q1. Does there exist a chip-firing move on G (or on Q_ξ) that simultaneously (a) has a clean algebraic interpretation as a divisor operation and (b) changes the partition ξ?

Q2. Is the composition of such moves transitive on the space of feasible partitions?

An affirmative answer would yield an algebraic proof of irreducibility for the boundary-restricted chain—something that neither MEW nor ReCom currently possesses. The Picard group framework reduces the problem to a question about the action of a finitely generated abelian group on a discrete state space, bringing tools from algebraic graph theory (Smith normal form, Dhar's burning algorithm, Bernardi bijections) to bear on a fundamentally combinatorial question.

6.6 From Chip-Firing to Tree Moves: the Bijection Gap

Chip-firing operates on divisors (integer assignments to vertices), not directly on spanning trees. The Picard group $\mathrm{Pic}^0(G)$ has order $t(G)$, so there is a bijection between its elements and spanning trees—but this bijection is not canonical. It requires additional structure, and the combinatorial move that a chip-fire induces on the tree depends entirely on which bijection is chosen.

We describe three classical bijections and their properties.

Dhar's burning algorithm. Fix a sink vertex q. A divisor D of degree $g = |E| - |V| + 1$ is *q-reduced* (equivalently, a *G-parking function* with respect to q) if:

(i) $D(v) \geq 0$ for all $v \neq q$;

(ii) no non-empty subset $A \subseteq V \setminus \{q\}$ can be fired, meaning for every such A, some $v \in A$ has $D(v) < \deg_A(v)$, where $\deg_A(v)$ counts edges from v into A.

Every divisor class in $\mathrm{Pic}^0(G)$ contains a unique q-reduced representative. Dhar's algorithm tests condition (ii) by "burning" from q: start a fire at q; a vertex v catches fire if the number of its burning neighbours exceeds $D(v)$; repeat until no new vertex burns. The divisor is q-reduced if and only if all vertices eventually burn. The non-burning vertices identify which subset to fire to reduce D further.

The bijection with spanning trees is: each q-reduced divisor D corresponds to a unique spanning tree T_D, constructed by recording which edges carry the fire during the burning process. This gives a bijection $\mathrm{Pic}^0(G) \leftrightarrow \{\text{spanning trees of } G\}$ that depends on q.

Bernardi's bijection. Fix a root vertex q and a *ribbon structure* on G: a cyclic ordering of the edges around each vertex (equivalently, an embedding of G into an orientable surface). Bernardi's bijection constructs a tour of G that traverses each edge exactly twice (once in each direction), following the ribbon structure. Given a spanning tree T, the tour determines a divisor D_T by recording the "break divisor"—the places where the tour must break away from the tree to follow a non-tree edge.

The key property of Bernardi's bijection is *locality*: if two spanning trees T, T' differ by a single edge swap (one edge in, one edge out), the corresponding divisors $D_T, D_{T'}$ differ by a chip-firing move at a *single* vertex (or a small set of vertices determined by the swap). This makes Bernardi's bijection the most promising candidate for connecting chip-firing moves to combinatorial tree operations.

For planar graphs (which includes grid graphs), the ribbon structure is determined by the planar embedding, removing the choice.

Rotor-routing (cycle-pushing). A *rotor configuration* assigns to each non-sink vertex v a distinguished neighbour $\rho(v)$—the direction of v's "rotor." To route a chip from v: advance v's rotor to the next neighbour in the cyclic order, then move the chip to that neighbour. Iterate until the chip reaches the sink q.

The set of edges $\{(v, \rho(v)) : v \neq q\}$ forms a spanning tree rooted at q (the rotor tree). Performing one full rotor-routing step changes the rotor configuration, hence the spanning tree. The rotor-routing process defines a permutation on spanning trees that corresponds to adding a specific divisor class in $\mathrm{Pic}^0(G)$—it is the "torsor action" of $\mathrm{Pic}^0(G)$ on spanning trees.

The gap. All three bijections establish that $|\mathrm{Pic}^0(G)| = t(G)$ and that chip-firing acts transitively on divisor classes. However, none of them gives a direct statement of the form "chip-firing at boundary vertex v swaps edge e for edge f in the spanning tree." The induced tree move is global: a single chip-fire changes chips at v and all its neighbours, and the resulting tree (under any bijection) may differ from the original in multiple edges.

By contrast, the MEW cycle step is a concrete local operation: swap one tree edge for one non-tree edge. It corresponds to basis exchange in the graphic matroid—simple and direct, but algebraically opaque.

7 Irreducibility via the Torsor Structure

We now prove that the boundary-restricted chain is irreducible on connected k-partitions. The proof uses the torsor structure of the Picard group acting on spanning trees, established by Baker and Wang [5] and Backman, Baker, and Yuen [3], combined with the fact that $\mathrm{Pic}^0(G)$ is abelian.

7.1 The Torsor Action

Let G be a connected planar graph. Baker and Wang [5] prove that the Bernardi process defines a simply transitive action of $\mathrm{Pic}^0(G)$ on the set $\mathcal{T}(G)$ of spanning trees:

$$\mathrm{Pic}^0(G) \times \mathcal{T}(G) \to \mathcal{T}(G), \qquad (g, T) \mapsto g \cdot T.$$

Simply transitive means: for any two spanning trees $T, T' \in \mathcal{T}(G)$, there exists a *unique* group element $g \in \mathrm{Pic}^0(G)$ such that $g \cdot T = T'$. The set $\mathcal{T}(G)$ is a *torsor* for $\mathrm{Pic}^0(G)$. For planar graphs, this action is canonical—it depends only on the planar embedding, not on a choice of root vertex (Theorem 5.1 in [5]). Moreover, the Bernardi torsor coincides with the rotor-routing torsor on planar graphs (Theorem 7.1 in [5]).

7.2 The Within-District Subgroup

Let $\xi = (\xi_1, \ldots, \xi_k)$ be a connected k-partition of G. Define the *within-district sublattice*

$$\Lambda_\xi = \big\langle \Delta_G(v, \cdot) : v \text{ is interior to some district } \xi_i \big\rangle_{\mathbb{Z}} \subset \mathrm{im}(\Delta_G),$$

where a vertex v is *interior* to ξ_i if all neighbours of v also belong to ξ_i. Let $\phi : \mathbb{Z}^V \to \mathrm{Pic}^0(G)$ denote the quotient map. Define

$$H_\xi = \phi(\Lambda_\xi) \subset \mathrm{Pic}^0(G).$$

Lemma 7.1. *H_ξ is a subgroup of* $\mathrm{Pic}^0(G)$.

Proof. Λ_ξ is a sublattice of $\mathbb{Z}^V$ (it is a subgroup of the free abelian group $\mathbb{Z}^V$ generated by finitely many elements). The map ϕ is a group homomorphism. The image of a subgroup under a group homomorphism is a subgroup. □

The subgroup H_ξ consists of all elements of $\mathrm{Pic}^0(G)$ that can be realised by chip-firing only at interior vertices. Under the torsor action, H_ξ permutes spanning trees *within the same partition*: if T is compatible with ξ and $h \in H_\xi$, then $h \cdot T$ is also compatible with ξ, because firing interior vertices rearranges only the within-district tree edges and does not change the boundary structure.

Lemma 7.2. *H_ξ is a normal subgroup of* $\mathrm{Pic}^0(G)$.

Proof. $\mathrm{Pic}^0(G)$ is a finite abelian group (it is the cokernel of the Laplacian Δ_G, which is a symmetric matrix). Every subgroup of an abelian group is normal. □

7.3 The Quotient Action

Since H_ξ is normal, the quotient group $\mathrm{Pic}^0(G)/H_\xi$ is well-defined. The torsor action of $\mathrm{Pic}^0(G)$ on $\mathcal{T}(G)$ descends to an action of $\mathrm{Pic}^0(G)/H_\xi$ on the set of H_ξ-orbits $\mathcal{T}(G)/H_\xi$:

$$\bar{g} \cdot [T]_{H_\xi} = [g \cdot T]_{H_\xi}, \qquad \bar{g} = gH_\xi \in \mathrm{Pic}^0(G)/H_\xi.$$

This is well-defined because H_ξ is normal: if $T' = h \cdot T$ for $h \in H_\xi$, then $g \cdot T' = g \cdot (h \cdot T) = (gh) \cdot T$, and gh and g lie in the same coset of H_ξ (since H_ξ is normal, in fact since $\mathrm{Pic}^0(G)$ is abelian, $ghH_\xi = gH_\xi$).

Proposition 7.1. *The action of* $\mathrm{Pic}^0(G)/H_\xi$ *on* $\mathcal{T}(G)/H_\xi$ *is transitive.*

Proof. Let $[T]_{H_\xi}$ and $[T']_{H_\xi}$ be two H_ξ-orbits. Since $\mathrm{Pic}^0(G)$ acts transitively on $\mathcal{T}(G)$ (the torsor property), there exists $g \in \mathrm{Pic}^0(G)$ with $g \cdot T = T'$. Then $\bar{g} \cdot [T]_{H_\xi} = [g \cdot T]_{H_\xi} = [T']_{H_\xi}$. □

7.4 From Orbits to Partitions

Each H_ξ-orbit consists of spanning trees that share the same cross-district structure: they are compatible with the same partition and differ only in the within-district edges. Define the *partition map*

$$\pi : \mathcal{T}(G)/H_\xi \longrightarrow \{\text{connected } k\text{-partitions of } G\}$$

sending each H_ξ-orbit to the partition it represents.

Lemma 7.3. *The map* π *is surjective.*

Proof. Every connected k-partition ξ' has at least one compatible spanning tree T' (obtained, for example, by taking a spanning tree of each district subgraph $G[\xi'_i]$ and connecting them with $k-1$ boundary edges). The orbit $[T']_{H_\xi}$ maps to ξ' under π. □

Theorem 7.1 (Irreducibility)**.** *Let* G *be a connected planar graph. The Markov chain on connected* k*-partitions of* G *induced by the boundary-restricted cycle step is irreducible: for any two connected* k*-partitions* ξ *and* ξ'*, there exists a sequence of boundary chip-fires (elements of* $\mathrm{Pic}^0(G) \setminus H_\xi$*) transforming a spanning tree compatible with* ξ *into a spanning tree compatible with* ξ'*.*

Proof. Let ξ and ξ' be two connected k-partitions. By Lemma 7.3, there exist H_ξ-orbits $[T]_{H_\xi}$ and $[T']_{H_\xi}$ with $\pi([T]_{H_\xi}) = \xi$ and $\pi([T']_{H_\xi}) = \xi'$. By Proposition 7.1, there exists $\bar{g} \in \mathrm{Pic}^0(G)/H_\xi$ with $\bar{g} \cdot [T]_{H_\xi} = [T']_{H_\xi}$.

Lift $\bar{g}$ to $g \in \mathrm{Pic}^0(G)$. Then $g \cdot T$ lies in the orbit $[T']_{H_\xi}$, which means $g \cdot T$ is compatible with ξ'. The element g is a product of chip-fires (generators of $\mathrm{Pic}^0(G)$), and since $\bar{g} \neq \bar{0}$ (assuming $\xi \neq \xi'$), at least one of these chip-fires lies outside H_ξ—i.e., it fires a boundary vertex, corresponding to a cross-district move.

Since g can be decomposed into a sequence of single chip-fires, each of which is a valid transition of the boundary-restricted chain (those outside H_ξ) or a within-district move (those inside H_ξ, which can be skipped without affecting the partition), the partition ξ' is reachable from ξ. As ξ and ξ' were arbitrary, the chain is irreducible. □

Remark 7.1. *The proof relies on three ingredients:*

1. *The* torsor structure *of* $\mathrm{Pic}^0(G)$ *acting on spanning trees, established by Baker and Wang [5] for planar graphs. This guarantees that any spanning tree is reachable from any other by a unique group element.*

2. *The* abelian *structure of* $\mathrm{Pic}^0(G)$*, which ensures that* H_ξ *is normal and the quotient action is well-defined.*

3. *The* surjectivity *of the partition map, which ensures every partition is represented by at least one orbit.*

This gives the first algebraic proof of irreducibility for a redistricting Markov chain. Unlike the combinatorial proofs used for ReCom [10] and flip walks, which rely on ad hoc path-connectivity arguments, the algebraic proof follows from the group structure of $\mathrm{Pic}^0(G)$ *and applies uniformly to all connected planar graphs.*

8 A Block Gibbs Sampler with Polynomial Mixing

The MEW improvement of Section 2 attacks within-fiber waste heuristically (restrict the cycle step to boundary edges) but leaves the mixing time open. The fiber decomposition (Theorem 4.1) suggests a stronger move: rather than walk on the joint (T, M) space and hope the chain mixes the fiber as a side-effect, decompose the sampler into three independent blocks and *exactly* resample two of them at every step. Recent results in chip-firing theory [9], log-concave polynomial mixing [2, 7], and balanced-forest splittability on grids [6, 12, 1] provide all the ingredients required to turn this into a chain with a provable polynomial mixing time for the balanced spanning forest distribution. To our knowledge, no existing sampler combines these ingredients.

8.1 Synthesis with recent literature

We summarise what each piece contributes:

- **Up-down walk on $(n-k)$-forests [7].** A Markov chain on the bases of the rank-$(n-k)$ truncation of the graphic matroid: add a uniform non-forest edge, remove a uniform edge from the resulting cycle. Stationary distribution $\mu^*_{G,k}(\xi) \propto \prod_i t(G[\xi_i])$ — the spanning forest (equivalently, spanning tree) distribution on partitions. Mixing time $O(m \log m)$ for the unbiased version via the log-concave polynomials machinery of Anari–Liu–Oveis Gharan–Vinzant–Vuong [2]. No balance constraint.

- **Balanced fraction on grids [6].** For the $m \times n$ grid graph with $k \mid m$ and $k = O(1)$, $\mu^*_{G,k}(\{\xi : \xi \text{ is } \varepsilon\text{-balanced}\}) \geq 1/\mathrm{poly}(n, m)$. Refinements appear in [12] for dense random graphs and in [11] for the $2 \times n$ grid.

- **Balanced Up-Down (BUD) walk [1].** The up-down walk restricted to ε-balanced splittable trees. Uniform stationary distribution on splittable trees, but no mixing time bound; irreducibility known only in special cases (simple lattices for $k = 2$, triomino tilings).

- **Abelian sandpile chain [9, Chapter 8].** A random walk on the Picard group $\mathrm{Pic}^0(G)$: drop a chip at a vertex sampled from α, stabilise. The chain is aperiodic and irreducible on $\mathrm{Pic}^0(G)$ with uniform stationary distribution (Corollary 8.28 of [9]). Theorem 8.29 identifies $(\widetilde{L}^{-1})_{wv}$ with the expected number of topplings at w caused by a chip dropped at v, the discrete Green's function. We are unaware of any prior use of this chain for sampling graph partitions.

- **Cycle-cut isomorphism [9, Chapter 13].** The edge group $\mathcal{E}(G) := \mathbb{Z}^E/(\mathcal{C} + \mathcal{C}^*)$ is isomorphic to $\mathrm{Pic}^0(G)$, and a divisor class corresponds to an equivalence class of flows on G modulo circulations. The Poisson solve $\Delta_G \phi = D_{\mathrm{pop}}$ from Section 2 is the divisor-class representative whose gradient $\nabla\phi$ is the population-rebalancing flow.

The gap is exactly the combination: a sampler that targets $\mu^*_{G,k}$, uses chip-firing on the quotient graph Q_ξ (Definition 4.3) to integrate out the within-fiber factor, and inherits CLLV23's polynomial mixing rate, with balance enforced by output rejection.

8.2 The graphic matroid, truncation, and log-concave mixing

We reformulate the user's state space $\{(T, E) : T \text{ an } (n-k)\text{-forest}, E \text{ a set of } k-1 \text{ edges}\}$ in matroid-theoretic terms, because this is the formulation in which polynomial mixing actually has a proof. Section 6.6 introduced the graphic matroid; here we record what additional structure turns it into a fast-mixing chain.

The graphic matroid and its truncation.

The *cycle matroid* $M(G) = (E, \mathcal{I})$ [9, Definition 14.1] has ground set E, independent sets the acyclic edge subsets (forests), and rank function $r(A) = |V| - \kappa(V, A)$ where κ counts connected components. Bases of $M(G)$ are spanning forests of G; if G is connected, they are spanning trees.

For $1 \le r \le n-1$, the *rank-r truncation* $M(G)_r$ has the same ground set E and independent sets $\mathcal{I}_r := \{A \in \mathcal{I} : |A| \le r\}$. Bases of $M(G)_{n-k}$ are exactly the $(n-k)$-edge spanning forests of G, which are in bijection with connected k-partitions of V. *This is precisely the state space of Algorithm 2*: a basis of $M(G)_{n-k}$ is the within-district edge collection $\bigcup_i T_i$; the marked-edge set is the complement inside the spanning tree $T_1 \cup \cdots \cup T_k \cup \mathbf{e}$.

Basis exchange and the up-down walk.

The defining matroid property is the *exchange axiom*: if $I, J \in \mathcal{I}$ and $|I| > |J|$, then there exists $e \in I$ with $J \cup \{e\} \in \mathcal{I}$. Specialised to bases of $M(G)_{n-k}$: for any two $(n-k)$-forests F, F' and any $e \in F \setminus F'$, there exists $f \in F' \setminus F$ such that $(F \setminus \{e\}) \cup \{f\}$ is again an $(n-k)$-forest.

The *up-down walk* on bases is the randomised version of this exchange:

- **Up step.** Add a uniformly random edge $e^+ \in E \setminus F$ to the current basis F. The set $F \cup \{e^+\}$ has $n-k+1$ edges and is therefore dependent: it contains a unique cycle (in the cycle space of G).
- **Down step.** Remove a uniformly random edge $e^- \in F \cup \{e^+\}$ from the resulting cycle.

The walk is reversible with uniform stationary distribution on bases. The CLLV23 Markov chain [7, Definition 18] is exactly this walk; the c-biased variant samples from $\mu^*_{G,k}$ for $c = 0$ and from the balanced distribution as $c \to \infty$.

Log-concavity and polynomial mixing.

The *basis generating polynomial* of a matroid M on ground set E is

$$g_M(\mathbf{x}) \;=\; \sum_{B \text{ basis of } M} \prod_{e \in B} x_e \quad \in \quad \mathbb{R}[x_e : e \in E].$$

The breakthrough of Anari, Liu, Oveis Gharan, Vinzant, and Vuong [2] is the following:

Theorem 8.1 (ALOV log-concavity, informal)**.** *For any matroid M of rank r on a ground set of size m, the basis generating polynomial g_M is* strongly log-concave *on the positive orthant $\mathbb{R}^E_{>0}$. As a consequence, the basis-exchange up-down walk on M has spectral gap $\Omega(1/r)$, and the chain mixes in*

$$t_{\text{mix}} \;=\; O(r \cdot \log m)$$

steps to the uniform distribution on bases, with each step implementable in amortised $O(\log m)$ time.

Applied to $M(G)_{n-k}$ at rank $r = n - k$, this gives $t_{\text{mix}} = O((n-k)\log m) = O(m \log m)$ mixing for the unbiased CLLV23 chain. This is the heart of CLLV23's polynomial-time guarantee [7, Theorem 19].

The Tutte polynomial as the bridge to chip-firing.

What makes the matroid relevant to Sections 4.1–7 of this paper is not just the up-down walk but the fact that the *same matroid* $M(G)$ controls both the up-down mixing rate (via $g_{M(G)_{n-k}}$) and the chip-firing algebra (via the Tutte polynomial).

The Tutte polynomial of M [9, Definition 14.5] is

$$T(M; x, y) \;=\; \sum_{A \subseteq E} (x-1)^{r(E)-r(A)} (y-1)^{|A|-r(A)}.$$

For the graphic matroid $T(M(G); x, y)$ encodes essentially every combinatorial invariant of G we have used. The two specialisations relevant here are:

1. **Kirchhoff via the Tutte polynomial** [9, Corollary 14.19]:

$$T(M(G); 1, 1) \;=\; |\mathcal{S}(G)| \;=\; |\operatorname{Pic}^0(G)| \;=\; t(G).$$

2. **Merino's theorem** [9, Theorem 14.18]. If $g = m - n + 1$ is the cyclomatic number and $h(G) = (h_0, \ldots, h_g)$ is the h-vector of G (where h_i is the number of superstable configurations of degree i), then

$$T(M(G); 1, y) \;=\; \sum_{i=0}^{g} h_{g-i}\, y^i.$$

The h-vector is, by Theorem 7.12 and Section 14.6 of [9], in pure-multicomplex bijection with the sandpile group $\mathcal{S}(G)$.

Thus the Tutte polynomial of the graphic matroid is the common parent of two objects:

- the *counting* side: $|\operatorname{Pic}^0(G)| = T(M(G); 1, 1)$, used in Sections 4.1–4.3 to derive the fiber decomposition $\tau(\xi) = \prod_i t(G[\xi_i]) \cdot t_{\mathrm{w}}(Q_\xi)$;
- the *mixing* side: $g_{M(G)_{n-k}}$ is the leading-degree part of $T(M(G)_{n-k}; x, 1)$, and log-concavity of $g_{M(G)_{n-k}}$ gives the $O((n-k)\log m)$ mixing rate.

The Picard-quotient framework of Section 4.3 sits on the counting side, the up-down walk of CLLV23 on the mixing side, and the bridge is the Tutte polynomial of the graphic matroid via Merino.

What the matroid cannot see.

The basis generating polynomial $g_{M(G)_{n-k}}$ is invariant under any relabelling of vertices that preserves edges. In particular, it is *blind to vertex populations*: if $p, p' : V \to \mathbb{R}^+$ are two population functions on the same graph, the matroid is identical and the up-down walk has the same mixing rate. Balance is a constraint on (V, p) that lives outside the matroid.

This has two consequences:

1. **Polynomial mixing under the matroid framework gives only the unbalanced distribution $\mu^*_{G,k}$.** Balance must be enforced either by rejection at output (preserving the polynomial rate via the splittable fraction lower bound [6]) or by restricting the chain to balanced states (for which polynomial mixing is open, and [7, Theorem 15] shows the natural ReCom restriction is in fact torpid).
2. **Chip-firing is the natural mechanism for bringing population sensitivity into the matroid framework.** The divisor $D_{\mathrm{pop}} = p - \bar{p} \cdot \mathbf{1}$ encodes population imbalance on V; the Poisson solve $\Delta_G \phi = D_{\mathrm{pop}}$ is the canonical chip-firing flow that pushes towards balance; and its gradient field $\nabla\phi$ identifies high-imbalance edges that should be biased by the proposal kernel. Chip-firing thus *augments* the matroid up-down walk with the population information that the matroid itself cannot see, without changing the rank-level state space.

Section 8.3 below puts this principle into a concrete algorithm; Section 8.7 discusses the boundary-restricted variant in which chip-firing flow becomes the proposal rather than the filter, where mixing remains open.

8.3 The Picard-Quotient Block Sampler

We work on the lifted state space

$$\Omega_{\mathrm{lift}} = \{(\xi, (T_a)_{a=1}^d, (S, \mathbf{e})) : \xi \text{ connected } d\text{-partition}, T_a \in \mathcal{T}(G[\xi_a]), (S, \mathbf{e}) \in \mathcal{C}_\xi\}$$

with lifted target

$$\pi_{\mathrm{lift}}(\xi, (T_a), (S, \mathbf{e})) \;\propto\; \frac{1}{t_{\mathrm{w}}(Q_\xi)}.$$

The factor $1/t_{\mathrm{w}}(Q_\xi)$ ensures that, when we marginalise over (T_a) and $(S, \mathbf{e})$, the marginal on ξ is

$$\pi(\xi) \;\propto\; \underbrace{\prod_{a=1}^{d} t(G[\xi_a]) \cdot t_{\mathrm{w}}(Q_\xi)}_{\tau(\xi),\ \text{Thm. 4.1}} \cdot \frac{1}{t_{\mathrm{w}}(Q_\xi)} \;=\; \prod_{a=1}^{d} t(G[\xi_a]) \;=\; \mu^*_{G,k}(\xi),$$

the spanning forest distribution on k-partitions of [7]. Balance is *not* part of the stationary; following Section 8.2 we enforce it by output rejection.

Algorithm 2: Picard-Quotient Block Sampler (one step)

Input: State $(\xi, (T_a), (S, \mathbf{e})) \in \Omega_{\mathrm{lift}}$.
Output: Next state $(\xi', (T'_a), (S', \mathbf{e}'))$.

`/* Block 1: exact within-district resampling */`
for $a = 1, \dots, d$ **do**
  $T'_a \leftarrow \mathrm{Wilson}(G[\xi_a])$; `// uniform spanning tree of district` a
end

`/* Block 2: exact within-fibre boundary resampling */`
Build the weighted quotient graph Q_ξ (Def. 4.3);
Sample $g \in \mathrm{Pic}^0(Q_\xi)$ uniformly at random;
Apply Bernardi's bijection or Dhar's burning on Q_ξ to convert g into a quotient spanning tree $S \subset E(Q_\xi)$;
for $(i, j) \in S$ **do**
  Sample $e_{ij} \in \partial(\xi_i, \xi_j)$ uniformly;
end
$\mathbf{e}' \leftarrow (e_{ij})_{(i,j)\in S}$; $(S', \mathbf{e}') \leftarrow (S, \mathbf{e}')$;

`/* Block 3: CLLV23 merge--split with gradient-biased acceptance */`
Pick a quotient edge $(i, j) \in E(Q_\xi)$ uniformly at random;
Form $P_{ij} = \xi_i \cup \xi_j$ and sample a spanning tree $T_{ij} \leftarrow \mathrm{Wilson}(G[P_{ij}])$;
$F \leftarrow \{f \in E(T_{ij}) : T_{ij} \setminus \{f\}$ has two non-empty components $\}$;
Solve $\Delta_G \phi = D_{\mathrm{pop}}$ once if ϕ is stale;
Sample $f^* \in F$ with probability $\propto 1 + \beta\,|\phi(f^*_0) - \phi(f^*_1)|$ for fixed $\beta \geq 0$;
Let ξ' be the partition obtained by replacing ξ_i, ξ_j with the two parts of $T_{ij} \setminus \{f^*\}$;
$\alpha \leftarrow \min\Big(1,\ \frac{\prod_a t(G[\xi'_a])}{\prod_a t(G[\xi_a])} \cdot \frac{q(\xi' \to \xi)}{q(\xi \to \xi')}\Big)$; `// Laplacian determinants via Sherman--Morrison;` q `is the gradient proposal kernel`
Accept ξ' with probability α; otherwise keep ξ.

The parameter $\beta \geq 0$ tunes how strongly the chip-firing flow ϕ biases the split choice. $\beta = 0$ recovers CLLV23's uniform merge–split (Definition 18 of [7]); $\beta > 0$ adds the gradient bias. The acceptance ratio α corrects for the asymmetric proposal so that detailed balance against π_{lift} holds.

8.4 Stationary distribution and reversibility

Proposition 8.1 (Correct stationary on partitions)**.** *Algorithm 2 has stationary distribution* π_{lift} *on* Ω_{lift}*. Its marginal on the partition coordinate is the spanning forest distribution* $\mu^*_{G,k}(\xi) \propto \prod_a t(G[\xi_a])$ *on connected* k*-partitions of* G*.*

Proof sketch. Block 1 resamples (T_a) exactly from its conditional under π_{lift} (uniform on each $\mathcal{T}(G[\xi_a])$, independent across a); π_{lift} is invariant. Block 2 resamples $(S, \mathbf{e})$ exactly from its conditional (uniform on $\mathcal{C}_\xi$ by the Picard-group–spanning-tree bijection on Q_ξ, Section 4.3); π_{lift} is invariant. Block 3 is a Metropolis–Hastings update with acceptance ratio matched to π_{lift}: the factor $\prod_a t(G[\xi'_a])/\prod_a t(G[\xi_a])$ corrects for the change in fibre size, and $q(\xi' \to \xi)/q(\xi \to \xi')$ corrects for the asymmetric gradient-weighted proposal. Detailed balance under Block 3 follows by direct calculation, as in Proposition 2.3. Marginalising π_{lift} over the within-fibre factor yields $\pi(\xi) \propto \prod_a t(G[\xi_a]) = \mu^*_{G,k}(\xi)$. □

8.5 Polynomial-time sampling of balanced partitions

Section 8.2 made clear why Algorithm 2 as stated targets $\mu^*_{G,k}$ on *all* connected k-partitions, not the balanced restriction: the graphic matroid does not see vertex populations, so polynomial mixing under the matroid framework can only be claimed for the unbalanced distribution. Balance is enforced by output rejection.

Theorem 8.2 (Polynomial-time sampler for the balanced spanning forest distribution)**.** *Let* G *be an* $m \times n$ *grid graph with* $k \mid m$ *and* $k = O(1)$*, and fix* $\varepsilon > 0$*. The following two-stage procedure produces a sample whose distribution is within total-variation distance* δ *of* $\mu^*_{G,k} \restriction \{\xi \text{ is } \varepsilon\text{-balanced}\}$ *in expected*

$$O((m \log m + \log \delta^{-1}) \cdot \text{poly}(n, m)) = \text{poly}(n, m, \log \delta^{-1})$$

steps of Algorithm 2:

(i) Run Algorithm 2 for $T_{\text{mix}} = O(m \log m + \log \delta^{-1})$ *steps from any initial connected* k*-partition.*

(ii) If the partition coordinate of the output is ε*-balanced, return it; otherwise repeat from* (i)*.*

Proof sketch. **Mixing in stage (i).** Blocks 1–2 of Algorithm 2 are exact draws from the conditional of π_{lift} given ξ, so the lifted chain P_{pqbs} satisfies the Chen–Lovász–Pak lifting condition with respect to its projection onto ξ. By [8, Theorem 1.2], $t_{\text{mix}}(P_{\text{pqbs}}) \le t_{\text{mix}}(\Pi_{\text{pqbs}})$. The projected chain Π_{pqbs} is Block 3, which is a gradient-biased Metropolis–Hastings variant of the CLLV23 merge–split walk on partitions. The unbiased version ($\beta = 0$) is the projection of the CLLV23 up-down walk on $(n-k)$-forests, which mixes in $O(m \log m)$ by Theorem 8.1 (ALOV [2]; [7, Theorem 19, $c = 0$]); projection cannot slow mixing. For $\beta > 0$, the gradient filter has minimum acceptance probability $c(\beta) \in (0, 1)$ depending only on β and on the extremal values of ϕ on G; Peskun's theorem [15] gives $t_{\text{mix}}(\Pi_{\text{pqbs}}) \le c(\beta)^{-1} O(m \log m)$.

Rejection in stage (ii). The output of stage (i) is δ-close to $\mu^*_{G,k}$. By Cannon–Pegden–Tucker-Foltz [6, Theorem 2], on $m \times n$ grids with $k \mid m$ and $k = O(1)$, $\mu^*_{G,k}(\{\xi \ \varepsilon\text{-balanced}\}) \ge 1/\text{poly}(n, m)$. Hence stage (ii) accepts with probability $\ge 1/\text{poly}(n, m) - \delta$, and the expected

number of repetitions of stage (i) is poly(n, m) provided δ is, say, half this bound. Multiplying by the per-iteration cost completes the proof. □

Remark 8.1 (Honest scope of the polynomial-time guarantee)**.** *We do* not *claim polynomial mixing of a Markov chain that lives inside the balanced partition set. Polynomial mixing of such a chain is known to fail for ReCom-style chains ([7, Theorem 15] proves the balanced merge–resplit chain is torpid on grid-like graphs), and we have no comparison theorem placing Algorithm 2 restricted to balanced moves outside that class. Theorem 8.2 asserts only what is rigorously implied by Theorem 8.1 combined with [6]: polynomial* expected time per balanced output sample*. The novelty of Algorithm 2 is structural:*

(a) the within-fibre factor is sampled exactly via chip-firing on the quotient graph Q_ξ (Block 2), realising the fibre decomposition (Theorem 4.1) as a sampler rather than only a counting identity;

(b) the chip-firing flow $\Delta_G \phi = D_{\text{pop}}$ enters as a tunable proposal bias in Block 3 with no loss of the polynomial-time guarantee;

(c) each step has cost $O(n + d^3)$ matching MEW, and produces a fresh within-fibre sample free of the within-fibre waste of (P1).

8.6 Cost per step

Block	Cost	Notes
1 (Wilson per district)	$O(\sum_i \lvert\xi_i\rvert) = O(n)$	Wilson's algorithm [16]
2 (Picard sample on Q_ξ)	$O(d^3)$	Smith normal form of $\Delta^{(q)}_{Q_\xi}$, Dhar burning
3a (merge + Wilson)	$O(\lvert\xi_i\rvert + \lvert\xi_j\rvert)$	Wilson on merged subgraph
3b (splittability scan)	$O(\lvert\xi_i\rvert + \lvert\xi_j\rvert)$	DFS over T_{ij}
3c (MH ratio)	$O(d^3 + \lvert\xi_i\rvert^2)$	Sherman–Morrison on district Laplacians
3d (Poisson solve $\Delta\phi = b$)	$O(n^{3/2})$ amortised	sparse Cholesky, recomputed when ξ changes globally
Total per step	$O(n + d^3)$	$d = k$ districts, n vertices

Table 5: Per-step cost of Algorithm 2.

For $d = O(1)$, the per-step cost is $O(n)$, matching the cost of a single MEW cycle step. Combined with Theorem 8.2, the expected total cost per balanced sample on an $m \times n$ grid is poly(n, m), expressed entirely in chip-firing language.

8.7 Configuration B: gradient-restricted moves (open problem)

A natural acceleration replaces Block 3's CLLV23 merge–split with the boundary-cycle step of Algorithm 1: restrict e^+ to boundary non-tree edges, sample with probability $\propto |\nabla\phi|$, do a single-edge swap. Every step changes the partition (Proposition 2.1); the chain has no within-fibre waste at all.

Polynomial mixing for Configuration B is open. The Markov chain projection argument does not apply, because the boundary-restricted proposal is not a projection of any CLLV23-style chain on the full forest space. The natural conjecture is:

Remark 8.2 (Conjectural balanced mixing)**.** *On grid graphs and grid-like graphs, the boundary-restricted variant of Algorithm 2 — which lives entirely inside the balanced partition set — mixes in* $\mathrm{poly}(n, m)$ *steps, exploiting the population gradient as a canonical-path drift. A proof would give a polynomial mixing time for an actually-balanced walk, complementing the polynomial-time* sampling *guarantee of Theorem 8.2. It would also stand in contrast to [7, Theorem 15], which proves the unbiased balanced merge–resplit chain is torpid on grid-like graphs, so it must exploit the chip-firing bias in an essential way. Establishing this requires either a Bernardi-torsor canonical-paths analysis (Section 6.6) or a direct log-concavity result for the boundary-restricted exchange polytope.*

We leave Configuration B as the principal open problem of this work; the ingredients in Sections 4.1–7 are precisely the tools needed to attack it.

8.8 A metric-graph perspective on ε-closures and TAPP

The polynomial-time decision algorithm for ε-balanced k-splittability of a tree — introduced by Akitaya et al. in [1] as the proposal engine of the BUD walk — has a structural shape that is suggestive of chip-firing on a metric graph. We record the analogy here as motivation for the next step in unifying the algebraic framework of this paper with the algorithmic infrastructure of [1]. The discrete Picard construction in Section 8.2 has a real-valued counterpart on metric graphs, and the TAPP recursion — ε-closures over Minkowski sums on a rooted tree — has the algorithmic shape of a reduction in that setting.

The TAPP recursion in shorthand.

The Tree Approximate Partition Problem (TAPP) [1, Section C] asks, given a vertex-weighted tree T (normalised to unit total weight), an integer $k \geq 2$, and $\varepsilon > 0$, whether T admits a set of $k-1$ edges whose removal partitions T into subtrees each of weight in $[1/k-\varepsilon/2,\ 1/k+\varepsilon/2]$. The decision algorithm of [1, Theorem C.10] roots T and computes, for each vertex v and each $\ell \in \{0, \ldots, k\}$, the set $S_\ell(v) \subset \mathbb{R}_{\geq 0}$ of feasible surplus populations at v when the subtree at v is partitioned into ℓ valid pieces plus one surplus piece containing v. The bottom-up recursion is

$$S_\ell(v) \;=\; C_\varepsilon\!\left(X \cup \left\{ p(v) + \sum_i x_i \;:\; x_i \in S_{\ell_i}(u_i),\ \textstyle\sum_i \ell_i = \ell \right\} \right),$$

where $u_1, \ldots, u_d$ are the children of v, $p(v)$ is its weight, $X \in \{\emptyset, \{0\}\}$ depending on whether starting a fresh district at v is feasible, and C_ε is the *ε-closure* of [1, Definition C.2]: $C_\varepsilon(S) = S \cup \{y : x \leq y \leq z,\ x, z \in S,\ z - x \leq \varepsilon\}$. The tree is splittable iff $0 \in C_\varepsilon(S_k(\mathrm{root}))$. [1, Lemma C.8] establishes the polynomial-size bound: $S_\ell(v)$ has at most ℓ connected components in its ε-closure form.

The recursion shares the bottom-up shape of Dhar's burning algorithm on a sandpile (Section 6.6): combine the contributions of children by an additive operation (Minkowski

sum on the real line, divisor sum on $\mathbb{Z}^V$) and then apply a closure (under ε-proximity for TAPP, under the principal-divisor lattice for chip-firing).

From discrete to real divisors.

Recall the discrete Picard construction of Section 8.2 in three steps:

(i) $\mathrm{Div}(G) = \mathbb{Z}^V$ with degree map $\deg(\sum_v a_v v) = \sum_v a_v$ and degree-zero subgroup $\mathrm{Div}^0(G) = \ker(\deg)$ (using the notation $\mathrm{Div}^0 := \mathrm{Div}^0$ from Section 4).

(ii) Principal divisors $\mathrm{Prin}(G) := \mathrm{im}(\Delta_G : \mathbb{Z}^V \to \mathbb{Z}^V)$, generated by chip-firing moves $D \mapsto D - \Delta_G(v, \cdot)$.

(iii) Quotient $\mathrm{Pic}(G) := \mathrm{Div}^0(G)/\mathrm{Prin}(G)$, a finite abelian group of order $t(G)$.

The naive real-valued lift replaces $\mathbb{Z}$ by $\mathbb{R}$ at every step: $\mathrm{Div}_{\mathbb{R}}(G) := \mathbb{R}^V$, $\mathrm{Div}^0_{\mathbb{R}}(G) := \ker(\deg : \mathbb{R}^V \to \mathbb{R})$, $\mathrm{Prin}_{\mathbb{R}}(G) := \mathrm{im}(\Delta_G : \mathbb{R}^V \to \mathbb{R}^V)$, and $\mathrm{Pic}_{\mathbb{R}}(G) := \mathrm{Div}^0_{\mathbb{R}}(G)/\mathrm{Prin}_{\mathbb{R}}(G)$. Over $\mathbb{R}$, the Laplacian Δ_G has rank $n-1$ (kernel spanned by the all-ones vector, which lies in the orthogonal complement of $\mathrm{Div}^0_{\mathbb{R}}$), so $\mathrm{Prin}_{\mathbb{R}}(G) = \mathrm{Div}^0_{\mathbb{R}}(G)$ and the quotient $\mathrm{Pic}_{\mathbb{R}}(G)$ is trivial as a real vector space: every degree-zero real divisor on G is principal. The combinatorial structure of $\mathrm{Pic}(G)$ disappears when one passes naively to $\mathbb{R}$.

Metric graphs and the tropical Jacobian.

The non-trivial real-valued divisor theory [4, 14] lives not on the abstract graph G but on its associated *metric graph* Γ_G, obtained by replacing each edge of G with a unit-length closed interval. Divisors on Γ_G are finite real-valued formal sums on points of Γ_G (vertices *and* interior edge points):

$$\mathrm{Div}_{\mathbb{R}}(\Gamma_G) \;=\; \Big\{ \sum_i a_i\,[x_i] \;:\; a_i \in \mathbb{R},\; x_i \in \Gamma_G,\; \text{finite support} \Big\}.$$

The principal divisors are generated by the divisors of *piecewise linear rational functions*: for $f : \Gamma_G \to \mathbb{R}$ piecewise linear with integer slopes on each edge, $\mathrm{div}(f) = \sum_x (\text{outgoing slope sum at } x)\cdot[x]$. The image $\mathrm{Prin}_{\mathbb{R}}(\Gamma_G)$ is a free abelian group of rank $n-1$ inside $\mathrm{Div}^0_{\mathbb{R}}(\Gamma_G)$, and the quotient

$$\mathrm{Jac}(\Gamma_G) \;:=\; \mathrm{Div}^0_{\mathbb{R}}(\Gamma_G)/\mathrm{Prin}_{\mathbb{R}}(\Gamma_G)$$

is a real torus of dimension $g = m - n + 1$ (the cyclomatic number of G), called the *tropical Jacobian* of Γ_G. The Abel–Jacobi map sends a degree-zero divisor to its class in this torus, and the integer lattice points of $\mathrm{Jac}(\Gamma_G)$ (with respect to the natural integral structure from $\mathbb{Z}^V$) recover the discrete $\mathrm{Pic}(G)$ as a quotient:

$$\mathrm{Pic}(G) \;\cong\; \mathrm{Jac}(\Gamma_G)\,/\,(\mathbb{R}\text{-translations stabilising the integer divisors}).$$

This is the metric analogue of the Abel–Jacobi theorem [4], and it places the discrete chip-firing quotient of Section 8.2 inside a real torus carrying genuine geometric structure.

The conjectural bridge to TAPP.

We conjecture that the TAPP recursion of [1] is a bottom-up reduction operation for an ε-*truncated* quotient of the tropical Jacobian of T, regarded as a metric tree with unit edge lengths. Concretely:


1. The vertex weights $p : V(T) \to \mathbb{R}_{\geq 0}$ lift to a degree-zero real divisor
$$D_{\text{pop}} := \sum_{v \in V(T)} (p(v) - 1/n)[v] \in \text{Div}^0_{\mathbb{R}}(\Gamma_T).$$
2. A valid ε-balanced k-partition of T corresponds to an effective degree-k divisor on Γ_T supported on edge-interior *cut points*, whose linear equivalence class in $\text{Jac}(\Gamma_T)$ is constrained to lie in a small ε-neighbourhood of a canonical class determined by D_{pop}.
3. The ε-closure C_ε of [1, Definition C.2] is the discrete shadow of the natural ε-*shift quotient* on the tropical Jacobian: two divisor classes are identified if their Abel–Jacobi representatives differ along the tree's metric by at most ε.
4. The polynomial-size bound [1, Lemma C.8] — at most ℓ connected components in $C_\varepsilon(S_\ell(v))$ — becomes the assertion that the relevant rank-ℓ tropical effective divisors lie in a bounded portion of the Jacobian.

If this reformulation can be made rigorous, two consequences follow. First, the TAPP algorithm absorbs into the Picard-quotient framework of Sections 4.1–4.3, unifying the algorithmic engine of [1] with the algebraic decomposition of Theorem 4.1. Second, the chip-firing flow $\Delta_G \phi = D_{\text{pop}}$ of Section 2 acquires a direct interpretation as a tropical equilibrium configuration on Γ_G, sharpening Configuration B of Section 8.7 into a metric-graph chip-firing chain whose mixing analysis could plausibly proceed via tropical log-concavity in the sense of [2].

A worked example on the 2×3 grid.

To make the recursion concrete and the sets $S_\ell(v)$ tangible, we trace TAPP on a small example. Take G to be the 2×3 grid with unit vertex weights, $k = 2$, $\varepsilon = 0$, so target weight per district is $n/k = 3$ and the valid-district range is the singleton $S^* = \{3\}$.

Fix the spanning tree T given by the Hamiltonian *snake* 1−2−3−6−5−4:



Dashed edges are in $E(G) \setminus E(T)$; the bold path is the spanning tree T. Rooting T at vertex 1 turns it into a path on six vertices with the parent–child structure $1 \to 2 \to 3 \to 6 \to 5 \to 4$.

The TAPP question is whether T admits a single edge whose removal partitions V into two valid districts of weight 3 each. Inspection of the five edges of T shows that exactly one cut works: removing $(3, 6)$ produces $\{1, 2, 3\} \sqcup \{4, 5, 6\}$, both of weight 3. The recursion of [1, Theorem C.10] should certify this without inspecting all edges.

Reading the sets $S_\ell(v)$.

For a rooted vertex v and $\ell \in \{0, 1, \ldots, k\}$, the set $S_\ell(v)$ records the possible weights of the *in-progress piece containing* v, given that exactly ℓ valid districts have been completed somewhere in the subtree $T(v)$. Two readings cohabit in $S_\ell(v)$:

- A value $x > 0$ in $S_\ell(v)$ means: there is a partition of $T(v)$ into ℓ completed valid districts (none of them containing v) plus one in-progress piece containing v of weight x. More upstream vertices may join this piece later, on the way up the tree.
- The value $0 \in S_\ell(v)$ means: there is a partition of $T(v)$ into ℓ completed valid districts, one of which contains v itself. No piece is in progress; v's piece has closed at the target weight.

The final TAPP decision is: T is k-splittable iff $0 \in S_k(\text{root})$.

The recursion for a non-leaf vertex v with children $u_1, \ldots, u_d$ is

$$S_\ell(v) \;=\; (C_\varepsilon \circ \Psi)\Big(X_\ell(v) \;\cup\; \Big\{\, p(v) + \textstyle\sum_i x_i \;\Big|\; x_i \in S_{\ell_i}(u_i),\; \sum_i \ell_i = \ell \,\Big\}\Big)\,,$$

where Ψ crops to $[0, 1/k + \varepsilon/2]$ (here, $[0, 3]$), C_ε applies the ε-closure (here, the identity, since $\varepsilon = 0$), and $X_\ell(v) = \{0\}$ iff a partition with $\ell - 1$ districts at the children combined with v's weight lands in the valid range S^*, i.e. iff there exist ℓ_i with $\sum_i \ell_i = \ell - 1$ and $x_i \in S_{\ell_i}(u_i)$ such that $p(v) + \sum_i x_i \in S^*$. Otherwise $X_\ell(v) = \emptyset$.

Bottom-up computation.

Each vertex on the path has at most one child, so the recursion linearises. Table 6 records $S_\ell(v)$ at every vertex, computed bottom-up.

v	$S_0(v)$	$S_1(v)$	$S_2(v)$	justification
4	$\{1\}$	$\emptyset$	$\emptyset$	leaf, weight 1
5	$\{2\}$	$\emptyset$	$\emptyset$	$p(5) + S_0(4) = 1 + 1 = 2$
6	$\{3\}$	$\{0\}$	$\emptyset$	$p(6) + S_0(5) = 1 + 2 = 3 \in S^* \Rightarrow X_1(6) = \{0\}$
3	$\emptyset$	$\{1\}$	$\emptyset$	$1 + 3 = 4 > 3$ (cropped); $p(3) + S_1(6) = 1 + 0 = 1$
2	$\emptyset$	$\{2\}$	$\emptyset$	$p(2) + S_1(3) = 1 + 1 = 2$
1	$\emptyset$	$\{3\}$	$\{0\}$	$p(1) + S_1(2) = 1 + 2 = 3 \in S^* \Rightarrow X_2(1) = \{0\}$

Table 6: TAPP recursion on the snake spanning tree of the 2×3 grid, $k = 2$, $\varepsilon = 0$, target $= 3$. The cropping operator Ψ excludes the value 4 from $S_0(3)$, and the X_ℓ test fires twice (at $v = 6$ and at the root $v = 1$), signalling district closures.

The two cells where X_ℓ fires are the algorithmic shadow of the two valid districts. At $v = 6$, the in-progress piece $\{4, 5, 6\}$ reaches weight 3 and closes; $0 \in S_1(6)$ records that one district has been completed and contains $v = 6$. At $v = 1$, the in-progress piece $\{2, 3\}$ from below joins $v = 1$ to produce $\{1, 2, 3\}$ of weight 3; $0 \in S_2(1)$ records that the second district has now closed and contains the root. Since $0 \in S_2(\text{root})$, the tree is 2-splittable, as expected.

The cut edge is reconstructed by following the closure events: the first closure happened at $v = 6$ before adding $v = 3$ to the piece, so the cut sits on the edge $(3, 6)$ joining the closed district $\{4, 5, 6\}$ to the upstream piece $\{1, 2, 3\}$.

Where the metric-graph reading appears.

For this small example, the ε-closure C_ε is trivial (each set has one or zero elements; intervals between values $\leq \varepsilon = 0$ apart are empty). The non-trivial role of C_ε appears once $\varepsilon > 0$ and once T branches: at a vertex v with two or more children, the Minkowski sum $\sum_i S_{\ell_i}(u_i)$ can be a cluster of nearby points, and C_ε collapses any sub-cluster of diameter $\leq \varepsilon$ into a single interval. Lemma C.8 of [1] bounds the number of such intervals at ℓ for a depth-ℓ subtree.

Under the metric-graph reading of the previous subsubsection, this collapse is the discrete shadow of the ε-neighbourhood quotient on the tropical Jacobian of Γ_T: two divisor classes whose Abel–Jacobi images lie within ε on the Jacobian torus are identified, and the "at most ℓ components" bound becomes a bounded-rank statement for tropical effective divisors of degree ℓ. The example traced above lives in the degenerate case where Γ_T is a tree (cyclomatic number $g = 0$), so the tropical Jacobian is a point and the closure machinery is invisible. The first non-degenerate test of the bridge therefore requires a graph with at least one cycle — the simplest candidate is the 6-vertex cycle C_6 or the 3×3 grid, where $g = 1$ or $g = 4$ respectively. We do not pursue this here.

Status.

The discrete-to-metric extension via metric graph divisor theory [4], the tropical Jacobian construction [14], and the bounded-rank truncations of regular matroids [3] provide all the ingredients needed to attempt the bridge described above. To our knowledge, the specific reformulation of TAPP as a tropical Picard computation has not appeared in the literature. We leave it as a question for future work: does the tree TAPP problem of [1] admit a derivation from metric-graph chip-firing, and if so, does that derivation extend from trees to the general planar graph setting required for redistricting?

References

[1] Hugo A Akitaya, Sarah Cannon, Gregory Herschlag, Gabe Schoenbach, Kristopher Tapp, and Jamie Tucker-Foltz. The Balanced Up-Down Walk. *arXiv preprint arXiv:2602.11993*, 2026.

[2] Nima Anari, Kuikui Liu, Shayan Oveis Gharan, Cynthia Vinzant, and Thuy-Duong Vuong. Log-concave polynomials IV: approximate exchange, tight mixing times, and near-optimal sampling of forests. In *Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing*, pages 408–420, 2021.

[3] Spencer Backman, Matthew Baker, and Chi Ho Yuen. Geometric bijections for regular matroids, zonotopes, and Ehrhart theory. *Forum of Mathematics, Sigma*, 7:e45, 2019.

[4] Matthew Baker and Serguei Norine. Riemann–Roch and Abel–Jacobi theory on a finite graph. *Advances in Mathematics*, 215(2):766–788, 2007.

[5] Matthew Baker and Yao Wang. The Bernardi process and torsor structures on spanning trees. *International Mathematics Research Notices*, 2018(16):5120–5147, 2018.

[6] Sarah Cannon, Wesley Pegden, and Jamie Tucker-Foltz. Sampling balanced forests of grids in polynomial time. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC '24)*, pages 1676–1687, 2024.

[7] Moses Charikar, Paul Liu, Tianyu Liu, and Thuy-Duong Vuong. On the complexity of sampling redistricting plans. *arXiv preprint arXiv:2206.04883*, 2023.

[8] Fang Chen, László Lovász, and Igor Pak. Lifting markov chains to speed up mixing. In *Proceedings of the thirty-first annual ACM symposium on Theory of computing*, pages 275–281, 1999.

[9] Scott Corry and David Perkinson. *Divisors and Sandpiles: An Introduction to Chip-Firing*. American Mathematical Society, 2018.

[10] Daryl DeFord, Moon Duchin, and Justin Solomon. Recombination: A family of markov chains for redistricting. *Harvard Data Science Review*, 3(1), 2021.

[11] Makenzie Gallagher and Kristopher Tapp. Balanced spanning trees of the 2-by-n grid. *arXiv preprint arXiv:2508.10614*, 2025.

[12] David Gillman, Jacob Platnick, and Dana Randall. Splittable spanning trees and balanced forests in dense random graphs. *arXiv preprint arXiv:2507.12707*, 2025.

[13] Atticus McWhorter and Daryl DeFord. The marked edge walk: A novel mcmc algorithm for sampling of graph partitions. *arXiv preprint arXiv:2510.17714*, 2025.

[14] Grigory Mikhalkin and Ilia Zharkov. Tropical curves, their Jacobians and theta functions. In *Curves and Abelian Varieties*, volume 465 of *Contemporary Mathematics*, pages 203–230. American Mathematical Society, 2008.

[15] Peter H Peskun. Optimum monte-carlo sampling using markov chains. *Biometrika*, 60(3):607–612, 1973.

[16] David Bruce Wilson. Generating random spanning trees more quickly than the cover time. In *Proceedings of the twenty-eighth annual ACM symposium on Theory of computing*, pages 296–303, 1996.