should be provided to ensure the continuous supply of such information in the event of failure of the craft'smain or emergency source of electrical power. 14.13 _Performance standards 14.13.1 All equipment to which this chapter applies should be of atype approved by the Administration. Such equipment should conform to appropriate performance standards not inferior to those adopted by the Organization*. Refer to the following resolutions adopted by the Assembly of the Organization: .1 Resolution A.525(13): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships . . 2 Resolution A.694(17): General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids . . 3 Resolution A.698(17): Performance standards for ship earth stations capable of two-way communications and resolution A.570(14): Type approval of ship earth stations . . 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio - . 3 Resolution A.698(17): Performance standards for ship earth stations capable of two-way communications and resolution A.570(14): Type approval of ship earth stations . . 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling . . 5 Resolution A.610(15): Performance standards for shipborne MF radio installations capable of voice communication and digital selective calling . . 6 Resolution A.613(15): Performance standards for shipborne MF/HF radio installations capable of voice communication, narrow-band direct-printing and digital selective calling . . 7 Resolution A.695(17): Performance standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz (see also Assembly resolution A.696(17): Type approval of satellite emergency position-indicating radio beacons (EPIRBs) operating in the COSPAS-SARSAT system). W/1687n/pp/EWP (RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT (Footnote continued) MSC 62/23/Add.2 ANNEX 18 Page 143 - operating in the COSPAS-SARSAT system). W/1687n/pp/EWP (RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT (Footnote continued) MSC 62/23/Add.2 ANNEX 18 Page 143 .8 Resolution A.697(17): Performance standards for survival craft radar transponders for use in search and rescue operations • . 9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indicating radio beacons . . 10 Resolution A.663(16): Performance standards for INMARSAT Standard-Cship earth stations capable of transmitting and rece~v~ng direct-printing communications and resolution A.570(14): Type approval of ship earth stations . . 11 Resolution A.664(16): Performance standards for enhanced group call equipment . . 12 Resolution A.661(16): Performance standards for float-free satellite emergency position-indicating radio beacons operating through the geostationary INMARSAT