subjected to the greater of the heeling moments in 1.1.2 and 1.1.4 of that annex. 2.3.2 Multihull craft should meet the relevant requirements of annex 7 for all permitted cases of loading. 2.3.3 Subject to 2.3.4, all other craft should meet the following criteria in all permitted conditions of loading: .1 resolution A.562(14) (weather criterion); W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 28 .2 the area under the righting lever curve (GZ curve) should not be less than 0.07 m.rad up to e = 15° when the maximum righting lever (GZ) occurs at e = 15° and 0.055 m.rad up to e = 30° when the maximum righting lever occurs at e = 30° or above. Where the maximum righting lever occurs at angles of between e = 15° and e = 30°, the corresponding area under the righting lever curve should be: A = 0.055 + 0.001 (30° - emax) (m.rad) where: emax is the angle of heel in degrees at which the righting lever curve reaches its maximum; .3 the area under the righting lever curve between e = 30° and e = 40° or between e = 30° and the angle of flooding - where: emax is the angle of heel in degrees at which the righting lever curve reaches its maximum; .3 the area under the righting lever curve between e = 30° and e = 40° or between e = 30° and the angle of flooding ef *, if this angle is less than 40°, should not be less than 0.03 m.rad; .4 the righting lever GZ should be at least 0.20 mat an angle of heel equal to or greater than 30°; .5 the maximum righting lever should occur at an angle of heel not less than 15°; and .6 the initial metacentric height GMo should not be less than 0.15 m. 2.3.4 Where the characteristics of the craft are unsuitable for application of 2.3.3, the Administration may accept alternative criteria equivalent to those stipulated in 2.3.3, appropriate to the type of craft and area of operation. 2.4 Intact stability in the non - displacement mode 2.4.1 The requirements of this section and section 2.12 should be applied on the assumption that any stabilization systems fitted are fully operational. 2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and - on the assumption that any stabilization systems fitted are fully operational. 2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and transient modes within approved operational limitations, the craft will, after adisturbance causing roll, pitch, heave or heel due to turning or any combination thereof, return to the original attitude. 2.4.3 The roll and pitch stability on the first and/or any other craft of aseries should be qualitatively assessed during operational safety trials as required by chapter 18 and annex 8. The results of such trials may indicate the need to impose operational limitations. In applying this criterion, small openings through which progressive flooding cannot take place need not be considered as open. Wll576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRA