The exposed surfaces of vapour barriers and adhesives used in conjunction with insulation materials should have low flame-spread characteristics. Furniture and furnishings in public spaces and crew accommodation should comply with the following standards: .1 all case furniture is constructed entirely of approved non-combustible or fire-restricting materials, except that acombustible veneer with acalorific value not exceeding 45 MJ/m 2 may be used on the exposed surface of such articles; .2 all other furniture such as chairs, sofas and tables is constructed with frames of non-combustible or fire-restricting materials; .3 all draperies, curtains and other suspended textile materials have qualities of resistance to the propagation of flame in accordance with standards* developed by the Organization; Refer to the Recommendation on test method for determining the resistance to flame of vertically supported textiles and films, adopted by the Organization by resolution A.47l(XII), and amendments to the recommendation adopted by resolution A.563(14). W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY - Organization by resolution A.47l(XII), and amendments to the recommendation adopted by resolution A.563(14). W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 7.4.3.4 7.4.3.5 7.4.3.6 7.4.3.7 7.4.3.8 MSC 63/23/Add.2 ANNEX 18 Page 61 .4 all upholstered furniture has qualities of resistance to the ignition and propagation of flame in accordance with standards* developed by the Organization; .5 all bedding components comply with the standards** developed by the Organization; and .6 all deck finish materials comply with the standards*** developed by the O~ganization. The following surfaces should, as aminimum standard be constructed of materials having low flame-spread characteristics: .1 exposed surfaces in corridors and stairway enclosures, and of bulkheads, wall and ceiling linings in all accommodation and service spaces and control stations; .2 concealed or inaccessible spaces in accommodation, service spaces and control stations. Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material. - .2 concealed or inaccessible spaces in accommodation, service spaces and control stations. Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material. Materials used in the craft, when exposed to fire, should not emit smoke or toxic gases in quantities that could be dangerous to humans as determined in tests of astandard developed by the Organization. Void compartments, where low density combustible materials are used to provide buoyancy, should be protected from adjacent fire hazard areas by fire-resisting divisions, in accordance with tables 7.4-1 and 7.4-2. Also, the space and closures to it should be gastight but it should be ventilated to atmosphere. In compartments where smoking is allowed, suitable non-combustible ash containers should be provided. In compartments where smoking is not allowed, adequate notices should be displayed. * Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Organization by resolution A.652(16). ** Refer to the Recommendation on fire test procedures for ignitability of - * Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Organization by resolution A.652(16). ** Refer to the Recommendation on fire test procedures for ignitability of bedding components, adopted by the Organization by resolution A.688(17). *** Refer to the Recommendation on improved fire test procedures for surface flammability of bulkhead, ceiling and deck finish materials, adopted by the Organization by resolution A.653(16) and the Recommendation on fire test procedures for ignitability of primary deck coverings, adopted by the Organization by resolution A.687(16). W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 62 7.4.3.9 The exhaust gas pipes should be arranged so that the risk of fire is kept to aminimum. To this effect, the exhaust system should be insulated and all the com