Communications Craft should be provided with the following radio life-saving appliances: .1 at least three two-way VHF radiotelephone apparatus should be provided on every passenger high speed craft and on every cargo high speed craft of 500 tons gross tonnage and upwards. Such apparatus should conform to performance standards not inferior to those adopted by the Organization.; .2 at least one radar transponder should be carried on each side of every passenger high speed craft and of every cargo high speed craft of 500 tons gross tonnage and upwards. Such radar transponders should conform to performance standards not inferior to those adopted by the Organization.** The radar transponders should be stowed in such locations that they can be rapidly placed in any one of the 1iferafts. Alternatively, one radar transponder should be stowed in each survival craft. * Refer to the Recommendation on performance standards for survival craft portable two-way VHF radiotelephone apparatus, adopted by the Organization by resolution A.605(15). ** Refer to the Recommendation on performance standards for survival craft - craft portable two-way VHF radiotelephone apparatus, adopted by the Organization by resolution A.605(15). ** Refer to the Recommendation on performance standards for survival craft radar transponders for use in search and rescue operations, adopted by the Organization by resolution A.697(17). WI1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2 ANNEX 18 Page 84 8.2.2 8.2.3 8.2.3.1 8.2.3.2 Craft should be provided with the following on-board communications and alarm systems: .1 an emergency means comprising either fixed or portable equipment or both for two-way communications between emergency control stations, muster and embarkation stations and strategic positions on board; and .2 ageneral emergency alarm system complying with the requirements of regulation III/50 of the Convention to be used for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either apublic address system or other suitable means of communication. The systems should be - for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either apublic address system or other suitable means of communication. The systems should be operable from the operating compartment. Signalling eguipment All craft should be provided with aportable daylight signalling lamp which is available for use in the operating compartment at all times and which is not dependent on the craft'smain source of electrical power. Craft should be provided with not less than 12 rocket parachute flares, complying with the requirements of regulation 111/35 of the Convention, stowed in or near the operating compartment. 8.3 Personal liLe - saying appliances 8.3.1 Where passengers or crew have access to exposed decks under normal operating conditions, at least one lifebuoy on each side of the c 'raft capable of quick release from the control compartment and from aposition at or near where it is stowed, should be provided with aself-igniting light and aself-activating smoke signal. The positioning and securing arrangements of the self-activating smoke - aposition at or near where it is stowed, should be provided with aself-igniting light and aself-activating smoke signal. The positioning and securing arrangements of the self-activating smoke signal should be such that it cannot be released or activated solely by the accelerations produced by collisions or groundings. 8.3.2 At least one lifebuoy should be provided adjacent to each normal exit from the craft and on each open deck to which passengers and crew have access, subject to aminimum of two being installed. 8.3.3 Lifebuoys fitted adjacent to each normal exit from the craft should be fitted with buoyant lines of at least 30 min length. 8.3.4 8.3.5 Not less than half the total with self-igniting lights. self-igniting lights should accordance with 8.3.3. number of lifebuoys should be fitted However, the lifebuoys provided with not include those provided with lines in Alifejacket complying with the requirements of regulat