operating in the COSPAS-SARSAT system). W/1687n/pp/EWP (RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT (Footnote continued) MSC 62/23/Add.2 ANNEX 18 Page 143 .8 Resolution A.697(17): Performance standards for survival craft radar transponders for use in search and rescue operations • . 9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indicating radio beacons . . 10 Resolution A.663(16): Performance standards for INMARSAT Standard-Cship earth stations capable of transmitting and rece~v~ng direct-printing communications and resolution A.570(14): Type approval of ship earth stations . . 11 Resolution A.664(16): Performance standards for enhanced group call equipment . . 12 Resolution A.661(16): Performance standards for float-free satellite emergency position-indicating radio beacons operating through the geostationary INMARSAT satellite system on 1.6 GHz • . 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment . . 14 Resolution A.699(17): System performance standard for the - . 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment . . 14 Resolution A.699(17): System performance standard for the promulgation and co-ordination of maritime safety information using high-frequency narrow-band direct-printing . . 15 Resolution A.700(17): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (MSI) by HF. W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2 ANNEX 18 Page 144 14.14 14.14.1 14.14.2 14.14.3 14.14.4 14.14.5 14 .14.6 14.14.1 14.14.8 Maint enance requ irements Equipment should be so designed that the main units can be replaced readily without elaborate recalibration or readjustment. Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes. Adequate information should be provided to enable the equipment - Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes. Adequate information should be provided to enable the equipment to be properly operated and maintained, taking into account the recommendations of the Organization*. Adequate tools and spares should be provided to enable equipment to be maintained . The Administration should ensure that radio equipment required by this chapter is maintained to provide the availability of the functional requirements specified in 14.4 and to meet the recommended performance standards of such equipment. On crafts engaged on voyages in sea areas Al and A2, the availability should be ensured by using such methods as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, or a combinat5 .on of these, as may be approved by the Administration. On crafts engaged on voyages i