Functional requirements Every craft, while at sea, should be capable: .1 except as provided in 14.7.1.1 and 14.9.1.4.3, of transmitting ship-to-shore distress alerts by at least two separate and independent means, each using adifferent radiocommunication service; .2 of receiving shore-to-ship distress alerts; .3 of transmitting and receiving ship-to-ship distress alerts; .4 of transmitting and receiving search and rescue co-ordinating communications; .5 of transmitting and receiving on-scene communications; .6 of transmitting and, as required by 13.5, receiving signals for locating~; .7 of transmitting and receiving** marine safety information; .8 of transmitting and receiving general radiocommunications to and from shore-based radio systems or networks subject to 14.14.8; and .9 of transmitting and receiving bridge-to-bridge communications. * Refer to resolution A.614(15) on carriage of radar operating in the frequency band 9,300-9,500 MHz adopted by the Organization. ** It should be noted that craft may have aneed for reception of certain maritime safety information while in port. W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) - frequency band 9,300-9,500 MHz adopted by the Organization. ** It should be noted that craft may have aneed for reception of certain maritime safety information while in port. W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 14.5 14.5.1 14.5.2 14.5.3 14.6 14.6.1 Radio installations MSC 62/23/Add.2 ANNEX 18 Page 133 Every craft should be provided with radio installations capable of complying with the functional requirements prescribed by 14.4 throughout its intended voyage and, unless exempted under 14.3, complying with the requirements of 14.6 and, as appropriate for the sea area or areas through which it will pass during its intended voyage, the requirements of either 14.7, 14.8, 14.9 or 14.10. Every radio installation should: .1 be so located that no harmful interference of mechanical, electrical or other origin affects its proper use, and so as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems; .2 be so located as to ensure the greatest possible degree of safety and operational availability; - as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems; .2 be so located as to ensure the greatest possible degree of safety and operational availability; .3 be protected against harmful effects of water, extremes of temperature and other adverse environmental conditions; .4 be provided with reliable, permanently arranged electrical lighting, independent of the main sources of electrical power, for the adequate illumination of the radio controls for operating the radio installation; and .5 be clearly marked with the call sign, the ship station identity and other codes as applicable for the use of the radio installation. Coritrol of the VHF radiotelephone channels, required for navigational safety, should be immediately available on the navigating bridge convenient to the conning position, and where necessary, facilities should be available to permit radiocommunications from