the Maritime Safety Committee, every craft should, in addition , be fitted with aradio installation consisting of aradiotelephone distress frequency watch receiver capable of operating on 2,182 kHz. Until 1 February 1999, every craft should, unless the craft is engaged on voyages in sea area Al only, be fitted with adevice for generating the radiotelephone alarm signal on the frequency 2,182 kHz*. The Administration may exempt craft constructed on or after 1 February 1997 from the requirements prescribed by 14.6.2 and 14.6.3. Radi oequ ipment : Sea area A1 In addition to meeting the requirements of 14.6, every craft engaged - 2,182 kHz*. The Administration may exempt craft constructed on or after 1 February 1997 from the requirements prescribed by 14.6.2 and 14.6.3. Radi oequ ipment : Sea area A1 In addition to meeting the requirements of 14.6, every craft engaged on voyages exclusively in sea area Al should be provided with aradio installation capable of initiating the transmission of ship-to-shore distress alerts from the position from which the craft is normally navigated, operating either: .1 on VHF using DSC; this requirement may be fulfilled by the EPIRB prescribed by 14.7.3, either by installing the EPIRB close to, or by remote activation from, the position from which the craft is normally navigated; or . 2 through the polar orbiting satellite service on 406 MHz; this requirement may be fulfilled by the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from the position from which the craft is normally navigated; or . 3 if the craft on voyages within coverage of MF coast stations equipped with DSC, on MF using DSC; or .4 on HF using DSC; or .5 through the INMARSAT geostationary satellite service; this - craft is normally navigated; or . 3 if the craft on voyages within coverage of MF coast stations equipped with DSC, on MF using DSC; or .4 on HF using DSC; or .5 through the INMARSAT geostationary satellite service; this requirement may be fulfilled by: .5.1 an INMARSAT ship earth station**; or * Refer to resolution A.421(XI) concerning operational standards for radiotelephone alarm signal generators, adopted by the Organization. ** This requirement can be met by INMARSAT ship earth stations capable of two-way communications, such as Standard-Aand B (resolution A.698(17» or Standard-C (resolution A.663(16» ship earth stations. Unless otherwise specified, this footnote applies to all requirements for an INMARSAT ship earth station prescribed by this chapter. W/16B7n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2 ANNEX lB Page 136 14.7.2 1