all stations at which control functions may be exercised. 11.4.2 The alarm system should meet appropriate constructional and operational requirements for required alarms.~ 11.4.3 Equipment monitoring the passenger, cargo and machinery spaces for fire and flooding should, so far as is practicable, form an integrated sub-centre incorporating monitoring and activation controls for all emergency situations. This sub-centre may require feed-back instrumentation to indicate that actions initiated have been fully implemented. 11.5 Safety system Where arrangements are fitted for overriding any automatic shutdown system for the main propulsion machinery in accordance ~ith 9.2.2, they should be such as to preclude inadvertent operation. When ashutdown system is activated, an audible and visual alarm should be given at the control station and means should be provided to override the automatic shutdown except in cases where there is arisk of complete breakdown or explosion. * Refer to the Code on alarms and indicators adopted by the Organization by resolution A.686(17). W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) - risk of complete breakdown or explosion. * Refer to the Code on alarms and indicators adopted by the Organization by resolution A.686(17). W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2 ANNEX 18 Page 110 12.1 12.1.1 12.1. 2 12.1. 3 12.1. 4 12.1. 5 12.2. 12.2.1 CHAPTER 12 - ELECTRICAL INSTALLATIONS PART A - GENERAL General Electrical insta11ations* should be such that: .1 all electrical auxiliary services necessary for maintaining the craft in normal operation and habitable conditions will be ensured without recourse to the emergency source of electrical power; .2 electrical services essential for safety will be ensured under various emergency conditions; and . 3 the safety of passengers, crew and craft from electrical hazards will be ensured. The FMEA should include the electrical system, taking into account the effects of electrical failure on the systems being supplied. In cases where faults can occur without being detected during routine checks on the installations, the analysis should take into account - the effects of electrical failure on the systems being supplied. In cases where faults can occur without being detected during routine checks on the installations, the analysis should take into account the possibility of faults occurring simultaneously or consecutively. The electrical system should be designed and installed so that the probability of the craft being at risk of failure of aservice is extremely remote. Where loss of particular essential service would cause serious risk to the craft, the service should be fed by at least two independent circuits fed in such away that no single failure in the electrical supply or distribution systems would effect both supplies. The securing arrangements for heavy items, i.e. accumulator batteries, should, as far as practicable, prevent excessive movemen' during the accelerations due to grounding or collision. Precautions should be taken to minimize risk of supplies to essential and emergency services being interrupted by the inadvertent or accidental opening of switches or circuit breakers. Main so urce o felectrical p~ Amain source of electrical power of sufficient capacity to supply - essential and emergency services being interrupted by the inadvertent or accidental opening of switches or circuit breakers. Main so urce o felectrical p~ Amain source of electrical power of sufficient capacity to supply all those services mentioned in 12.1.1 should be provided. The main source of electrical power should consist of at least two generating sets. Refer to the recommendations published by the International Electrotechnical Commission and, in particu,lar, Publication 92 - Electrical installations in ships. WIl687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 12.2.2 12.2.3 12.2.4 12.2.5 12.2.6 12.2.7 12.2.8 12.2.9 MSC 62123/Add.2 ANNEX 18 Page J.11 The capacity of these generating sets should be such that in the event of anyone generating set being stopped or failing it will still be possible to supply those services necessary to pro