means of access for inspections, intended to facilitate close-up inspections and thickness measurements of the ship■sstructure referred to in SOLAS regulation II-1/3-6 on Access to and within spaces in the cargo area of oil tankers and bulk carriers. Definitions Terms used in the Technical provisions have the same meaning as those defined in the 1974 SOLAS Convention, as amended, and in resolution A.744(18), as amended. Technical provisions 1 Structural members subject to the close-up inspections and thickness measurements of the ship■sstructure referred to in SOLAS regula tion II-1/3-6, except those in double bottom spaces, shall be provided with apermanent means of acce ss to the extent as specified in table 1 and table 2, as applicable. For oil tankers and wing ba llast tanks of ore carriers, rafting may be used in addition to the specified permanent means of access, provided that the structure allows for its safe and effective use. 2 Elevated passageways, where fitted, sha ll have aminimum width of 600 mm and be provided with toe boards not less than 150 mm high and guard rails over both sides of their entire - safe and effective use. 2 Elevated passageways, where fitted, sha ll have aminimum width of 600 mm and be provided with toe boards not less than 150 mm high and guard rails over both sides of their entire length. Sloping structure providing part of the access shall be of anon-skid construction. Guard rails shall be 1,000 mm in height and consist of arail and intermediate bar 500 mm in height and of substantial construction. Stanchions shall be not more than 3 mapart. 3 Access to elevated passageways and vertical openings from the ship■sbottom shall be provided by means of easily accessible passageways, la dders or treads. Treads shall be provided with lateral support for the foot. Where the rungs of ladders are fitted against avertical surface, the distance from the centre of the rungs to the surface shall be at least 150 mm. Where vertical manholes are fitted higher than 600 mm above the walking level, access shall be facilitated by means of treads and hand grips with platform landings on both sides. RESOLUTION MSC.133(76) (adopted on 12 December 2002) ADOPTION OF TECHNICAL PROVISIONS FOR MEANS OF ACCESS FOR INSPECTIONSMSC 76/23/Add.1 ANNEX 2 - means of treads and hand grips with platform landings on both sides. RESOLUTION MSC.133(76) (adopted on 12 December 2002) ADOPTION OF TECHNICAL PROVISIONS FOR MEANS OF ACCESS FOR INSPECTIONSMSC 76/23/Add.1 ANNEX 2 Page 3 I:\MSC\76\23-ADD.1.DOC 4 Tunnels passing through cargo holds shall be equipped with ladders or steps at each end of the hold so that personnel may easily cross such tunnels. 5 Permanent ladders, except for vertical ladders, which are fitted on vertical structures for close-up inspection or thickness measurement, shall be inclined at an angle of less than 70”. There shall be no obstructions within 750 mm of th eface of the inclined ladder, except that in way of an opening this clearance may be reduced to 600 mm. The flights of ladders shall not be more than 9 min actual length. Resting platform sof adequate dimensions shall be provided. Ladders and handrails shall be constructed of steel or equivalent