rate of heat release from building products adopted by ISO by ISO 5660. ** Refer to the Improved recommendation on test method for qualifying marine construction materials as non-combustible adopted by the Organization by resolution A.472(XII). *** Refer to the Recommendation on improved fire test procedures for "A", "B" and "F" class divisions, adopted by the Organization by resolution A.754(18). **** Refer to the Recommendation on improved fire test procedures for surface flammability of bulkhead, ceiling and deck finish materials adopted by the Organization by resolution A.653(16). W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT Machinery spaces Open vehicle spaces Spaces containing dangerous goods Special category spaces Store-rooms containing flammable liquids MSC 63/23/Add.2 ANNEX 18 Page 55 .2 "Areas of moderate fire hazard" referred to in tables 7.4-1 and 7.4-2 by B, include the following spaces: Auxiliary machinery spaces, as defined in 1.4.3 Bond stores containing packaged beverages with alcohol content not exceeding 24% by volume Crew accommodations - and 7.4-2 by B, include the following spaces: Auxiliary machinery spaces, as defined in 1.4.3 Bond stores containing packaged beverages with alcohol content not exceeding 24% by volume Crew accommodations Service spaces .3 "Areas of minor fire hazard" referred to in tables 7.4-1 and 7.4-2 by C, include the following spaces: Auxiliary machinery spaces, as defined in 1.4.4 Cargo spaces Fuel tank compartments Public spaces Tanks, voids and areas of little or no fire risk .4 "Control stations" referred to in tables 7.4-1 and 7.4-2 by D, as defined in 1.4.13 . . 5 "Evacuation stations and external escape routes" referred to in tables 7.4-1 and 7.4-2 by E, include the following areas: External stairs and open decks used for escape routes Muster stations, internal and external Open deck spaces and enclosed promenades forming lifeboat and liferaft embarkation and lowering stations The craft'sside to the waterline in the lightest seagoing condition, superstructure and deckhouse sides situated below and adjacent to the liferaft'sand evacuation slide'sembarkation areas .6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 by F, include the following areas: - condition, superstructure and deckhouse sides situated below and adjacent to the liferaft'sand evacuation slide'sembarkation areas .6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 by F, include the following areas: W/1576n/pp/EWP Open spaces locations other than evacuation stations and external escape routes and control stations. RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 56 - N-e~ of rraj a- f 1r-e /'"e%lr'O .o.r.e~ of /Tcc::):"Idte f'ire t-czlr'O .. .Are=~ of' min::r fire ~z:rd.. - CO"1r:rc! ~tct!cn. A 6 c 0 e: e:~ticn stdticns ~e~ n:ut". , F Open Spaces WI1576n/pp/EWP Table 7.4-1 STRUCTURAL FIRE PROTECTION TIMES FOR SEPARATING BULKHEADS AND DECKS OF PASSENGER CRAFT / A I e I c /. . 0 -/ e: I F IN. I~ I~~I~' ~ , 2 I ,8 I ' I I 7 I .) - IN ~ ~~~ ~ I~ ~~~ N~G;· ~- - " ". :5 , I~~ . . ~ RESOLU