provide automatic inflation of liferafts (for example, when the liferafts are associated with an MES), the arrangement should be such that the craft can be evacuated within the time specified in 4.8.1. 8.6.5 Survival craft should be capable of being launched and then boarded from the designated embarkation stations in all operational conditions and also in all conditions of flooding after receiving damage to the extent prescribed in chapter 2. 8.6.6 Survival craft launching stations should be in such positions as to ensure safe launching having particular regard to clearance from the propeller or waterjet and steeply overhanging portions of the hull. Refer to Symbols related to life-saving appliances and arrangements, adopted by the Organization by resolution A.760(18). W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT n 8.6.7 8.6.8 8.6.9 8.6.10 8.6.11 8.6.12 8.7 8.7.1 8.7.2 MSC 62/23/Add.2 ANNEX 18 Page 87 During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately - 8.6.7 8.6.8 8.6.9 8.6.10 8.6.11 8.6.12 8.7 8.7.1 8.7.2 MSC 62/23/Add.2 ANNEX 18 Page 87 During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately illuminated by the lighting supplied from the main and emergency sources of electrical power required by chapter 12. Means should be available to prevent any discharge of water on to survival craft when launched. Each survival craft should be stowed: .1 so that neither the survival craft nor its stowage arrangements will interfere with the operation of any other survival craft or rescue boat at any other launching station; .2 in astate of continuous readiness: .3 fully equipped; and .4 as far as practicable, in asecure and sheltered position and protected from damage by fire and explosion. Every liferaft should be stowed with its painter permanently attached to the craft and with afloat free arrangement complying with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink. - with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink. Rescue boats should be stowed: .1 in astate of continuous readiness for launching in not more than 5 min; .2 in aposition suitable for launching and recovery; and .3 so that neither the rescue boat nor its stowage arrangements will interfere with the operation of survival craft at any other launching station. Rescue boats and survival craft should be secured and fastened to the deck so that they at least withstand the loads likely to arise due to adefined horizontal collision load for the actual craft, and the vertical design load at the stowage position. Survival craft and rescue boat embarkation and recovery arrangements Embarkation stations should be readily accessible from accommodation and work areas. If the designated muster stati