out in Annexes 1 to 4 to the present resolution: (a) Resolution A. 803(19) - Performance Standards for Shipborne VHF Radio Installations Capable of Voice Communication and Digital Selective Calling (Annex 1); (b) Resolution A.804(19) - Performance Standards for Ship borne MF Radio Installations Capable of Voice Communication and Digital Selective Calling (Annex 2); (c) Resolution A. 806(1 9) - Performance Standards for Shipborne MFIHF Radio Installations Capable of Voice Communication, Narrow-Band Direct-Printing and Digital Selective Calling (Annex 3); and (d) Resolution A. 807(19) - Performance Standards for Inmarsat-C Ship Earth Stations Capable of Transmitting and Receiving Direct-Printing Communications (Annex 4); 2. RECOMMENDS Governments to ensure that equipment and systems listed in the present resolution and installed on or after 1 January 2000 conform to the amended performance standards specified in the attached Annexes . I:\MSC\68\23 -Add.l - resolution and installed on or after 1 January 2000 conform to the amended performance standards specified in the attached Annexes . I:\MSC\68\23 -Add.l RESOLUTION MSC.68(68) (adopted on 6 June 1997) ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT MSC 68/23/ Add. 1 ANNEX 10 Page 2 ANNEX 1 AMENDMENTS TO RESOLUTION A.803(19) ~ PERFORMANCE STANDARDS FOR VHF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION AND DIGITAL SELECTIVE CALLING Modify paragraphs 11.2.5 and 11.2.6 of the Annex, as follows: ".5 facilities to automatically update the ship'sposition and the time at which the position was determined from asuitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include asuitable interface conforming to the appropriate international standard; 1 - of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include asuitable interface conforming to the appropriate international standard; 1 .6 means for manual entry of position information and the time at which the position was determined; and" Add new paragraph 11.2.7 : ".7 means to activate an alarm when no position data is received from the electronic position-fixing aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 23 Y2 hours should be erased." Modify paragraph 11.3.2, as follows: ".3.2 These messages should be stored until readout and should be erased 48 hours after their reception. II Modify the second sentence of paragraph 11.4, as follows: "11. 4 ..... The means for initiating adistress alert should be as prescribed in 2.6 to 2.8. II IEC 1162 J:\MSC\68\23-Add .l RESOLUTION MSC.68(