could take into account relevant guidelines such as the Procedure for approval of ballast water management systems that make use of active substances (G9) (resolution MEPC.126(53)), and, if necessary, additional washwater discharge criteria should be established. RESOLUTION MEPC.259(68) (adopted on 15 May 2015) 2015 GUIDELINES FOR EXHAUST GAS CLEANING SYSTEMSMEPC 68/21/Add.1 Annex 1, page 17 Documents/English/MEPC 68-21-ADD.1 (E).doc 10.2 Washwater monitoring 10.2.1 pH, oil content (as measured by PAH levels), and turbidity should be continuously monitored and recorded as recommended in section 7 of these guidelines. The monitoring equipment should also meet the performance criteria described below: pH 10.2.2 The pH electrode and pH meter should have aresolution of 0.1 pH units and temperature compensation. The electrode should comply with the requirements defined in BS 2586 or of equivalent or better performance and the meter should meet or exceed BS EN ISO 60746-2:2003. PAH 10.2.3 The PAH monitoring equipment should be capable to monitor PAH in water in a - BS 2586 or of equivalent or better performance and the meter should meet or exceed BS EN ISO 60746-2:2003. PAH 10.2.3 The PAH monitoring equipment should be capable to monitor PAH in water in arange to at least twice the discharge concentration limit given in the table above. The equipment should be demonstrated to operate correctly and not deviate more than 5% in washwater with turbidity within the working range of the application. 10.2.4 For those applications discharging at lower flow rates and higher PAH concentrations, ultraviolet light monitoring technology or equivalent, should be used due to its reliable operating range. Turbidity 10.2.5 The turbidity monitoring equipment should meet requirements defined in ISO 7027:1999 or USEPA 180.1. 10.3 Washwater monitoring data recording The data recording system should comply with the requirements of sections 7 and 8 and should continuously record pH, PAH and Turbidity as specified in the washwater criteria. 10.4 Washwater residue 10.4.1 Residues generated by the EGC unit should be delivered ashore to adequate - should continuously record pH, PAH and Turbidity as specified in the washwater criteria. 10.4 Washwater residue 10.4.1 Residues generated by the EGC unit should be delivered ashore to adequate reception facilities. Such residues should not be discharged to the sea or incinerated on board. 10.4.2 Each ship fitted with an EGC unit should record the storage and disposal of washwater residues in an EGC log, including the date, time and location of such storage and disposal. The EGC log may form apart of an existing log-book or electronic recording system as approved by the Administration. RESOLUTION MEPC.259(68) (adopted on 15 May 2015) 2015 GUIDELINES FOR EXHAUST GAS CLEANING SYSTEMSMEPC 68/21/Add.1 Annex 1, page 18 Documents/English/MEPC 68-21-ADD.1 (E).doc APPENDIX 1 FORM OF SOX EMISSION COMPLIANCE CERTIFICATE NAME OF ADMINISTRATION SOX EMISSION COMPLIANCE CERTIFICATE CERTIFICATE