the Marine Environment Protection Committee of the Organization by resolutions MSC.4(48) and MEPC.19(22) respectively, as amended. The existing text of 3.16. 10(a) is replaced by the fol lowing : filter type respiratory protection is unacceptable; The following words are inserted after the third sentence of the existing text of 4.7.21; Remote manual operation should be arranged such that remote starting of pumps supplying the water spray system and remote operation of any normally closed valves in the system can be carried out from asuitable location outside the cargo area, adjacent to the accommodation spaces and readily accessible and operab l ein the event of fire in the areas protected. RESOLUTION MEPC.56(33) (adopted on 30 October 1992) ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)- 4 - The existing text of 4.10 is amended as follows: New 4.10 Cargoes protected by add itives - ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)- 4 - The existing text of 4.10 is amended as follows: New 4.10 Cargoes protected by add itives 4.10.1 Certai nca rgoes with areference in colu mn 'm' in th eta ble of chapter VI. by the nat ure of their chemical make-u p, tend under cer tain conditions of temperat ure , exposure to ai ror contact with aca tal ys t. to undergo polymerization, decomposition, oxidation or other chemical chang es. Mitigation of this tendency is carried ou tby introducing small amounts of chemical additives into the liquid cargo or by controlling the cargo tank environment. 4.10.2 No change. 4 .10.3 Care should be taken to ensure th a tthese cargoes are suffi cie ntly pro tected to prevent de l e terious chemical change at all times during the voyage. Ships carrying such cargoes should be provided with acertificate of protection from the manufa cture rand kept during the voyage specifying: .1 the name and amount of addi tive present; .2 whether the additive is oxygen-dependent; .3 date additive was put in the product and duration of - with acertificate of protection from the manufa cture rand kept during the voyage specifying: .1 the name and amount of addi tive present; .2 whether the additive is oxygen-dependent; .3 date additive was put in the product and duration of effectiveness; .4 any temperature limitations qua lif ying the add itive'seffective lifetime; and .5 the action to be taken should the le ngth of voyage exceed the effective lifetime of the additive. 4.10.4 Ships using the exc lusion of air as the method of preventing oxidatio nof the cargo should comply with 2.19.3 . 4.10.5 Aproduct co ntaini ng an oxygen-dependent additive should be carried without inert ion. 4 .1 0 . 6 A, existing 4.10.5 . 4.10.7 Mexisting 4.10.6. 4.23 is added ., follows: 4.23 Temperature sensors Temperature sensors should be used to monitor the cargo pump temperature to detect overheating due to pump failures. RESOLUTION MEPC.56(33) (adopted on 30 October 1992)