.3 an approved method is not yet commercially available as described in paragraph 7.2 of this regulation; or .4 an approved method is not applicable. 7.4 Subject to regulation 3 of this Annex, the operation of amarine diesel engine described in paragraph 7.1 of this regulation is prohibited, except when the emission of nitrogen oxides (calculated as the total weighted emission of NO 2) from the engine is within the following limits, where n = rated engine speed (crankshaft revolutions per minute): .1 17.0 g/kWh when nis less than 130 rpm; .2 45 n(–0.2) g/kWh when nis 130 or more but less than 2,000 rpm; and .3 9.8 g/kWh when nis 2,000 rpm or more. 25 Refer to the 2014 Guidelines on the approved method process (resolution MEPC.243(66)). 26 Refer to the 2014 Guidelines in respect of the information to be submitted by an Administration to the Organization covering the certification of an approved method as required under regulation 13.7.1 of MARPOL Annex VI (resolution MEPC.242(66)). RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION - MARPOL Annex VI (resolution MEPC.242(66)). RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1 Annex 11, page 29 I:\MEPC\MEPC 83-17-Add.1.docx 7.5 Certification of an approved method shall be in accordance with chapter 7 of the revised NOx Technical Code 2008 and shall include verification: .1 by the designer of the base marine diesel engine to which the approved method applies that the calculated effect of the approved method will not decrease engine rating by more than 1.0%, increase fuel consumption by more than 2.0% as measured according to the appropriate test cycle set forth in the revised NOx Technical Code 2008, or adversely affect engine durability or reliability; and .2 that the cost of the approved method is not excessive, which is determined by acomparison of the amount of NO xreduced by the approved method to achieve the standard set forth in paragraph 7.4 of this regulation and the cost of purchasing and installing such approved method.27 Certification - by acomparison of the amount of NO xreduced by the approved method to achieve the standard set forth in paragraph 7.4 of this regulation and the cost of purchasing and installing such approved method.27 Certification 8 The revised NOx Technical Code 2008 shall be applied in the certification, testing and measurement procedures for the standards set forth in this regulation. 9 The procedures for determining NO xemissions set out in the revised NO x Technical Code 2008 are intended to be representative of the normal operation of the engine. Defeat devices and irrational emission control strategies undermine this intention and shall not be allowed. This regulation shall not prevent the use of auxiliary control devices that are used to protect the engine and/or its ancillary equipment against operating conditions that could result in damage or failure or that are used to facilitate the starting of the engine. Regulation 14 Sulphur oxides (SOx) and particulate matter General requirements 1 The sulphur content of fuel oil used or carried for use on board aship shall not exceed 0.50% m/m. - Regulation 14 Sulphur oxides (SOx) and particulate matter General requirements 1 The sulphur content of fuel oil used or carried for use on board aship shall not exceed 0.50% m/m. 2 The worldwide average sulphur content of residual fuel oil supplied for use on board ships shall be monitored taking into account the guidelines developed by the Organization.28 Requirements within emission control areas 3 For the purpose of this regulation, an emission control area shall be any sea area, including any port area, designated by the Organization in accordance with the criteria and procedures set forth in appendix III. The emission control areas under this regulation are: .1 the Baltic Sea area as defined in regulation 1.11.2 of Annex Iof the present Convention; 27 The cost of an approved method shall not exceed 375 Special Drawing Rights/metric tonne NOx calculated in accordance with the cost-effectiveness (Ce) formula belo