In its most simple form, the attained annual operational CII of individual ships is calculated as the ratio of the total mass of CO 2 (M) emitted to the total transport work (W) undertaken in agiven calendar year, as follows: (1) 4.1 Mass of CO2 emissions (M) The total mass of CO2 is the sum of CO2 emissions (in grams) from all the fuel oil consumed on board aship in agiven calendar year, as follows: ■■ = ■■■■■■ × ■■■■■■ (2) where: ■ is the fuel oil type; ■ is the total mass (in grams) of consumed fuel oil of type in the calendar year, as reported under IMO DCS; and ■ represents the fuel oil mass to CO 2 mass conversion factor for fuel oil type , in line with those specified in the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73)), as may be further amended. In case the type of the - calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73)), as may be further amended. In case the type of the fuel oil is not covered by the guidelines, the conversion factor should be obtained from the fuel oil supplier supported by documentary evidence. 4.2 Transport work (W) In the absence of the data on actual transport work, the supply-based transport work (Ws) can be taken as aproxy, which is defined as the product of aship ■s capacity and the distance travelled in agiven calendar year, as follows: Ws= C×Dt (3) where: ■ Crepresents the ship■s capacity: - For bulk carriers, tankers, container ships, gas carriers, LNG carriers, ro- ro cargo ships, general cargo ships, refrigerated cargo carrier and combination carriers, deadweight tonnage (DWT)1 should be used as Capacity; - For cruise passenger ships, ro- ro cargo ships (vehicle carriers) and ro- ro - carriers, deadweight tonnage (DWT)1 should be used as Capacity; - For cruise passenger ships, ro- ro cargo ships (vehicle carriers) and ro- ro passenger ships, gross tonnage (GT)2 should be used as Capacity; and ■ Dt represents the total distance travelled (in nautical miles), as reported under IMO DCS. 1 Deadweight tonnage (DWT) means the difference in tonnes between the displacement of aship in water of relative density of 1,025 kg/m3 at the summer load draught and the lightweight of the ship. The summer load draught should be taken as the maximum summer draught as certified in the stability booklet approved by the Administration or any organization recognized by it. 2 Gross tonnage (GT) should be calculated in accordance with the International Convention on Tonnage Measurement of Ships, 1969. / shipattained CII M W= j jFC j jFC j RESOLUTION MEPC.336(76) (adopted on 17 June 2021) - Measurement of Ships, 1969. / shipattained CII M W= j jFC j jFC j RESOLUTION MEPC.336(76) (adopted on 17 June 2021) 2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)MEPC 76/15/Add.2 Annex 10, page 4 I:\MEPC\76\MEPC 76-15-Add.2.docx 5 Operational carbon intensity indicator (CII) of individual ships for trial purpose The following metrics are encouraged to be used for trial purposes, where applicable: .1 Energy Efficiency Performance Indicator (EEPI) ■■■■■■■■ = ■■■■×■■■■ .2 cbDIST ■■■■■■ ■■■■■■ = ■■■■ ■■■■×■■■■ .3 clDIST ■■ ■■■■■■■■■■ = ■■■■■■ ■■■■■■■■■■■■■■■■×■■■■ .4 EEOI, as defined in MEPC.1/Circ.684 on Guidelines for voluntary use of the ship energy efficiency operational indicator (EEOI). In the formulas above: • the mass of CO2 (M), the ship■s capacity (C) and the total distance travelled (Dt) are ---CHUNK--- SOURCE: MEPC.336