is installed; and .7 SFCSteamTurbine for steam turbine, as specified in paragraph 2.2.7.2 of the EEDI Calculation Guidelines. If the calculation is not available from the manufacturer, SFCSteamTurbine may be calculated by the submitter. Asample of an EEXI Technical File is provided in the appendix. 2 Electric power tables should be validated separately, taking into account the guidelines set out in appendix 2 of the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI) (resolution MEPC.254(67), as amended by resolutions MEPC.261(68) and MEPC.309(73)); consolidated text: MEPC.1/Circ.855/Rev.2, as may be further amended). RESOLUTION MEPC.334(76) (adopted on 17 June 2021) 2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2 Annex 8, page 6 I:\MEPC\76\MEPC 76-15-Add.2.docx 4.2.3 The SFC should be corrected to the value corresponding to the ISO standard reference conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and ISO 3046-1:2002. For the confirmation of the SFC, acopy of the approved NOX Technical File and - conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and ISO 3046-1:2002. For the confirmation of the SFC, acopy of the approved NOX Technical File and documented summary of the correction calculations should be submitted to the verifier. 4.2.4 For ships equipped with dual-fuel engine(s) using LNG and fuel oil, the CF-factor for gas (LNG) and the specific fuel consumption (SFC) of gas fuel should be used by applying the criteria specified in paragraph 4.2.3 of the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI), as amended,3 as abasis for the guidance of the Administration. 4.2.5 Notwithstanding paragraphs 4.2.3 and 4.2.4, in cases where overridable Shaft / Engine Power Limitation is installed, or in cases where engines do not have atest report included in the NOX Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory and acceptable to the verifier. - Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory and acceptable to the verifier. 4.2.6 The verifier may request further information from the submitter, as specified in paragraph 4.2.7 of the EEDI Survey and Certification Guidelines, in addition to that contained in the EEXI Technical File, as necessary, to examine the calculation process of the attained EEXI. 4.2.7 In cases where the sea trial report as specified in paragraph 4.2.2.9 is submitted, the verifier should request further information from the submitter to confirm that: .1 the sea trial was conducted in accordance with the conditions specified in paragraphs 4.3.3, 4.3.4 and 4.3.7 of the EEDI Survey and Certification Guidelines, as applicable; .2 sea conditions were measured in accordance with ISO 15016:2002 or the equi