in accordance with the cost-effectiveness (Ce) formula below: Refer to Definitions for the cost-effectiveness formula in regulation 13.7.5 of the revised MARPOL Annex VI (MEPC.1/Circ.678). 28 Refer to the 2020 Guidelines for monitoring the worldwide average sulphur content of fuel oils supplied for use on board ships (resolution MEPC.326(75)). RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI) Cost of approved method• 10• Ce =---------- Power (kW) • 0.768 • 6,000 (hours/year) · 5 (years) · 6NOx (g/kWh) MEPC 83/17/Add.1 Annex 11, page 30 I:\MEPC\MEPC 83-17-Add.1.docx .2 the North Sea area as defined in regulation 1.14.6 of Annex Vof the present Convention; .3 the North American Emission Control Area, which means the area described by the coordinates provided in appendix VII; .4 the United States Caribbean Sea Emission Control Area, which means the area described by the coordinates provided in appendix VII; .5 the Mediterranean Sea Emission Control Area, which means the area described by the coordinates provided in appendix VII; - area described by the coordinates provided in appendix VII; .5 the Mediterranean Sea Emission Control Area, which means the area described by the coordinates provided in appendix VII; .6 the Canadian Arctic Emission Control Area, which means the area described by the coordinates provided in appendix VII; .7 the Norwegian Sea as defined in regulation 13.9.4 of Annex II of the present Convention; and .8 the North -East Atlantic Emission Control Area, which means the area described by the coordinates provided in appendix VII. 4 While aship is operating within an emission control area, the sulphur content of fuel oil used on board that ship shall not exceed 0.10% m/m. 5 The sulphur content of fuel oil referred to in paragraph 1 and paragraph 4 of this regulation shall be documented by its supplier as required by regulation 18 of this Annex. 6 Those ships using separate fuel oils to comply with paragraph 4 of this regulation and entering or leaving an emission control area set forth in paragraph 3 of this regulation shall carry awritten procedure showing how the fuel oil changeover is to be done, allowing sufficient - entering or leaving an emission control area set forth in paragraph 3 of this regulation shall carry awritten procedure showing how the fuel oil changeover is to be done, allowing sufficient time for the fuel oil service system to be fully flushed of all fuel oils exceeding the applicable sulphur content specified in paragraph 4 of this regulation prior to entry into an emission control area. The volume of low sulphur fuel oils in each tank as well as the date, time and position of the ship when any fuel oil changeover operation is completed prior to the entry into an emission control area or commenced after exit from such an area shall be recorded in such logbook or electronic record book29 as prescribed by the Administration. 7 During the first 12 months immediately following entry into force of an amendment designating aspecific emission control area under paragraph 3 of this regulation, ships operating in that emission control a