EEDI Calculation Guidelines). 2.2.2.3 In cases where the electric power table is not available, the P AE value may be approximated either by: .1 annual average figure of P AE at sea from onboard monitoring obtained prior to the EEXI certification; .2 for cruise passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below: ■■■■■■■,■■■■■■■ = 0.1193 × ■■■■■ + 1814.4 [kW] .3 for ro-ro passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below: ■■■■■■■,■■■■■■■ = 0.866 × ■■■■■0.732 [kW] 2.2.3 Vref ; Ship speed 2.2.3.1 For ships falling into the scope of the EEDI requirement, the ship speed Vref should be obtained from an approved speed-power curve as defined in the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI) , as amended (resolution MEPC.254(67), as amended). 2.2.3.2 For ships not falling into the scope of the EEDI requirement, the ship speed Vref should be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey and certification of the attained EEXI (resolution MEPC.334(76)). - be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey and certification of the attained EEXI (resolution MEPC.334(76)). 2.2.3.3 For ships not falling into the scope of the EEDI requirement but whose sea trial results, which may have been calibrated by the tank test, under the EEDI draught and the sea condition as specified in paragraph 2.2.2 of the EEDI Calculation Guidelines are included in the sea trial report, the ship speed Vref may be obtained from the sea trial report: ■■■■■■■■■ = ■■■■■,■■■■■■■ ■■ × ■ ■■■■■■■ ■■■■■,■■■■■■■ ■■ ■ 1 3 [knot] RESOLUTION MEPC.333(76) (adopted on 17 June 2021) 2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2 Annex 7, page 5 I:\MEPC\76\MEPC 76-15-Add.2.docx where, VS,EEDI, is the sea trial service speed under the EEDI draught; and PS,EEDI is power of the main engine corresponding to VS,EEDI. 2.2.3.4 For containerships, bulk carriers or tankers not falling into the scope of the EEDI requirement but whose sea trial results, which may have been calibrated by the tank test, under - 2.2.3.4 For containerships, bulk carriers or tankers not falling into the scope of the EEDI requirement but whose sea trial results, which may have been calibrated by the tank test, under the design load draught and sea condition as specified in paragraph 2.2.2 of the EEDI Calculation Guidelines are included in the sea trial report, the ship speed Vref may be obtained from the sea trial report: ■■■■■■■■■ = ■■ 1 3 × ■■■■■■■■■■,■■■■■■■■■■■■■■■ ■■■■■■■■■■■■■■■■■■■ ■ 2 9 × ■■■■■,■■■■■ ■■ ■■■■■■■■■ × ■ ■■■■■■■■■■■,■■■■■■■■■■■■■■■ 1 3 [knot] where, VS,service is the sea trial service speed under the design load draught; DWTS,service is the deadweight under the design load draught; PS,service is the power of the main engine corresponding to VS,service; kis the scale coefficient, which should be: .1 0.95 for containerships with 120,000 DWT or less; .2 0.93 for containerships with more than 120,000 DWT; .3 0.97 for bulk carrier with 200,000 DWT or less; .4 1.00 for bulk carrier with more than 200,000 DWT; .5 0.97 for tanker with 100,000 DWT or less; and .6 1.00 for tanker with more than 100,000 DWT. - .3 0.97 for bulk carrier with 200,000 DWT or less; .4 1.00 for bulk carrier with more than 200,000 DWT; .5 0.97 for tanker with 100,000 DWT or less; and .6 1.00 for tanker with more than 100,000 DWT. 2.2.3.5 In cases where the speed-power curve is not available or the sea trial report does not contain the EEDI or design load draught condition, the ship speed Vref can be approximated by Vref,app to be obtained from statistical mean of distribution of ship speed and engine power, as defined below: ■■■■■■■■■,■■■■■■■ = (■■■■■■■■■,■■■■■■■ – ■■■■■) × ■ ∑ ■■■■■■■ 0.75×■■■■■■■■■■■■■■ ■ 1 3 [knot] For LNG carriers having diesel electric propulsion system and cruise passenger ship having non-conventional propulsion, ■■■■■■■■■,■■■■■■■ = (■■■■■■■■■,■■■■■■■ – ■■■■■) × ■ ∑ ■■■■■ ■■■■■■■■■■■■■■ ■■■■■■■■■■■■■■ ■ 1 3 [knot] RESOLUTION MEPC.333(76) (adopted on 17 June 2021) 2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY