• the means to enable the bridge team to handle alert announcements, and • the means to manage all alert related stat es in adistributed system structure in consistent manner. 18.2 If practicable, there should be not more than one alert fo rone situation that requires attention. 18.3 The alert management should as aminimum be able to handle all alerts required by performance standards adopted by the Organization for navigational equipment comprised by the INS or connected to the INS. The alert management should have the capability to handle all other alerts of navigational equipment comprised by the INS or connected to the INS in identical manner and should incorporate all alerts that are critical to the safety of navigation. 3 MSC.128(75), MSC.191(79). RESOLUTION MSC.252(83) (adopted on 8 October 2007) ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3 ANNEX 30 Page 24 I:\MSC\83\28-Add-3.doc 18.4 The logical architecture of the alert mana gement and the handling concept for alerts - ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3 ANNEX 30 Page 24 I:\MSC\83\28-Add-3.doc 18.4 The logical architecture of the alert mana gement and the handling concept for alerts should provide the capability to minimize the number of alerts especially those on ahigh priority level (e.g. using system knowledge from redundancy concepts inside INS and evaluating inherent necessities for alerts against navigational situat ions, operational modes or activated navigational functions). 18.5 It should be possible to provide the centr al alert management HMI at least on the navigating and manoeuvring workstation and allowing the handling by the bridge team. 18.6 The audible announcement of alerts should en hance the guidance of the bridge team to the task stations or displays which are directly assigned to the function generating the alert and presenting the cause of the announcement and related information for decision support, e.g., dangerous target alarms should appear and have to be acknowledged at the workstation where the collision avoidance function is provided. - presenting the cause of the announcement and related information for decision support, e.g., dangerous target alarms should appear and have to be acknowledged at the workstation where the collision avoidance function is provided. 18.7 As alerts can be displayed at several locations , the system should be consistent as far as practicable with respect to how alerts are displayed, silen ced and acknowledged at any one task station of the INS. 19 Priorities and categories 19.1 Priorities of alerts 19.1.1 The alert management should distinguis hbetween the three priorities listed: • Alarms • Warnings and • Cautions 19.1.2 Alarms should indicate conditions requiri ng immediate attention and action by the bridge team. 19.1.3 Warnings should indicate changed conditions and should be presented for precautionary reasons which are not immediately hazardous but which may become so, if no action is taken. 19.1.4 Cautio